

## SLOVENSKI STANDARD SIST ISO 5690-1:1995

01-september-1995

# Stroji za trosenje mineralnih gnojil - Postopki preskušanja - 1. del: Trosilniki mineralnih gnojil za trosenje po celi delovni širini

Equipment for distributing fertilizers -- Test methods -- Part 1: Full width fertilizer distributors

# iTeh STANDARD PREVIEW

Matériels de distribution des fertilisants - Méthodes d'essai -- Partie 1: Distributeurs d'engrais en nappe

SIST ISO 5690-1:1995

Ta slovenski standard je istoveten z: 1995-930-1-1995

ICS:

65.060.25 Oprema za skladiščenje, pripravo in razdeljevanje gnojiv

Equipment for storage, preparation and distribution of fertilizers

SIST ISO 5690-1:1995

en



# iTeh STANDARD PREVIEW (standards.iteh.ai)





INTERNATIONAL ORGANIZATION FOR STANDARDIZATION MEX CHAPOCHAR OPPAHUSALUR TO CTAH CAPTUSALUNOORGANISATION INTERNATIONALE DE NORMALISATION

# Equipment for distributing fertilizers — Test methods — Part 1: Full width fertilizer distributors

Matériels de distribution des fertilisants — Méthodes d'essai — Partie 1: Distributeurs d'engrais en nappe

## Second edition – 1985-12-01eh STANDARD PREVIEW (standards.iteh.ai)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting **CANDARD PREVIEW** 

International Standard ISO 5690/1 was prepared by Technical Committee ISO/TC 23, Tractors and machinery for agriculture and forestry.

This second edition cancels and replaces the first edition (150)5690/201982)2 annex A of which has been revised technically/standards.iteh.ai/catalog/standards/sist/750638a3-060d-4a65-93ce-0d74f644a34f/sist-iso-5690-1-1995

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

## Contents

	Pag	ge
0 Introduction	••	1
1 Scope and field of application	••	1
2 References	••	1
<b>3</b> Definitions	••	1
4 General test conditions	••	1
5 Mandatory tests	••	2
6 Results (standards iteh ai)	•••	4
7 Test report	••	5
Figures 47430 5690-1:1995 https://standards.iteh.ai/catalog/standards/sist/750638a3-060d-4a65-93ce- Adīnéxes/a34f/sist-iso-5690-1-1995	6,	, 7
A Determination of physical properties of fertilizers	•••	8
B Optional tests		9
<b>C</b> Example of a test report on a full width fertilizer distributor	••	10



# iTeh This page intentionally left blank EVIEW (standards.iteh.ai)

### **INTERNATIONAL STANDARD**

## Equipment for distributing fertilizers — Test methods — Part 1: Full width fertilizer distributors

#### Introduction n

The aim of this part of ISO 5690 is to harmonize the testing of full width solid fertilizer distributors, first to fix the variable conditions of laboratory testing, and second to give guidance for field test conditions.

The laboratory tests determine the influence of forward speed, flow rate, fertilizer level in hoppers, bumps and transverse tilting.

Optional field tests (see annex B) will complete the laboratory tests by describing the influence of slope, the condition of the ground and of the wind.

application rate (of fertilizer): The quantity, expressed as

#### Scope and field of application (standards.iteh.ai) 1

This part of ISO 5690 specifies a test method for equipment for 4.10 General test conditions full width distribution of solid fertilizers; it applies to agricultural full width fertilizer distributorshttps://standards.iteh.ai/catalog/standards/ NOTE — The manufacturer or his representative shall be entitled to be 0d74f644a34f/sist-iso-

NOTE - Equipment designed for distributing microgranular pesticides or herbicides is excluded. Part 2 of ISO 5690 deals with distributors of fertilizers in lines. (See ISO 3339/0 for the classification.)

#### 2 References

ISO 500, Agricultural tractors - Power take-off and drawbar - Specification.

ISO 565, Test sieves - Woven metal wire cloth, perforated plate and electroformed sheet - Nominal sizes of openings.

ISO 3339/0, Tractors and machinery for agriculture and forestry - Classification and terminology - Part 0 : Classification system and classification.

ISO 3534, Statistics — Vocabulary and symbols.

ISO 3789, Tractors, machinery for agriculture and forestry, powered lawn and garden equipment - Location and method of operation of operator's controls ----

Part 1: Common controls.

Part 2: Controls for agricultural tractors and machinery.

ISO 3944, Fertilizers - Determination of bulk density (loose).

ISO 5698, Agricultural machinery – Hoppers – Manual loading height.

ISO 5699, Agricultural machines, implements and equipment Dimensions for mechanical loading with bulk goods.

#### 3 Definitions

The definitions relating to the distribution of fertilizers will be covered in ISO 3339/5.

For the purpose of this part of ISO 5690, the following definition applies.

Teh STANDAR mass or volume, of fertilizer distributed per unit length or unit area.

#### Fertilizer distributor 4.1

#### 4.1.1 Selection

present at the tests.

The fertilizer distributor to be submitted to testing may be selected by the representative of the test station in agreement with the manufacturer.

The fertilizer distributor shall, in every regard, be strictly in accordance with the specifications which the manufacturer is required to send to the test station in writing.

The test report (see annex C) shall specify how the distributor to be tested has been selected.

#### 4.1.2 Manufacturer's instructions

The distributor shall be used in accordance with the instructions given in the manufacturer's user's handbook, to avoid in particular the use of fertilizers which are specified as not suitable for the machine. Any restrictions of this kind should be specified in the test report.

#### 4.1.3 Checking of specifications

During the checking of specifications, the distributor shall rest on a solid horizontal surface.

#### 4.2 Fertilizer

#### 4.2.1 Types of fertilizer used for the tests

Carry out, unless indicated otherwise by the manufacturer of the machine (comment in the test report), each of the performance tests with the following types of fertilizer :

- type a: a powdered fertilizer;
- type b: a granular fertilizer;
- type c: a crystalline or prilled fertilizer;

- type d: optionally, any other fertilizer which the test station considers of sufficient importance and the physical properties of which differ from those of the fertilizers indicated above.

#### 4.2.2 Physical properties of the fertilizer

Determine the physical properties of the fertilizer used in the tests (see annex A) : particle size, (loose) bulk density, moisture content, angle of repose. (The last two are under study.) These values shall be noted in the test report.

#### 4.3 Filling of distributor

Fill the hopper with the fertilizer in accordance with the specifications of the manufacturer of the distributor immediately prior to testing so that there is no time for settling or con-consolidation.

#### 4.5 Distribution application rates

The planned distribution quantities are as follows :

- a) **powdered fertilizers**: 600 kg/ha and maximum and minimum quantities currently used in agricultural practice for this type of fertilizer;
- b) granular fertilizer: 400 kg/ha and maximum and minimum quantities currently used in agricultural practice for this type of fertilizer;
- c) **crystalline or prilled fertilizer:** 150 kg/ha and maximum and minimum quantities currently used in agricultural practice for this type of fertilizer.

The transverse tests for evenness shall be carried out at rates a), b), c), and with the maximum quantity and the minimum quantity as shown by the manufacturer in the features of the equipment.

The longitudinal tests shall also be carried out with rates a), b) and c).

#### 4.6 Devices for receiving fertilizer

The collecting containers shall have external dimensions of either 1 000 mm  $\times$  250 mm, or 500 mm  $\times$  500 mm and shall have a minimum depth of 150 mm. However, for full-width distributors, only containers of 1 000 mm  $\times$  250 mm shall be used.

Measures shall be taken to avoid spillage by ricochet out of the <u>SIST ISO 5690- Containers</u>, such as

## **4.4 Test procedure** https://standards.iteh.ai/catalog/standards/sist/75963interlocking.inserts for dividing the containers into cells 0d74f644a34f/sist-iso-569(of \_dimensions 50 mm × 50 mm, with a height not ex-The tests shall be carried out on an even, horizontal and hard ceeding half the height of the container (see figure 1);

surface, either indoors or outdoors. In the case of outdoor testing, for mandatory tests, the wind speed shall not exceed 2 m/s; for optional tests, the wind speed shall not exceed 7 m/s.

If the tests are carried out on concrete or on the ground, precautions shall be taken to avoid ricochet.

The p.t.o. rotational frequency shall be that for which the distributor is designed. The p.t.o. rotational frequency on the tractor shall be in accordance with ISO 500.

If the manufacturer provides different instructions, the rotational frequency used shall be quoted in the test report. Prior to testing, check the p.t.o. rotational frequency.

The forward speed at which runs are made shall be constant. The forward speeds for testing are 8 km/h or 15 km/h by choice of the manufacturer, except for tests on the effect of forward speeds. The distributing mechanism shall be at the same height above the fertilizer-collecting receptacles (for example the upper edge of the containers) as that recommended by the manufacturer for work above ground or crop. unstretched net (see figure 2) draped over the con-

## 5 Mandatory tests<sup>1)</sup>

tainers.

#### 5.1 Evenness of transverse distribution

#### 5.1.1 Arrangement of containers

Containers (see 4.6) placed side by side with their edges parallel to the ground surface shall cover the total distributing width so that their longitudinal axis is parallel to the forward axis of the distributor.

If it is necessary to allow spaces between the containers for the passage of tractor wheels, these shall be as small as possible and shall be a multiple of the width of a container.

#### 5.1.2 Procedure

Carry out the test at 8 km/h or 15 km/h with a half-full hopper but with a quantity of fertilizer not exceeding 2 t.

<sup>1)</sup> For the optional tests, see annex B.

Distribute each quantity envisaged (see 4.5) in at least two runs without intervening weighing so as to eliminate the influence of lengthwise distribution unevenness. The number of runs shall be sufficient to ensure that the amount collected by a container allows weighing with a minimum accuracy of 1 % (0,1 g per 10 g).

Successive runs shall be perfectly coincident with each other. The number of runs and the quantities distributed shall be quoted in the test report.

Weigh the fertilizer collected in each container.

#### 5.1.3 Tilt (to simulate transverse imbalance)

Repeat the previous test

- in the case of trailed equipment by driving one of the wheels of the distributor on to moving rollers raised 100 mm;

— in the case of mounted equipment, by driving one of the wheels of the tractor on to moving rollers in order to give a lateral inclination of 7 % (in the case of adjustable track widths, use the maximum width setting).

### 5.2 Evenness of longitudinal distribution

#### 5.2.1 Arrangement of containers

can be used for two tests (see the table). (standards.iteh.ai) Table – Programming of mobile tests

5.2.1.1 Case of full-width distributors Arrange the containers side by side in five rows 10 m long sodards/sist/750638a3-060
that their longitudinal axis is perpendicular to the forward axisist-iso690-1-1995
of the distributor.

These five rows are arranged as follows:

- one on the axis of the distributor;
- two to the right and two to the left of the axis so that the outer edge of the outer row is located at the end of the theoretical working width given by the manufacturer and the middle row is at the same distance from the outside row as from the centre row.

In order to limit the number of containers to be used, each side may be tested in succession. The centre row can be dispensed with for trailed distributors with a small space between wheels. The two intermediate rows are then placed as close as possible to the run of the outer edges of the tyres.

5.2.1.2 Case of centrifugal distributors

A single row of containers is necessary.

This row is located between the wheels of the distributor and/or of the tractor, or, in the case of a narrow-tracked trailed distributor, on the outside of the wheels but as near as possible to the run of the outer edges of the tyre.

#### 5.2.2 Procedure

Distribute each quantity envisaged (see 4.5) in a single run.

5.2.3 Effect of forward speed

Carry out this test for distributors fitted with a dispersing mechanism which is land-wheel driven. Perform the test at 8 km/h or 15 km/h, and at the maximum speed shown by the manufacturer, using the opening adjusted to the quantities envisaged (see 5.5) and a half-filled hopper but with the quantity of fertilizer not exceeding 2 t.

**5.2.4 Effect of bumps** (mandatory for trailed distributors and optional for mounted distributors)

Repeat the test conditions (see 5.2.3) with only the speeds of 8 km/h or 15 km/h and maximum.

Place in the path of the trailer, or of the tractor if the equipment is mounted, and perpendicular to the axis of displacement, an obstacle 200 mm long and 80 mm high, preceded by a ramp of 250 mm minimum length and having a width greater than that of the tyres, allowing the machine to rise 80 mm above ground level.

In the case of a trailer, the wheels of the distributor shall pass over the obstacle but those of the tractor shall not.

#### 5.3 Programming of mobile tests

In order to avoid unnecessary duplication of tests, certain tests can be eliminated as being of no interest and for others one run can be used for two tests (see the table).

Test ist/750638a3-060d-4a65-93ce-		Speed	Appli- cation rate	lype of ferti- lizer
5690-1-1 <u>995</u> Туре	No.	km/h (see 4.4)	kg/ha (see 4.5)	(see 4.2.1)
a) Transverse	101	8 or 15	min.	aorc
regularity	102	8 or 15	600 or 150	aorc
1) horizontal	103	8 or 15	max.	aorc
distributor	104	8 or 15	min.	b
	105	8 or 15	400	b
	106	8 or 15	max.	b
	107	8 or 15	min.	d <sup>1)</sup>
	108	8 or 15	max.	d <sup>1)</sup>
2) inclined	109	8 or 15	min.	aorc
distributor	110	8 or 15	max.	aorc
	111	8 or 15	min.	ь
	112	8 or 15	max.	b
	113	8 or 15	min.	d <sup>1)</sup>
	114	8 or 15	max.	d1)
b) Longitudinal	201	8 or 15	600	а
regularity	202	8 or 15	400	b
1) without	203	8 or 15	150	с
bumps	204	optimal	600	а
	205	optimal	400	b
	206	optimal	150	С
	207	max.	600	a
	208	max.	400	Ь
	209	max.	150	c
2) with bumps	210	8 or 15	600	а
	211	8 or 15	400	b
	212	8 or 15	150	с
	213	max.	600	а
	214	max.	400	b
	215	max.	150	С
			•	

Optional.

#### 5.4 **Rate tests**

Measures shall be taken to collect all the fertilizer.

Carry out the tests with the types of fertilizer envisaged (see 4.2.1) with the hopper half full but the quantity of fertilizer not exceeding 2 t.

#### 5.4.1 Effect of flow adjustment

Use a sufficient number of adjustments to establish the approximate shape of the curve representing the flow in relation to the position of the control lever (five tests per type of fertilizer) by covering the range of flow shown by the manufacturer.

The duration of each test shall be such that a quantity of fertilizer sufficient to be weighed can be obtained. It should not be less than 30 s. In order to convert flows expressed in kilograms per second into quantities expressed in kilograms per hectare, use the optimum working width as previously established in 5.1.

#### 5.4.2 Effect of the level of fertilizer in the hopper

#### 6.1.2 Degree of unevenness of transverse distribution

The degree of unevenness shall be shown by the coefficient of variation (see ISO 3534), a, given by the equation

 $a = \frac{s}{\overline{x}}$ 

where

s, the standard deviation, is given by the equation

$$s = \sqrt{\frac{1}{n-1}\sum (x_i - \overline{x})^2}$$

in which

n is the number of containers;

 $x_i$  is the amount collected in each container;

 $\overline{x}$ , the absolute mean, is given by the equation

## Adjust the feed setting so as to obtain a flow as near as possible to 0.1 kg/s per metro of distribution to 0,1 kg/s per metre of distribution width. standards.iteh.ai)

Fill the hopper, unless its capacity is in excess of 2 t, in which 6.1.3 Working width case use 2 t. <u>SIST ISO 56</u>90-1:19

https://standards.iteh.ai/catalog/standards/sist/750638a3-060d-4a65-93ce-Start up the feed mechanism. 0d74f644a34f/sist-iso-693.11Full-width distributors

Take samples over a period of 1 min at regular intervals during emptying until complete emptying is achieved.

This test will be limited to fertilizer type a.

#### Results 6

#### 6.1 Transverse distribution

#### 6.1.1 Weighing

Weigh the quantities collected in each container separately. Divide each of these values by the number of runs in order to determine the mean quantity distributed per run, and illustrate using a histogram.

For ease of comparison of the results, the following scales are recommended:

- horizontal axis : 1 cm per 1 m;
- vertical axis: 1 cm per 20 %.

(See the graph in figure 3.)

The optimum width of work of full-width distributors shall be that stated by the manufacturer.

#### 6.1.3.2 Centrifugal distributors

The test station shall determine the optimum width by using the histogram (see 6.1.1). This shall be established by using the methods described in the two following cases:

a) for circular distribution, superposition by translation of the histogram,

b) for to-and-fro distribution, superposition by translation of the histogram with its mirror image,

to plot the graph of the coefficients of variation.

In agreement with the manufacturer, the lowest coefficient of variation corresponding to a working width compatible with the way of using the fertilizer shall be taken.

#### 6.1.4 Irregularities of transverse distribution on sloping ground

Establish the results in accordance with the principles specified in 6.1.2 and 6.1.3.

#### 6.2 Longitudinal distribution

#### 6.2.1 Forward speed index

Evenness of longitudinal distribution shall be recorded and a graph shall be prepared for each row of containers. Should no particular unevenness be found in the longitudinal distribution, show the standard deviations on the test length by summarizing the extent of the variations. If significant cyclic variations occur, show their origin and amplitude, if necessary after taking careful measurements.

#### 6.2.2 Effects of bumps

Follow the same procedure as in 6.2.1.

#### 6.3 Rate testing

#### 6.3.1 Flow adjustment effects

Prepare a graph showing the correlation between the control lever positions and flow (see figure 4).

#### 6.3.2 Effects of fertilizer level in the hopper

Note the results as a percentage in relation to the first recording.

### 7 Test report

A typical model of a test report is shown in annex C.

# iTeh STANDARD PREVIEW (standards.iteh.ai)