



**SLOVENSKI STANDARD**  
**SIST ISO 5763:2011**

**01-julij-2011**

---

**Fotografija - Elektronske bliskavice - Avtomatski nadzor ekspozicije**

Photography - Electronic flash equipment - Automatic control of exposure

Photographie - Équipement électronique à éclairs - Contrôle automatique de l'exposition

**Ta slovenski standard je istoveten z: ISO 5763:1989**

[SIST ISO 5763:2011](https://standards.iteh.ai/catalog/standards/sist/fdd030f0-dfd3-443f-9191-22c45ed8d08b/sist-iso-5763-2011)

<https://standards.iteh.ai/catalog/standards/sist/fdd030f0-dfd3-443f-9191-22c45ed8d08b/sist-iso-5763-2011>

**ICS:**

37.040.10	Fotografska oprema. Projektorji	Photographic equipment. Projectors
-----------	------------------------------------	---------------------------------------

**SIST ISO 5763:2011**

**en,fr**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 5763:2011](#)

<https://standards.iteh.ai/catalog/standards/sist/fdd030f0-dfd3-443f-9191-22c45ed8d08b/sist-iso-5763-2011>

# INTERNATIONAL STANDARD

# ISO 5763

Second edition  
1989-10-01

---

---

## Photography — Electronic flash equipment — Automatic control of exposure

*Photographie — Équipement électronique à éclairs — Contrôle automatique de  
l'exposition*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 5763:2011](https://standards.iteh.ai/catalog/standards/sist/fdd030f0-dfd3-443f-9191-22c45ed8d08b/sist-iso-5763-2011)

[https://standards.iteh.ai/catalog/standards/sist/fdd030f0-dfd3-443f-9191-  
22c45ed8d08b/sist-iso-5763-2011](https://standards.iteh.ai/catalog/standards/sist/fdd030f0-dfd3-443f-9191-22c45ed8d08b/sist-iso-5763-2011)



Reference number  
ISO 5763 : 1989 (E)

## ISO 5763 : 1989 (E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 5763 was prepared by Technical Committee ISO/TC 42, *Photography*.

[SIST ISO 5763:2011](https://standards.iteh.ai/standards/sist/6110309-dfd3-443f-9191-22c45ed8d08b/sist-iso-5763-2011)

This second edition cancels and replaces the first edition (ISO 5763 : 1982), of which it constitutes a minor revision.

Annex A of this International Standard is for information only.

© ISO 1989

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

## Introduction

This International Standard gives conditions and measuring values for the calibration of electronic flash equipment with automatic control of exposure.

The calibration values are principally related to the exposure of film in the focal plane. They are equivalent to the exposure in the focal plane of a camera with an automatic exposure control mechanism (see ISO 2721) and are related to an object exposure which is equivalent to that produced when the light output is controlled by the guide number (see ISO 1230).

To establish this correlation it is assumed that most pictures are taken under rather similar conditions.

Deviations from these "average" conditions by special scenes or by special constructions of flash equipment may, however, require the consideration of calibration values other than those given in this International Standard.

Certain electronic flash equipment with automatic control of exposure, designed exclusively for a particular camera, may not comply with some of the requirements specified in this International Standard, which are prepared for "general purpose" automatic flash equipment. This is because, in designing "special" flash equipment, all parameters of the particular camera are taken into consideration, i.e. camera lens transmittance, vignetting, the relationship between the field of taking lens and the angle of coverage and the acceptance angle of the sensor of the automatic flash equipment, etc., and these parameters will sometimes be different from those of the "average" camera. Tolerances may also be different for the special automatic flash equipment. For example, equipment for instant picture cameras will require a tolerance of  $\pm 1/3 E_v$  whereas equipment for the cameras using 110 size colour negative films, according to ISO 5800, the tolerance  $+ 3 E_v$  or  $- 1 E_v$  is acceptable.

Furthermore, even for general purpose automatic flash equipment, deviation from the "average" conditions by special scenes or by special constructions of flash equipment may require the consideration of calibration values other than those given in this International Standard.

Therefore, when testing electronic flash equipment with automatic control of exposure according to the methods specified in this International Standard, the above-mentioned special cases must be taken into consideration. A photographic check of the correct exposure is recommended.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

This page intentionally left blank

[SIST ISO 5763:2011](#)

<https://standards.iteh.ai/catalog/standards/sist/fdd030f0-dfd3-443f-9191-22c45ed8d08b/sist-iso-5763-2011>

# Photography — Electronic flash equipment — Automatic control of exposure

## 1 Scope

This International Standard applies exclusively to the automatic exposure control built into or coupled with electronic flash equipment.

It specifies the methods for measuring the characteristics peculiar to the control such as its accuracy and repeatability. It also lays down the numerical values of the integral of time of the object luminance and of the exposure given to an object by flash equipment with automatic exposure control, as well as the maximum deviation from these nominal values. Furthermore, the measuring conditions are stated under which the adjustment of the automatic exposure control is to be tested.

Definitions and measuring methods concerning electronic flash equipment without automatic control of exposure are specified in ISO 2827.

It is assumed that when testing the automatic exposure control, the optical axis of the sensor of the control and of the lamp head of the electronic flash equipment are, when fitted to a camera, substantially coincident with that of the taking lens of the camera.

## 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 517 : 1973, *Photography — Still cameras — Lens aperture markings*.

ISO 1230 : 1973, *Photography — Determination of flash guide numbers*.

ISO 2240 : 1982, *Photography — Colour reversal camera films — Determination of ISO speed*.

ISO 2721 : 1982, *Photography — Cameras — Automatic controls of exposure*.

ISO 2827 : 1988, *Photography — Electronic flash equipment — Determination of light output and performance*.

ISO 5800 : 1987, *Photography — Colour negative films for still photography — Determination of ISO speed*.

ISO 6728 : 1983, *Photography — Camera lenses — Determination of colour contribution index*.

CIE Publication No. 38.9 (TC-2.3.) : 1977, *Radiometric and photometric characteristics of materials and their measurement*.

## 3 Definitions

For the purposes of this International Standard, the following definitions apply.

**3.1 automatic exposure control:** Exposure control by a photoelectric measuring device which measures the luminance of the object, integrates the light with respect to time, and terminates the exposure when the integral reaches a predetermined value.

**3.2 automatic distance range:** The range of distance between the object and the flash equipment in which the automatic exposure control can be used in accordance with the indications of the manufacturer. This range depends among others on the guide number of the flash equipment, on the adjustment of the automatic exposure control, and on the luminance coefficient of the object.

**3.3 angle of response of sensor for automatic operation:** The angle of response is the half angle from axis of the reflector of the flash equipment within which the response does not change more than 10 % under the conditions specified in 4.2.2. There are four half angles of response, i.e. on the right, on the left, at the top, and at the bottom of the axis of the reflector.

## ISO 5763 : 1989 (E)

## 4 Adjustment of automatic flash-exposure control

### 4.1 Measurement of the adjustment

#### 4.1.1 Exposure in the focal plane of a camera

The calibration adjustment of the exposure control shall provide, in a camera (with lens transmittance  $\tau = 0,90$ ), focal-plane exposure of

$$H_F = \frac{H_C}{S} \quad \text{or} \quad H_F = \frac{H_C}{10^{(S^\circ - 1)/10}} \quad \dots (1)$$

where

$H_C$  is a constant, in lux seconds (= 10 lx·s);

$S$  is the ISO speed (arithmetic);

$S^\circ$  is the ISO speed (logarithmic);

the equipment being used with the standard test object.

NOTE — The exposure determined above is expected to be the same as that obtained without automatic exposure control using the manufacturer's assigned guide number  $Z$  and with the flash located at a distance  $d = Z/A_z$  (expressed in metres), when the standard test object is used.  $A_z$  is the  $f$ -number of the camera lens.

The measured value of the exposure in the focal plane of a camera (with lens transmittance  $\tau = 0,90$ ) shall not differ from the value  $H_F$  according to equation (1) by more than the difference which corresponds to 0,5  $E_v$  (1  $E_v$ , exposure value, is equivalent to a factor of 2 changes in exposure), i.e. it shall lie between 0,7  $H_F$  and 1,4  $H_F$  (manufacturing tolerance).

#### 4.1.2 Standard test object

The standard test object shall be a non-selective neutral colour, having a diffusely reflecting plane surface. The light reflected from the test object is expressed in terms of its luminance in candelas per square metre per lux of illuminance. The term is named "luminance coefficient  $q$ ", the standard value being  $q_n = 0,08 \text{ cd}\cdot\text{m}^{-2}\cdot\text{lx}^{-1}$ . This corresponds with a reflectance of about 25 % for a uniform diffuser.

NOTE — In the case of illuminating the object by means of an artificial light source, the exposure  $H_F$  in the focal plane of a camera is

$$H_F = \frac{bq \Omega_0}{A^2 d^2} \int I dt \quad \dots (2)$$

where

$b$  is a constant, in lux square metres per candela, by means of which mainly the radiation attenuation in a representative lens is considered ( $b = 0,65 \text{ lx}\cdot\text{m}^2\cdot\text{cd}^{-1}$ );

$q$  is the luminance coefficient, in candelas per square metre per lux, of the object;

$A$  is the  $f$ -number;

$\Omega_0$  is the solid angle = 1 sr;

$d$  is the distance, in metres, of the light source from the object;

$I$  is the luminous intensity, in candelas, of the light source.

ISO 2721 specifies the mean exposure required by a film with the speed ISO 100/21° to 0,10 lx·s. The defining equation for the guide number (see ISO 1230) establishes a relation between the output or the time integral of the luminous intensity of the artificial light source and the guide number. When inserting the corresponding values in the equation (2), one obtains the luminance coefficient of a mean object, in the case of indoor photography being  $q_n = 0,08 \text{ cd}\cdot\text{m}^{-2}\cdot\text{lx}^{-1}$ . This value has been confirmed by measurements on different indoor scenes, where the lighting is generally from the normal to the object.

#### 4.1.3 Distance from flash source to test object

Using the standard test object, and with the equipment preset for film speed ISO 100/21°, the measuring distance  $d_m$  from the front face of source to test object is

$$\begin{aligned} d_m &= 2 \text{ m for } d_{\text{max}} < 8 \text{ m} \\ d_m &= 4 \text{ m for } d_{\text{max}} > 6 \text{ m} \end{aligned} \quad \dots (3)$$

NOTE — In the  $d_{\text{max}}$  range between 6 m and 8 m  $d_m$  may be either 2 m or 4 m.

Flash equipment of special design that does not include the 2 m or 4 m distance in its normal automatic distance range may be tested at a different distance as specified by the manufacturer.

If the test object has a luminance coefficient different from  $q_n$ , the distance for test can be calculated from equation

$$d'_m = d_m \left( \frac{q}{q_n} \right)^{1/2} \quad \dots (4)$$

#### 4.1.4 Conditions for test

Test conditions, in addition to those of 4.1.3, shall be as follows:

- measurements shall be made under conditions of dark, non-reflective surroundings;
- the ambient temperature shall be  $23 \text{ }^\circ\text{C} \pm 3 \text{ }^\circ\text{C}$  and relative humidity of  $65 \% \pm 20 \%$ ;
- the axis of the reflector shall be within  $2^\circ$  of the optical axis accurately aligned with the normal to the centre of the test object;
- the test object shall subtend an angle substantially larger than the angle of response of the sensor in or at the automatic flash equipment or the field of the taking lens of the camera used for a test, whichever is larger;
- the test object should be a uniform diffuser, or at least its diffusing characteristics shall be such that when illuminated from the normal, the luminance when measured from an angle  $60^\circ$  from the normal shall be not less than 50 % of that measured from the normal;
- the spectral reflectance of the test object shall be uniform within  $\pm 10 \%$  over the wavelength range from 380 nm to 1 050 nm;
- the capacitors in the electronic flash unit shall be initially charged for three times the time interval required for the ready light signal to show;
- immediately prior to measuring the integrated luminous energy, the equipment must be flashed a number of times



equal to one-tenth the claimed number of flashes per charge, but not fewer than 5 flashes nor more than 25 flashes. Each flash shall be released at "ready indication". For line powered equipment, the unit shall be operated 25 times;

i) the integrated luminous energy for three successive flashes at 1 min intervals shall be measured. The average of three readings shall be taken.

#### 4.1.5 Measurement of exposure in the focal plane

The exposure in the focal plane of a camera is measured as described in ISO 2721.

The following conditions shall be observed in setting up a standard laboratory camera:

a) the camera shall be located at the measuring distance  $d_m$  and the  $f$ -number of the camera lens adjusted for a given film speed as prescribed by the manufacturer of the flash equipment;

b) the camera shall conform to the following requirements:

- 1) the format shall be 24 mm × 36 mm;
- 2) operation of the camera shutter shall not prevent the flash light from reaching any part of the focal plane;
- 3) the focal length of the camera lens shall be about 50 mm and all apertures ( $f$ -numbers) shall be calibrated in accordance with ISO 517;
- 4) camera flare correction factor shall be not greater than 1,03;
- 5) colour contribution of the lens shall conform to ISO 6728. The transmittance at 360 nm shall be less than 0,10;
- 6) total visual transmittance of the lens shall be about 0,90;
- 7) the lens shall be focused at the test object distance;
- 8) the vignetting factor shall be 1,0;
- 9) the flash unit axis should be substantially coincident with the lens axis;
- 10) the value of the constant  $b$  of the test camera shall be equal to  $0,65 \text{ lx}\cdot\text{m}^2\cdot\text{cd}^{-1}$ .

#### 4.1.6 Measurement of the time integral of object luminance

Another method of evaluating the luminous output of the electronic flash unit is to measure the luminance of the test object during the flash. This measurement is made with an integrating luminance meter. The instantaneous values of test object luminance  $L_o$  for corresponding instantaneous values of focal-plane illuminance  $E_F$ , are given by the equation

$$E_F = \frac{bL_o}{A^2} \quad \dots (5)$$

The corresponding value is

$$H_F = \frac{b}{A^2} \int L_o dt \quad \dots (6)$$

from which the integral of the test object luminance is

$$\int L_o dt = \frac{A^2 H_F}{b} \quad \dots (7)$$

where

$L_o$  is the luminance, measured in candelas per square metre, of the object;

$A$  is the  $f$ -number of camera lens;

$t$  is the time, in seconds;

$b$  is a constant, in lux square metres per candela ( $= 0,65 \text{ lx}\cdot\text{m}^2\cdot\text{cd}^{-1}$ );

$H_F$  is the exposure, in lux seconds, measured in the focal plane (for film speed ISO 100/21°); [the value of  $H_F$  can be calculated from the measurement and from the equation (6)].

#### 4.1.7 Measurement of the object exposure

The third method of measuring the light output of the electronic flash unit is to measure the exposure  $H_o$  of the test object. Knowing the luminance coefficient of the test object,  $q$ , the required exposure of the test object can be calculated from equation (9).

$$E_o \stackrel{\text{def}}{=} \frac{L_o}{q} \quad \text{and} \quad H_o \stackrel{\text{def}}{=} \int E_o dt = \int \frac{L_o}{q} dt \quad \dots (8)$$

By use of equation (6)

$$H_o = \int E_o dt = \frac{A^2 H_F}{qb} \quad \dots (9)$$

The value of  $H_o$  can be measured with an integrating light-meter and the focal-plane exposure calculated from equation (9).

#### 4.1.8 Repeatability of automatic exposure control

The repeatability of the exposure, measured by any of the three methods, for successive flashes of the same flash unit shall be within  $\pm 0,25 E_v$ .

#### Test method

To determine repeatability of the light output 10 flashes are evaluated, the flash being fired under conditions as in 4.1.2, 4.1.3 and 4.1.4 at not less than 30 s after ready light indication. The light may be evaluated by any of the three methods described above, the method given in 4.1.7 is, however, recognized as being the most simple.