

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Multicore and symmetrical pair/quad cables for digital communications –
Part 7: Symmetrical pair cables with transmission characteristics up to
1 200 MHz – Sectional specification for digital and analog communication cables**

**Câbles multiconducteurs à paires symétriques et quartes pour transmissions
numériques –**

**Partie 7: Câbles à paires symétriques avec caractéristiques de transmission
jusqu'à 1 200 MHz – Spécification intermédiaire pour câbles de transmissions
numériques et analogiques**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2012 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Liens utiles:

Recherche de publications CEI - www.iec.ch/searchpub

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Just Published CEI - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Multicore and symmetrical pair/quad cables for digital communications – Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analog communication cables

Câbles multiconducteurs à paires symétriques et quartes pour transmissions numériques –

Partie 7: Câbles à paires symétriques avec caractéristiques de transmission jusqu'à 1 200 MHz – Spécification intermédiaire pour câbles de transmissions numériques et analogiques

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.120.20

ISBN 978-2-8322-0563-1

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES
FOR DIGITAL COMMUNICATIONS –****Part 7: Symmetrical pair cables with transmission
characteristics up to 1 200 MHz –
Sectional specification for digital and analog
communication cables**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 61156-7 edition 1.1 contains the first edition (2003) [documents 46C/573/FDIS and 46C/591/RVD] and its amendment 1 (2012) [documents 46C/956/CDV and 46C/965/RVC].

A vertical line in the margin shows where the base publication has been modified by amendment 1. Additions and deletions are displayed in red, with deletions being struck through.

International Standard IEC 61156-7 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories.

The bilingual version (2003-11) replaces the English version including its Corrigendum 1 (2003-09).

The French version has not been voted upon.

This standard is to be read in conjunction with IEC 61156-1.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

IEC 61156-7:2003

<https://standards.iteh.ai/en/standards/iec/2a0dae41-4fbf-4170-a92c-b09e04d6ad03/iec-61156-7-2003>

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analog communication cables

1 General

1.1 Scope

This sectional specification relates to IEC 61156-1.

The cables described herein may be used for various communication systems as well as for analog systems, such as video, that exist or are under development and which may use as many as four pairs simultaneously. In this sense, this sectional specification provides the cable characteristics required by system developers to evaluate new systems as well as to enhance present systems.

It covers a cable having four individually screened (STP) pairs. The cable may be provided with a common screen over the cable core.

The transmission characteristics are specified up to a frequency of 1 200 MHz and at a temperature of 20 °C.

The cables covered by this sectional specification are intended to operate with voltages and currents normally encountered in communication systems. These cables are not intended to be used in conjunction with low impedance sources, for example, the electric power supply of public utility mains.

1.2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60189-1:1986, *Low-frequency cables and wires with PVC insulation and PVC sheath – Part 1: General test and measuring methods*

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 61156-1:2002, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC 61156-7-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 7-1: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Blank detail specification for digital and analog communication cables*

IEC 62153-4-2, *Metallic telecommunication cable test methods – Part 4-2: Electromagnetic compatibility (EMC) – Screening and coupling attenuation – Injection clamp method*

1.3 Installation considerations

Under consideration.

1.4 Climatic conditions

Under static conditions, the cables shall operate in the temperature range from -20 °C to $+60\text{ °C}$. The temperature dependence of the cables is specified for screened cables and should be taken into account for the design of actual cabling systems.

The recommended temperature range during installation should be indicated in the relevant detail specification.

2 Definitions, materials and cable construction

2.1 Definitions

See 2.1 of IEC 61156-1.

2.2 Materials and cable construction

2.2.1 General remarks

The choice of materials and cable construction shall be suitable for the intended application and installation of the cable. Particular care shall be taken to meet any special requirements for fire performance (such as burning properties, smoke generation, evolution of halogen gas, etc.). A detail specification may be prepared.

2.2.2 Cable construction

The cable construction shall be in accordance with the materials, dimensions and assembly details given in the relevant detail specification.

2.2.3 Conductor

The conductor shall be a solid annealed copper conductor, in accordance with 2.2.3 of IEC 61156-1, and shall have a diameter between 0,5 mm and 0,8 mm.

2.2.4 Insulation

The conductor shall be insulated with a suitable thermoplastic material.

Examples of suitable materials are:

- polyolefin;
- fluoropolymer;
- low-smoke zero-halogen thermoplastic material.

The insulation may be solid or cellular with or without a solid dielectric skin. The insulation shall be continuous and shall have a thickness such that the completed cable meets the specified requirements. The nominal thickness of the insulation shall be compatible with the method of conductor termination.

2.2.5 Colour code of insulation

The colour code is not specified but shall be indicated in the relevant detail specification. The colours shall be readily identifiable and shall correspond reasonably with the standard colours shown in IEC 60304.

NOTE It is acceptable to mark or stripe the "a" wire with the colour of the "b" wire to facilitate pair identification.

2.2.6 Cable element

The cable element shall be a tested pair.

2.2.7 Screening of the cable element

The screen for the cable element shall be in accordance with 2.2.7 of IEC 61156-1. If a braid is used, the minimum braid coverage shall be such as to meet the screening requirements of this standard. The individual components used to screen the cable element shall be in electrical contact.

2.2.8 Cable make-up

The core of the cable may be protected by wrappings of a non-hygroscopic tape.

2.2.9 Screening of cable core

A screen for the cable core may be provided. The screen shall be in accordance with 2.2.9 of IEC 61156-1.

2.2.10 Sheath

The sheath material shall consist of a suitable thermoplastic material.

Examples of suitable materials are:

- polyolefin;
- PVC;
- fluoropolymer;
- low-smoke zero-halogen thermoplastic material.

The sheath shall be continuous, having a uniform thickness.

A non-metallic ripcord may be provided. When provided, the ripcord shall be non-hygroscopic.

2.2.11 Colour of sheath

The colour of the sheath is not specified, but it should be stated in the relevant detail specification.

2.2.12 Identification

Each length of cable shall be identified as to the manufacturer and, when indicated in the relevant detail specification, the year of manufacture, using one of the following methods:

- a) appropriately coloured threads or tapes;
- b) with a printed tape;
- c) printing on the cable core wrapping;
- d) marking on the sheath.

Additional markings, such as length marking etc., are permitted on the cable sheath. When used, such markings should be indicated in the relevant detail specification.

2.2.13 Finished cable

The finished cable shall be adequately protected for storage and shipment.

3 Characteristics and requirements

3.1 General remarks

This clause lists the characteristics and minimum requirements of a cable complying with this specification. Test methods shall be in accordance with Clause 3 of IEC 61156-1. A detail specification may be prepared to identify a specific product and its performance capabilities (see Clause 4).

3.2 Electrical characteristics

The tests shall be carried out on a cable length of not less than 100 m unless otherwise specified.

3.2.1 Conductor resistance

When measured in accordance with 5.1 of IEC 60189-1, the maximum loop-resistance shall not exceed 17,0 Ω /100 m of cable.

3.2.2 Resistance unbalance

When measured in accordance with 2.1.1 of IEC 61156-1, the resistance unbalance of a pair shall not exceed 2,0 %.

3.2.3 Dielectric strength

The test shall be performed on conductor/conductor and conductor/screen with 1,0 kV d.c. for 1 min or, alternately, with 2,5 kV d.c. for 2 s. An a.c. voltage may be used. The a.c. voltage levels in these cases shall be 0,7 kV a.c. for 1 min or, alternately, 1,7 kV a.c. for 2 s.

NOTE When installed in conjunction with power cables, local regulations may require a higher test voltage.

3.2.4 Insulation resistance

The test shall be performed both on

- conductor/conductor;
- conductor/screen.

The minimum insulation resistance at 20 °C shall not be less than 5 000 M Ω ·km.

3.2.5 Mutual capacitance

The mutual capacitance is not specified but may be indicated in the relevant detail specification.

3.2.6 Capacitance unbalance pair to ground

The maximum capacitance unbalance pair to ground shall not exceed 1 200 pF/km at a frequency of 1 kHz.

3.2.7 Transfer impedance

The transfer impedance shall not exceed the values listed in Table 1 at the indicated frequencies.

Table 1 – Transfer impedance

Frequency MHz	Max. surface transfer impedance mΩ/m
1	10
10	10
30	30
100	60

3.2.8 Resistance of the screen

The maximum longitudinal d.c. resistance value of the individual screens or an overall screen ~~is not specified but may be indicated in the relevant detail specification~~ shall be less than 15 mΩ/m.

3.3 Transmission characteristics

All the tests shall be carried out on a cable length of 100 m unless otherwise specified.

3.3.1 Velocity of propagation, delay and differential delay (delay skew)

3.3.1.1 Velocity of propagation

The minimum velocity of propagation for any screened cable element shall be equal to, or greater than, $0,6 \times c$ (c is the speed of light in vacuum) for all frequencies between 4 MHz and 1 200 MHz.

NOTE The velocity of propagation, group velocity and phase velocity are approximately equal for frequencies greater than 4 MHz when measured on symmetric cables, i.e. when the cables are operated in a balanced mode.

3.3.1.2 Delay

The delay for a specified length of cable is understood as the inverse of the velocity of propagation. The maximum delay shall be less than or equal to:

$$\text{delay} = 500 + \frac{36}{\sqrt{f}} \quad [\text{ns}/100 \text{ m}] \quad (1)$$

where f is the frequency in MHz.

3.3.1.3 Differential delay (delay skew)

Differential delay (delay skew) is the difference in delay between any two screened cable elements.

When the delay is measured at $-20 \text{ °C} \pm 2 \text{ °C}$, $20 \text{ °C} \pm 3 \text{ °C}$ and $60 \text{ °C} \pm 1 \text{ °C}$, the maximum differential delay (delay skew) at a given temperature shall not be greater than 25,0 ns/100 m in the frequency range from 4 MHz to 1 200 MHz.

3.3.1.4 Environmental effects

The differential delay (delay skew) due to temperature shall not vary by more than ± 10 ns/100 m over the temperature range from -20 °C to $+60 \text{ °C}$ while still meeting the differential delay (delay skew) of 3.3.1.3

3.3.2 Attenuation

The maximum attenuation α of any pair in the frequency range 4,0 MHz to 1 200 MHz shall be less than, or equal to, the value obtained from equation (2) using the corresponding values of the constants given in Table 2.

$$\alpha = A \times \sqrt{f} + B \times f + \frac{C}{\sqrt{f}} \quad [\text{dB}/100 \text{ m}] \quad (2)$$

Table 2 – Attenuation, constant values

Constants		
A	B	C
1,645	0,01	0,25

The values in Table 3 are for information only.

Table 3 – Attenuation values

Frequency MHz	Attenuation at 20 °C dB/100 m
4	3,5
10	5,4
16	6,8
31,25	9,6
62,5	13,7
100	17,5
200	25,3
300	31,5
600	46,3
900	58,3
1 000	62,0
1 200	69,0

3.3.2.1 Environmental effects

The increase in attenuation due to elevated temperature shall not be greater than 0,2 %/°C.

NOTE The method for determining compliance with this requirement is under consideration.

3.3.3 Unbalance attenuation

The minimum unbalance attenuation near-end (transverse conversion loss or TCL) shall be equal to, or greater than, the value obtained from equation (3) for the frequency range from 1 MHz to 200 MHz.

Unbalance attenuation near-end (TCL):

$$\text{TCL} = 40,0 - 10 \times \log_{10}(f) \quad [\text{dB}] \quad (3)$$

where f is the frequency in MHz.

NOTE The need for ELTCTL and TCL values above 200 MHz are under consideration.