

### **ISO/IEC TS 29125**

Edition 1.0 2024-10

## INTERNATIONAL STANDARD

#### **AMENDMENT 2**

Information technology – Telecommunications cabling requirements for remote powering of terminal equipment

(https://standards.iteh.ai)
Document Preview

ISO/IEC TS 29125:2017/AMD2:2024

ottps://standards.iteh.ai/catalog/standards/jec/0382081d-56cb-4d05-bab0-676ddf15b2c0/jso-jec-ts-29125-2017-amd2-202





### THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2024 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Tel.: +41 22 919 02 11

IEC Secretariat 3, rue de Varembé CH-1211 Geneva 20

info@iec.ch www.iec.ch

Switzerland

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

#### IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Document Preview

(SO/IEC TS 29125:2017/AMD2:2024

ttps://standards.iteh.ai/catalog/standards/iec/0382081d-56cb-4d05-bab0-676ddf15b2c0/iso-iec-ts-29125-2017-amd2-2024



### **ISO/IEC TS 29125**

Edition 1.0 2024-10

## INTERNATIONAL STANDARD

**AMENDMENT 2** 

Information technology – Telecommunications cabling requirements for remote powering of terminal equipment

**Document Preview** 

[SO/IEC TS 29125:2017/AMD2:2024

attps://standards.iteh.ai/catalog/standards/iec/0382081d-56cb-4d05-bab0-676ddf15b2c0/iso-iec-ts-29125-2017-amd2-2024

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 35.200 ISBN 978-2-8322-9893-0

Warning! Make sure that you obtained this publication from an authorized distributor.

# INFORMATION TECHNOLOGY – TELECOMMUNICATIONS CABLING REQUIREMENTS FOR REMOTE POWERING OF TERMINAL EQUIPMENT

#### **AMENDMENT 2**

#### **FOREWORD**

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO National bodies.
- 3) IEC and ISO documents have the form of recommendations for international use and are accepted by IEC and ISO National bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC and ISO documents is accurate, IEC and ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC and ISO National bodies undertake to apply IEC and ISO documents transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC and ISO document and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC and ISO do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC and ISO marks of conformity. IEC and ISO are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this document.
- 7) No liability shall attach to IEC and ISO or their directors, employees, servants or agents including individual experts and members of its technical committees and IEC and ISO National bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this ISO/IEC document or any other IEC and ISO documents.
- https://standar8) Attention is drawn to the Normative references cited in this document. Use of the referenced publications is 7-amd 2-2024 indispensable for the correct application of this document.
  - 9) IEC and ISO draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC and ISO take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC and ISO had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch and www.iso.org/patents. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 2 to IEC ISO/IEC TS 29125:2017 has been prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The text of this Amendment is based on the following documents:

Draft	Report on voting				
JTC1-SC25/3272/DTS	JTC1-SC25/3289/RVDTS				

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Amendment is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1, and the ISO/IEC Directives, JTC 1 Supplement available at www.iec.ch/members\_experts/refdocs and www.iso.org/directives.

#### INTRODUCTION to the amendment

This amendment incorporates changes necessary to extend the current for remote powering using single pair cabling up to 2 000 mA.

#### Introduction

Insert the following after the first bullet of the fourth paragraph:

· guidance on wire diameter and bundling on heating;

#### 1 Scope

Replace the second bullet of list item a), added by Amendment 1, with:

1-pair balanced cabling using currents per conductor of up to 2 000 mA;

In the NOTE, delete "4-pair".

#### 6.3 Temperature rise and current capacity

Replace the last sentence of the first paragraph with the following sentence:

The standards in the ISO/IEC°11801 series specify this temperature up to 60 °C in MICE  $C_1$  environments and 70 °C in MICE  $C_2$  and  $C_3$  environments.

Replace the existing Table 5, added by Amendment 1, with the following new Table 5:

Table 5 – Maximum current per conductor versus temperature rise in a 37 1-pair cable bundle in air and conduit

Temperature rise	Current per conductor							
	0,57 mm wi	re diameter	0,40 mm str diameter		1,02 mm stranded wire diameter (cords)			
К	mA		m.	A	mA			
	air	conduit	air	conduit	air	conduit		
5	866	738	608	518	1 550	1 320		
7,5	1 061	904	744	634	1 900	1 620		
10	1 225	1 044	860	732	2 190	1 870		
12,5	1 370	1 167	961	819	-	2 090		
15	1 501	1 278	1 053	897	-	-		
17,5	1 621	1 381	1 137	969	-	-		
20	1 733	1 476	1 216	1 036	-	-		

Temperature rise above 10 K shown in grey background is not recommended for cables installed in an environment that can reach 50 °C.

NOTE 1 These values are based on conductor temperature measurement of typical cables and cords.

NOTE 2 Currents above 2 000 mA are for information only.

In Table 6, added by Amendment 1, delete column "0,32 mm diameter", as follows:

Table 6 – Calculated worst case current per conductor versus temperature rise in a bundle of 37 1-pair cables of different conductor diameters in air and conduit

	0,40 mm diameter		0,51 mm diameter		0,57 mm diameter		0,65 mm diameter		0,81 mm diameter		1,02 mm diameter	
$\Delta T$	mA											
°C	air	conduit										
2	384	327	490	417	548	466	624	532	779	663	981	835
4	543	463	693	590	775	660	883	753	1 101	938	1 387	1 181
6	666	567	849	723	949	808	1 082	922	1 349	1 149	1 699	1 446
8	769	655	981	835	1 096	933	1 249	1 065	1 558	1 327	1 962	1 670
10	860	732	1 096	934	1 225	1 044	1 397	1 190	1 742	1 484	2 194	1 867
12	942	802	1 201	1 023	1 342	1 143	1 530	1 304	1 908	1 625	2 403	2 046
14	1 017	867	1 297	1 105	1 450	1 235	1 653	1 409	2 061	1 755	2 596	2 210
16	1 087	926	1 387	1 181	1 550	1 320	1 767	1 506	2 203	1 877	2 775	2 362
18	1 153	983	1 471	1 253	1 644	1 400	1 874	1 597	2 337	1 991	2 943	2 506
20	1 216	1 036	1 551	1 321	1 733	1 476	1 976	1 684	2 463	2 098	3 102	2 641

Temperature rise above 10 °C shown in grey background is not recommended.

The values in this table are based on the implicit DC resistance derived from the insertion loss of the various conductor diameters of cable. Manufacturers' and/or suppliers' specifications give information relating to a specific cable.

NOTE 1 The current per conductor for each 1-pair cable is also dependent on the cable construction.

NOTE 2 Currents above 2 000 mA are for information only.