

INTERNATIONAL STANDARD

IEC 60947-1

Fourth edition
2004-03

Low-voltage switchgear and controlgear – Part 1: General rules

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

IEC 60947-1:2004

<https://standards.iteh.ai/doc/standards/iec/51218c7-3112-49f8-aa3c-d50ccb1436b7/iec-60947-1-2004>

This **English-language** version is derived from the original **bilingual** publication by leaving out all French-language pages. Missing page numbers correspond to the French-language pages.



Reference number
IEC 60947-1:2004(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 60947-1

Fourth edition
2004-03

Low-voltage switchgear and controlgear – Part 1: General rules

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

IEC 60947-1:2004

<https://standards.iteh.ai/catalog/standards/iec/251218c7-3112-49f8-aa3c-d50ccb1436b7/iec-60947-1-2004>

© IEC 2004 Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembe, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE **XH**

For price, see current catalogue

CONTENTS

FOREWORD.....	11
1 General	15
1.1 Scope and object.....	15
1.2 Normative references	17
2 Definitions	21
2.1 General terms.....	31
2.2 Switching devices	35
2.3 Parts of switching devices.....	41
2.4 Operation of switching devices.....	49
2.5 Characteristic quantities	57
2.6 Tests	75
3 Classification	77
4 Characteristics.....	77
4.1 General	79
4.2 Type of equipment.....	79
4.3 Rated and limiting values for the main circuit.....	79
4.4 Utilization category	91
4.5 Control circuits	91
4.6 Auxiliary circuits	93
4.7 Relays and releases	93
4.8 Co-ordination with short-circuit protective devices (SCPD)	93
4.9 Switching overvoltages	93
5 Product information.....	93
5.1 Nature of information.....	93
5.2 Marking	95
5.3 Instructions for installation, operation and maintenance.....	97
6 Normal service, mounting and transport conditions.....	99
6.1 Normal service conditions.....	99
6.2 Conditions during transport and storage.....	101
6.3 Mounting	101
7 Constructional and performance requirements	103
7.1 Constructional requirements	103
7.2 Performance requirements.....	117
7.3 Electromagnetic compatibility (EMC).....	133
8 Tests	135
8.1 Kinds of test	135
8.2 Compliance with constructional requirements.....	139
8.3 Performance.....	151
8.4 Tests for EMC	191

Annex A (informative) Examples of utilization categories for low-voltage switchgear and controlgear.....	251
Annex B (informative) Suitability of the equipment when conditions for operation in service differ from the normal conditions	257
Annex C (normative) Degrees of protection of enclosed equipment.....	261
Annex D (informative) Examples of terminals	275
Annex E (informative) Description of a method for adjusting the load circuit.....	289
Annex F (informative) Determination of short-circuit power-factor or time-constant	293
Annex G (informative) Measurement of creepage distances and clearances	297
Annex H (informative) Correlation between the nominal voltage of the supply system and the rated impulse withstand voltage of equipment	309
Annex J (informative) Items subject to agreement between manufacturer and user	313
Annex L (normative) Terminal marking and distinctive number.....	315
Annex M (normative) Flammability test.....	327
Annex N (normative) Requirements and tests for equipment with protective separation.....	333
Annex O (informative) Environmental aspects.....	341
Annex P (informative) Terminal lugs for low voltage switchgear and controlgear connected to copper conductors.....	355
Figure 1 – Test equipment for flexion test (see 8.2.4.3 and Table 5)	219
Figure 2 – Gauges of form A and form B (see 8.2.4.5.2 and Table 7).....	219
Figure 3 – Diagram of the test circuit for the verification of making and breaking capacities of a single-pole equipment on single-phase a.c. or on d.c. (see 8.3.3.5.2)	221
Figure 4 – Diagram of the test circuit for the verification of making and breaking capacities of a two-pole equipment on single-phase a.c. or on d.c. (see 8.3.3.5.2)	223
Figure 5 – Diagram of the test circuit for the verification of making and breaking capacities of a three-pole equipment (see 8.3.3.5.2).....	225
Figure 6 – Diagram of the test circuit for the verification of making and breaking capacities of a four-pole equipment (see 8.3.3.5.2).....	227
Figure 7 – Schematic illustration of the recovery voltage across contacts of the first phase to clear under ideal conditions (see 8.3.3.5.2, item e).....	229
Figure 8a – Diagram of a load circuit adjustment method: load star-point earthed	231
Figure 8b – Diagram of a load circuit adjustment method: supply star-point earthed.....	233
Figure 9 – Diagram of the test circuit for the verification of short-circuit making and breaking capacities of a single-pole equipment on single-phase a.c. or on d.c. (see 8.3.4.1.2)	235
Figure 10 – Diagram of the test circuit for the verification of short-circuit making and breaking capacities of a two-pole equipment on single-phase a.c. or on d.c. (see 8.3.4.1.2)	237
Figure 11 – Diagram of the test circuit for the verification of short-circuit making and breaking capacities of a three-pole equipment (see 8.3.4.1.2).....	239
Figure 12 – Diagram of the test circuit for the verification of short-circuit making and breaking capacities of a four-pole equipment (see 8.3.4.1.2).....	241

Figure 13 – Example of short-circuit making and breaking test record in the case of a single-pole equipment on single-phase a.c. (see 8.3.4.1.8)	243
Figure 14 – Verification of short-circuit making and breaking capacities on d.c. (see 8.3.4.1.8)	245
Figure 15 – Determination of the prospective breaking current when the first calibration of the test circuit has been made at a current lower than the rated breaking capacity (see 8.3.4.1.8, item b))	247
Figure 16 – Actuator test force (see 8.2.5.2.1 and Table 17)	249
Figure C.1 – IP Codes	269
Figure D.1 – Screw terminals	275
Figure D.2 – Pillar terminals	277
Figure D.3 – Stud terminals	279
Figure D.4 – Saddle terminals	281
Figure D.5 – Lug terminals	283
Figure D.6 – Mantle terminals	285
Figure D.7 – Screwless-type terminals	287
Figure E.1 – Determination of the actual value of the factor γ	291
Figure G.1 – Measurement of ribs	299
Figure G.2 – Creepage distance across the fixed and moving insulation of contact carriers ..	299
Figure M.1 – Test fixture for hot wire ignition test	327
Figure M.2 – Circuit for arc ignition test	329
Figure O.1 – Environmental aspects for products related to the life cycle	347
Figure P.1 – Dimensions	355
Table 1 – Standard cross-sections of round copper conductors and approximate relationship between mm ² and AWG/kcmil sizes (see 7.1.7.2)	193
Table 2 – Temperature-rise limits of terminals (see 7.2.2.1 and 8.3.3.3.4)	193
Table 3 – Temperature-rise limits of accessible parts (see 7.2.2.2 and 8.3.3.3.4)	195
Table 4 – Tightening torques for the verification of the mechanical strength of screw-type terminals (see 8.3.2.1, 8.2.6 and 8.2.6.2)	197
Table 5 – Test values for flexion and pull-out tests for round copper conductors (see 8.2.4.4.1)	199
Table 6 – Test values for pull-out test for flat copper conductors (see 8.2.4.4.2)	199
Table 7 – Maximum conductor cross-sections and corresponding gauges (see 8.2.4.5.1)	201
Table 8 – Tolerances on test quantities (see 8.3.4.3, item a))	201
Table 9 – Test copper conductors for test currents up to 400 A inclusive* (see 8.3.3.3.4)	203
Table 10 – Test copper conductors for test currents above 400 A and up to 800 A inclusive* (see 8.3.3.3.4)	203
Table 11 – Test copper bars for test currents above 400 A and up to 3 150 A inclusive (see 8.3.3.3.4)	205
Table 12 – Impulse withstand test voltages	207
Table 12A – Dielectric test voltage corresponding to the rated insulation voltage	207

Table 13 – Minimum clearances in air.....	209
Table 14 – Test voltages across the open contacts of equipment suitable for isolation	209
Table 15 – Minimum creepage distances	211
Table 16 – Values of power-factors and time-constants corresponding to test currents, and ratio n between peak and r.m.s. values of current (see 8.3.4.3, item a)	213
Table 17 – Limits of actuator test force for given types of actuator (see 8.2.5.2.1).....	213
Table 20 – Test values for conduit pull-out test (see 8.2.7.1)	213
Table 21 – Test values for conduit bending test (see 8.2.7.2).....	215
Table 22 – Test values for conduit torque test (see 8.2.7.1 and 8.2.7.3).....	215
Table 23 – Tests for EMC – Immunity (see 8.4.1.2)	215
Table 24 – Acceptance criteria when EM disturbances are present	217
Table H.1 – Correspondence between the nominal voltage of the supply system and the equipment rated impulse withstand voltage, in case of overvoltage protection by surge-arresters according to IEC 60099-1	311
Table M.1 – HWI and AI characteristics	331
Table P.1 – Examples of terminal lugs for low voltage switchgear and controlgear connected to copper conductors.....	355

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

IEC 60947-1:2004

<https://standards.iteh.ai/standards/iec/5f218c7-3112-49f8-aa3c-d50ccb1436b7/iec-60947-1-2004>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR –**Part 1: General rules**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60947-1 has been prepared by subcommittee 17B: Low-voltage switchgear and controlgear, of IEC technical committee 17: Switchgear and controlgear.

This fourth edition of IEC 60947-1 cancels and replaces the third edition published in 1999, amendment 1 (2000) and amendment 2 (2001).

The document 17B/1324/FDIS, circulated to the National Committees as amendment 3, led to the publication of this new edition.

The text of this standard is based on the third edition, its amendments 1 and 2, and the following documents:

FDIS	Report on voting
17B/1324/FDIS	17B/1330/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until 2007. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

Withdrawing

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

IEC 60947-1:2004
<https://standards.iteh.ai/catalog/standards/iec/51218c7-3112-49f8-aa3c-d50ccb1436b7/iec-60947-1-2004>

LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 1: General rules

1 General

The purpose of this standard is to harmonize as far as practicable all rules and requirements of a general nature applicable to low-voltage switchgear and controlgear in order to obtain uniformity of requirements and tests throughout the corresponding range of equipment and to avoid the need for testing to different standards.

All those parts of the various equipment standards which can be considered as general have therefore been gathered in this standard together with specific subjects of wide interest and application, e.g. temperature-rise, dielectric properties, etc.

For each type of low-voltage switchgear and controlgear, only two main documents are necessary to determine all requirements and tests:

- 1) this basic standard, referred to as "Part 1" in the specific standards covering the various types of low-voltage switchgear and controlgear;
- 2) the relevant equipment standard hereinafter referred to as the "relevant product standard" or "product standard".

For a general rule to apply to a specific product standard, it shall be explicitly referred to by the latter, by quoting the relevant clause or subclause number of this standard followed by "IEC 60947-1" e.g. "7.2.3 of IEC 60947-1".

A specific product standard may not require, and hence may omit, a general rule (as being not applicable), or it may add to it (if deemed inadequate in the particular case), but it may not deviate from it, unless there is a substantial technical justification.

NOTE The product standards due to be part of the series of IEC standards covering low-voltage switchgear and controlgear are:

- 60947-2: Part 2: Circuit-breakers
- 60947-3: Part 3: Switches, disconnectors, switch-disconnectors and fuse combination units
- 60947-4: Part 4: Contactors and motor-starters
- 60947-5: Part 5: Control-circuit devices and switching elements
- 60947-6: Part 6: Multiple function equipment
- 60947-7: Part 7: Ancillary equipment

1.1 Scope and object

This standard applies, when required by the relevant product standard, to switchgear and controlgear hereinafter referred to as "equipment" and intended to be connected to circuits, the rated voltage of which does not exceed 1 000 V a.c. or 1 500 V d.c.

It does not apply to low-voltage switchgear and controlgear assemblies which are dealt with in IEC 60439.

NOTE In certain clauses or subclauses of this standard, the equipment covered by this standard is also referred to as "device", to be consistent with the text of such clauses or subclauses.

The object of this standard is to state those general rules and requirements which are common to low-voltage equipment as defined in 1.1, including for example:

- definitions;
- characteristics;
- information supplied with the equipment;
- normal service, mounting and transport conditions;
- constructional and performance requirements;
- verification of characteristics and performance.

1.2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050(151):2001, *International Electrotechnical Vocabulary (IEV) – Chapter 151: Electrical and magnetic devices*

IEC 60050(441):1984, *International Electrotechnical Vocabulary (IEV) – Chapter 441: Switchgear, controlgear and fuses*
Amendment 1 (2000)

IEC 60050(604):1987, *International Electrotechnical Vocabulary (IEV) – Chapter 604: Generation, transmission and distribution of electricity – Operation*
Amendment 1 (1998)

IEC 60050(826):1982, *International Electrotechnical Vocabulary (IEV) – Chapter 826: Electrical installations of buildings*
Amendment 1 (1990)
Amendment 2 (1995)
Amendment 3 (1999)

IEC 60060, *High-voltage test techniques*

IEC 60068-2-78:2001, *Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state*

IEC 60071-1:1993, *Insulation co-ordination – Part 1: Definitions, principles and rules*

IEC 60073:2002, *Basic and safety principles for man-machine interface, marking and identification – Coding principles for indicators and actuators*

IEC 60085:1984, *Thermal evaluation and classification of electrical insulation*

IEC 60112:2003, *Method for the determination of the proof and the comparative tracking indices of solid insulating materials*

IEC 60216, *Guide for the determination of thermal endurance properties of electrical insulating materials*

IEC 60269-1:1998, *Low-voltage fuses – Part 1: General requirements*

IEC 60269-2:1986, *Low-voltage fuses – Part 2: Supplementary requirements for fuses for use by authorized persons (fuses mainly for industrial application)*
Amendment 1 (1995)
Amendment 2 (2001)

IEC 60364-4-44:2001, *Electrical installations of buildings – Part 4-44: Protection for safety – Protection against voltage disturbances and electromagnetic disturbances*
Amendment 1 (2003)

IEC 60417-DB:2002¹, *Graphical symbols for use on equipment*

IEC 60439-1:1999, *Low-voltage switchgear and controlgear assemblies – Part 1: Type-tested and partially type-tested assemblies*

IEC 60445:1999, *Basic and safety principles for man-machine interface, marking and identification – Identification of equipment terminals and of terminations of certain designated conductors, including general rules of an alphanumeric system*

IEC 60447:1993, *Man-machine interface (MM) – Actuating principles*

IEC 60529:1989, *Degrees of protection provided by enclosures (IP code)*
Amendment 1 (1999)

IEC 60617-DB:2001¹, *Graphical symbols for diagrams*

IEC 60664-1:1992, *Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests – Basic safety publication*
Amendment 1 (2000)
Amendment 2 (2002)

IEC 60695-2-2:1991, *Fire hazard testing – Part 2: Test methods – Section 2: Needle-flame test*
Amendment 1 (1994)

IEC 60695-2-10:2000, *Fire hazard testing – Part 2-10: Glowing/hot-wire based test methods – Glow-wire apparatus and common test procedure*

IEC 60695-2-11:2000, *Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products*

IEC 60695-11-10:1999, *Fire hazard testing – Part 11-10: Test flames – 50 W horizontal and vertical flame test methods*

IEC 60947-5-1:1997, *Low-voltage switchgear and controlgear – Part 5-1: Control circuit devices and switching elements – Electromechanical control circuit devices*
Amendment 1 (1999)
Amendment 2 (1999)

IEC 60981:1989, *Extra-heavy duty rigid steel conduits for electrical installations*

IEC 61000-3-2:2000, *Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)*
Amendment 1 (2001)

IEC 61000-3-3:1994, *Electromagnetic compatibility (EMC) – Part 3: Limits – Section 3: Limitation of voltage fluctuations and flicker in low-voltage supply systems for equipment with rated current ≤ 16 A*
Amendment 1 (2001)

¹ “DB” refers to the IEC on-line database.

IEC 61000-4-2:1995, *Electromagnetic compatibility (EMC) – Part 4: Testing and measurement techniques – Section 2: Electrostatic discharge immunity test* – Basic EMC publication
Amendment 1 (1998)
Amendment 2 (2000)

IEC 61000-4-3:2002, *Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test*
Amendment 1:2002

IEC 61000-4-4:1995, *Electromagnetic compatibility (EMC) – Part 4: Testing and measurement techniques – Section 4: Electrical test transient/burst immunity test* – Basic EMC publication
Amendment 1 (2000)
Amendment 2 (2001)

IEC 61000-4-5:1995, *Electromagnetic compatibility (EMC) – Part 4: Testing and measurement techniques – Section 5: Surge immunity test*
Amendment 1 (2000)

IEC 61000-4-6:1996, *Electromagnetic compatibility (EMC) – Part 4: Testing and measurement techniques – Section 6: Immunity to conducted disturbances, induced by radio-frequency fields*
Amendment 1 (2000)

IEC 61000-4-8:1993, *Electromagnetic compatibility (EMC) – Part 4: Testing and measurement techniques – Section 8: Power frequency magnetic field immunity test* – Basic EMC Publication
Amendment 1 (2000)

IEC 61000-4-11:1994, *Electromagnetic compatibility (EMC) – Part 4: Testing and measurement techniques – Section 11: Voltage dips, short interruptions and voltage variations immunity tests*
Amendment 1 (2000)

IEC 61000-4-13:2002, *Electromagnetic compatibility (EMC) – Part 4-13: Testing and measurement techniques – Harmonics and interharmonics including mains signalling at a.c. power port, low-frequency immunity tests*

IEC 61140:2001, *Protection against electric shock – Common aspects for installation and equipment*

IEC 61180 (all parts), *High-voltage test techniques for low voltage equipment*

CISPR 11:2003, *Industrial, scientific and medical (ISM) radio-frequency equipment – Electromagnetic disturbance characteristics – Limits and methods of measurement*

2 Definitions

NOTE 1 Most of the definitions listed in this clause are taken unchanged from the IEV (IEC 60050). When this is the case, the IEV reference is given in brackets with the title (the first group of 3 figures indicates the IEV chapter reference).

When an IEV definition is amended, the IEV reference is not indicated with the title, but in an explanatory note.

Alphabetical index of definitions

NOTE 2 The alphabetical list of ratings, characteristics and symbols is given in clause 4.

	Reference	Page
A		
"a" contact	2.3.12	45
Actuating force (moment)	2.4.17	53
Actuating system (of a mechanical switching device)	2.3.16	45
Actuator	2.3.17	45
Ambient air temperature	2.1.9	33
Anti-pumping device	2.3.20	47
Applied voltage (for a switching device)	2.5.32	67
Arcing contact	2.3.8	43
Arcing time (of a multipole switching device)	2.5.41	69
Arcing time (of a pole or a fuse)	2.5.40	69
Automatic control	2.4.5	49
Auxiliary circuit (of a switching device)	2.3.4	43
Auxiliary contact	2.3.10	45
Auxiliary switch (of a mechanical switching device)	2.3.11	45
B		
"b" contact	2.3.13	45
Back-up protection	2.5.24	65
Break contact	2.3.13	45
Breaking capacity (of a switching device or a fuse)	2.5.12	61
Breaking current (of a switching device or a fuse)	2.5.11	61
Break time	2.5.42	69
C		
Circuit-breaker	2.2.11	39
Clamping unit	2.3.25	47
Clearance	2.5.46	71
Clearance between open contacts (gap)	2.5.49	71
Clearance between poles	2.5.47	71
Clearance to earth	2.5.48	71
Closed position (of a mechanical switching device)	2.4.20	53
Closing operation (of a mechanical switching device)	2.4.8	51
Closing time	2.5.44	69
Comparative tracking index (CTI)	2.5.65	75
Conditional short-circuit current (of a circuit or a switching device)	2.5.29	65
Conductive part	2.1.10	33
Contact (of a mechanical switching device)	2.3.5	43
Contact piece	2.3.6	43
Contact (mechanical)	2.2.12	39
Contact relay	2.2.14	39
Control circuit (of a switching device)	2.3.3	43
Control circuit device	2.2.16	39
Control contact	2.3.9	43
Controlgear	2.1.3	31
Control switch (for control and auxiliary circuits)	2.2.17	41
Conventional non-tripping current (of an over-current relay or release)	2.5.30	65
Conventional tripping current (of an over-current relay or release)	2.5.31	65
Co-ordination of insulation	2.5.61	75
Creepage distance	2.5.51	71
Critical load current	2.5.16	61
Critical short-circuit current	2.5.17	63
Current setting (of an over-current or overload relay or release)	2.4.37	57
Current setting range (of an over-current or overload relay or release)	2.4.38	57
Cut-off current	2.5.19	63