

SLOVENSKI STANDARD
SIST EN 61076-2:2002**01-september-2002**

Connectors with assessed quality, for use in d.c., low frequency analogue and digital high-speed data applications - Part 2: Circular connectors with assessed quality - Sectional specification (IEC 61076-2:1990)

Connectors for use in d.c. low-frequency analogue and in digital high-speed data applications -- Part 2: Circular connectors with assessed quality - Sectional specification

Steckverbinder für Gleichspannungs- und Niederfrequenzanwendungen sowie digitale Anwendungen mit hoher Übertragungsrate -- Teil 2: Rundsteckverbinder mit bewerteter Qualität - Rahmenspezifikation (standards.iteh.ai)

Connecteurs pour applications analogiques en courant continu et à basse fréquence et pour applications numériques utilisant des débits élevés pour le transfert des données -- Partie 2: Connecteurs circulaires sous assurance de la qualité - Spécification intermédiaire

Ta slovenski standard je istoveten z: EN 61076-2:1999

ICS:

31.220.10 Xcã ãñ Ácã } ã^É [] ^\ q |lä Plug-and-socket devices.
Connectors

SIST EN 61076-2:2002**en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 61076-2:2002

<https://standards.iteh.ai/catalog/standards/sist/ea9b39da-43b0-40ce-88c2-8fc0ebc5f66a/sist-en-61076-2-2002>

EUROPEAN STANDARD
 NORME EUROPÉENNE
 EUROPÄISCHE NORM

EN 61076-2

April 1999

ICS 31.220.10

English version

**Connectors for use in d.c. low-frequency analogue and
 digital high-speed data applications
 Part 2: Circular connectors with assessed quality
 Sectional specification
 (IEC 61076-2:1998)**

Connecteurs pour applications
 analogiques en courant continu et à
 basse fréquence et pour applications
 numériques utilisant des débits élevés
 pour le transfert des données
 Partie 2: Connecteurs circulaires sous
 assurance de la qualité - Spécification
 intermédiaire
 (CEI 61076-2:1998)

Steckverbinder für Gleichspannungs-
 und Niederfrequenzanwendungen
 sowie digitale Anwendungen mit hoher
 Übertragungsrate
 Teil 2: Rundsteckverbinder mit
 bewerteter Qualität
 Rahmenspezifikation
 (IEC 61076-2:1998)

This European Standard was approved by CENELEC on 1999-04-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
 Comité Européen de Normalisation Electrotechnique
 Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 48B/731/FDIS, future edition 1 of IEC 61076-2, prepared by SC 48B, Connectors, of IEC TC 48, Electromechanical components and mechanical structures for electronic equipment, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 61076-2 on 1999-04-01.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2000-01-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2002-01-01

Annexes designated "normative" are part of the body of the standard.
In this standard, annex ZA is normative.
Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 61076-2:1998 was approved by CENELEC as a European Standard without any modification.

(standards.iteh.ai)

SIST EN 61076-2:2002

<https://standards.iteh.ai/catalog/standards/sist/ea9b39da-43b0-40ce-88c2-8f0ebc5f66a/sist-en-61076-2-2002>

CONTENTS

Clause	Page
1 General	4
1.1 Scope	4
1.2 Normative references	4
2 Technical information	5
2.1 Terminology	5
2.2 Classification into climatic categories	5
2.3 Creepage and clearance distances	5
2.4 Current-carrying capacity	5
2.5 IEC type designation	6
2.6 Marking.....	6
2.7 Groups of related connectors	7
2.8 Interchangeability level (under consideration)	7
2.9 Delivery conditions	7
2.9.1 Packaging	7
2.9.2 Storage	7
3 Quality assessment procedures	8
4 Tests and test schedules	8
4.1 General.....	8
4.2 Test procedures and measuring methods	8
4.3 Preconditioning	8
4.4 Wiring and mounting of specimens	8
4.4.1 Wiring	8
4.4.2 Mounting	9
4.5 Test schedules	9
4.5.1 Basic (minimum) test schedule	10
4.5.2 Full test schedule	11
4.5.2.1 Test group P – Preliminary tests	12
4.5.2.2 Test group AP – Dynamic/climatic tests	13
4.5.2.3 Test group BP – Mechanical/climatic tests	15
4.5.2.4 Test group CP – Moisture	16
4.5.2.5 Test group DP – Endurance	17
4.5.2.6 Test group EP – Mould/Fire	18
4.5.2.7 Test group FP – Fluids.....	18
4.5.2.8 Test group GP – Connection method tests	19
4.5.2.9 Test group HP – Accessories	19
4.5.2.10 Test group KP – Climatic sequence.....	20
4.5.2.11 Test group LP – Dynamic corrosion.....	20
4.5.3 Qualification approval test schedule.....	21
4.5.4 Quality conformance inspection, lot-by-lot tests	23
4.5.5 Quality conformance inspection, periodic tests	24
4.5.6 Capability approval.....	25
5 Blank detail specification – General	25
Annex ZA (normative) Normative references to international publications with their corresponding European publications	26

**CONNECTORS FOR USE IN DC,
LOW-FREQUENCY ANALOGUE AND DIGITAL
HIGH SPEED DATA APPLICATIONS –**

**Part 2: Circular connectors with assessed quality –
Sectional specification**

1 General

1.1 Scope

This part of IEC 61076 establishes uniform specifications, type testing requirements and quality assessment procedures for circular connectors.

It contains a choice of all test methods and sequences, severities and preferred values for dimensions and characteristics.

It gives guidance on the rules for the preparation of detail specifications for circular connectors of assessed quality, used in electronic and electrical equipment and systems.

It should be used in conjunction with the generic specification IEC 61076-1 and with the relevant detail specification.

In the event of conflict between the sectional specification and the detail specification, the requirements of the detail specification shall prevail.

1.2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 61076. At the time of publication, the editions indicated were valid. All normative documents are subject to revision, and parties to agreements based on this part of IEC 61076 are encouraged to investigate the possibility of applying the most recent editions of the normative documents listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60352-1:1997, *Solderless connections – Part 1: Solderless wrapped connections – General requirements, test methods and practical guidance*

IEC 60352-2:1990, *Solderless connections – Part 2: Solderless crimped connections – General requirements, test methods and practical guidance*

IEC 60352-3:1993, *Solderless connections – Part 3: Solderless accessible insulation displacement connections – General requirements, test methods and practical guidance*

IEC 60352-4:1994, *Solderless connections – Part 4: Solderless non-accessible insulation displacement connections – General requirements, test methods and practical guidance*

IEC 60352-5:1995, *Solderless connections – Part 5: Solderless press-in connections – General requirements, test methods and practical guidance*

IEC 60512: — *Electromechanical components for electronic equipment - Basic testing procedures and measuring methods*

IEC 61076-1:1995, *Connectors with assessed quality, for use in d.c. low frequency analogue and in digital high speed data applications – Part 1: Generic specification*

2 Technical information

2.1 Terminology

The terminology used in and applicable to this specification is stated in 2.1 of IEC 61076-1. IEC 60512-1 also contains applicable terms.

2.2 Classification into climatic categories

The lower and upper temperatures and the duration of the damp heat, steady state test should, unless otherwise impractical, be selected from the preferred values stated in 2.2 of IEC 61076-1. The connectors are classified into climatic categories in accordance with the general rules given in IEC 60068-1. The following preferred temperature ranges and severities of the damp heat steady state test have been selected.

Table 1 – Climatic categories – selected values

Climatic category	Temperature range °C	Damp heat, steady state in days	Identification code ¹⁾
65/350/56	–65 °C to 350 °C	56	U
65/260/56	–65 °C to 260 °C	56	T
65/200/56	–65 °C to 200 °C	56	S
65/175/56	–65 °C to 175 °C	56	X
65/150/56	–65 °C to 150 °C	56	R
65/125/56	–65 °C to 125 °C	56	O
55/155/56	–55 °C to 155 °C	56	Y
55/125/21	–55 °C to 125 °C	21	P
40/100/21	–40 °C to 100 °C	21	N
40/100/10	–40 °C to 100 °C	10	M
25/085/21	–25 °C to 85 °C	21	L
25/070/10	–25 °C to 70 °C	10	K
10/070/04	–10 °C to 70 °C	4	I

¹⁾ Identification code to be used for IEC designation.

2.3 Creepage and clearance distances

The detail specification shall specify creepage and clearance distances in accordance with the requirements of 2.3 of IEC 61076-1. Operating voltages depend on the application and on the applicable or specified safety requirements.

2.4 Current-carrying capacity

The detail specification shall specify the current-carrying capacity of connectors in accordance with the requirements of 2.4 of IEC 61076-1.

2.5 IEC type designation

Connectors conforming to this standard shall be identified by the following indications and in the order given:

- a) The letters "IEC".
- b) The number (2) denoting this sectional specification.
- c) The number of the detail specification (without dashes), being nine characters (e.g. 610764100).
- d) A letter denoting the style of the connector (the system shall be specified in the detail specification).
- e) A letter denoting a housing or body size.
- f) Two numbers denoting the insert arrangement (not necessarily the number of contacts).
- g) A letter denoting the type of contact:
 - M male contact
 - F female contact
 - H hermaphroditic contact
- h) A letter denoting the basic type of termination. The following letters shall be used:
 - E solder termination eyelet
 - S solder termination, solder bucket
 - P solder termination, printed wires
 - C crimp
 - W wire wrap termination
 - I insulation displacement
- i) A letter or number denoting the connector polarization by a particular arrangement of keys and keyways on housing (shell) or bodies, or position of insert in housing such as N, A, B, C, D, W, X, Y, Z or 0, 1, 2, 3, etc. where N and 0 are the neutral position. Neutral position is the normal or standard position.
- j) If prescribed in the detail specification, the variant code may optionally be extended to cover further information, such as climatic category, colour etc.
- k) Where the detail specification provides for a variation of performance and assessment levels, a single number and a letter shall be used to denote performance level (PL) and assessment level (AL) respectively. The number and letter shall be described in the detail specification and shall be included as the final characters of the type of designation.
- l) Identification code letter given in 2.2.

Grouping of information

 - Basic description: a – b – c – d;
 - Body size, contact arrangement; contact type: e – f – g – h;
 - Polarization: i;
 - Performance variant: j – k.

2.6 Marking

Each connector and its associated package shall be marked in accordance with the requirements specified in 2.6 of IEC 61076-1.

2.7 Groups of related connectors

Groups of connectors within a subfamily having common features. Typical examples are: same mounting features but different kinds and numbers of contacts, or equal coupling features but different inserts and types of contacts. A group of related connectors is covered by a single detail specification.

- Type: connectors within a particular subfamily such as a multicontact connector with a threaded coupling.
- Range: the housing (shell) sizes and contact arrangements within a type.
- Style: a particular connector within a type, for example fixed connector for single hole mounting.
- Variant: variations within a type, style or range.

Examples

- family: connector;
- subfamily: circular connector;
- type: circular multi-contact connector with threaded coupling;
- range: shell size 1 with 2 contacts to shell size 3 with 62 contacts;
- variant: shell size 1 with 2 contacts – electroless nickel plating, insulation displacement termination etc.

Iteh STANDARD PREVIEW
(standards.iteh.ai)

2.8 Interchangeability level

Under consideration.

SIST EN 61076-2:2002

2.9 Delivery conditions

Connectors may be delivered with or without contacts (*for removable contacts*) depending on the order. The detail specification shall specify if the shell front face shall be protected with plastic caps. For connectors delivered with contacts the detail specification shall specify:

- the number of additional contacts per size;
- the number of insertion/extraction tools per contact size; and
- the number of filler plugs.

2.9.1 Packaging

The connectors with, if applicable, their contacts, filler plugs and tools shall be packed in transparent, inert plastic bags. The contacts and filler plugs shall be packed in a rigid container to prevent damage. Designation affixed on the packaging shall be in conformity with the product standard designation.

2.9.2 Storage

Storage shall be in a place free from ultraviolet rays and temperature and humidity extremes. Every five years, an inspection shall be made. The date of inspection shall be marked and the product repackaged in accordance with the packaging.

3 Quality assessment procedures

See clause 3 of IEC 61076-1.

4 Tests and test schedules

4.1 General

See clause 4 of IEC 61076-1.

The detail specification shall state the test sequence (in accordance with this standard), and the number of specimens for each test sequence (not less than four mated pairs).

Individual variants may be submitted to type tests for approval of those particular variants.

It is permissible to limit the number of variants tested to a selection representative of the whole range for which approval is required (which may be less than the range covered by the detail specification), but each feature and characteristic shall be proved.

The connectors shall have been processed in a careful and workmanlike manner, in accordance with good current practice.

4.2 Test procedures and measuring methods

The test methods specified and given in the relevant standards are the preferred methods but not necessarily the only ones which can be used. In case of dispute, however, the specified method shall be used as the reference method.

Unless otherwise specified, all tests shall be carried out under standard atmospheric conditions for testing as specified in IEC 60068-1.

Where approval procedures are involved and alternative methods are employed it is the responsibility of the manufacturer to satisfy the authority granting approval that any alternative methods which he may use give results equivalent to those obtained by the methods specified.

4.3 Preconditioning

Before the tests are made, the connectors shall be preconditioned under standard atmospheric conditions for testing as specified in IEC 60068-1 for a period of 24 h unless otherwise specified by the detail specification.

4.4 Wiring and mounting of specimens

4.4.1 Wiring

Where wiring of test specimens is required, the detail specification shall contain information suitable to comply with the selected methods of test.

4.4.2 Mounting

When mounting is required in a test, unless otherwise specified, the connectors shall be rigidly mounted on a metal plate or to specified accessories, whichever is applicable, using the specified connection methods, fixing devices and panel cut-outs as laid down in the detail specification.

4.5 Test schedules

To provide for different applications of connectors, the extent of the test schedule may be different in the various detail specifications.

The *basic* (minimum) test schedule is given in 4.5.1.

The detail specification shall state the tests to be carried out, and shall specify the requirements to be fulfilled.

It is a requirement of this standard that in no case shall the tests required by the detail specification be less than those listed in 4.5.1.

A *full* test schedule is laid down in 4.5.2. This should be used to evaluate connectors used in severe environments (e.g. aircraft or marine environments).

For most connector types, an *intermediate* test schedule may be appropriate. This intermediate test schedule shall then be formed by omitting entire groups and/or conditionings from the full test schedules that are not necessary. Test phase numbers shall not be modified but used as given in 4.5.2.

In the circumstances that the sequence of the test phases in a test group is not entirely appropriate to a particular type or style, the sequence of the tests but not the measurement to be performed subsequent to tests, may be altered for that particular detail specification. The test phase number shall be retained for each test thereby affording clarity should such alteration in sequence be conducted.

Where a detail specification includes additional characteristics which require testing and/or specific test sequences, the appropriate existing or new test (in the form of an annex to the detail specification) shall be in the appropriate place in the test table. These may be specified in an additional test group or groups; see test group HP.