

SLOVENSKI STANDARD
SIST EN 301 842-2 V1.1.1:2003
01-april-2003

Elektromagnetna združljivost (EMC) in zadeve v zvezi z radijskim spektrom (ERM) - Radijska oprema za podatkovno povezavo VHF zrak-tla, 4. način - Tehnične karakteristike in meritve metode za talno opremo - 1. del: Plast podatkovnih povezav

Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment; Part 2: Data link layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 842-2 V1.1.1:2003](#)
<https://standards.iteh.ai/catalog/standards/sist/ad2366df-dd67-4ef6-af30-c21a024c35a7/sist-en-301-842-2-v1-1-1-2003>

Ta slovenski standard je istoveten z: EN 301 842-2 Version 1.1.1

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general
35.100.20	Podatkovni povezovalni sloj	Data link layer

SIST EN 301 842-2 V1.1.1:2003

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 842-2 V1.1.1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/ad2366df-dd67-4eff-af30-c21a024c35a7/sist-en-301-842-2-v1-1-1-2003>

ETSI EN 301 842-2 V1.1.1 (2002-08)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
VHF air-ground Data Link (VDL)
Mode 4 radio equipment;
Technical characteristics and
methods of measurement
for ground-based equipment;
Part 2: Data link layer**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 842-2 V1.1.1:2003

<https://standards.iteh.ai/catalog/standards/sist/ad2366df-dd67-4ef6-af30-c21a024c35a7/sist-en-301-842-2-v1-1-1-2003>



Reference

DEN/ERM-RP05-016-2

Keywords

aeronautical, radio, testing, VHF, digital

ETSI

650 Route des Lucioles
 F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
 Association à but non lucratif enregistrée à la
 Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 842-2 V1.1.1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/ad2366df-dd67-4ef6-af30-c21a024c3577> [Important notice](#)

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
 The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
 All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	7
Foreword.....	7
Introduction	8
1 Scope	9
2 References	10
3 Definitions and abbreviations.....	11
3.1 Definitions.....	11
3.1.1 Basic reference model definitions.....	11
3.1.2 Service conventions definitions	11
3.1.3 General definitions.....	11
3.2 Abbreviations	14
4 General description of VDL Mode 4 ground station link layer.....	15
4.1 General	15
4.2 Ground quarantine.....	15
4.3 System timing.....	15
4.4 Net entry	16
4.5 Autotune capability	16
4.6 Autonomous and fixed access	16
5 Minimum performance specification under standard test conditions.....	16
5.1 MAC sublayer	16
5.1.1 Services.....	16
5.1.2 MAC sublayer services	17
5.1.3 MAC sublayer parameters	17
5.1.3.1 Void..... https://standards.iteh.ai/catalog/standards/sist/ad2366df-dd67-4cf6-af30-022-v1-1-2003	17
5.1.3.2 Parameter M1 (number of slots per superframe)..... https://standards.iteh.ai/catalog/standards/sist/ad2366df-dd67-4cf6-af30-022-v1-1-2003	17
5.1.4 Time synchronization	17
5.1.4.1 Primary.....	17
5.1.4.2 Secondary.....	18
5.1.4.3 Alignment to UTC second	18
5.1.4.4 Data quality level	18
5.1.5 Slot idle/busy notification	18
5.1.5.1 Slot idle detection.....	18
5.1.5.2 Slot busy detection	18
5.1.5.3 Slot occupied detection	19
5.1.6 Transmission processing	19
5.1.7 Received transmission processing	19
5.2 VSS sublayer	19
5.2.1 Services.....	19
5.2.1.1 Error detection.....	19
5.2.1.2 Channel congestion	19
5.2.2 Burst format.....	20
5.2.2.1 VSS burst structure	20
5.2.2.2 Version number.....	20
5.2.2.3 Source address.....	21
5.2.2.4 Station address encoding	21
5.2.2.5 Message ID	21
5.2.2.6 Information field	22
5.2.2.7 Reservation fields.....	23
5.2.2.8 TCP change flag	23
5.2.3 VSS sublayer parameters	23
5.2.3.1 Void.....	24
5.2.3.2 Parameter VS1 (number of ground quarantined slots)	24
5.2.3.3 Parameter VS2 (minimum CCI performance).....	25

5.2.3.4	Parameter VS4 (quarantine slot re-use range).....	25
5.2.4	VSS quality of service parameters.....	25
5.2.4.1	Void.....	25
5.2.4.2	Parameter Q1 (priority)	25
5.2.4.3	Parameters Q2a to Q2d (slot selection range constraint for level n)	26
5.2.4.4	Parameter Q3 (replace queued data)	26
5.2.4.5	Parameter Q4 (number of available slots).....	27
5.2.5	Received transmission processing	27
5.2.6	Reserved access protocol specification.....	28
5.2.6.1	Reservation table	28
5.2.6.2	Selecting slots for transmission or reservation	28
5.2.6.3	Reserved transmissions	30
5.2.6.4	Reservation conflicts	31
5.2.7	Random access protocol specification	32
5.2.7.1	Void.....	32
5.2.7.2	Random access parameters.....	32
5.2.7.3	Random access procedures.....	33
5.2.8	Fixed access protocol specification	34
5.2.8.1	Void.....	34
5.2.8.2	Recommendation	34
5.2.9	Null reservation protocol specification	34
5.2.9.1	Null reservation burst format	34
5.2.10	Periodic broadcast protocol specification	35
5.2.10.1	Periodic broadcast reservation burst format	35
5.2.10.2	Periodic broadcast timers	35
5.2.10.3	Periodic broadcast parameters.....	36
5.2.10.4	Periodic broadcast reception procedures	36
5.2.10.5	Periodic broadcast transmission procedures.....	38
5.2.11	Incremental broadcast protocol specification	40
5.2.11.1	Incremental broadcast reservation burst format	40
5.2.11.2	Incremental broadcast parameters	41
5.2.11.3	Incremental broadcast reception procedures	42
5.2.11.4	Incremental broadcast transmission procedures	42
5.2.12	Combined periodic broadcast and incremental broadcast protocol specification	42
5.2.12.1	Combined periodic broadcast and incremental broadcast reservation burst.....	42
5.2.13	Big negative dither (BND) broadcast protocol specifications	43
5.2.13.1	BND reservation burst format	43
5.2.13.2	BND broadcast parameters.....	44
5.2.13.3	BND broadcast reception procedures	44
5.2.14	Unicast request protocol specification	44
5.2.14.1	Unicast request reservation burst format	44
5.2.14.2	Unicast request reception procedures	45
5.2.15	Information transfer request protocol specification	45
5.2.15.1	Information transfer request reservation burst format	45
5.2.15.2	Information transfer request reception procedures	47
5.2.16	Directed request protocol specification.....	47
5.2.16.1	Directed request reservation burst format	47
5.2.16.2	Directed request parameters	51
5.2.16.3	Directed request reception procedures	51
5.2.16.4	Directed request transmission procedures.....	52
5.2.17	Block reservation protocols specification	53
5.2.17.1	Superframe block reservation burst format	53
5.2.17.2	Second frame block reservation burst format.....	54
5.2.17.3	Superframe block reservation parameters	55
5.2.17.4	Superframe block reservation reception procedures	56
5.2.17.5	Second frame block reservation parameters	58
5.2.17.6	Second frame block reservation reception procedures	58
5.2.17.7	Superframe block reservation transmission procedures	59
5.2.17.8	Second frame block reservation transmission procedures.....	60
5.2.18	Response protocol specification	60
5.2.18.1	Response burst format.....	60
5.2.19	General request protocol specification.....	61

5.2.19.1	General request burst format	61
5.2.19.2	General request procedures	62
5.2.20	General response protocol specification	62
5.2.20.1	General response burst format	62
5.2.20.2	General response procedures	64
5.3	Link Management Entity sublayer	64
5.3.1	Services	64
5.3.2	Synchronization burst format	64
5.3.2.1	Void	64
5.3.2.2	Fixed and variable data fields	64
5.3.2.3	Fixed data field format	65
5.3.2.4	Variable data field format	68
5.3.2.5	Synchronization burst request	68
5.3.2.6	XID burst	69
5.3.3	Exchange identity (XID) parameter formats	69
5.3.4	LME procedures	74
5.3.4.1	Synchronization burst procedures	74
5.3.4.2	Network entry protocol specifications	76
5.4	Additional requirements for ground stations	77
5.4.1	System timing requirements	77
5.4.1.1	Maintenance of Primary time	77
5.4.2	Ground station interface requirements	77
5.4.2.1	Ground station coordination	77
5.4.2.2	Fixed transmission parameters	78
5.4.2.3	Protection of fixed access protocol transmissions by ground quarantine	78
5.4.2.4	Protection of fixed access protocol transmissions by use of appropriate reservation protocols	78
5.4.2.5	Restriction of autotune reservations	79
5.4.2.6	Transmission time for autotune reservations	79
5.4.2.7	Reporting of channel usage	79
6	General design requirements	80
6.1	Controls and indicators	80
6.2	Operation of controls	80
6.3	Warm up	80
6.4	Effects of tests	80
6.5	Software management	80
6.6	Recovery from failure	80
6.6.1	Failure of the VDL equipment	80
6.7	Monitoring of proper operation	80
7	Protocol test procedures	81
7.1	General	81
7.1.1	Input voltage	81
7.1.2	Power input frequency	81
7.1.3	Adjustment of equipment	81
7.1.4	Equipment configuration	81
7.1.5	Test equipment	81
7.1.6	Test equipment precautions	82
7.1.7	Ambient conditions	82
7.1.8	Connected loads	82
7.1.9	Warm-up period	82
7.2	Required test rig	82
7.3	Protocol test-suite description methodology	84
7.4	Detailed protocol test procedures	85
7.4.1	Test-suite overview	85
7.4.2	Declarations	89
7.4.3	Constraints	89
7.4.3.1	Abbreviations	89
7.4.3.1.1	Subfield mnemonics	89
7.4.3.1.2	Special characters used in the subfield definitions	90
7.4.3.1.3	Station addresses and positions	90
7.4.3.1.4	VDL bursts and frames	91

7.4.3.2	Test cases	113
7.4.3.2.1	Test case macros.....	114
7.4.3.2.2	Test case descriptions	115
Annex A (informative): Cross reference matrix.....		270
Annex B (informative): Description of ISO 9646 Test Methodology.....		282
B.1	Overview of the Structure of the ISO 9646 Test-Suites.....	282
B.2	The Test Case Description	282
B.3	The Queue Action	284
B.4	The Repeat Construct	284
B.5	Macro Definitions	285
B.6	Test Case Naming	285
History		288

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 842-2 V1.1.1:2003

<https://standards.iteh.ai/catalog/standards/sist/ad2366df-dd67-4ef6-af30-c21a024c35a7/sist-en-301-842-2-v1-1-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 2 of a multi-part deliverable covering the VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment, as identified below:

Part 1: "General description and physical layer";

Part 2: "Data link layer";

Part 3: "Additional broadcast aspects";

Part 4: "Point-to-point functions".

iTeh STANDARD PREVIEW
(standards.iteh.ai)

<small>SIST EN 301 842-2 V1.1.1:2003</small>	
<small>National transposition dates</small>	
Date of adoption of this EN:	c21a024c35a7/sist-en-301-842-2-v1-1-1-2003 2 August 2002
Date of latest announcement of this EN (doa):	30 November 2002
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2003
Date of withdrawal of any conflicting National Standard (dow):	31 May 2003

Introduction

The present document states the technical specifications for Very High Frequency (VHF) Digital Link (VDL) Mode 4 ground-based radio transmitters, transceivers and receivers for air-ground communications operating in the VHF band (117,975 MHz to 136,975 MHz), using Gaussian-filtered Frequency Shift Keying (GFSK) Modulation with 25 kHz channel spacing. Optionally, the transmitters, transceivers and receivers may tune between 113 MHz to 117,975 MHz.

The present document may be used to produce tests for the assessment of the performance of the equipment. The performance of the equipment submitted for type testing should be representative of the performance of the corresponding production model.

The present document has been written on the assumption that:

- the type test measurements will be performed only once, in an accredited test laboratory and the measurements accepted by the various authorities in order to grant type approval;
- if equipment available on the market is required to be checked it will be tested in accordance with the methods of measurement specified in the present document or a documented alternative approved by the certifying authority;
- Equipment comply with EN 301 489-22 [3].

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 301 842-2 V1.1.1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/ad2366df-dd67-4ef6-af30-c21a024c35a7/sist-en-301-842-2-v1-1-1-2003>

1 Scope

The present document states the minimum performance requirements for radio transmitters, receivers and transceivers for ground-based VHF Datalink mode 4 (VDL mode 4) equipment intended to be used for air-ground data communications, operating in the VHF band (117,95 MHz to 137 MHz and optionally 113 MHz to 117,95 MHz) allocated to the aeronautical mobile service. It is designed to ensure that equipment certified to it will be compatible with the relevant ICAO VHF Digital Link (VDL) Standards and Recommended Practices (SARPs) and VDL Mode 4 Technical Manual (TM) [1].

Manufacturers should note that in the future, all or part of the frequency band 108,000 MHz to 117,975 MHz might become available for aeronautical communications.

The present document applies to Gaussian-filtered Frequency Shift Keying (GFSK) systems, with channel separations of 25 kHz intended for air-ground communications. The scope of the present document is limited to ground base stations.

The VDL system provides data communication exchanges between aircraft and ground based systems supporting surveillance applications. The supported modes of communication include:

- broadcast and point-to-point communication;
- air-air and ground-air;
- operation without ground infrastructure.

VDL Mode 4 is designed to be an Air/Ground subsystem of the Aeronautical Telecommunication Network (ATN) using the AM(R)S band and it is organized according to the Open Systems Interconnection (OSI) model (defined by ISO). It provides reliable sub network services to the ATN system.

The present document specifies functional specifications of radio transmitters, receivers and transceivers at ground-based VHF communication equipment intended to be used for air-ground and air-air data communications. The present document is derived from the specifications:

- Mode 4 standards produced under the auspices of the International Civil Aviation Organization (ICAO) [1].
- Other relevant standards as defined in clause 2.

EN 301 842-1 [5] deals with tests of the physical layer. The present document deals with tests of the link layer sufficient to support broadcast functionality. The present document also includes requirements and tests sufficient to recognize and respond to transmissions associated with point-to-point communication. Detailed requirements for point-to-point communication are beyond the scope of the present document.

The present document includes:

- references, definitions, abbreviations and symbols are provided in clauses 2 and 3;
- clause 4 describes the VDL Mode 4 ground station link layer;
- clause 5 performance specifications for the VDL Mode 4 ground station;
- clause 6 provides general design requirements;
- clause 7 provide protocol tests which emphasize the ADS-B functions of the system;
- a document history is contained in clause 8;
- clause A provides a detailed cross-reference to the relevant requirements contained in reference [1];
- annex B provides a description of the ISO/IEC 9646 [8] Test Methodology.

Note that the system can support a very wide range of functions. It is not practical to provide specific tests for all aspects of functionality. The approach used is to provide detailed tests for the core ADS-B functionality and to provide tests of those remaining requirements which, if wrongly implemented, could cause a deterioration in the service offered by other VDL Mode 4 stations. Therefore:

- a detailed set of protocol tests are provided for the broadcast functionality necessary to support ADS-B functions;
- a detailed test of position encoding and decoding is provided because of the importance of position in the management of the VDL Mode 4 link specifically and the need to support ADS-B applications in general.

Mandating and Recommendation Phrases

a) "Shall":

the use of the word "Shall" indicates a mandated criterion; i.e. compliance with the particular procedure or specification is mandatory and no alternative may be applied.

b) "Should":

the use of the word "Should" (and phrases such as "It is recommended that...", etc.) indicates that though the procedure or criterion is regarded as the preferred option, alternative procedures, specifications or criteria may be applied, provided that the manufacturer, installer or tester can provide information or data to adequately support and justify the alternative.

2 References

iTeh STANDARD PREVIEW

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.
(standards.iteh.ai)

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
<https://standards.iteh.ai/catalog/standards/sist/ad2366df-dd67-4ef6-af30-00024357sist-en-301-842-2-v1-1-1-2003>
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] Annex 10 to the Convention on International Civil Aviation, International Civil Aviation Organization (VDL Mode 4 Technical Manual).
- [2] EUROCAE ED-108: "Interim MOPS for VDL Mode 4 Aircraft Transceiver for ADS-B".
- [3] ETSI EN 301 489-22: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 22: Specific conditions for ground based VHF aeronautical mobile and fixed radio equipment".
- [4] ISO/IEC 3309 (1993): "Information technology - Telecommunications and information exchange between systems - High-level data link control (HDLC) procedures - Frame structure".
- [5] ETSI EN 301 842-1 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment; Part 1: General description and physical layer".
- [6] ISO/IEC 7498-1 (1994): "Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model".
- [7] ISO/IEC 10731 (1994): "Information technology - Open Systems Interconnection - Basic Reference Model - Conventions for the definition of OSI services".
- [8] ISO/IEC 9646: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework".
- [9] ED-14D/DO-160D: "Environmental conditions and Test Procedures for Airborne Equipment".

3 Definitions and abbreviations

3.1 Definitions

3.1.1 Basic reference model definitions

The present document is based on the concepts developed in the open systems interconnect basic reference model and makes use of the following terms defined in ISO/IEC 7498-1 [6]:

- layer;
- sublayer;
- entity;
- service;
- physical layer;
- data link layer.

3.1.2 Service conventions definitions

For the purposes of the present document, the terms and definitions given in ISO/IEC 10731 [7] apply:

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

- service provider;
 - request;
 - indication;
 - confirm.
- [SIST EN 301 842-2 V1.1.1:2003](#)
<https://standards.iteh.ai/catalog/standards/sist/ad2366df-dd67-4ef6-af30-c21a024c35a7/sist-en-301-842-2-v1-1-1-2003>

3.1.3 General definitions

For the purposes of the present document, the following terms and definitions apply:

aeronautical mobile service: mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate

Aeronautical Telecommunications Network (ATN): internetwork architecture that allows ground, air/ground, and aircraft data sub networks to interoperate by adopting common interface services and protocols based on the International Organization for Standardization Open Systems Interconnection Reference Model

aircraft address: unique combination of 24 bits available for assignment to an aircraft for the purpose of air-ground communications, navigation and surveillance

NOTE: An aircraft may choose not to use this unique address and can use instead a non-unique address.

Automatic Dependent Surveillance-Broadcast (ADS-B): surveillance application transmitting parameters, such as position, track and ground speed, via a broadcast mode data link for use by any air and/or ground users requiring it

NOTE: ADS-B is a surveillance service based on aircraft self-determination of position/velocity/time and automatic, periodic or random, broadcast of this information along with auxiliary data such as aircraft identity (ID), communications control parameters, etc. ADS-B is intended to support multiple high-level applications and associated services such as cockpit display of traffic information, traffic alert and collision avoidance functionality, enhanced traffic management in the air and on the ground, search and rescue support and others.

autotune function: function, performed by the Link Management Entity, which allows a ground VDL Mode 4 station to command an aircraft to change the operating characteristics of synchronization burst transmissions

burst: VHF Digital Link (VDL) specific services burst is composed of a sequence of source address, burst ID, information, slot reservation, and Frame Check Sequence (FCS) fields, bracketed by opening and closing flag sequences.

NOTE: The start of a burst may occur only at quantized time intervals and this constraint allows the propagation delay between the transmission and reception to be derived.

burst length: number of slots across which the VDL Mode 4 burst is transmitted

current slot: slot in which a received transmission begins

delayed burst: VDL Mode 4 burst that begins sufficiently after the beginning of a slot so that the transmitting VDL Mode 4 station is confident that no other VDL Mode 4 station that it could receive from and is within the guard range is transmitting in the slot.

NOTE: The delayed VDL Mode 4 burst terminates by the end of the slot in which it began (its length is shortened to ensure completion by the nominal time).

Global Signalling Channel (GSC): channel available on a world wide basis which provides for communication control

ground base station: aeronautical station equipment, in the aeronautical mobile service, for use with an external antenna and intended for use at a fixed location

link: connects a mobile DLE and a ground DLE and is uniquely specified by the combination of mobile DLS address and the ground DLS address

NOTE: A different sub network entity resides above every link endpoint.

link layer: lies immediately above the physical layer in the Open Systems Interconnection protocol model

NOTE: The link layer provides for the reliable transfer of information across the physical media. It is subdivided into the data link sublayer and the media access control sublayer.

Link Management Entity (LME): protocol state machine capable of acquiring, establishing, and maintaining a connection to a single peer system

SIST EN 301 842-2 V1.1.1:2003

NOTE: A LME establishes data link and sub network connections, "hands-off" those connections, and manages the media access control sublayer and physical layer. An aircraft LME tracks how well it can communicate with the ground stations of a single ground system. An aircraft VDL Management Entity (VME) instantiates an LME for each ground station that it monitors. Similarly, the ground VME instantiates an LME for each aircraft that it monitors. An LME is deleted when communication with the peer system is no longer viable.

Media Access Control (MAC): the sublayer that acquires the data path and controls the movement of bits over the data path

mobile: radio equipment designed for installation into vehicles

mode 4: data link using a Gaussian Filtered Frequency Shift Keying modulation scheme and self organizing time division multiple access

NOTE: Mode 4 has been validated for surveillance applications.

physical layer: lowest level layer in the Open Systems Interconnection protocol model

NOTE: The physical layer is concerned with only the transmission of binary information over the physical medium (e.g. VHF radio).

primary time source: normal operation timing mode in which a VDL Mode 4 station maintains time synchronization to Universal Time Coordinated (UTC) second

private parameters: contained in exchange identity (XID) frames and that are unique to the VHF digital link environment

secondary time source: timing source used in a failure mode, which applies when the primary time source fails, in which a VDL Mode 4 station maintains time synchronization to UTC second

slot: In VDL Mode 4, time is divided into a series of time slots of equal period. Each VDL Mode 4 burst transmission starts at the beginning of a slot.

station: VDL Mode 4 Specific Services (VSS)-capable entity

NOTE: A station may be either a mobile station or a ground station. A station is a physical entity that transmits and receives bursts over the RF interface (either A/G or air-to-air (A/A)) and comprises, at a minimum: a physical layer, media access control sublayer, and a unique VSS address. A station which is also a DLS station has the same address.

superframe: group of slots that span a period of one minute

NOTE: The start of the current superframe is aligned with the start of the slot that is currently being used for transmission. The next superframe starts one minute after the current slot.

synchronization burst (or "sync" burst): VDL Mode 4 burst which announces, as a minimum, existence and position

NOTE: Ground stations announce existence, position, and the current time. Mobile stations lacking timing information can then derive the slot structure from ground synchronization bursts. Mobile stations lacking position information can derive position from both mobile and ground synchronization bursts. This periodic information is used in various ways including ADS-B, secondary navigation, and simplifying the LME algorithms.

tertiary time source: timing source used in a failure mode, which applies when the primary and secondary time sources fail, in which a VDL Mode 4 station maintains time synchronization to an estimate of the mean slot start times of a set of VDL Mode 4 stations

VDL Mode 4 Burst: VHF Digital Link (VDL) Mode 4 burst is composed of a sequence of source address, burst ID, information, slot reservation, and Frame Check Sequence (FCS) fields, bracketed by opening and closing flag sequences

NOTE: The start of a burst may occur only at quantized time intervals and this constraint allows the propagation delay between the transmission and reception to be derived.

SIST EN 301 842-2 V1.1.1:2003

VDL Mode 4 Specific Services (VSS) sublayer: resides above the MAC sublayer and provides VDL Mode 4 specific access protocols including reserved, random and fixed protocols

(standards.iteh.ai)

SIST EN 301 842-2 V1.1.1:2003

VSS user: user of the VDL Mode 4 Specific Services

NOTE: The VSS user could be higher layers in the VDL Mode 4 TM or an external application using VDL Mode 4.

VDL Management Entity (VME): VDL-specific entity that provides the quality of service requested by the ATN-defined sub network system management entity

NOTE: A VME uses the LMEs (that it creates and destroys) to acquire the quality of service available from peer systems.

VDL Mode 4 station: physical entity that transmits and receives VDL Mode 4 bursts over the RF interface (either A/G or air-to-air (A/A)) and comprises, as a minimum: a physical layer, Media Access Control sublayer and a VSS sublayer

NOTE: A VDL Mode 4 station may either be a mobile VDL Mode 4 station or a ground VDL Mode 4 station.

VDL Mode 4 Station Address: 27-bit identifier used to uniquely identify a VDL Mode 4 station

VDL Station: VDL-capable entity

NOTE: A station may either be a mobile station or a ground station. A station is a physical entity that transmits and receives frames over the Air/Ground (A/G) interface and comprises, at a minimum: a physical layer, media access control sublayer, and a unique DLS address. The particular initiating process (i.e. DLE or LME) in the station cannot be determined by the source DLS address. The particular destination process cannot be determined by the destination DLS address. These can be determined only by the context of these frames as well as the current operational state of the DLEs.