

# INTERNATIONAL STANDARD

**ISO/IEC  
11801**

Second edition  
2002-09

**Information technology –  
Generic cabling for customer premises**

iTeah Standards

(<https://standards.iteh.ai>)

Document Preview

[ISO/IEC 11801:2002](#)

<https://standards.iteh.ai/cd/cp/standards/icc/e5ac56ca-c491-4f6b-ba45-337fb9321369/iso-iec-11801-2002>



Reference number  
ISO/IEC 11801:2002(E)

**Withdrawn**

iTeh Standards  
(<https://standards.iteh.ai>)

Document Preview

<https://standards.iteh.ai/cd/cp/standards/icc/e5ac56ca-c491-4f6b-ba45-337fb9321369/iso-iec-11801-2002>

[ISO/IEC 11801:2002](https://standards.iteh.ai/cd/cp/standards/icc/e5ac56ca-c491-4f6b-ba45-337fb9321369/iso-iec-11801-2002)

# INTERNATIONAL STANDARD

ISO/IEC  
**11801**

Second edition  
2002-09

Information technology –  
Generic cabling for customer premises

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ISO/IEC 11801:2002](#)

<https://standards.iteh.ai/cd/cp/standards/iec/e9ac56ca-c491-4f6b-ba45-337fb9321369/iso-iec-11801-2002>

© ISO/IEC 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland



PRICE CODE XB

*For price, see current catalogue*

Information technology –  
Generic cabling for customer premises

**CORRIGENDUM 1**

Page 23

**3.2. Abbreviations**

Add, after the abbreviation ATM, the following new abbreviation:

BCT Broadcast and communications technologies, sometimes referred to as HEM

Replace, the explanation of HEM by the following:

HEM Home Entertainment & Multimedia, see BCT

Page 50

**7.2.2.1 Component choice**

Add, on page 51, after the third bullet, the following new note:

NOTE For the relationship and requirements of classes and categories in earlier editions of this standard, see Annex I.

<https://standards.iteh.ai/corrigendum/iso-iec-11801-2002>

Page 132

**Bibliography**

Delete, on page 133, the reference:

IEC 61300-2-2, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-2: Tests – Mating durability*

Delete, on page 134, the reference:

IEC 61300-3-6, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-6: Examinations and measurements – Return loss*

Delete, on page 135, the reference:

ISO/IEC TR 14763-2, *Information technology – Implementation and operation of customer premises cabling – Part 2: Planning and installation*

ISO/IEC 11801  
(Second edition – 2002)

**Information technology –  
Generic cabling for customer premises**

**CORRIGENDUM 2**

Page 66

**10.2.4.2 Telecommunications outlets**

*Replace, in the fourth line of the first paragraph, “...as specified in 0.” by ... “as specified in 10.2.5.”*

<https://standards.iteh.ai/corrigendum/iso-iec-11801-2002>

## CONTENTS

|  |    |
|--|----|
| FOREWORD .....   | 10 |
| INTRODUCTION .....                                       | 11 |
| 1 Scope .....  | 13 |
| 2 Normative references .....                             | 13 |
| 3 Definitions, abbreviations and symbols .....           | 17 |
| 3.1 Definitions .....                                    | 17 |
| 3.2 Abbreviations .....                                  | 23 |
| 3.3 Symbols .....  | 24 |
| 3.3.1 Variables .....                                    | 24 |
| 3.3.2 Indices .....                                      | 25 |
| 4 Conformance .....                                      | 25 |
| 5 Structure of the generic cabling system .....          | 26 |
| 5.1 General .....  | 26 |
| 5.2 Functional elements .....                            | 26 |
| 5.3 Cabling subsystems .....                             | 27 |
| 5.3.1 General .....                                      | 27 |
| 5.3.2 Campus backbone cabling subsystem .....            | 27 |
| 5.3.3 Building backbone cabling subsystem .....          | 28 |
| 5.3.4 Horizontal cabling subsystem .....                 | 28 |
| 5.3.5 Design objectives .....                            | 28 |
| 5.4 Interconnection of subsystems .....                  | 29 |
| 5.4.1 General .....                                      | 29 |
| 5.4.2 Centralised cabling architecture .....             | 30 |
| 5.5 Accommodation of functional elements .....           | 30 |
| 5.6 Interfaces .....                                     | 30 |
| 5.6.1 Equipment interfaces and test interfaces .....     | 30 |
| 5.6.2 Channel and permanent link .....                   | 32 |
| 5.6.3 External network interface .....                   | 32 |
| 5.7 Dimensioning and configuring .....                   | 32 |
| 5.7.1 Distributors .....                                 | 32 |
| 5.7.2 Cables .....                                       | 34 |
| 5.7.3 Work area cords and equipment cords .....          | 34 |
| 5.7.4 Patch cords and jumpers .....                      | 34 |
| 5.7.5 Telecommunications outlet (TO) .....               | 35 |
| 5.7.6 Consolidation point .....                          | 36 |
| 5.7.7 Telecommunications rooms and equipment rooms ..... | 36 |
| 5.7.8 Building entrance facilities .....                 | 36 |
| 5.7.9 External services cabling .....                    | 36 |
| 6 Performance of balanced cabling .....                  | 37 |
| 6.1 General .....  | 37 |
| 6.2 Layout .....   | 38 |
| 6.3 Classification of balanced cabling .....             | 39 |
| 6.4 Balanced cabling performance .....                   | 39 |
| 6.4.1 General .....                                      | 39 |

|        |  |    |
|--------|--|----|
| 6.4.2  | Return loss .....  | 39 |
| 6.4.3  | Insertion loss/attenuation.....  | 40 |
| 6.4.4  | NEXT .....   | 41 |
| 6.4.5  | Attenuation to crosstalk ratio (ACR).....                                      | 44 |
| 6.4.6  | ELFEXT.....  | 45 |
| 6.4.7  | Direct current (d.c.) loop resistance .....                                    | 47 |
| 6.4.8  | Direct current (d.c.) resistance unbalance.....                                | 48 |
| 6.4.9  | Current carrying capacity.....   | 48 |
| 6.4.10 | Operating voltage .....  | 48 |
| 6.4.11 | Power capacity .....   | 48 |
| 6.4.12 | Propagation delay .....  | 48 |
| 6.4.13 | Delay skew .....   | 49 |
| 6.4.14 | Unbalance attenuation.....   | 49 |
| 6.4.15 | Coupling attenuation.....  | 50 |
| 7      | Reference implementations for balanced cabling .....                           | 50 |
| 7.1    | General .....  | 50 |
| 7.2    | Balanced cabling .....   | 50 |
| 7.2.1  | General .....  | 50 |
| 7.2.2  | Horizontal cabling .....   | 50 |
| 7.2.3  | Backbone cabling .....   | 54 |
| 8      | Performance of optical fibre cabling .....                                     | 55 |
| 8.1    | General .....  | 55 |
| 8.2    | Component choice .....   | 55 |
| 8.3    | Channel attenuation .....  | 56 |
| 8.4    | Channel topology .....   | 56 |
| 8.5    | Propagation delay .....  | 58 |
| 9      | Cable requirements .....   | 58 |
| 9.1    | General .....  | 58 |
| 9.2    | Balanced cables .....  | 58 |
| 9.2.1  | Basic performance requirements .....   | 58 |
| 9.2.2  | Additional requirements .....  | 59 |
| 9.2.3  | Additional performance requirements for flexible cables .....                  | 60 |
| 9.3    | Additional crosstalk considerations for cable sharing in balanced cables ..... | 60 |
| 9.3.1  | General .....  | 60 |
| 9.3.2  | Power summation in backbone cables .....                                       | 60 |
| 9.3.3  | Hybrid, multi-unit and cables connected to more than one TO .....              | 60 |
| 9.4    | Optical fibre cables .....   | 61 |
| 9.4.1  | Optical fibre types .....  | 61 |
| 9.4.2  | Generic performance requirements .....   | 61 |
| 9.4.3  | Multimode optical fibre cable .....  | 61 |
| 9.4.4  | Single-mode optical fibre cables .....   | 62 |
| 10     | Connecting hardware requirements .....   | 62 |
| 10.1   | General requirements .....   | 62 |
| 10.1.1 | Applicability .....  | 62 |
| 10.1.2 | Location .....   | 63 |
| 10.1.3 | Design .....   | 63 |
| 10.1.4 | Operating environment .....  | 63 |
| 10.1.5 | Mounting .....   | 63 |

|   |    |
|---|----|
| 10.1.6 Installation practices .....   | 63 |
| 10.1.7 Marking and colour coding .....                                      | 64 |
| 10.2 Connecting hardware for balanced cabling .....                         | 64 |
| 10.2.1 General requirements .....   | 64 |
| 10.2.2 Performance marking .....  | 64 |
| 10.2.3 Mechanical characteristics .....                                     | 64 |
| 10.2.4 Electrical characteristics .....                                     | 66 |
| 10.2.5 Telecommunications outlet requirements .....                         | 72 |
| 10.2.6 Design considerations for installation .....                         | 73 |
| 10.3 Optical fibre connecting hardware .....                                | 74 |
| 10.3.1 General requirements .....   | 74 |
| 10.3.2 Marking and colour coding .....                                      | 74 |
| 10.3.3 Mechanical and optical characteristics .....                         | 74 |
| 10.3.4 Telecommunications outlet requirements .....                         | 75 |
| 10.3.5 Connection schemes for optical fibre cabling .....                   | 75 |
| 11 Screening practices .....  | 77 |
| 11.1 General .....  | 77 |
| 11.2 Electromagnetic performance .....                                      | 77 |
| 11.3 Earthing .....   | 78 |
| 12 Administration .....   | 78 |
| 13 Balanced cords .....   | 78 |
| 13.1 Introduction .....   | 78 |
| 13.2 Insertion loss .....   | 78 |
| 13.3 Return loss .....  | 79 |
| 13.4 NEXT .....   | 79 |
| Annex A (normative) Balanced permanent link and CP link performance .....   | 82 |
| A.1 General .....   | 82 |
| A.2 Performance .....   | 82 |
| A.2.1 General .....   | 82 |
| A.2.2 Return loss .....   | 83 |
| A.2.3 Insertion loss/attenuation .....                                      | 84 |
| A.2.4 NEXT .....  | 85 |
| A.2.5 Attenuation to crosstalk ratio (ACR) .....                            | 88 |
| A.2.6 ELFEXT .....  | 89 |
| A.2.7 Direct current (d.c.) loop resistance .....                           | 92 |
| A.2.8 Direct current (d.c.) resistance unbalance .....                      | 93 |
| A.2.9 Propagation delay .....   | 93 |
| A.2.10 Delay skew .....   | 94 |
| Annex B (normative) Test procedures .....                                   | 96 |
| B.1 General .....   | 96 |
| B.2 Channel and link performance testing .....                              | 96 |
| B.2.1 Testing balanced cabling channels, permanent links and CP links ..... | 96 |
| B.2.2 Testing optical fibre cabling channels .....                          | 96 |
| B.2.3 Channel and link test schedules .....                                 | 96 |
| B.3 Transmission testing of cords for balanced cabling .....                | 97 |
| B.4 Transmission testing of components for cabling .....                    | 98 |
| B.4.1 Transmission testing of copper cables for balanced cabling .....      | 98 |

|                       |  |     |
|-----------------------|--|-----|
| B.4.2                 | Transmission testing of connecting hardware for balanced cabling .....   | 98  |
| B.4.3                 | Transmission testing of cables for optical cabling .....   | 98  |
| B.4.4                 | Transmission testing of connectors for optical cabling .....   | 98  |
| Annex C (normative)   | Mechanical and environmental performance testing of connecting hardware for balanced cabling .....                         | 99  |
| C.1                   | Introduction .....   | 99  |
| C.2                   | Test requirements .....  | 99  |
| C.2.1                 | General .....  | 99  |
| C.2.2                 | Initial test measurements.....   | 99  |
| C.2.3                 | Environmental and mechanical performance.....  | 100 |
| Annex D (informative) | Electromagnetic characteristics .....  | 104 |
| Annex E (informative) | Acronyms for balanced cables.....  | 105 |
| Annex F (informative) | Supported applications .....   | 107 |
| F.1                   | Supported applications for balanced cabling .....  | 107 |
| F.2                   | Supported applications for optical fibre cabling.....  | 109 |
| Annex G (informative) | Channel and permanent link models for balanced cabling .....   | 113 |
| G.1                   | General .....  | 113 |
| G.2                   | Insertion loss .....   | 113 |
| G.2.1                 | Insertion loss of the channel configuration .....  | 113 |
| G.2.1                 | Insertion loss of the permanent link configurations .....  | 114 |
| G.2.2                 | Assumptions for insertion loss .....   | 114 |
| G.3                   | NEXT .....   | 115 |
| G.3.1                 | NEXT of the channel configuration .....  | 115 |
| G.3.2                 | NEXT of the permanent link configurations .....  | 115 |
| G.3.3                 | Assumptions for NEXT .....   | 116 |
| G.4                   | ELFEXT.....  | 119 |
| G.4.1                 | ELFEXT of the channel configuration .....  | 119 |
| G.4.2                 | ELFEXT for the permanent link configurations .....   | 119 |
| G.4.3                 | Assumptions for ELFEXT .....   | 120 |
| G.5                   | Return loss .....  | 120 |
| G.5.1                 | Return loss of the channel and permanent link configurations.....  | 120 |
| G.5.2                 | Assumptions for the return loss circuit analysis method .....  | 121 |
| Annex H (informative) | Class F channel and permanent link with two connections .....  | 124 |
| Annex I (informative) | Significant changes to balanced cabling requirements with respect to earlier editions of this International Standard ..... | 125 |
| I.1                   | General .....  | 125 |
| I.2                   | References.....  | 125 |
| I.3                   | Structural elements .....  | 125 |
| I.4                   | Product designation.....   | 125 |
| I.5                   | Component requirements .....   | 125 |
| I.6                   | Installed cabling requirements .....   | 126 |
| Bibliography.....     |  | 132 |

|   |     |
|---|-----|
| Figure 1 – Structure of generic cabling .....   | 27  |
| Figure 2 – Hierarchical structure of generic cabling.....   | 29  |
| Figure 3 – Structures for centralised generic cabling.....  | 29  |
| Figure 4 – Accommodation of functional elements .....   | 30  |
| Figure 5 – Interconnect models.....   | 31  |
| Figure 6 – Cross-connect models.....  | 31  |
| Figure 7 – Equipment and test interfaces .....  | 31  |
| Figure 8 – Example of a generic cabling system with combined BD and FD .....  | 33  |
| Figure 9 – Inter-relationship of functional elements in an installation with redundancy .....                         | 34  |
| Figure 10 – Channel, permanent link and CP link of a balanced cabling.....  | 37  |
| Figure 11 – Example of a system showing the location of cabling interfaces<br>and extent of associated channels ..... | 38  |
| Figure 12 – Horizontal cabling models .....   | 52  |
| Figure 13 – Backbone cabling model .....  | 54  |
| Figure 14 – Combined backbone/horizontal channels .....   | 57  |
| Figure 15 – Eight-position outlet pin and pair grouping assignments (front view<br>of connector) .....                | 73  |
| Figure 16 – Duplex SC connectivity configuration .....  | 76  |
| Figure 17 – Optical fibre patch cord .....  | 77  |
| Figure A.1 – Link options .....   | 82  |
| Figure E1 – Cable naming schema .....   | 105 |
| Figure E.2 – Cable types .....  | 106 |
| Figure G.1 – Example of computation of NEXT with higher precision .....   | 116 |
| Figure H.1 – Two connection channel and permanent link.....   | 124 |
| Figure I.1 – Horizontal cabling model.....  | 127 |
| Figure I.2 – Backbone cabling model .....   | 127 |

|  |    |
|--|----|
| Table 1 – Maximum channel lengths .....  | 32 |
| Table 2 – Return loss for channel .....  | 40 |
| Table 3 – Informative return loss values for channel at key frequencies .....                                    | 40 |
| Table 4 – Insertion loss for channel .....   | 41 |
| Table 5 – Informative insertion loss values for channel at key frequencies .....                                 | 41 |
| Table 6 – NEXT for channel .....   | 42 |
| Table 7 – Informative NEXT values for channel at key frequencies .....   | 42 |
| Table 8 – PS NEXT for channel .....  | 43 |
| Table 9 – Informative PS NEXT values for channel at key frequencies .....  | 43 |
| Table 10 – Informative ACR values for channel at key frequencies .....   | 44 |
| Table 11 – Informative PS ACR values for channel at key frequencies .....  | 45 |
| Table 12 – ELFEXT for channel .....  | 46 |
| Table 13 – Informative ELFEXT values for channel at key frequencies .....  | 46 |
| Table 14 – PS ELFEXT for channel .....   | 47 |
| Table 15 – Informative PS ELFEXT values for channel at key frequencies .....                                     | 47 |
| Table 16 – Direct current (d.c.) loop resistance for channel .....   | 47 |
| Table 17 – Propagation delay for channel .....   | 48 |
| Table 18 – Informative propagation delay values for channel at key frequencies .....                             | 49 |
| Table 19 – Delay skew for channel .....  | 49 |
| Table 20 – Unbalance attenuation for channel .....   | 50 |
| Table 21 – Horizontal link length equations .....  | 53 |
| Table 22 – Backbone link length equations .....  | 55 |
| Table 23 – Channel attenuation .....   | 56 |
| Table 24 – Basic requirements of balanced cables .....   | 58 |
| Table 25 – Mechanical characteristics of balanced cables .....   | 59 |
| Table 26 – Optical fibre cable attenuation .....   | 61 |
| Table 27 – Multimode optical fibre modal bandwidth .....   | 62 |
| Table 28 – Mechanical characteristics of connecting hardware for use with balanced cabling .....                 | 65 |
| Table 29 – Electrical characteristics of telecommunications outlets intended for use with balanced cabling ..... | 67 |
| Table 30 – Return loss .....   | 68 |
| Table 31 – Insertion loss .....  | 68 |
| Table 32 – Near end crosstalk (NEXT) .....   | 68 |
| Table 33 – Power sum near end crosstalk (PS NEXT) .....  | 69 |
| Table 34 – Far end crosstalk (FEXT) .....  | 69 |
| Table 35 – Power sum far end crosstalk (PS FEXT) .....   | 70 |
| Table 36 – Input to output resistance .....  | 70 |
| Table 37 – Input to output resistance unbalance .....  | 70 |
| Table 38 – Current carrying capacity .....   | 71 |
| Table 39 – Propagation delay .....   | 71 |
| Table 40 – Delay skew .....  | 71 |

|   |     |
|---|-----|
| Table 41 – Transverse conversion loss (TCL) f.f.s .....   | 71  |
| Table 42 – Transfer impedance (screened connectors only) .....  | 72  |
| Table 43 – Insulation resistance .....  | 72  |
| Table 44 – Voltage proof.....   | 72  |
| Table 45 – Matrix of backward compatible mated modular connector performance.....   | 73  |
| Table 46 – Mechanical and optical characteristics of optical fibre connecting hardware .....                                      | 75  |
| Table 47 – Minimum return loss for balanced cords .....   | 79  |
| Table 48 – Informative values of return loss at key frequencies for Category 5, 6<br>and 7 cords.....                             | 79  |
| Table 49 – Informative values of NEXT at key frequencies for Category 5, 6<br>and 7 cords.....                                    | 81  |
| Table A.1 – Return loss for permanent link or CP link .....   | 83  |
| Table A.2 – Informative return loss values for permanent link with maximum<br>implementation at key frequencies .....             | 83  |
| Table A.3 – Insertion loss for permanent link or CP link .....  | 84  |
| Table A.4 – Informative insertion loss values for permanent link with maximum<br>implementation at key frequencies .....          | 85  |
| Table A.5 – NEXT for permanent link or CP link.....   | 86  |
| Table A.6 – Informative NEXT values for permanent link with maximum implementation<br>at key frequencies .....                    | 86  |
| Table A.7 – PS NEXT for permanent link or CP link .....   | 87  |
| Table A.8 – Informative PS NEXT values for permanent link with maximum<br>implementation at key frequencies .....                 | 88  |
| Table A.9 – Informative ACR values for permanent link with maximum implementation<br>at key frequencies .....                     | 89  |
| Table A.10 – Informative PS ACR values for permanent link with maximum<br>implementation at key frequencies .....                 | 89  |
| Table A.11 – ELFEXT for permanent link or CP link .....   | 90  |
| Table A.12 – Informative ELFEXT values for permanent link with maximum<br>implementation at key frequencies .....                 | 91  |
| Table A.13 – PS ELFEXT for permanent link or CP link .....  | 92  |
| Table A.14 – Informative PS ELFEXT values for permanent link with maximum<br>implementation at key frequencies .....              | 92  |
| Table A.15 – Direct current (d.c.) loop resistance for permanent link or CP link .....  | 93  |
| Table A.16 – Informative d.c. loop resistance for permanent link with maximum<br>implementation .....                             | 93  |
| Table A.17 – Propagation delay for permanent link or CP link .....  | 94  |
| Table A.18 – Informative propagation delay values for permanent link with maximum<br>implementation at key frequencies .....      | 94  |
| Table A.19 – Delay skew for permanent link or CP link .....   | 95  |
| Table A.20 – Informative delay skew for permanent link with maximum implementation .....  | 95  |
| Table B.1 – Cabling characteristics of copper and optical fibre cabling for acceptance,<br>compliance and reference testing ..... | 97  |
| Table C.1 – Group P .....   | 100 |
| Table C.2 – Group A .....   | 101 |
| Table C.3 – Group B .....   | 102 |
| Table C.4 – Group C .....   | 103 |

|  |     |
|--|-----|
| Table C.5 – Group D .....  | 103 |
| Table F.1 – Applications using balanced cabling .....  | 107 |
| Table F.2 – Modular connector pin assignment for applications .....  | 109 |
| Table F.3 – Supported applications using optical fibre cabling .....   | 110 |
| Table F.4 – Maximum channel lengths supported by optical fibre applications for multimode fibre .....                                      | 111 |
| Table F.5 – Maximum channel length supported by optical fibre applications for single-mode fibres.....                                     | 112 |
| Table G.1 – Insertion loss deviation.....  | 114 |
| Table H.1 – ACR and PS ACR values for 2 connection class F channels and permanent links at key frequencies .....                           | 124 |
| Table I.1 – Principal transmission performance requirements of $150 \Omega$ connecting hardware .....                                      | 126 |
| Table I.2 – Minimum return loss limits for links, permanent links and channels for the different cabling classes .....                     | 128 |
| Table I.3 – Maximum attenuation limits for links, permanent links and channels for the different cabling classes .....                     | 128 |
| Table I.4 – Minimum NEXT limits for links, permanent links and channels for the different cabling classes .....                            | 129 |
| Table I.5 – Minimum ACR limits for links, permanent links and channels for the different cabling classes .....                             | 129 |
| Table I.6 – Maximum propagation delay limits for links, permanent links and channels for the different cabling classes .....               | 130 |
| Table I.7 – Maximum d.c. loop resistance limits for links, permanent links and channels for the different cabling classes .....            | 130 |
| Table I.8 – Minimum unbalance attenuation (LCL/LCTL) limits for links, permanent links and channels for the different cabling classes..... | 130 |
| Table I.9 – Minimum PS NEXT, PS ACR, ELFEXT and PS ELFEXT limits for permanent links and channels for the different cabling classes .....  | 131 |
| Table I.10 – Maximum delay skew limits for permanent links and channels for the different cabling classes .....                            | 131 |

## INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES

### FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 11801 was prepared by subcommittee 25; Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

This second edition cancels and replaces the first edition published in 1995 and its amendments 1 (1999) and 2 (1999) and constitutes a technical revision. The significant changes with respect to the first edition and its amendments are listed in Annex I.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This International Standard has taken into account requirements specified in application standards listed in Annex F. It refers to International Standards for components and test methods whenever appropriate International Standards are available.

The contents of corrigendum 1 of September 2002, corrigendum 2 of December 2002 and corrigendum 3 of September 2008 have been included in this copy.  
<https://standards.iteh.ai/37fb9321369/iso-iec-11801-2002>