

9`Y_fca U[bYfbUnXfi y`'j cghf9 A 7 L]b`nUXYj Yj`nj Ynj`n'fUX]`g_ ja `gdY_fca `f9 FA L!
6 UnbY`dcbgHUY`f6 G L]b`i dcfUVb]y`_UcdfYa Ufl 9 L`nUW] bc`ca fYy`Y`=AH!&\$\$\$`fYrY
[YbYfUMY`! ("XY.`< Ufa cb]n]fUb]9 B`nU`=AH!&\$\$\$Z7 8 A 5 `í Ai`h!
7 Uff]Yfí`f7 8 A 5 &\$\$\$L`fl 9 Lz`_]`nUYa UV]ghj YbY`nU hYj Y` `YbU' "&X]fY`hj YF/ HH9

Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS) and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 4: Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (UE) covering essential requirements of article 32 of the R&TTE Directive

(standards.iteh.ai)

[SIST EN 301 908-4:2002](https://standards.iteh.ai/catalog/standards/sist/d0a06301-4cc5-4ee3-bf5e-c9d55ba53231/sist-en-301-908-4-2002)

<https://standards.iteh.ai/catalog/standards/sist/d0a06301-4cc5-4ee3-bf5e-c9d55ba53231/sist-en-301-908-4-2002>

Ta slovenski standard je istoveten z: EN 301 908-4 Version 1.1.1

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST EN 301 908-4:2002

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 908-4:2002](#)

<https://standards.iteh.ai/catalog/standards/sist/d0a06301-4cc5-4ee3-bf5e-c9d55ba53231/sist-en-301-908-4-2002>

ETSI EN 301 908-4 V1.1.1 (2002-01)

Candidate Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Base Stations (BS) and User Equipment (UE) for
IMT-2000 Third-Generation cellular networks;
Part 4: Harmonized EN for IMT-2000,
CDMA Multi-Carrier (cdma2000) (UE)
covering essential requirements
of article 3.2 of the R&TTE Directive**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 908-4:2002](https://standards.iteh.ai/catalog/standards/sist/d0a06301-4cc5-4ee3-bf5e-c9d55ba53231/sist-en-301-908-4-2002)

<https://standards.iteh.ai/catalog/standards/sist/d0a06301-4cc5-4ee3-bf5e-c9d55ba53231/sist-en-301-908-4-2002>



Reference

DEN/ERM-TFES-001-4

KeywordsIMT-2000, 3G, digital, cellular, mobile,
cdma2000, 3GPP2, radio, regulation, UMTS**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 908-4:2002

<https://standards.iteh.ai/catalog/standards/sist/d0a06301-4cc5-4ee3-bf5e-c9d55ba53231/sist-en-301-908-4-2002>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	7
1 Scope	9
2 References	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols.....	17
3.3 Abbreviations	20
4 Technical requirements specifications	21
4.1 Environmental profile.....	21
4.2 Conformance requirements	21
4.2.1 Introduction.....	21
4.2.2 Conducted spurious emissions when transmitting	21
4.2.2.1 Definition	21
4.2.2.2 Limits	22
4.2.2.2.1 Spreading rate 1	22
4.2.2.2.2 Spreading rate 3	22
4.2.2.3 Conformance	23
4.2.3 Maximum RF output power.....	23
4.2.3.1 Definition	23
4.2.3.2 Limits	23
4.2.3.3 Conformance	23
4.2.4 Minimum controlled output power.....	23
4.2.4.1 Definition	23
4.2.4.2 Limits	24
4.2.4.3 Conformance.....	24
4.2.5 Conducted spurious emissions when not transmitting	24
4.2.5.1 Definition	24
4.2.5.2 Limits	24
4.2.5.3 Conformance.....	24
4.2.6 Receiver blocking characteristics	24
4.2.6.1 Definition	24
4.2.6.2 Limits	24
4.2.6.3 Conformance.....	24
4.2.7 Intermodulation spurious response attenuation.....	25
4.2.7.1 Definition	25
4.2.7.2 Limits	25
4.2.7.3 Conformance.....	25
4.2.8 Adjacent channel selectivity	25
4.2.8.1 Definition	25
4.2.8.2 Limits	25
4.2.8.3 Conformance.....	25
4.2.9 Supervision of paging channel.....	25
4.2.9.1 Definition	25
4.2.9.2 Limits	25
4.2.9.3 Conformance.....	25
4.2.10 Supervision of forward traffic channel	26
4.2.10.1 Definition	26
4.2.10.2 Limits	26
4.2.10.3 Conformance.....	27
5 Testing for compliance with technical requirements.....	27
5.1 Conditions for testing	27

5.1.1	Introduction.....	27
5.1.2	Standard equipment under test.....	27
5.1.2.1	Basic equipment.....	27
5.1.2.2	Ancillary equipment.....	27
5.2	Interpretation of the measurement results	27
5.3	Essential radio test suites.....	28
5.3.1	Conducted spurious emissions when transmitting	28
5.3.2	Maximum RF output power.....	30
5.3.3	Minimum controlled output power	32
5.3.4	Conducted spurious emissions when not transmitting	32
5.3.5	Receiver blocking characteristics	33
5.3.6	Intermodulation spurious response attenuation.....	34
5.3.7	Adjacent channel selectivity	35
5.3.8	Supervision of paging channel.....	36
5.3.9	Supervision of forward traffic channel	37
Annex A (normative):	The EN Requirements Table (EN-RT)	39
Annex B (informative):	Environmental profile and standard test conditions	41
B.1	Introduction	41
B.2	CDMA environmental requirements	41
B.2.1	Temperature and power supply voltage.....	41
B.2.1.1	Definition.....	41
B.2.1.2	Method of measurement	41
B.2.1.3	Minimum standard.....	42
B.2.2	High humidity	42
B.2.2.1	Definition.....	42
B.2.2.2	Method of measurement	42
B.2.2.3	Minimum standard.....	42
B.2.3	Vibration stability.....	42
B.2.3.1	Definition.....	42
B.2.3.2	Method of measurement	43
B.2.3.3	Minimum standard.....	43
B.2.4	Shock stability	43
B.2.4.1	Definition.....	43
B.2.4.2	Method of measurement	43
B.2.4.3	Minimum standard.....	43
B.3	Standard test conditions.....	43
B.3.1	Standard environmental test conditions.....	43
B.3.2	Standard conditions for the primary power supply.....	43
B.3.2.1	General.....	43
B.3.2.2	Standard DC test voltage from accumulator batteries.....	44
B.3.2.3	Standard AC voltage and frequency	44
Annex C (informative):	The EN title in the official languages	45
Annex D (informative):	Bibliography	46
History		47

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Candidate Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The present document is part 4 of a multi-part deliverable covering the Base Stations (BS) and User Equipment (UE) for IMT-2000 Third-Generation cellular networks, as identified below:

- SIST EN 301 908-4:2002
<http://standards.etsi.org/standards/sist/301908-4/301-908-4-0202-990a35251/sist-en-301-908-4-2002>
- Part 1: "Harmonized EN for IMT-2000, introduction and common requirements, covering essential requirements of article 3.2 of the R&TTE Directive";
 - Part 2: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
 - Part 3: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
 - Part 4: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";**
 - Part 5: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
 - Part 6: "Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
 - Part 7: "Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
 - Part 8: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
 - Part 9: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
 - Part 10: "Harmonized EN for IMT-2000 FDMA/TDMA (DECT) covering essential requirements of article 3.2 of the R&TTE Directive".

Technical specifications relevant to Directive 1999/5/EC [1] are given in annex A.

National transposition dates	
Date of adoption of this EN:	4 January 2002
Date of latest announcement of this EN (doa):	30 April 2002
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 October 2002
Date of withdrawal of any conflicting National Standard (dow):	31 October 2003

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 908-4:2002](https://standards.iteh.ai/catalog/standards/sist/d0a06301-4cc5-4ee3-bf5e-c9d55ba53231/sist-en-301-908-4-2002)

<https://standards.iteh.ai/catalog/standards/sist/d0a06301-4cc5-4ee3-bf5e-c9d55ba53231/sist-en-301-908-4-2002>

Introduction

The present document is part of a set of standards designed to fit in a modular structure to cover all radio and telecommunications terminal equipment under the R&TTE Directive [1]. Each standard is a module in the structure. The modular structure is shown in figure 1.




Figure 1: Modular structure for the various standards used under the R&TTE Directive

The left hand edge of the figure 1 shows the different clauses of article 3 of the R&TTE Directive [1].

For article 3.3 various horizontal boxes are shown. Dotted lines indicate that at the time of publication of the present document essential requirements in these areas have to be adopted by the Commission. If such essential requirements are adopted, and as far and as long as they are applicable, they will justify individual standards whose scope is likely to be specified by function or interface type.

The vertical boxes show the standards under article 3.2 for the use of the radio spectrum by radio equipment. The scopes of these standards are specified either by frequency (normally in the case where frequency bands are harmonized) or by radio equipment type.

For article 3.1b, figure 1 shows EN 301 489 [9], the multi-part product EMC standard for radio used under the EMC Directive [2].

For article 3.1a, figure 1 shows the existing safety standards currently used under the LV Directive [3] and new standards covering human exposure to electromagnetic fields. New standards covering acoustic safety may also be required.

The bottom of figure 1 shows the relationship of the standards to radio equipment and telecommunications terminal equipment. A particular equipment may be radio equipment, telecommunications terminal equipment or both. A radio spectrum standard will apply if it is radio equipment. An article 3.3 standard will apply as well only if the relevant essential requirement under the R&TTE Directive [1] is adopted by the Commission and if the equipment in question is covered by the scope of the corresponding standard. Thus, depending on the nature of the equipment, the essential requirements under the R&TTE Directive [1] may be covered in a set of standards.

The modularity principle has been taken because:

- it minimizes the number of standards needed. Because equipment may, in fact, have multiple interfaces and functions it is not practicable to produce a single standard for each possible combination of functions that may occur in an equipment;
- it provides scope for standards to be added:
 - under article 3.2 when new frequency bands are agreed; or
 - under article 3.3 should the Commission take the necessary decision without requiring alteration of standards that are already published;
- it clarifies, simplifies and promotes the usage of Harmonized Standards as the relevant means of conformity assessment.

The product specifications upon which all parts of EN 301 908 are based differ in presentation, and this is reflected in the present document.

1 Scope

The present document applies to the following radio equipment type:

- Mobile stations for IMT-2000 CDMA Multi-Carrier (cdma2000).

These radio equipment types are capable of operating in all or any part of the frequency bands given in table 1.

Table 1: CDMA Multi-Carrier mobile stations service frequency bands

Direction of transmission	CDMA Multi-Carrier mobile stations service frequency bands
Transmit	1 920 MHz to 1 980 MHz
Receive	2 110 MHz to 2 170 MHz

The present document is intended to cover the provisions of Directive 1999/5/EC [1] (R&TTE Directive) article 3.2, which states that "..... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [1] will apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- SIST EN 301 908-4:2002
<https://standards.iteh.ai/catalog/standards/sist/d0a06301-4cc5-4ee3-bf5e-c9d55ba53231/sist-en-301-908-4-2002>
- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
 - For a specific reference, subsequent revisions do not apply.
 - For a non-specific reference, the latest version applies.
- [1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity.
- [2] Council Directive 89/336/EEC of 3 May 1989 on the approximation of the laws of the Member States relating to electromagnetic compatibility.
- [3] Council Directive 73/23/EEC of 19 February 1973 on the harmonization of the laws of Member States relating to electrical equipment designed for use within certain voltage limits.
- [4] ANSI/TIA/EIA-98-D (2001): "Recommended Minimum Performance Standards for Dual-Mode Spread Spectrum Mobile Stations (ANSI/TIA/EIA-98-D-2001)".
- [5] ANSI/TIA/EIA/IS-2000.2-A-1 (2000): "Physical Layer Standard for cdma2000 Spread Spectrum Systems, Addendum 1".
- [6] ANSI/TIA/EIA-97-D (2001): "Recommended Minimum Performance Standard for Base Stations Supporting Dual-Mode Spread Spectrum Cellular Mobile Stations (ANSI/TIA/EIA-97-D-2001)".
- [7] ANSI/TIA/EIA/IS-870 (2001): "Test Data Service Option (TDSO) for cdma2000 Spread Spectrum Systems".
- [8] ANSI/TIA/EIA/IS-871 (2001): "Markov Service Option (MSO) for cdma2000 Spread Spectrum Systems".

- [9] ETSI EN 301 489 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services".
- [10] ANSI/TIA/EIA/IS-2000.5-A-1 (2000): "Upper Layer (Layer 3) Signaling Standard for cdma2000 Spread Spectrum Systems, Addendum 1".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [1] and the following apply:

Access Attempt: sequence of one or more access probe sequences on the Access Channel or Enhanced Access Channel containing the same message

NOTE: See also Access Probe, Access Probe Sequence, and Enhanced Access Probe.

Access Channel: reverse CDMA Channel used by mobile stations for communicating to the base station

NOTE: The Access Channel is used for short signalling message exchanges, such as call originations, responses to pages, and registrations. The Access Channel is a slotted random access channel.

Access Channel Preamble: preamble of an access probe consisting of a sequence of all-zero frames that is sent at the 4 800 bps rate

Access Probe: one Access Channel transmission consisting of a preamble and a message

NOTE: The transmission is an integer number of frames in length, and transmits one Access Channel message. See also Access Probe Sequence and Access Attempt.

Access Probe Sequence: sequence of one or more access probes on the Access Channel or Enhanced Access Channel

NOTE: The same Access Channel or Enhanced Access Channel message is transmitted in every access probe of an access attempt. See also Access Probe, Enhanced Access Probe, and Access Attempt.

Active Frame: frame that contains data and therefore is enabled in terms of traffic power

Additional Preamble: preamble sent after the last fractional preamble on the Reverse Pilot Channel, prior to transmitting on the Enhanced Access Channel or on the Reverse Common Control Channel

Adjacent Channel Leakage Ratio: ratio of the on-channel transmit power to the power measured in one of the adjacent channels

Bad Frame: frame classified with insufficient frame quality or for Radio Configuration 19 600 bps primary traffic only, with bit errors (see also Good Frame)

Band Class: set of frequency channels and a numbering scheme for these channels

NOTE: Band classes are defined in TIA/EIA-98-D [4], clause 3.1, and TIA/EIA-97-D [6], clause 3.1.

Band Class 6: frequencies as identified in table 1

Base Station: fixed station used for communicating with mobile stations

NOTE: For the purpose of tests in clause 5 of the present document the term Base Station may also apply to a Base Station simulator having the capabilities defined in TIA/EIA-98-D [4], clause 6.4.3.

Basic Access Mode: mode used on the Enhanced Access Channel where a mobile station transmits an Enhanced Access Channel preamble and Enhanced Access data in a method similar to that used on the Access Channel

Broadcast Control Channel: code channel in a Forward CDMA Channel used for transmission of control information from a base station to a mobile station

Candidate Frequency: frequency for which the base station specifies a search set, when searching on other frequencies while performing mobile-assisted handoffs

CDMA Channel: set of channels transmitted from the base station and the mobile stations on a given frequency

CDMA Channel Number: 11-bit number corresponding to the centre of the CDMA frequency assignment

CDMA Frequency Assignment: 1,23 MHz segment of spectrum

NOTE: For Band Class 0, the channel is centred on one of the 30 kHz channels. For Band Classes 1, 4, 6, 7, 8 and 9, the channel is centred on one of the 50 kHz channels. For Band Classes 2 and 3, the channel is centred on one of the 25 kHz channels. For Band Class 5, the channel is centred on one of the 20 kHz or 25 kHz channels.

CDMA Preferred Set: set of CDMA channel numbers in a CDMA system corresponding to frequency assignments that a mobile station will normally search to acquire a CDMA Pilot Channel

Code Channel: subchannel of a Forward CDMA Channel or Reverse CDMA Channel

NOTE: Each subchannel uses an orthogonal Walsh function or quasi-orthogonal function.

Code Division Multiple Access (CDMA): technique for spread-spectrum multiple-access digital communications that creates channels through the use of unique code sequences

Code Symbol: output of an error-correcting encoder

NOTE: Information bits are input to the encoder and code symbols are output from the encoder (see Convolutional Code and Turbo Code).

Common Assignment Channel: forward common channel used by the base station to acknowledge a mobile station accessing the Enhanced Access Channel, and in the case of Reservation Access Mode, to transmit the address of a Reverse Common Control Channel and associated Common Power Control Subchannel

Common Power Control Channel: forward common channel which transmits power control bits (i.e. common power control subchannels) to multiple mobile stations

NOTE: The Common Power Control Channel is used by mobile stations operating in the Power Controlled Access Mode, Reservation Access Mode, or Designated Access Mode.

Common Power Control Subchannel: subchannel on the Common Power Control Channel used by the base station to control the power of a mobile station when operating in the Power Controlled Access Mode on the Enhanced Access Channel or when operating in the Reservation Access Mode or the Designated Access Mode on the Reverse Common Control Channel

Continuous Transmission: mode of operation in which Discontinuous Transmission is not permitted

Convolutional Code: type of error-correcting code

NOTE: A code symbol can be considered as the convolution of the input data sequence with the impulse response of a generator function.

Cyclic Redundancy Code: class of linear error detecting codes which generate parity check bits by finding the remainder of a polynomial division (see also Frame Quality Indicator)

Discontinuous Transmission: mode of operation in which a base station or a mobile station switches its transmitter or a particular code channel on and off autonomously

NOTE: For the case of DTX operation on the Forward Dedicated Control Channel, the Forward Power Control Subchannel is still transmitted.

Effective Radiated Power: product of the power supplied to the antenna and the antenna gain in a direction relative to a half-wave dipole