



IEC 62271-102

Edition 1.2 2013-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE



High-voltage switchgear and controlgear –
Part 102: Alternating current disconnectors and earthing switches

Appareillage à haute tension –
Partie 102: Sectionneurs et sectionneurs de terre à courant alternatif

<https://standards.iteh.ai/xct/lego/standards/Iec/61bd11c0-9a09-4c49-b7d7-7810de6afbe6/iec-62271-102-2001>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2013 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Liens utiles:

Recherche de publications CEI - www.iec.ch/searchpub

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Just Published CEI - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



IEC 62271-102

Edition 1.2 2013-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE



High-voltage switchgear and controlgear –
Part 102: Alternating current disconnectors and earthing switches

Appareillage à haute tension –
Partie 102: Sectionneurs et sectionneurs de terre à courant alternatif

<https://standards.iteh.ai/xtdl/leg/standards/IC/611d1fc0-9a09-4c49-b7d7-7810de6afbe6/iec-62271-102-2001>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.130.10; 29.130.99

ISBN 978-2-8322-0650-8

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD	6
1 General	10
1.1 Scope	10
1.2 Normative references	10
2 Normal and special service conditions	11
3 Definitions	11
3.1 General terms	11
3.2 Assemblies of switchgear and controlgear	11
3.3 Parts of assemblies	11
3.4 Switching devices	11
3.5 Parts of switching devices	13
3.6 Operation	14
3.7 Characteristic quantities	15
4 Ratings	18
4.1 Rated voltage (U_r)	18
4.2 Rated insulation level	18
4.3 Rated frequency (f_r)	19
4.4 Rated normal current and temperature rise	19
4.5 Rated short-time withstand current (I_k)	19
4.6 Rated peak withstand current (I_p)	19
4.7 Rated duration of short-circuit (t_k)	19
4.8 Rated supply voltage of closing and opening devices and of auxiliary and control circuits (U_a)	19
4.9 Rated supply frequency of closing and opening devices and of auxiliary circuits	19
4.10 Rated pressure of compressed gas supply for insulation and/or operation	19
5 Design and construction	23
5.1 Requirements for liquids in disconnectors and earthing switches	23
5.2 Requirements for gases in disconnectors and earthing switches	23
5.3 Earthing of disconnectors and earthing switches	23
5.4 Auxiliary and control equipment	23
5.5 Dependent power operation	24
5.6 Stored energy operation	24
5.7 Independent manual operation	24
5.8 Operation of releases	24
5.9 Low- and high-pressure interlocking and monitoring devices	24
5.10 Nameplates	24
5.11 Interlocking devices	25
5.12 Position indication	25
5.13 Degree of protection by enclosures	25
5.14 Creepage distances	26
5.15 Gas and vacuum tightness	26
5.16 Liquid tightness	26
5.17 Flammability	26
5.18 Electromagnetic compatibility (EMC)	26

6	Type tests	28
6.1	General	28
6.2	Dielectric tests.....	29
6.3	Radio interference voltage (riv) test	31
6.4	Measurement of the resistance of circuits	32
6.5	Temperature-rise tests.....	32
6.6	Short-time withstand current and peak withstand current tests.....	32
6.7	Verification of the protection	34
6.8	Tightness tests	34
6.9	Electromagnetic compatibility tests (EMC)	34
7	Routine tests	46
7.1	Dielectric test on the main circuit	46
7.2	Dielectric test on auxiliary and control circuits	46
7.3	Measurement of the resistance of the main circuit	47
7.4	Tightness test.....	47
7.5	Design and visual checks	47
8	Guide to the selection of disconnectors and earthing switches	47
9	Information to be given with enquiries, tenders and orders	50
10	Rules for transport, storage, installation, operation and maintenance	53
10.1	Conditions during transport, storage and installation.....	53
10.2	Installation.....	53
10.3	Operation	54
10.4	Maintenance	54
11	Safety.....	54
11.1	Electrical aspects	54
11.2	Mechanical aspects	54
11.3	Thermal aspects	54
11.4	Operation aspects	54
	Annex A (normative) Design and testing of position indicating devices.....	65
	Annex B (normative) Bus-transfer current switching by disconnectors	70
	Annex C (normative) Induced current switching by earthing switches	77
	Annex D (informative) Test voltage for the most disadvantageous dielectric position of an earthing switch during operation (temporary approach)	87
	Annex E (normative) Special requirements for disconnectors and earthing switches used in gas-insulated and/or metal-enclosed switchgear	88
	Annex F (normative) Gas-insulated metal-enclosed switchgear for rated voltages 72,5 kV and above – Requirements for switching of bus-charging currents by disconnectors	93
	Annex G (normative) Alternative test methods for short-circuit current making tests	101
	Annex H (normative) Specific requirements for resistor fitted disconnector in metal-enclosed gas insulated switchgear.....	103
	Bibliography.....	106

Figure 1 – Fixed contact parallel to support	54
Figure 2 – Fixed contact (as indicated in figure 8) perpendicular to support	55
Figure 3 – Three-phase test arrangement for disconnectors and earthing switches with rated voltages below 52 kV.....	56
Figure 4 – Single-phase test arrangement for disconnectors with a horizontal isolating distance and for earthing switches with rated voltage of 52 kV and above.....	58
Figure 5 – Single-phase test arrangement for divided support disconnectors (earthing switches) with a vertical isolating distance with rated voltages of 52 kV and above to be used with flexible conductors	60
Figure 6 – Single-phase test arrangement for divided support disconnectors (earthing switches) with a vertical isolating distance with rated voltages of 52 kV and above to be used with rigid conductors	62
Figure 7 – Example of the application of rated mechanical terminal loads to a two-column disconnector	63
Figure 8 – Example of the application of rated mechanical terminal loads to a pantograph disconnector.....	64
Figure A.1 – Position indicating device	69
Figure B.1 – Test circuits for bus-transfer current making and breaking tests.....	76
Figure C.1 – Test circuit for electromagnetically induced current making and breaking tests	85
Figure C.2 – Test circuits for electrostatically induced current making and breaking tests	86
Figure F.1 – Test circuit for test duty 1	95
Figure F.2 – Typical voltage waveform (Including VFT and FT components)	96
Figure F.3 – Test circuit for test duty 2	97
Figure F.4 – Test circuit for test duty 3	98
Figure H.1 – Examples of resistor fitted disconnectors	103

<https://standards.iteh.ai/ctf/02/standards/kc/61fd1fc0-9a09-4c49-b7d7-7810de6afbe6/iec-62271-102-2001>

Table 1 – Recommended contact zones for "fixed" contacts supported by flexible conductors	20
Table 2 – Recommended contact zones for "fixed" contacts supported by rigid conductors	21
Table 3 – Recommended static mechanical terminal loads.....	22
Table 3a – Classification of disconnectors for mechanical endurance	23
Table 4 – Nameplate information	25
Table 5 – Power frequency 1 min withstand voltages	31
Table 6 – Power frequency voltage tests.....	46
Table 7 – Classification of earthing switch for electrical endurance	23
Table 8 – Requirements on making current and pre-arc time	37
Table 9 – Invalid tests	38
Table B.1 – Rated bus-transfer voltages for disconnectors.....	71
Table C.1 – Standardized values of rated induced currents and voltages for earthing switches	79
Table C.2 – Standardized values of recovery voltages for electromagnetically induced current breaking tests	82
Table C.3 – Test circuit capacitances (C_1 values) for electrostatically induced current making and breaking tests	83

Table F.1 – Test voltages for making and breaking tests.....	95
Table F.2 – Specified bus-charging currents	98
Table F.3 – Specified number of tests	98



<https://standards.iteh.ai/ctolog/standards/IEC/61110-102:2001>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –**Part 102: Alternating current disconnectors
and earthing switches****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of IEC 62271-102 consists of the first edition (2001) [documents 17A/617/FDIS and 17A/619/RVD], its amendment 1 (2011) [documents 17A/972/FDIS and 17A/978/RVD], its amendment 2 (2013) [documents 17A/1029/FDIS and 17A/1035/RVD] its corrigenda of April 2002, May 2003, February 2005, January 2012 and June 2014. It bears the edition number 1.2.

The technical content is therefore identical to the base edition and its amendments and has been prepared for user convenience. A vertical line in the margin shows where the base publication has been modified by amendments 1 and 2. Additions and deletions are displayed in red, with deletions being struck through.

International Standard IEC 62271-102 has been prepared by subcommittee 17A: High-voltage switchgear and controlgear, of IEC technical committee 17: Switchgear and controlgear.

The bilingual version (2003-08) corresponds to the monolingual English version, published in 2001-12.

The French version of this standard has not been voted upon.

Annexes A, B, C, E, F, G and H form an integral part of this standard.

Annex D is for information only.

This standard should be read in conjunction with IEC 60694, second edition, published in 1996, to which it refers and which is applicable, unless otherwise specified. In order to simplify the indication of corresponding requirements, the same numbering of clauses and subclauses is used as in IEC 60694. Additional subclauses are numbered from 101.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

<https://standards.iec.ch/62271-102-2001>

**COMMON NUMBERING OF IEC 62271 PUBLICATIONS FALLING UNDER
THE RESPONSIBILITY OF SUBCOMMITTEES SC 17A AND SC 17C**

In accordance with the decision taken at the joint SC 17A/SC 17C meeting in Frankfurt, June 1998 (item 20.7 of 17A/535/RM), a common numbering system has been established for the publications falling under the responsibility of SC 17A and SC 17C. IEC 62271 – *High-voltage switchgear and controlgear* is the publication number and main title element for the common publications.

The numbering of these publications will apply the following principle.

- a) Common standards prepared by SC 17A and SC 17C will start with IEC 62271-1.
- b) Standards of SC 17A will start with IEC 62271-100.
- c) Standards of SC 17C will start with number IEC 62271-200.
- d) Publications prepared by SC 17A and SC 17C will start with number IEC 62271-300.

The table below relates the new numbers to the old numbers. The parts numbered (xxx) will be given a final number pending the decision to publish the revised publication as standard or technical report.

<https://standards.iteh.ai/ctalog/standards/IEC/61bd1fc0-9a09-4c49-b7d7-7810de6afbe6/iec-62271-102-2001>

**Common numbering of IEC 62271 publications falling under the responsibility
of subcommittees SC 17A and SC 17C**

IEC 62271 series	HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR – New title	Old IEC number, if any
Part	New title	
1	Common specifications	IEC 60694
2	Seismic qualification for rated voltages of 72,5 kV and above	-
100	High-voltage alternating current circuit-breakers	IEC 60056
101	Synthetic testing	IEC 60427
102	High-voltage alternating current disconnectors and earthing switches	IEC 60129
103	Switches for rated voltages above 1 kV and less than 52 kV	IEC 60265-1
104	Switches for rated voltages of 52 kV and above	IEC 60265-2
105	Alternating current switch-fuse combinations	IEC 60420
106	Alternating current contactors and contactor-based motor starters	IEC 60470
107	Alternating current switchgear-fuse combinations	-
108	Switchgear having combined functions	-
109	Series capacitor by-pass switches	-
200	AC metal-enclosed switchgear and controlgear for rated voltages above 1 kV and up to and including 52 kV	IEC 60298
201	Insulation-enclosed switchgear and controlgear for rated voltages up to and including 52 kV	IEC 60466
202	High-voltage/low-voltage prefabricated substations	IEC 61330
203	Gas-insulated metal-enclosed switchgear for rated voltages above 52 kV	IEC 60517
204	High-voltage gas-insulated transmission lines for rated voltages of 72,5 kV and above	IEC 61640
(300)	Guide for seismic qualification of high-voltage alternating current circuit-breakers	IEC 61166
(301)	Guide for inductive load switching	IEC 61233
(302)	Guide for short-circuit and switching test procedures for metal-enclosed and dead tank circuit-breakers	IEC 61633
(303)	Use and handling of sulphur hexafluoride (SF_6) in high-voltage switchgear and controlgear	IEC 61634
(304)	Additional requirements for enclosed switchgear and controlgear from 1 kV to 72,5 kV to be used in severe climatic conditions	IEC 60932
(305)	Cable connections for gas-insulated metal-enclosed switchgear for rated voltages above 52 kV	IEC 60859
(306)	Direct connection between power transformers and gas-insulated metal-enclosed switchgear and controlgear for rated voltages above 52 kV	IEC 61639
(307)	Use of electronic and associated technologies in auxiliary equipment of switchgear and controlgear	IEC 62063
308	Guide for asymmetrical short-circuit breaking test duty T100a	-
309	TRV parameters for high-voltage switchgear and controlgear for rated voltages above 1 kV and less than 100 kV	-
310	Electrical endurance testing for circuit-breakers rated 72,5 kV and above	-

HIGH-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 102: Alternating current disconnectors and earthing switches

1 General

1.1 Scope

This part of IEC 62271 applies to alternating current disconnectors and earthing switches, designed for indoor and outdoor enclosed and open terminal installations for voltages above 1 000 V and for service frequencies up to and including 60 Hz.

It also applies to the operating devices of these disconnectors and earthing switches and their auxiliary equipment.

Additional requirements for disconnectors and earthing switches in enclosed switchgear and controlgear are given in IEC 60298, IEC 60466 and IEC 60517.

NOTE Disconnectors in which the fuse forms an integral part are not covered by this standard.

1.2 Normative references

Subclause 1.2 of IEC 60694 is applicable with the following additions:

IEC 60137:1995, *Insulating bushings for alternating voltages above 1 000 V*

IEC 60265-1:1998, *High-voltage switches – Part 1: Switches for rated voltages above 1 kV and less than 52 kV*

IEC 60265-2:1988, *High-voltage switches – Part 2: High-voltage switches for rated voltages of 52 kV and above*

IEC 60298:1990, *A.C. metal-enclosed switchgear and controlgear for rated voltages above 1 kV and up to and including 52 kV*

IEC 60466:1987, *A.C. insulation-enclosed switchgear and controlgear for rated voltages above 1 kV and up to and including 38 kV*

IEC 60517:1990, *Gas-insulated metal-enclosed switchgear for rated voltages of 72,5 kV and above*

IEC 60694:1996, *Common specifications for high-voltage switchgear and controlgear standards*

IEC 60865-1:1993, *Short-circuit currents – Calculation of effects – Part 1: Definitions and calculation methods*

IEC 62271-1:2007, *High-voltage switchgear and controlgear – Part 1: Common specifications*

IEC 62271-100:2008, *High-voltage switchgear and controlgear – Part 100: Alternating-current circuit-breakers*

ISO 2768-1:1989, *General tolerances – Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*

2 Normal and special service conditions

Clause 2 of IEC 60694 is applicable.

3 Definitions

Clause 3 of IEC 60694 is applicable with the following additions:

This clause covers required definitions, most of them by reference to IEC 60050(151), IEC 60050(441) and IEC 60050(604).

3.1 General terms

3.1.101

indoor switchgear and controlgear

[IEV 441-11-04]

3.1.102

outdoor switchgear and controlgear

[IEV 441-11-05]

3.1.103

temperature rise (of a part of a disconnector or earthing switch)

difference between the temperature of the part and the ambient air temperature

3.1.104

user

person or legal entity using the disconnectors or earthing switches

NOTE 1 This may include the purchaser (for example an electricity supplier), but it may also include the contracting company, the staff responsible for installation, the maintenance or operating staff or anybody else temporarily or permanently responsible for the disconnector, earthing switch or substation, or even the operation of the switchgear.

3.2 Assemblies of switchgear and controlgear

No particular definitions.

3.3 Parts of assemblies

No particular definitions.

3.4 Switching devices

3.4.101

disconnector

IEV 441-14-05 is applicable with the following additional notes:

NOTE 1 "Negligible current" implies currents such as the capacitive currents of bushings, busbars, connections, very short lengths of cable, currents of permanently connected grading impedances of circuit-breakers and currents of voltage transformers and dividers. For rated voltages of 420 kV and below, a current not exceeding 0.5 A is a negligible current for the purpose of this definition; for rated voltage above 420 kV and currents exceeding 0.5 A, the manufacturer should be consulted.

"No significant change in voltage" refers to such applications as the bypassing of induction voltage regulators or circuit-breakers.

NOTE 2 For a disconnector having a rated voltage of 52 kV and above, a rated ability of bus-transfer current switching may be assigned.

NOTE 1 "Negligible current" implies currents such as the capacitive currents of bushings, busbars, connections, very short lengths of cable, currents of permanently connected grading impedances of circuit-breakers and currents of voltage transformers and dividers (see also IEC 62271-305). For rated voltages of 420 kV and below, a current not exceeding 0,5 A is a negligible current for the purpose of this definition; for rated voltage above 420 kV and currents exceeding 0,5 A, the manufacturer should be consulted. "No significant change in voltage" refers to such applications as the by-passing of induction voltage regulators or circuit-breakers and bus transfer.

NOTE 2 For a disconnector having a rated voltage of 52 kV and above, a rated ability of bus transfer current switching may be assigned.

3.4.101.1

disconnector class M0

disconnector having a mechanical endurance of 1 000 operating cycles, suitable for applications in distribution and transmission systems fulfilling the general requirements of this standard

3.4.101.2

disconnector class M1

disconnector having an extended mechanical endurance of 2 000 operating cycles, mainly for applications where the disconnector is operated in conjunction with a circuit-breaker of an equal class

3.4.101.3

disconnector class M2

disconnector having an extended mechanical endurance of 10 000 operating cycles, mainly for applications where the disconnector is operated in conjunction with a circuit-breaker of an equal class

3.4.102

divided support disconnector (earthing switch)

[IEV 441-14-06(07)]

NOTE Examples are pantograph and semi-pantograph disconnectors.

3.4.103 centre-break disconnector

[IEV 441-14-08]

3.4.104 double-break disconnector

[IEV 441-14-09]

3.4.105

earthing switch

IEV 441-14-11 is applicable with the following additional notes:

NOTE An earthing switch having a rated voltage of 52 kV and above may have a rating for switching and carrying induced currents.

~~Classes E1, E2 and E3 of IEC 60265-1 are based on electrical endurance of switches and switch-disconnectors. These devices may sometimes be operated against a short-circuit as a normal operation duty and the electrical endurance may be the measure of "low maintenance".~~

NOTE 101 An earthing switch having a rated voltage of 52 kV and above may have a rating for switching and carrying induced currents.

NOTE 102 These devices may sometimes be operated against short-circuit. The different classes of earthing switches are related to the number of short-circuit making operations.

NOTE 103 For special applications such as fault initiating earthing switches the test procedures and the number of tests may be agreed upon between the manufacturer and the user.