

**SLOVENSKI STANDARD
SIST EN 301 815-5 V1.1.1:2005
01-januar-2005**

ü]fc_cdUgcj bc 'X][]HJbc 'ca fYy'Y n']bhY[f]fUb]a]'ghcf]lj Ua]'fb !=G8 BŁĘDfc hc_c`
X][]HJbYbUfc b]ý_Yg][bU]nU]Y'ýH" & fB GG&ŁĘF UrnfYX_U_cj cgh'ghcf]lj Y]b
]bX]_U]UdUfUa Yfcj 'df]j ndcghUj 'Ub1 ' `]WU#nj YnY'Ę) "XY. 'N[fUXVU
dfYg_i ýUbY[Ub]nU]b'bUa Yb'dfYg_i ýUb'UfHGG' HDŁĘGdYW]_U]Ua ca fYy'Y

Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Quality of Service class and parameters indication at call/connection establishment; Part 5: Test Suite Structure and Test Purposes (TSS&TP) specification for the network

iTeh STANDARD PREVIEW

(standards.iteh.ai)

[SIST EN 301 815-5 V1.1.1:2005](#)
<https://standards.iteh.ai/catalog/standards/sist/165330c6-55ae-47df-9ef0-63b39fe591/sist-en-301-815-5-v1-1-1-2005>

Ta slovenski standard je istoveten z: EN 301 815-5 Version 1.1.1

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

SIST EN 301 815-5 V1.1.1:2005 en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 301 815-5 V1.1.1:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/165330c6-55ae-47df-9ef0-63fb39fe591/sist-en-301-815-5-v1-1-1-2005>

ETSI EN 301 815-5 V1.1.1 (2002-10)

European Standard (Telecommunications series)

**Broadband Integrated Services Digital Network (B-ISDN);
Digital Subscriber Signalling System No. two (DSS2) protocol;
Quality of Service class and parameters indication
at call/connection establishment;
Part 5: Test Suite Structure and Test Purposes (TSS&TP)
specification for the network**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 815-5 V1.1.1:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/165330c6-55ae-47df-9ef0-63fb39fe591/sist-en-301-815-5-v1-1-2005>



Reference

DEN/SPAN-130251-5

Keywords

B-ISDN, DSS2, network, quality, TSS&TP

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 815-5 V1.1.1:2005

<https://standards.iteh.ai/catalog/standards/sist/165330c6-55ae-47df-9ef0-63f339fe5d> Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:
editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	4
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.1.1 Definitions related to conformance testing	6
3.1.2 Definitions related to EN 301 815-1	6
3.2 Abbreviations	6
4 Test Suite Structure (TSS).....	7
5 Test Purposes (TP)	7
5.1 Introduction	7
5.1.1 TP naming convention	7
5.1.2 Source of TP definition	7
5.1.3 Test strategy	7
5.1.4 Test of call states	7
5.2 TPs for the Quality of Service Class and Parameters indication, network	8
5.2.1 Support of Quality of Service classes (01).....	8
5.2.2 Signalling of individual Quality of Service parameters.....	8
5.2.2.1 End-to-end transit delay procedures (02).....	8
5.2.2.2 Extended QoS parameters procedures (03).....	10
6 Compliance.....	11
7 Requirements for a comprehensive testing service.....	11
Annex A (informative): Bibliography	12
History	13

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN).

The present document is part 5 of a multi-part deliverable covering the Digital Subscriber Signalling System No. two (DSS2) protocol specification for the Broadband Integrated Services Digital Network (B-ISDN) to support Quality of Service class and parameters indication at call/connection establishment, as identified below:

- Part 1: "Protocol specification [ITU-T Recommendations Q.2965.1 (1999) and Q.2965.2 (1999), modified]";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification [ITU-T Recommendations Q.2965.1B (2000) and Q.2965.2B (2000), modified]";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user":
<https://standards.ieee.org/catalog/standards/sist/165330c6-55ae-47df-9ef0-638296a591/sist-en-201815-5-v1-1-1-2005>
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";**
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

National transposition dates	
Date of adoption of this EN:	11 October 2002
Date of latest announcement of this EN (doa):	31 January 2003
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2003
Date of withdrawal of any conflicting National Standard (dow):	31 July 2003

1 Scope

The present document specifies the network Test Suite Structure and Test Purposes (TSS&TP) for the T_B reference point or coincident S_B and T_B reference point (as defined in ITU-T Recommendation I.413 [5]) of implementations conforming to the standards for the Broadband Integrated Services Digital Network (B-ISDN) Digital Subscriber Signalling System No. two (DSS2) protocol specification for support of Quality of Service Class and parameters indication at call/connection establishment defined in EN 301 815-1 [1].

A further part of the present document specifies the Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma based on the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] ETSI EN 301 815-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Quality of Service Class and parameters indication at call/connection establishment; Part 1: Protocol specification [ITU-T Recommendations Q.2965.1 (1999) and Q.2965.2 (1999), modified]".
- [2] ETSI EN 301 815-2: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Quality of Service class and parameters indication at call/connection establishment; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification [ITU-T Recommendations Q.2965.1B (2000) and Q.2965.2B (2000), modified]".
- [3] ISO/IEC 9646-1 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [4] ISO/IEC 9646-2 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract Test Suite specification".
- [5] ITU-T Recommendation I.413 (1993): "B-ISDN user-network interface".
- [6] ETSI ETS 300 406: "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [7] ETSI EN 300 443-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]".
- [8] ITU-T Recommendation Q.2965.1: "Digital Subscriber Signalling System No. 2 - Support of Quality of Service classes".
- [9] ITU-T Recommendation Q.2965.2: "Digital Subscriber Signalling System No. 2 - Signalling of individual Quality of Service parameters".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 301 815-1 [1], EN 300 443-1 [7] and the following apply.

3.1.1 Definitions related to conformance testing

abstract test case: Refer to ISO/IEC 9646-1 [3].

Abstract Test Method (ATM): Refer to ISO/IEC 9646-1 [3].

Abstract Test Suite (ATS): Refer to ISO/IEC 9646-1 [3].

Implementation Under Test (IUT): Refer to ISO/IEC 9646-1 [3].

Lower Tester (LT): Refer to ISO/IEC 9646-1 [3].

Protocol Implementation Conformance Statement (PICS): Refer to ISO/IEC 9646-1 [3].

PICS proforma: Refer to ISO/IEC 9646-1 [3].

Protocol Implementation eXtra Information for Testing (PIXIT): Refer to ISO/IEC 9646-1 [3].

PIXIT proforma: Refer to ISO/IEC 9646-1 [3].

Test Purpose (TP): Refer to ISO/IEC 9646-1 [3].

(standards.iteh.ai)

3.1.2 Definitions related to EN 301 815-1

network: DSS2 protocol entity at the Network side of the user-network interface where a T_B reference point or coincident S_B and T_B reference point applies

network (S_B/T_B): DSS2 protocol entity at the Network side of the user-network interface where a coincident S_B and T_B reference point applies

network (T_B): DSS2 protocol entity at the Network side of the user-network interface where a T_B reference point applies (user is the private ISDN)

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATM	Abstract Test Method
ATS	Abstract Test Suite
B-ISDN	Broadband Integrated Services Digital Network
DSS2	Digital Subscriber Signalling System No. two
IUT	Implementation Under Test
N0	Null call/connection state
N10	Active call/connection state
N3	Outgoing Call Proceeding call/connection state
N6	Call Present call/connection state
N7	Call Received call/connection state
N9	Incoming Call Proceeding call/connection state
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing

QoS	Quality of Service
TP	Test Purpose
TSS	Test Suite Structure

4 Test Suite Structure (TSS)

- Support of Quality of Service classes (01)
- Signalling of individual Quality of Service parameters
 - End-to-end transit delay procedures (02)
 - Extended QoS parameters procedures (03)

5 Test Purposes (TP)

5.1 Introduction

For each test requirement a TP is defined.

5.1.1 TP naming convention

TPs are numbered, starting at 01, within each group. Groups are organized according to the TSS. Additional references are added to identify the actual test suite (see table 1).
(standards.iteh.ai)

Table 1: TP identifier naming convention scheme

SIST EN 301 815-5 V1.1.1:2005

Identifier: <suite_id>_<group>_<nnn>	https://standards.iteh.ai/catalog/standards/sist/165330c6-55ae-47df-9ef0-63f39eb91/sist-en-301-815-5-v1-1-1-2005
<suite_id> = service + type of IUT:	"QOSN" for Quality Of Service class and parameters indication, IUT = Network
<group> = group number:	two character field representing the group reference according to TSS
<nn> = sequential number:	(01-99)

5.1.2 Source of TP definition

The TPs are based on EN 301 815-1 [1].

5.1.3 Test strategy

As the base standard EN 301 815-1 [1] contains no explicit requirements for testing, the TPs were generated as a result of an analysis of the base standard and the PICS specification EN 301 815-2 [2].

The TPs are only based on conformance requirements related to the externally observable behaviour of the IUT and are limited to conceivable situations to which a real implementation is likely to be faced (ETS 300 406 [6]).

5.1.4 Test of call states

Many TPs include a reference to the IUT's final call state after the realization of the TP. In these cases the TP includes the requirement to ensure that the IUT has entered this particular final call state. Ensuring that the IUT is in a particular call state shall be realized by following the procedures described in clause 5.6.11 of EN 300 443-1 [7]. According to these procedures, the IUT on receipt of a STATUS ENQUIRY message, shall respond with a STATUS message indicating, in the fifth octet of the Call state information element, the current call state of the IUT. This exchange of messages is not mentioned explicitly in each TP but is considered to be implicit in the reference to the final call state. This way of phrasing the TPs has been used to avoid over-complicating the text and structure of the TPs and to improve the readability.