



**SLOVENSKI STANDARD**  
**SIST EN 302 085 V1.1.2:2003**

**01-december-2003**

---

: ]\_gb]`fUX]`g\_]`g]ghYa ]`È`5 bhYbY`hjdU`lc \_U]j Y `lc \_`È`5 bhYbY`nU`Z]\_gbY`fUX]`g\_]`Y`g]ghYa Y`hjdU`lc \_U]j Y `lc \_]`j`dUgi`cX`' `; <n`Xc`%%; <n

Fixed Radio Systems; Point-to-Multipoint Antennas; Antennas for point-to-multipoint fixed radio systems in the 3 GHz to 11 GHz band

**iteh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Ta slovenski standard je istoveten z: **EN 302 085 Version 1.1.2**

SIST EN 302 085 V1.1.2:2003  
<https://standards.iteh.ai/catalog/standards/sist/c942eb5f-c1b2-4713-ad4b-471a6b7af843/sist-en-302-085-v1-1-2-2003>

---

**ICS:**

33.060.30	Radiorelejni in fiksni satelitski komunikacijski sistemi	Radio relay and fixed satellite communications systems
33.120.40	Antene	Aerials

**SIST EN 302 085 V1.1.2:2003**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 302 085 V1.1.2:2003](https://standards.iteh.ai/catalog/standards/sist/c942eb5f-c1b2-47f3-ad4b-471a6b7af843/sist-en-302-085-v1-1-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/c942eb5f-c1b2-47f3-ad4b-471a6b7af843/sist-en-302-085-v1-1-2-2003>

# ETSI EN 302 085 V1.1.2 (2001-02)

---

*European Standard (Telecommunications series)*

## **Fixed Radio Systems; Point-to-Multipoint Antennas; Antennas for point-to-multipoint fixed radio systems in the 3 GHz to 11 GHz band**

---

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 302 085 V1.1.2:2003](https://standards.iteh.ai/catalog/standards/sist/c942eb5f-c1b2-47f3-ad4b-471a6b7af843/sist-en-302-085-v1-1-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/c942eb5f-c1b2-47f3-ad4b-471a6b7af843/sist-en-302-085-v1-1-2-2003>



---

**Reference**

REN/TM-04138

---

**Keywords**DRRS, radio, antenna, multipoint, CDMA, FDMA,  
RLL, TDMA, transmission**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**SIST EN 302 085 V1.1.2:2003<https://standards.iteh.ai/catalog/standards/sist/c942eb5f-c1b2-47f3-ad4b-471a6b7af843/sist-en-302-085-v1-1-2-2003>

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:  
editor@etsi.fr

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.  
All rights reserved.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Introduction.....	5
1 Scope.....	6
2 References.....	6
3 Definitions, symbols and abbreviations .....	7
3.1 Definitions .....	7
3.2 Symbols .....	8
3.3 Abbreviations.....	8
4 Frequency bands.....	8
5 Types and classification of antennas.....	9
5.1 Antenna Types .....	9
5.2 Antenna classifications.....	9
5.2.1 CS Classes.....	9
5.2.2 TS Classes .....	10
6 Electrical Characteristics.....	10
6.1 Terminal Station (TS) Antennas.....	10
6.1.1 TS Radiation Pattern Envelope (RPE).....	10
6.1.1.1 Range 1 (3,0 GHz to 5,9 GHz).....	11
6.1.1.2 Range 2 (5,9 GHz to 8,5 GHz).....	13
6.1.1.3 Range 3 (8,5 GHz to 11,0 GHz).....	14
6.1.2 TS Minimum Boresight Gain .....	15
6.2 Central Station (CS) Sectored Antennas.....	15
6.2.1 CS Azimuth Radiation Pattern Envelope (RPE), Sectored.....	15
6.2.1.1 Class CS 1.....	16
6.2.1.2 Class CS 2.....	16
6.2.1.3 Class CS 3.....	17
6.2.2 Minimum Boresight Gain, Sectored.....	17
6.3 Central Station (CS) Omni-Directional Antennas .....	18
6.4 Central Station (CS) Omni and Sectored Elevation RPEs .....	18
6.4.1 Symmetric elevation RPEs .....	18
6.4.2 Asymmetric elevation patterns .....	19
6.5 Polarization, Terminal (TS) and Central (CS) Stations.....	20
6.6 Radomes .....	20
7 Conformance tests .....	20
<b>Annex A (informative): Antenna Characteristics .....</b>	<b>21</b>
A.1 Mechanical Characteristics .....	21
A.1.1 Environmental characteristics .....	21
A.1.2 Antenna stability .....	21

A.2	Antenna input connectors.....	22
A.3	VSWR at the input port(s).....	22
A.4	Inter-port isolation.....	22
A.5	Antenna labelling.....	22
A.6	Passive intermodulation performance.....	22
<b>Annex B (informative):</b>	<b>Bibliography.....</b>	<b>23</b>
History .....		24

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 302 085 V1.1.2:2003](https://standards.iteh.ai/catalog/standards/sist/c942eb5f-c1b2-47f3-ad4b-471a6b7af843/sist-en-302-085-v1-1-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/c942eb5f-c1b2-47f3-ad4b-471a6b7af843/sist-en-302-085-v1-1-2-2003>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Transmission and Multiplexing (TM).

The current revision V1.1.2 was produced because of errors in figures 4 and 5. Tables 16 and 17 were introduced for readability reasons.

The purpose of the present document is to define the antenna performance standards necessary to ensure optimum frequency co-ordination between the systems and/or different services by the Regulatory Authorities in the 3 GHz to 11 GHz band. These nominal frequency limits have been chosen to reflect the WARC '92 Final Acts [6] and the frequency plans as given in CEPT Recommendations T/R 13-02 [1] and ITU-R Recommendation F.748-1 [5].

Point-to-multipoint antennas, whether integrated within station equipment or not, may need to meet environmental, mechanical and electrical characteristics not covered by the present document, in order that the systems will operate as intended. Additional parameters and characteristics may be subject to agreement between the equipment purchaser and the supplier; these are considered and guidance is provided in annex A.

<https://standards.iteh.ai/catalog/standards/sist/c942eb5f-c1b2-47f3-ad4b-471a6b7af843/sist-en-302-085-v1-1-2-2003>

### National transposition dates

Date of latest announcement of this EN (doa):	31 May 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2001
Date of withdrawal of any conflicting National Standard (dow):	30 November 2001

---

## Introduction

The purpose of the present document is to define the requirements for antennas used in conjunction with point-to-multipoint (P-MP) systems necessary to facilitate frequency co-ordination between services in the frequency bands 3 GHz to 11 GHz.

---

## 1 Scope

The present document specifies the essential electrical requirements for linear polarization, fixed beam antennas to be utilized with new Point-to-Multipoint (P-MP) systems, including central station and terminal station applications, operating in frequency bands from 3 GHz to 11 GHz. These systems use various multiple access schemes. Electronically steerable antennas and circularly polarized antennas are not considered in the present document.

Only in exceptional circumstances, and after a consultation period with operators and manufacturers, the Regulatory Authority may impose the use of tighter requirements than the minimum values given in the present document, in order to maximize the use of scarce spectrum resources.

For some high gain, point-to-multipoint requirements, antennas may be used having performance as per the appropriate point-to-point antenna standard. For these antennas, minimum requirements are given in EN 300 833 [8].

---

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, subsequent revisions do apply.

- iTeh STANDARD PREVIEW*  
*(standards.iteh.ai)*
- [1] CEPT Recommendation T/R 13-02: "Preferred channel arrangements for fixed services in the range 22,0 GHz to 29,5 GHz".
- [2] CEPT/ERC/REC 12-05: "Harmonized radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 10,0 GHz to 10,68 GHz".
- [3] CEPT/ERC/REC 14-03: "Harmonized radio frequency channel arrangements for low and medium capacity systems in the band 3 400 MHz to 3 600 MHz".
- [4] ITU-R Recommendation F.747: "Radio-frequency channel arrangements for radio-relay systems operating in the 10 GHz band".
- [5] ITU-R Recommendation F.748-1 (1994): "Radio- Frequency channel arrangements for radio-relay systems operating in the 25, 26 and 28 GHz bands".
- [6] Void.
- [7] ETSI ETS 300 019-1-4: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weatherprotected locations".
- [8] ETSI EN 300 833: "Fixed Radio Systems; Point-to-point Antennas; Antennas for point-to-point fixed radio systems operating in the frequency band 3 GHz to 60 GHz".
- [9] ETSI EN 301 126-3-2: "Fixed Radio Systems; Conformance testing; Part 3-2: Point-to-Multipoint antennas - Definitions, general requirements and test procedures".
- [10] IEC 60154-1: "Flanges for waveguides. Part 1: General requirements".
- [11] IEC 60154-2: "Flanges for waveguides. Part 2: Relevant specifications for flanges for ordinary rectangular waveguides".
- [12] IEC 60169 (part 1 and applicable subparts): "Radio-frequency connectors. Part 1: General requirements and measuring methods".



## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purpose of the present document the following terms and definitions apply:

**antenna:** that part of the transmitting or receiving system that is designed to transmit or receive electromagnetic radiation

**boresight:** axis of the main beam in a directional antenna

**Central Station (CS):** base station which communicates each way with many terminal stations and, in many cases, repeater stations

**co-polar pattern:** diagram representing the radiation pattern of a test antenna when the reference antenna is similarly polarized, scaled in dBi or dB relative to the measured antenna gain

**cross-polar pattern:** diagram representing the radiation pattern of a test antenna when the reference antenna is orthogonally polarized, scaled in dBi, or dB relative to the measured antenna gain

**cross-polar discrimination:** difference between the peak of the co-polarized main beam and the maximum cross-polarized signal over an angle measured within a defined region

**fixed beam:** radiation pattern in use is fixed relative to a defined mechanical reference plane

**gain:** ratio of the radiation intensity in a given direction to the radiation intensity that would be obtained if the power accepted by the antenna was radiated isotropically

**Half Power BeamWidth (HPBW):** angle, relative to the main beam axis, between the two directions at which the measured co-polar pattern is 3 dB below the value on the main beam axis

**inter-port isolation:** ratio in dB of the power level applied to one port of a multi-port antenna to the power level received in any other port of the same antenna as a function of frequency

**isotropic radiator:** hypothetical, lossless antenna having equal radiation intensity in all directions

**input port(s):** flange(s) or connector(s) through which access to the antenna is provided

**main beam axis:** direction for which the radiation intensity is a maximum

**main beam:** radiation lobe containing the direction of maximum radiation

**mechanical tilt:** fixed angular shift in elevation of the antenna main beam axis by a change to the physical mounting

**Radiation Pattern Envelope (RPE):** envelope within which the radiation pattern shall fit

**radiation pattern:** diagram relating power flux density at a constant distance from the antenna to the direction relative to the notional antenna main beam axis. Specifically referenced in the present document to the zero degree reference direction

**radome:** cover, of dielectric material, intended for protecting an antenna from the effects of its physical environment

**Repeater Station (RS):** radio station providing the connection via the air to both the central station and the terminal station(s). The remote station may also provide the interfaces to the subscriber equipment, if applicable

**sector angle:** declared angle of coverage in azimuth of a sectored antenna, defined as  $2\alpha$  in the present document

**Terminal Station (TS):** remote (out) station which communicates with a central station

**tilt:** fixed, angular shift of the antenna main beam axis (boresight) in the elevation plane by either electrical, electronic or mechanical means

**zero degree (0°):** declared direction as referenced to the antenna

**reference direction:** mechanical characteristics, used as reference for the RPE

## 3.2 Symbols

For the purposes of the present document the following symbols apply:

$\alpha$	Alpha (= half the sector angle)
dBi	Decibels relative to an isotropic source
$f_o$	Nominal centre frequency of declared antenna operating range
GHz	GigaHertz
MHz	Megahertz
ROUND ( )	Round up or down to nearest integer

## 3.3 Abbreviations

For the purposes of the present document the following abbreviations apply:

CS	Central Station
HPBW	Half Power BeamWidth
P-MP	Point-to-MultiPoint
PIM	Passive InterModulation
RPE	Radiation Pattern Envelope
RS	Repeater Station
TS	Terminal Station
VSWR	Voltage Standing Wave Ratio

---

## 4 Frequency bands

The present document applies to a number of frequency ranges within the 3 GHz to 11 GHz frequency bands considered within CEPT/ERC and ETSI for allocation to the fixed services. Suitable sub-bands for allocation to point-to-multipoint use are subject to channel plans described in references [2], [3] and [4].

For the purpose of the present document, the overall frequency bands 3 GHz to 11 GHz are divided into three ranges as follows:

- range 1: 3,0 GHz to 5,9 GHz;
- range 2: 5,9 GHz to 8,5 GHz;
- range 3: 8,5 GHz to 11,0 GHz.

