



SLOVENSKI STANDARD SIST I-ETS 300 131:1999

01-oktober-1999

FUX]g_UcdfYa U]b'g]ghYa]'f9GL!'GdYWZ_UW'Ug_i dbY[UfUX]g_Y[Uj a Ygb]_Už_] gYi dcfUV^UnUa YXgYVc^bc^XYcj Ub^Y^VfYnj fj] b] h^YZ^bg_] ^UdUfUcj] ZY_j Yb bYa ^dUgi ^cX', *(Ž%A<n^Xc', *, Ž%A<n^j _^f bc^g^g^f]h] Ua]^Uj bY[U XcghcdU

Radio Equipment and Systems (RES); Common air interface specification to be used for the interworking between cordless telephone apparatus in the frequency band 864,1 MHz to 868,1 MHz, including public access services

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST I-ETS 300 131:1999](https://standards.iteh.ai/catalog/standards/sist/3c4d967a-b221-4207-af6f-65e343a41f45/sist-i-ets-300-131-1999)

<https://standards.iteh.ai/catalog/standards/sist/3c4d967a-b221-4207-af6f-65e343a41f45/sist-i-ets-300-131-1999>

Ta slovenski standard je istoveten z: I-ETS 300 131 Edition 2

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
-----------	-----------------------------	--------------------------------------

SIST I-ETS 300 131:1999

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST I-ETS 300 131:1999

<https://standards.iteh.ai/catalog/standards/sist/3c4d967a-b221-4207-af6f-65e343a41f45/sist-i-ets-300-131-1999>



EUROPEAN
TELECOMMUNICATION
STANDARD

I-ETS 300 131

November 1994

Second Edition

Source: ETSI TC-RES

Reference: RI/RES-03015

ICS: 33.060.20

Key words: CT2, CAI

Radio Equipment and Systems (RES);
Common air interface specification to be used for
the interworking between cordless telephone apparatus
in the frequency band 864,1 Mhz to 868,1 MHz,
including public access services

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

Some of the material contained herein is the copyright of, or has been supplied by, the United Kingdom Department of Trade and Industry, the British Standards Institution and the companies listed in annex H.

© European Telecommunications Standards Institute 1994. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST I-ETS 300 131:1999

<https://standards.iteh.ai/catalog/standards/sist/3c4d967a-b221-4207-af6f-65e343a41f45/sist-i-ets-300-131-1999>

Contents

Foreword	15
Introduction	15
1 Scope	17
2 Normative references	18
3 Definitions and abbreviations	19
3.1 Definitions.....	19
3.2 Abbreviations.....	20
4 Radio frequency interface	24
4.1 General.....	24
4.2 Channel frequencies	24
4.2.1 Channel centre frequencies	24
4.2.2 Channel frequency accuracy.....	24
4.2.3 Rate of change of transmit centre frequency	25
4.2.4 CTA access.....	25
4.3 Signalling strategy.....	25
4.3.1 CTA access.....	25
4.3.2 Signalling whilst in the communication state	25
4.3.3 Signalling outside the communication state	25
4.4 Dynamic channel allocation strategy	25
4.4.1 Incoming calls.....	25
4.4.2 Outgoing calls.....	25
4.4.3 Channel selection strategies.....	26
4.4.4 Free channel.....	26
4.4.4.1 Free channel selection for primary services	26
4.4.4.2 Free channel selection for secondary services	26
4.5 Radio transmitters.....	27
4.5.1 RF power	27
4.5.1.1 Maximum RF power.....	27
4.5.1.2 Minimum RF power.....	27
4.5.1.3 Output power at low power setting	27
4.5.2 Modulation.....	27
4.5.3 Adaptive transmitter power strategy	27
4.5.3.1 General	27
4.5.3.2 CPP only.....	27
4.5.3.3 CPP and CFP.....	27
4.5.3.4 Power level changes.....	28
4.5.4 Transmitter burst envelope.....	28
4.5.4.1 Amplitude.....	28
4.5.4.2 Dispersion effects.....	28
4.5.4.3 Guard time.....	28
4.5.4.4 Synchronisation of transmitter burst envelopes.....	29
4.5.5 Adjacent channel power (narrow band)	29
4.5.6 Out of band power arising from transmitter transients	29
4.5.7 Intermodulation attenuation	29
4.6 Radio receivers.....	29
4.6.1 General	29
4.6.1.1 CTA including three or more RFPs.....	29
4.6.1.2 Other CTAs.....	29
4.6.1.3 CTAs without integral or supplied antenna	29

4.6.2	Sensitivity	30
4.6.2.1	Receiver sensitivity for CFP or CPP using an integral or supplied antenna.....	30
4.6.2.2	Receiver sensitivity with a 50 ohm connector.....	30
4.6.3	Interference rejection.....	30
4.6.3.1	Unmodulated interfering carrier signal.....	30
4.6.3.2	Modulated asynchronous interfering signal	31
4.6.4	Blocking due to spurious responses	31
4.6.5	Intermodulation response rejection.....	32
4.7	Combined radio transmitter/receivers.....	32
4.7.1	Adverse power supply conditions.....	32
4.7.2	Spurious emissions of the combined transmitter/receiver	32
4.8	Termination of the communication state.....	33
4.8.1	Clear down signal sequence.....	33
4.8.2	Cessation of RF activity	33
4.8.3	Off-line timing.....	33
4.9	Channel scanning	33
4.9.1	Available channels	33
4.9.2	Response times	33
4.9.2.1	Outgoing	33
4.9.2.2	Incoming	33
4.10	In-communication channel switching	33
4.10.1	Capability.....	33
4.10.2	Channel change delay	34
4.11	Controls.....	34
4.12	Synthesisers and PLL systems.....	34
5	Signalling layer one.....	34
5.1	Data structure and timing.....	35
5.1.1	Data rate	35
5.1.2	Time-division duplexing.....	35
5.1.3	Master-slave relationship.....	35
5.2	Sub-channel multiplexes.....	36
5.2.1	Channel Markers (CHM) and synchronism markers (SYNC).....	36
5.2.2	Multiplex one	37
5.2.3	Multiplex two	38
5.2.4	Multiplex three.....	38
5.3	Calling channel detection.....	40
5.3.1	Calling channel detection at the CPP	40
5.3.2	Calling channel detection at the CFP	41
5.4	Link set up and establishment.....	41
5.4.1	Link set up from CFP to CPP	42
5.4.2	Link set up from CPP to CFP	42
5.4.3	Set up collision resolution	43
5.4.4	Link re-establishment on the existing channel	43
5.4.4.1	Action at the CPP	44
5.4.4.2	Action at the CFP	44
5.4.5	Link re-establishment on a re-selected channel.....	44
5.4.5.1	At the CPP.....	44
5.4.5.2	At the CFP	45
5.4.6	Synchronous re-establishment	45
5.4.6.1	Action at the CFP	46
5.4.6.2	Action at the CPP	47
5.5	ID handshaking	47
5.5.1	General	47
5.5.1.1	Handshake code series	47
5.5.1.2	Code allocation.....	47
5.5.1.3	Code matching	48
5.5.1.4	Code recognition.....	48
5.5.1.5	Communication state.....	48

iTech STANDARD PREVIEW

(standards.itech.ai)

SIST I-ETS 300 131:1999

<https://standards.itech.ai/catalog/standards/sist/3c4d967a-b221-4207-af6f-65e343a21815/sist-i-ets-300-131-1999>

	5.5.1.6	Lack of in-communication handshake: RF activity	48
	5.5.1.7	Lack of in-communication handshake: off-line state	48
	5.5.2	ID handshake operation	48
	5.5.3	Handshake protocol.....	48
	5.5.4	Reception of valid handshakes	49
	5.5.5	ID handshake mechanism	49
6	Signalling layer two.....		50
	6.1	Code word usage.....	50
	6.2	General message format	51
	6.3	General packet format.....	51
	6.3.1	Order of transmission and field mapping convention	51
	6.3.2	IDLE_D	52
	6.3.3	Synchronisation word (SYNCD).....	52
	6.3.4	Code Words - (address and data code words).....	52
	6.3.5	Code word transmission sequence	53
	6.3.6	Check field encoding (octets 7 and 8)	53
	6.4	Fixed length packet format (FT = 0).....	53
	6.4.1	SR (octet 1 (part)).....	54
	6.4.2	LS (octet 1 (part))	54
	6.4.3	HIC (octets 1 (part), 2, 3)	55
	6.4.4	MIC (octet 4)	55
	6.4.5	LID (octets 5 and 6)	55
	6.4.5.1	Allocation of LID values	56
	6.4.5.2	Link set up from the CPP: LID use by the CPP in LINK_REQUEST	57
	6.4.5.3	Link set up from the CPP: LID use by the CFP in LINK_GRANT	57
	6.4.5.4	Polling of CPPs (including link set up from the CFP): LID use by the CFP in ID_OK	57
	6.4.5.5	CPP poll response : LID use by the CPP in ID_OK.....	58
	6.4.5.6	Link set up from the CFP: LID use by the CPP in LINK_REQUEST	58
	6.4.5.7	Link set up from the CFP: LID use by the CFP in LINK_GRANT	58
	6.4.5.8	Established or re-established link: LID use by the CPP in ID_OK and ID_LOST	58
	6.4.5.9	Established or re-established link: LID use by the CFP in ID_OK and ID_LOST	58
	6.4.5.10	Link re-establishment: LID use by the CPP in LINK_REQUEST	58
	6.4.5.11	Link re-establishment: LID use by the CFP in LINK_GRANT	58
	6.4.5.12	Validity of handshakes	59
	6.4.6	CFP Identity and Status Code Word (CIS)	59
6.5	Variable length packet format (FT = 1)		61
	6.5.1	PI (octet 1)	62
	6.5.2	L3_end (octet 1)	62
	6.5.3	Endwrđ and code word no/rem encoding (octet 1)	62
	6.5.4	Control (octet 2).....	62
	6.5.5	Content	64
	6.5.6	Link supervisory messages	64
	6.5.6.1	Transmit power level control.....	65
	6.5.6.2	Reserved for future use.....	65
	6.5.6.3	Reserved for future use.....	65
	6.5.6.4	Link re-establishment	65
	6.5.6.5	Protocol initialisation (SABM), basic and extended	67
	6.5.6.6	Protocol acknowledgment (SABM_ACK), basic and extended.....	69
	6.5.6.7	Layer 2 code set shift	69

	6.5.6.7.1	Secondary service channel availability	70
	6.5.6.8	NULL message	71
	6.5.7	Fill-in	71
6.6		Link establishment and re-establishment	71
	6.6.1	Link set up from the CPP	71
	6.6.2	Link re-establishment	72
	6.6.3	Link set up from the CFP	73
	6.6.4	CFP polling	73
	6.6.5	CPP poll response	74
	6.6.6	CPP link set up and standard re-establishment diagram	75
	6.6.7	CFP link set up diagram	76
	6.6.8	Synchronous re-establishment diagram	78
6.7		Layer two link protocol set up and control	78
	6.7.1	Layer two link protocol timings	79
	6.7.2	Layer two link operation	79
	6.7.2.1	Link initialisation (see subclause 6.5.6.5)	79
	6.7.2.2	Packet transmission	80
	6.7.2.3	Packet reception	80
6.8		Location tracking of CPPs	81
	6.8.1	Polling only location tracking	82
	6.8.2	CIS assisted location tracking	82
	6.8.2.1	CIS only transmissions	83
	6.8.2.2	Combined CIS/polling transmissions	83
	6.8.2.3	Requesting the service	83
	6.8.2.4	CIS monitoring by the CPP	84
	6.8.2.5	In range indication to the user	84
7		Signalling layer three	85
	7.1	Single octet information elements	85
	7.2	Variable length information elements	86
	7.2.1	Keypad information element (KP)	88
	7.2.2	Display information element (DISP)	91
	7.2.3	Signal information element (SIG)	92
	7.2.4	Feature activation information element (FA)	94
	7.2.4.1	Use of FAs for answering incoming calls	99
	7.2.5	Feature indication information element (FI)	99
	7.2.6	Channel control information element (CC)	103
	7.2.7	Initialisation information element (INIT)	103
	7.2.8	Authentication request information element (AUTH_REQ)	104
	7.2.9	Authentication response information element (AUTH_RES)	105
	7.2.10	Terminal capabilities information element (TERM_CAP)	107
	7.2.11	Base capabilities information element (BAS_CAP)	109
	7.2.12	Character information element (CHAR)	111
	7.2.13	On-air (de-)registration acknowledge information element (OARAC)	111
	7.2.14	Parameter set information element (PAR_SET)	112
	7.2.15	Parameter request information element (PAR_REQ)	112
	7.2.16	Parameter response information element (PAR_RES)	112
	7.2.17	Alternative authentication request information element (AUTH2_REQ)	113
	7.2.18	Alternative authentication response information element (AUTH2_RES)	113
	7.2.19	Number of CPPs polled information element (NO_POLL)	113
	7.2.20	Change slot information element (CHANGE_SLOT)	114
	7.2.21	Network authentication request (NET_AUTH_REQ)	114
	7.2.22	Network authentication response (NET_AUTH_RES)	115
	7.2.23	Terminal registration data allocate information element (TRD_ALLOC)	115
	7.2.24	Key allocate information element (KEY_ALLOC)	116
	7.2.25	Location registration parameters information element (LR_PARAMS)	117
	7.2.26	Polling Lid information element (POLLING_LID)	119
	7.2.27	Data bearer capability information element (DAT_CAP)	120
	7.2.28	Data bearer response information element (DAT_RES)	121
7.3		Layer three mandatory syntax	122

iTech STANDARD PREVIEW

(standards.itech.ai)

<https://standards.itech.ai/catalog/standards/sist/3c4d967a-b221-4207-af6f-65e343a41815/sist-ets-300-131-1999>
 SIST I-ETS 300 131:1999

	7.3.1	Access to layer three.....	122
	7.3.2	Exit from layer three.....	122
	7.3.3	Emergency access.....	122
	7.3.4	On-air registration.....	123
7.4		Parameter values for PAR_SET, PAR_REQ, PAR_RES.....	123
	7.4.1	Parameter type = 0; class of service.....	123
	7.4.2	Parameter type = 1; extension number (BCD).....	124
	7.4.3	Parameter type = 2; language preference.....	124
	7.4.4	Parameter type = 3; enhanced display.....	124
		7.4.4.1 Display Behaviour types.....	125
		7.4.4.2 Minimum character set.....	125
		7.4.4.3 Display mapping.....	125
		7.4.4.4 Scrolling behaviour and window origins.....	125
		7.4.4.5 Display behaviour.....	126
	7.4.5	Parameter type = 4; Parameter List.....	127
	7.4.6	Parameter type = 5; Preferred channels.....	128
8		Speech coding and telephony.....	128
	8.1	Definitions.....	129
		8.1.1 Cordless Portable Part (CPP).....	129
		8.1.2 Fixed geometry CPP.....	129
		8.1.3 Variable geometry CPP.....	129
		8.1.4 CAI ADPCM voice codec (CIC = 0).....	129
	8.2	Speech transmission algorithm.....	129
		8.2.1 Speech coding algorithm.....	129
		8.2.2 Codec for public access CFP.....	129
	8.3	Bit transmission sequence.....	129
	8.4	Frequency responses.....	130
		8.4.1 Sending frequency response.....	130
		8.4.2 Receiving frequency response.....	131
	8.5	Digital signal level.....	131
	8.6	Sending and receiving loudness ratings.....	131
		8.6.1 CPP ambient noise rejection.....	132
	8.7	Sidetone loudness ratings.....	133
		8.7.1 Sidetone for analogue telephony.....	133
		8.7.2 Sidetone for digital telephony.....	133
		8.7.2.1 Talker sidetone.....	133
		8.7.2.2 Listener sidetone.....	133
	8.8	Clipping.....	133
	8.9	Distortion.....	133
		8.9.1 Sending distortion.....	133
		8.9.2 Receiving distortion.....	134
		8.9.3 Sidetone distortion.....	134
	8.10	Noise.....	134
		8.10.1 Sending.....	134
		8.10.2 Sending (narrow-band noise).....	134
		8.10.3 Receiving.....	134
	8.11	Delay.....	134
		8.11.1 CPP delay.....	134
		8.11.2 CFP delay.....	135
		8.11.3 Network echo from a CFP with a 2-wire analogue interface.....	135
	8.12	Terminal coupling loss.....	135
		8.12.1 Weighted terminal coupling loss (TCLw).....	135
		8.12.2 Stability loss (fixed geometry CPPs).....	135
		8.12.3 Stability loss (variable geometry CPPs).....	135
		8.12.4 CFP with a 4-wire interface.....	135
	8.13	Out of band signals.....	136
		8.13.1 Discrimination against out-of-band input signals (sending).....	136
		8.13.2 Spurious out-of-band signals (receiving).....	136
	8.14	Sampling frequency level (receiving).....	136

8.15	Acoustic shock.....	136
8.15.1	Maximum intended sound pressure level.....	136
8.15.2	Maximum possible sound pressure level.....	136
8.16	Audible incoming call indication.....	136
8.16.1	Provided on CPP: sound pressure level.....	136
8.16.2	Generated other than through the earpiece: maximum sound pressure level.....	137
9	Radio frequency parametric and system tests.....	137
9.1	Test conditions, power sources and ambient temperatures.....	137
9.1.1	Normal and extreme test conditions.....	137
9.1.2	Test power source.....	137
9.1.3	Normal test conditions.....	137
9.1.3.1	Normal temperature and humidity.....	137
9.1.3.2	Normal test power source.....	137
9.1.3.2.1	Mains voltage.....	137
9.1.3.2.2	Regulated lead acid battery power sources.....	138
9.1.3.2.3	Nickel cadmium battery.....	138
9.1.3.2.4	Other power sources.....	138
9.1.4	Extreme test conditions.....	138
9.1.4.1	Extreme temperatures.....	138
9.1.4.2	Extreme test source voltages.....	138
9.1.4.2.1	Mains voltage.....	138
9.1.4.2.2	Regulated lead acid battery power sources.....	138
9.1.4.2.3	Nickel cadmium battery.....	138
9.1.4.2.4	Other power sources.....	138
9.1.5	Procedure for tests at extreme temperatures.....	139
9.2	Electrical test conditions.....	139
9.2.1	Arrangements for signals to be applied to the fixed and portable receivers.....	139
9.2.2	Artificial antenna.....	139
9.2.3	Test fixture for integral antenna.....	139
9.2.4	Test site and general arrangements for measurements involving the use of radiated fields.....	140
9.2.4.1	Outdoor test site.....	140
9.2.4.2	Test antenna.....	140
9.2.4.3	Substitution antenna.....	140
9.2.4.4	Optional additional indoor site.....	141
9.2.5	Combined transmitter/receiver test facility.....	142
9.2.6	Guidance on the use of radiation test sites.....	142
9.2.7	Further optional alternative indoor test site using an anechoic chamber.....	142
9.2.8	Test frequencies.....	142
9.3	Transmitter.....	142
9.3.1	Transmitter carrier power.....	142
9.3.1.1	Definition.....	142
9.3.1.2	Method of measurement for equipment with an antenna connection.....	143
9.3.1.3	Method of measurement for equipment with an integral antenna.....	143
9.3.1.3.1	Method of measurement under normal test conditions.....	143
9.3.1.3.2	Method of measurement under extreme test conditions.....	143
9.3.1.4	Limits.....	144
9.3.2	Adjacent channel power (narrow-band).....	144
9.3.2.1	Definition.....	144
9.3.2.2	Method of measurement.....	144
9.3.2.3	Characteristics of the spectrum analyser.....	145
9.3.2.4	Integrating and power summing device.....	145
9.3.2.5	Limits.....	145
9.3.3	Out of band power arising from transmitter transients.....	145
9.3.3.1	Definition.....	145
9.3.3.2	Method of measurement.....	145

	9.3.3.3	Characteristics of the spectrum analyser	146
	9.3.3.4	Limits.....	146
9.3.4	Intermodulation attenuation		146
	9.3.4.1	Definition.....	146
	9.3.4.2	Method of measurement	146
	9.3.4.3	Limits.....	147
9.3.5	Prevention of mis-operation due to adverse power supply conditions.....		147
	9.3.5.1	Definition.....	147
	9.3.5.2	Method of measurement	147
	9.3.5.3	Limits.....	147
9.4	Spurious emissions.....		147
	9.4.1	Spurious emissions of the combined transmitter/receiver	147
	9.4.1.1	Definition.....	147
	9.4.1.2	Method of measuring the power level, subclause 9.4.1.1, (1).....	148
	9.4.1.3	Method of measuring the effective radiated power, subclause 9.4.1.1, (2).....	148
	9.4.1.4	Limits.....	148
9.5	Radio frequency system operation.....		149
	9.5.1	Definitions.....	149
	9.5.2	Channel frequencies	149
	9.5.2.1	Ability to transmit on each of the 40 channels.....	149
	9.5.2.2	Ability to receive on each of the 40 channels.....	149
	9.5.2.3	Ability to receive when the carrier frequency is up to ± 10 kHz from nominal.....	149
	9.5.2.4	Ability to receive when carrier frequency is varying at a rate of up to 1 kHz/ms.....	149
9.5.3	Dynamic RF channel allocation strategy		149
	9.5.3.1	No channel is occupied.....	149
	9.5.3.2	One channel only below the threshold.....	149
	9.5.3.3	All channels occupied.....	149
9.5.4	Adaptive CPP transmitter power control.....		149
9.5.5	RF modulation.....		150
	9.5.5.1	Peak frequency deviation: transmission	150
	9.5.5.2	Peak frequency deviation: reception.....	150
9.5.6	RF envelope		150
	9.5.6.1	Transmitter output: ramp-down.....	150
	9.5.6.2	Transmitter output: ramp-up	150
	9.5.6.3	CPP transmit amplitude during off period.....	150
	9.5.6.4	CFP transmit amplitude during off period.....	150
9.5.7	Radio receiver sensitivity.....		151
	9.5.7.1	Raw bit error rate.....	151
9.5.8	Radio receiver blocking performance		152
	9.5.8.1	Ability to receive in the presence of unmodulated interfering signals.....	152
	9.5.8.2	Ability to receive in the presence of asynchronous modulated interfering signals	152
9.5.9	Blocking due to spurious responses		152
	9.5.9.1	Blocking requirements.....	152
	9.5.9.2	Intermodulation response rejection.....	152
9.6	Transmitter modulation		152
9.7	Power supply units		153
9.8	Declarations by the manufacturer		153
9.9	Identification		153
10	Signalling system tests		153
	10.1	Multiplex alignment and timing	153
	10.1.1	Alignment of D and B channels in MUX1.....	153
	10.1.2	Alignment of D and SYN channels in MUX2	153
	10.1.3	Transmit/listen timing of MUX3	153

10.1.4	Alignment of P, D and SYN channels in MUX3	153
10.2	Calling channel detection at the CPP	154
10.3	Calling channel detection at the CFP	154
10.4	Link set up from CFP to CPP	154
10.4.1	For a CFP	154
10.4.1.1	To acquire a free RF channel and generate MUX2 Transmissions	154
10.4.1.2	Generation of LINK_GRANT	154
10.4.1.3	If no valid MUX2 response is received	154
10.4.2	For a CPP	154
10.5	Link set up from CPP to CFP	154
10.5.1	For a CPP	154
10.5.1.1	To acquire a free RF channel and generate MUX3 transmissions of LINK_REQUEST	154
10.5.1.2	Valid MUX2 response	155
10.5.1.3	No valid MUX2 response	155
10.5.2	For a CFP	155
10.6	Set up collision resolution	155
10.7	Link re-establishment on the existing channel	155
10.7.1	For a CPP	155
10.7.1.1	Valid link re-establishment message	155
10.7.1.2	Valid MUX2 response	155
10.7.1.3	No valid MUX2 response	155
10.7.2	For a CFP	156
10.7.2.1	Valid link re-establishment message	156
10.7.2.2	Valid MUX3 LINK REQUEST	156
10.7.2.3	No valid MUX3 LINK REQUEST	156
10.8	Link re-establishment on a different channel	156
10.8.1	For a CPP	156
10.8.2	For a CFP	156
10.9	Generation and reception of valid handshakes	156
10.9.1	Handshake intervals	156
10.9.2	For a CPP	156
10.9.2.1	Response to loss of valid handshakes	156
10.9.2.2	Re-acquisition of valid handshakes	156
10.9.3	For a CFP	157
10.9.3.1	Response to loss of valid handshakes	157
10.9.3.2	Re-acquisition of valid handshakes	157
10.10	Layer two parameters	157
10.11	Layer one and layer two timers	158
10.12	Acknowledged message protocol validation	158
10.12.1	CPP response to received packets	158
10.12.2	CPP transmit actions	159
10.12.3	CFP response to received packets	159
10.12.4	CFP transmit actions	159
10.13	Handshake operation	159
10.14	Layer three parameters	160
10.14.1	The receiving end	160
10.14.2	The transmitting end	160
10.15	Layer three timers	160
10.16	Declarations by the manufacturer	160
10.16.1	Information	160
10.16.2	Declarations	161
10.17	Additional test requirements	162
10.17.1	Specifics for authentication to UKF1	162
10.17.2	Reserved for future use	162
10.18	Characteristics of the reference test set	162
11	Speech and telephony tests	163
11.1	Measurement philosophy	163

11.2	Digital signal level.....	164
11.3	General conditions of test.....	164
11.4	Sending sensitivity frequency response (subclause 8.4.1).....	165
11.5	Receiving sensitivity frequency response (subclause 8.4.2).....	165
11.6	CPP sending loudness rating (subclause 8.6 (1)).....	165
11.7	CPP receiving loudness rating (subclause 8.6 (2)).....	166
11.8	CPP sidetone masking rating (subclause 8.7.2.1).....	166
11.9	Sending distortion (subclause 8.9.1).....	166
11.10	Receiving distortion (subclause 8.9.2).....	166
11.11	Sending noise (subclause 8.10.1).....	166
11.12	Sending noise (narrow band) (subclause 8.10.2).....	167
11.13	Receiving noise (subclause 8.10.3).....	167
11.14	CPP delay (subclause 8.11.1).....	167
11.15	Weighted terminal coupling loss (subclause 8.12.1).....	169
11.16	Stability loss - fixed geometry (subclause 8.12.2).....	170
11.17	Stability loss - variable geometry (subclause 8.12.3).....	170
11.18	Out of band (sending) (subclause 8.13.1).....	170
11.19	Out of band (receiving) (subclause 8.13.2).....	170
11.20	Sampling frequency level (receiving) (subclause 8.14).....	170
11.21	Acoustic shock (subclause 8.15).....	170
11.22	Listener sidetone (subclause 8.7.2.2).....	171
11.23	Sidetone distortion (subclause 8.9.3).....	171
11.24	Subjective speech quality.....	171
	11.24.1 Overall requirements.....	171
	11.24.2 CTA tested as an entirety.....	172
	11.24.3 Codec to be treated in isolation.....	172
	11.24.4 CTA incorporating codec complying with 11.24.3.....	173
	11.24.5 Standard of performance.....	173
11.25	CPP ambient noise rejection (subclause 8.6.1).....	174
Annex A (normative): Layer three mandatory syntax diagrams..... 174		
A.1	CPP mandatory layer three initialisation syntax.....	175
A.2	CFP mandatory layer three initialisation syntax.....	176
A.3	Public access CPP mandatory layer three syntax.....	177
A.4	Public access CFP mandatory layer three syntax.....	178
Annex B (normative): Authentication procedures..... 179		
B.1	Minimum configuration for CPPs using authentication.....	179
B.2	Minimum configuration for public access CFPs using authentication.....	180
B.3	Authentication.....	182
	B.3.1 Introduction.....	182
	B.3.2 Basis of operation.....	183
	B.3.2.1 Identification information.....	184
	B.3.2.2 KEY number.....	185
	B.3.2.3 Function "F".....	186
	B.3.2.4 Assignment of KEY numbers.....	186
	B.3.3 ZAP facility.....	186
B.4	Entry of registration and authentication data.....	186
	B.4.1 Manual registration.....	186
	B.4.1.1 Basic data entry.....	187
	B.4.1.2 Check digits.....	188
	B.4.1.3 Termination of data entry.....	188

B.4.1.4	Example	188
B.4.1.5	Man-machine interface (MMI) for manual registration	190
B.4.2	Over the air registration	191
B.4.2.1	Pre-registration of LID only	191
B.4.2.2	Pre-registration of LID and EPID	192
B.4.2.3	Man-machine interface (MMI) for OTAR pre-registration	194
B.4.2.4	On-air registration process	194
B.4.2.5	FTD1 Decryption Algorithm	195
B.4.3	CPP registration capacity	196
B.4.3.1	Manual registration slot	196
B.4.3.2	OTAR registration slot	197
Annex C (normative):	Serial number and GPID format	198
Annex D (normative):	Accuracy of measurement	199
D.1	Radio frequency parametric and system tests	199
D.2	Signalling system tests	199
D.3	Speech and telephony tests	200
Annex E (informative):	Interim arrangements	201
E.1	Minimum RF power	201
E.2	Radio receiver sensitivity	201
E.3	Portable part ADPCM voice codec	201
E.4	Weighted terminal coupling loss	201
E.5	Alternative authentication algorithms	201
E.6	Alternative re-establishment algorithms	202
E.6.1	Interim wording for subclause 5.4.4	202
E.6.2	Interim wording for subclause 5.4.5	202
E.7	CPP ramp-up and ramp-down specifications	202
E.7.1	Interim wording for subclause 4.5.4.1	202
E.8	In Communication channel switching	202
E.9	Acknowledgement of KP, FA, AUTH_REQ, AUTH_RES, TERM_CAP and BAS_CAP information elements	203
E.10	Interference rejection	203
E.10.1	Interim values for table 1	203
E.10.2	Interim values for table 2	203
E.11	Spurious emissions of the combined transmitter/receiver	203
E.11.1	Interim wording for subclause 4.7.2	204
E.11.2	Interim wording for subclause 9.4.1.2	204
E.11.3	Interim wording for subclause 9.4.1.3	204
E.12	Intermodulation rejection	205
E.12.1	Interim wording for subclause 4.6.5	205
E.13	Initial location registration and terminate location registration FAs	205

ITeH STANDARD PREVIEW

(standards.iteh.ai)

[SIST I-ETS 300 131:1999](https://standards.iteh.ai/catalog/standards/sist/3c4d967a-b221-4207-af6f-65e343a41f45/sist-i-ets-300-131-1999)

<https://standards.iteh.ai/catalog/standards/sist/3c4d967a-b221-4207-af6f-65e343a41f45/sist-i-ets-300-131-1999>

Annex F (informative):	Message sequence diagrams	206
F.1	Call set up to a public access CFP	207
F.2	Call set up to a private CFP	208
F.3	Private CFP incoming (group) call	209
F.4	Public access CFP incoming call	210
F.5	Call clear down	211
F.6	On air identity registration from CPP to private CFP	211
Annex G (informative):	Code word example	213
Annex H (informative):	Intellectual property rights	214
Annex J (normative):	Subjective speech quality tests	216
J.1	Preparation of master recordings	216
J.1.1	Speech material	216
J.1.2	Apparatus and environment	217
J.1.3	Recording procedure	217
J.1.4	Calibration signals and speech levels	219
J.2	Processing of recordings	219
J.2.1	General	219
J.2.2	Processing through the apparatus under test	220
J.2.3	Processing through controlled distortion	221
J.3	Conduct of listening test	222
J.3.1	Apparatus, calibration and environment	222
J.3.2	Selection of subjects	222
J.3.3	Procedure	222
J.4	Treatment of results	225
J.5	Determination of laboratory-specific Q-rating boundaries for the purposes of subclause 11.24.5	232
J.6	References	232
Annex K (informative):	Artificial echo loss for a CFP with a 4-wire interface	234
Annex L (informative):	Network echo from a CFP with a 2-wire analogue interface	235
Annex M (normative):	Code for the representation of names of languages	236
Annex N (normative):	External synchronisation ports	237
N.1	External synchronisation ports	237
N.1.1	External synchronisation output port	237
N.1.2	External synchronisation input port	237
N.2	Synchronisation	238
N.2.1	External synchronisation input signal	239
N.2.2	Envelope synchronisation	239
N.3	Interconnection	239