



SLOVENSKI STANDARD
SIST EN 300 396-3 V1.2.1:2006

01-april-2006

Df]nYa b]`gbc dcj b]`fUX]c`fH9 HF 5 ĹĚ`HM b] bY`nU H]j Y`nU`bYdcgfYXb]`bU]b`nj YnY
fB A CĹĚ` "XY. Dfc lc`c`fUX]g`Y[U]j a Ygb]`UfĚ ĹcX`a cV]`bY`dcgHUY`Xc`a cV]`bY
dcgHUY`fA G!A GĹ

Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 3: Mobile Station to Mobile Station (MS-MS) Air Interface (AI) protocol

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 396-3 V1.2.1:2006](https://standards.iteh.ai/catalog/standards/sist/8325077c-7a2f-45ea-ae10-f8b93173e210/sist-en-300-396-3-v1-2-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/8325077c-7a2f-45ea-ae10-f8b93173e210/sist-en-300-396-3-v1-2-1-2006>

Ta slovenski standard je istoveten z: EN 300 396-3 Version 1.2.1

ICS:

33.070.10

Prizemni snopovni radio
(TETRA)

Terrestrial Trunked Radio
(TETRA)

SIST EN 300 396-3 V1.2.1:2006

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 396-3 V1.2.1:2006

<https://standards.iteh.ai/catalog/standards/sist/8325077c-7a2f-45ea-aef0-f8b93173e210/sist-en-300-396-3-v1-2-1-2006>

ETSI EN 300 396-3 V1.2.1 (2004-12)

European Standard (Telecommunications series)

Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 3: Mobile Station to Mobile Station (MS-MS) Air Interface (AI) protocol

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 396-3 V1.2.1:2006](https://standards.iteh.ai/catalog/standards/sist/8325077c-7a2f-45ea-ae10-f8b93173e210/sist-en-300-396-3-v1-2-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/8325077c-7a2f-45ea-ae10-f8b93173e210/sist-en-300-396-3-v1-2-1-2006>



Reference

REN/TETRA-08064

Keywords

air interface, protocol, radio, TETRA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 396-3 V1.2.1:2006<https://standards.iteh.ai/catalog/standards/sist/8325077c-7a2f-45ea-ae0-f8b93173e240/etsi-en-300-396-3-v1-2-1-2006> **Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2004.
All rights reserved.

DECT™, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	11
Foreword.....	11
1 Scope	12
2 References	12
3 Definitions and abbreviations.....	13
3.1 Definitions	13
3.2 Abbreviations	15
4 Overview of protocol.....	17
4.1 General	17
4.2 The DM channel.....	17
4.3 DM call procedures	18
4.3.1 Constraints on the frame structure	19
4.3.2 Setting up a call	19
4.3.2.1 Call set-up without presence check.....	19
4.3.2.1.1 Basic procedure	19
4.3.2.1.2 Procedure in frequency efficient mode.....	20
4.3.2.2 Call set-up with presence check.....	21
4.3.3 Changeover in a call	21
4.3.4 Pre-emption of a DM call	22
4.3.5 Terminating a call	23
4.3.6 DM short data call	23
4.3.6.1 Unacknowledged short data message.....	23
4.3.6.2 Acknowledged short data message	24
4.4 DM protocol layering	24
5 Layer 3 service description.....	25
5.1 Introduction	25
5.2 Services offered.....	25
5.3 Primitive description	26
5.3.1 DMCC-COMplete primitive.....	26
5.3.2 DMCC-RELEASE primitive	27
5.3.3 DMCC-REPORT primitive	27
5.3.4 DMCC-SDS DATA primitive	27
5.3.5 DMCC-SDS REPORT primitive	28
5.3.6 DMCC-SDS UNITDATA primitive.....	28
5.3.7 DMCC-SETUP primitive	29
5.3.8 DMCC-TPNI primitive.....	30
5.3.9 DMCC-TX CEASED primitive.....	30
5.4 Parameter description.....	30
5.5 States for DMCC-SAP	35
6 Layer 3 protocol	36
6.1 Introduction	36
6.1.1 DMCC protocol states	36
6.1.1.1 IDLE	36
6.1.1.2 CALL SETUP NORMAL ORIGINATING.....	36
6.1.1.3 CALL SETUP NORMAL TERMINATING	36
6.1.1.4 CALL SETUP PRES_CHECK ORIGINATING.....	36
6.1.1.5 CALL SETUP PRES_CHECK TERMINATING.....	36
6.1.1.6 PRE-EMPTION	36
6.1.1.7 CALL ACTIVE TX OCCUPATION.....	36
6.1.1.8 CALL ACTIVE TX RESERVATION	37
6.1.1.9 CALL ACTIVE RX OCCUPATION.....	37
6.1.1.10 CALL ACTIVE RX RESERVATION.....	37
6.1.1.11 WAIT RSP OCCUPATION	37

6.1.1.12	WAIT RSP RESERVATION.....	37
6.1.1.13	ACK'D SHORT DATA INITIATED.....	37
6.1.1.14	UNACK'D SHORT DATA INITIATED.....	37
6.2	Circuit mode calls.....	37
6.2.1	Procedures for call set-up without presence check.....	38
6.2.1.1	Outgoing call.....	38
6.2.1.2	Incoming call.....	40
6.2.1.3	Temporary group address.....	41
6.2.2	Procedures for call set-up with presence check.....	41
6.2.2.1	Outgoing call.....	41
6.2.2.2	Incoming call.....	43
6.2.3	Usage of DM-OCCUPIED PDU.....	44
6.2.3.1	Sending of DM-OCCUPIED PDU by master DM-MS.....	44
6.2.3.2	Late entry by slave DM-MS.....	44
6.2.4	Procedures during occupation.....	44
6.2.4.1	Master DM-MS.....	44
6.2.4.2	Slave DM-MS.....	45
6.2.4.3	Transmitting Party Number Identification (TPNI).....	47
6.2.5	Procedures during reservation.....	47
6.2.5.1	Master DM-MS.....	47
6.2.5.2	Slave DM-MS.....	49
6.2.5.3	Pre-emption of short data sent as a transaction within a circuit mode call.....	51
6.2.6	Procedures to set up a new call by pre-emption.....	51
6.3	Short Data Service (SDS) procedures.....	52
6.3.1	Sending short data.....	53
6.3.1.1	Sending short data on a free channel.....	53
6.3.1.1.1	Sending unacknowledged short data on a free channel.....	53
6.3.1.1.2	Sending acknowledged short data on a free channel.....	55
6.3.1.2	Sending short data by pre-emption.....	57
6.3.1.3	Sending short data during circuit mode transmission.....	58
6.3.1.4	Sending short data as a transaction within a circuit mode call.....	59
6.3.1.4.1	Pre-emption to send short data as a transaction within a circuit mode call.....	59
6.3.1.4.2	Changeover to send short data as a transaction within a circuit mode call.....	60
6.3.1.4.3	Sending the short data as master of the circuit mode call.....	60
6.3.2	Receiving short data.....	60
6.3.2.1	Receiving unacknowledged short data.....	60
6.3.2.2	Receiving acknowledged short data.....	61
6.3.3	Additional addressing.....	61
6.3.4	Extended error protection.....	61
6.3.5	SDS-TL service in DMO.....	62
6.3.5.1	Service primitives at the DMTL-SDS-SAP.....	62
6.3.5.2	DMTL-SDS primitives' parameters.....	65
6.3.5.3	DMTL-SDS PDUs.....	67
6.3.5.4	DMTL-SDS procedures.....	67
6.4	Usage of DMA-UNITDATA primitive.....	70
7	Layer 2 service description.....	71
7.1	Introduction.....	71
7.2	Layer 2 architecture.....	72
7.2.1	Lower layer management in layer 2.....	73
7.3	Service descriptions.....	73
7.3.1	Services at the DMA-SAP.....	73
7.3.1.1	Services provided to layer 3.....	73
7.3.1.2	Service primitives at the DMA-SAP.....	74
7.3.1.2.1	DMA-REPORT primitive.....	74
7.3.1.2.2	DMA-UNITDATA primitive.....	74
7.3.2	Services at the DMC-SAP.....	75
7.3.2.1	Services provided to layer 3.....	75
7.3.2.2	Service primitives at the DMC-SAP.....	75
7.3.2.2.1	DMC-CONFIGURE primitive.....	76
7.3.2.2.2	DMC-REPORT primitive.....	76
7.3.3	Services at the DMD-SAP.....	76

7.3.3.1	Services provided to the U-plane application.....	76
7.3.3.2	Service primitives at the DMD-SAP.....	76
7.3.3.2.1	DMD-REPORT primitive.....	77
7.3.3.2.2	DMD-UNITDATA primitive.....	77
7.4	Parameter listing.....	77
7.4.1	Air interface encryption information.....	77
7.4.2	Air interface encryption state.....	77
7.4.2A	Called party in ongoing call.....	78
7.4.3	Call release.....	78
7.4.4	Call set-up after pre-emption or changeover.....	78
7.4.5	Changeover request held during occupation.....	78
7.4.5A	Channel selection information.....	78
7.4.6	Circuit mode information.....	78
7.4.7	Circuit mode type.....	78
7.4.8	Communication type.....	78
7.4.9	Destination address.....	78
7.4.10	Destination address type.....	79
7.4.10A	DM channel.....	79
7.4.11	DM-SDU.....	79
7.4.12	DM-SDU length.....	79
7.4.12A	Dual watch information.....	79
7.4.13	FCS flag.....	79
7.4.14	Half slot condition.....	79
7.4.15	Half slot content.....	79
7.4.16	Half slot importance.....	79
7.4.17	Half slot position.....	79
7.4.18	Half slot synchronization.....	80
7.4.19	Handle to the request.....	80
7.4.20	Immediate retransmission.....	80
7.4.21	Incomplete DM-SDS DATA/ACK received.....	80
7.4.21A	Lower layer quality information.....	80
7.4.21B	Master of ongoing call.....	80
7.4.22	Message type.....	80
7.4.23	New call pre-emption.....	80
7.4.24	Number of repeats.....	81
7.4.25	Priority.....	81
7.4.26	Priority of ongoing call.....	81
7.4.27	Recent user changeover request.....	81
7.4.28	Recent user priority.....	81
7.4.29	Report.....	81
7.4.30	Reservation time.....	81
7.4.31	SDS transaction type.....	81
7.4.32	Source address.....	81
7.4.33	Source address type.....	81
7.4.34	Stealing priority.....	82
7.4.35	Stolen indication.....	82
7.4.36	Type of pre-emption.....	82
7.4.37	Valid addresses.....	82
8	Layer 2 protocol.....	82
8.1	Introduction.....	82
8.1.1	Functions of lower MAC.....	82
8.1.2	Functions of upper MAC.....	83
8.2	Interface between lower and upper MAC.....	83
8.2.1	Logical channels defined at the DMV-SAP.....	83
8.2.2	Service primitives at the DMV-SAP.....	84
8.2.3	PDU mapping of the logical channels at the DMV-SAP.....	85
8.2.4	Scrambling mechanism.....	86
8.2.5	PDU error detection.....	86
8.2.6	Modes of operation.....	87
8.2.6.1	DM-MS modes of operation.....	87
8.2.6.1.1	Idle mode.....	87

8.2.6.1.2	Signalling mode	87
8.2.6.1.3	Traffic mode	87
8.2.6.2	Operation in traffic mode	88
8.2.6.2.1	Traffic transmission	88
8.2.6.2.2	Stealing mechanism	89
8.2.6.3	Selection of the mode of operation	89
8.3	Basic capabilities of the Physical Layer (PL)	90
8.3.1	DM-MS capabilities	90
8.3.1.1	DM only and dual mode capable MS operation	90
8.3.1.2	Dual watch capable MS operation	91
8.3.1.2.1	Full Dual Watch Mobile Station (F-DW-MS)	91
8.3.1.2.2	Idle Dual Watch Mobile Station (I-DW-MS)	91
8.4	Usage of DM channel	91
8.4.1	Definition of DM channel	91
8.4.1.1	DM channel arrangement	91
8.4.1.2	DM channel A operation	91
8.4.1.3	DM channel B operation	92
8.4.2	DM-MAC states	93
8.4.2.1	DM-MAC state definitions	93
8.4.2.2	DM-MS channel surveillance procedures	94
8.4.2.2.1	Initial determination of DM channel state	94
8.4.2.2.2	Fast call set-up surveillance in idle mode	96
8.4.2.2.3	DM-MS channel surveillance at call set-up	99
8.4.2.3	Master DM-MS channel maintenance procedures during a call	101
8.4.2.4	Slave DM-MS channel maintenance procedures during a call	101
8.4.2.4.1	Slave MS channel maintenance during call transaction	102
8.4.2.4.2	Slave MS signal quality measurement during call transaction	102
8.4.2.4.3	Slave MS channel maintenance during reservation	102
8.4.2.5	Additional master MS procedures in frequency efficient mode	102
8.4.2.5.1	Channel A master MS procedures	103
8.4.2.5.2	Channel B master MS procedures	103
8.4.3	Criteria for changing DM-MAC state	103
8.4.3.1	Criteria for changing DM-MAC state for master DM-MS	103
8.4.3.2	Criteria for changing DM-MAC state for slave DM-MS	104
8.4.3.3	Criteria for changing DM-MAC state for idle DM-MS	105
8.4.4	DM-MS channel monitoring procedures	107
8.4.4.1	DM channel during call set-up with presence check	108
8.4.4.2	DM channel in occupation during a circuit mode call	108
8.4.4.3	DM channel in reservation during a circuit mode call	108
8.4.4.4	DM channel in occupation during an SDS call	108
8.4.4.5	DM channel usage during pre-emption signalling	109
8.4.4.6	DM channel usage during timing change request signalling	109
8.4.5	Transmission of layer 3 messages by DM-MAC	109
8.4.5.1	Transmission of C-plane messages by DM-MAC	109
8.4.5.1.1	Transmitting DM-SETUP	109
8.4.5.1.2	Transmitting DM-SETUP PRES	110
8.4.5.1.3	Transmitting DM-CONNECT	111
8.4.5.1.4	Transmitting DM-DISCONNECT	111
8.4.5.1.5	Transmitting DM-CONNECT ACK	111
8.4.5.1.6	Transmitting DM-RELEASE	111
8.4.5.1.7	Transmitting DM-OCCUPIED	112
8.4.5.1.8	Transmitting DM-TX CEASED	112
8.4.5.1.9	Transmitting DM-TX REQUEST	113
8.4.5.1.10	Transmitting response to DM-TX REQUEST	113
8.4.5.1.11	Transmitting DM-PREEMPT	114
8.4.5.1.12	Transmitting response to DM-PREEMPT	114
8.4.5.1.13	Transmitting DM-SDS UDATA and DM-SDS DATA	115
8.4.5.1.14	Transmitting response to DM-SDS DATA	116
8.4.5.1.15	Transmitting DM-INFO	116
8.4.5.2	Transmission of U-plane messages by DM-MAC	116
8.4.6	Transmission of layer 2 messages generated by DM-MAC	116
8.4.6.1	Transmitting DM-RESERVED	117

8.4.6.2	Transmitting DM-SDS OCCUPIED	117
8.4.6.3	Transmitting DM-TIMING REQUEST	118
8.4.6.4	Transmitting DM-TIMING ACK.....	118
8.4.7	General DM-MAC procedures	118
8.4.7.1	DM-MAC repeat transmissions	118
8.4.7.2	DM-MAC frame countdown procedure	118
8.4.7.3	Use of timers	119
8.4.7.4	Linearization	119
8.4.7.5	Fragmentation	119
8.4.7.6	Fill bit indication	119
8.4.7.7	Selection of pseudo address	119
8.4.7.8	Slot flag indication	120
8.4.7.9	Requests bitmap	120
8.4.7.10	DM aspects of dual watch operation	120
8.4.7.10.1	Full and idle dual watch operation.....	120
8.4.7.10.2	DM aspects of full dual watch operation.....	120
8.4.7.10.3	DM aspects of idle dual watch operation	124
8.4.7.11	Air interface encryption	126
8.4.7.12	Channel A or B operation	126
8.4.7.13	Sending short data as a transaction within a circuit mode call.....	126
8.4.7.14	SDS time remaining	127
8.4.7.15	Timing change procedure.....	127
8.4.7.16	Timing change at changeover or pre-emption.....	129
8.5	MAC procedures for transfer of signalling messages.....	129
8.5.1	Formation of MAC PDU	129
8.5.2	Addressing	130
8.5.2.1	Transmission of message	130
8.5.2.1.1	Addressing in synchronization burst	130
8.5.2.1.2	Addressing in normal burst.....	132
8.5.2.2	Reception of message.....	132
8.5.3	Use of air interface encryption.....	133
8.5.4	Fragmentation and reconstruction.....	134
8.5.4.1	Fragmentation.....	134
8.5.4.2	Reconstruction	135
8.5.5	Fill bit addition and deletion.....	136
8.5.5.1	Fill bit addition.....	136
8.5.5.2	Fill bit deletion.....	136
8.5.5.3	Null PDU	137
8.5.6	Transmission and reception of messages by layer 2 unacknowledged service	137
8.5.6.1	Transmission of message	138
8.5.6.2	Reception of message.....	139
8.5.7	Random access protocol	141
8.5.7.1	Introduction.....	141
8.5.7.2	Procedures for master DM-MS	141
8.5.7.2.1	Indicating frames available for requests	141
8.5.7.2.2	Monitoring frames available for requests	141
8.5.7.2.3	Response to pre-emption or changeover request	142
8.5.7.2.4	Response to timing change request.....	143
8.5.7.3	Procedures for requesting DM-MS	144
8.5.7.3.1	Preparing for random access.....	144
8.5.7.3.2	First transmission of request.....	144
8.5.7.3.3	Valid access slots.....	145
8.5.7.3.4	Waiting for response.....	145
8.5.7.3.5	Subsequent transmission of request.....	146
8.5.7.3.6	Abandoning random access attempt.....	146
8.6	MAC procedures in traffic mode.....	147
8.6.1	Introduction.....	148
8.6.2	Criteria for transmission and reception of traffic	148
8.6.3	Change of U-plane mode	149
8.6.3.1	Call set-up without presence check	149
8.6.3.1.1	Outgoing call	149
8.6.3.1.2	Incoming call	149

8.6.3.2	Call set-up with presence check	149
8.6.3.2.1	Outgoing call	149
8.6.3.2.2	Incoming call	150
8.6.3.3	Late entry	150
8.6.3.4	End of traffic transmission	150
8.6.3.4.1	Master DM-MS	150
8.6.3.4.2	Slave DM-MS	150
8.6.4	Exchange of information at the DMD-SAP	150
8.6.4.1	Interface at transmitting DM-MS	152
8.6.4.2	Interface at receiving DM-MS	153
8.6.5	Stealing from circuit mode capacity	154
8.6.5.1	Transmission on STCH	154
8.6.5.2	Criteria for C-plane stealing	155
8.6.5.3	Reception on STCH	155
9	PDU descriptions	156
9.1	Layer 2 PDUs sent in DSB	156
9.1.1	DMAC-SYNC PDU	156
9.2	Layer 2 PDUs sent in DNB	157
9.2.1	DMAC-DATA PDU	158
9.2.2	DMAC-FRAG PDU	158
9.2.3	DMAC-END PDU	158
9.2.4	DMAC-U-SIGNAL PDU	159
9.2.5	DMAC-TRAFFIC PDU	159
9.3	Layer 2 information element coding	159
9.3.1	A/B channel usage	160
9.3.2	Air interface encryption state	160
9.3.3	Communication type	160
9.3.4	Destination address	160
9.3.5	Destination address type	161
9.3.6	DM-SDU	161
9.3.7	Encryption key number	161
9.3.8	Fill bit indication	161
9.3.9	Fragmentation flag	161
9.3.10	Frame countdown	162
9.3.11	Frame number	162
9.3.12	Gateway address	162
9.3.13	Gateway generated message flag	162
9.3.14	Key Stream Generator (KSG) number	162
9.3.15	MAC PDU subtype	163
9.3.16	MAC PDU type	163
9.3.17	Master/slave link flag	163
9.3.18	Message dependent elements	163
9.3.19	Message type	164
9.3.20	Mobile Network Identity (MNI)	164
9.3.21	Null PDU flag	164
9.3.22	Number of SCH/F slots	165
9.3.23	Repeater address	165
9.3.24	Second half slot stolen flag	165
9.3.25	Slot number	165
9.3.26	Source address	165
9.3.27	Source address type	165
9.3.28	SYNC PDU type	166
9.3.29	System code	166
9.3.30	Time Variant Parameter (TVP)	166
9.3.31	U-plane DM-SDU	166
9.4	Messages generated by layer 2	166
9.4.1	DM-RESERVED	167
9.4.2	DM-SDS OCCUPIED	167
9.4.3	DM-TIMING REQUEST	168
9.4.4	DM-TIMING ACK	168
9.5	Layer 3 PDUs	168

9.5.1	DM-SETUP	169
9.5.2	DM-SETUP PRES	169
9.5.3	DM-CONNECT	170
9.5.4	DM-DISCONNECT	170
9.5.5	DM-CONNECT ACK	171
9.5.6	DM-OCCUPIED	171
9.5.7	DM-RELEASE	172
9.5.8	DM-TX CEASED	172
9.5.9	DM-TX REQUEST	173
9.5.10	DM-TX ACCEPT	173
9.5.11	DM-PREEMPT	174
9.5.12	DM-PRE ACCEPT	174
9.5.13	DM-REJECT	174
9.5.14	DM-INFO	175
9.5.15	DM-SDS UDATA	175
9.5.16	DM-SDS DATA	175
9.5.17	DM-SDS ACK	176
9.6	Message dependent elements coding	177
9.6.1	Changeover requests flag	177
9.6.2	Channel reservation type	177
9.6.3	Circuit mode type	177
9.6.3A	Dual watch synchronization flag	177
9.6.4	FCS flag	178
9.6.5	LCH in frame 3 flag	178
9.6.6	New call pre-emption	178
9.6.7	Perceived channel state	179
9.6.8	Power class	179
9.6.9	Power control flag	179
9.6.10	Pre-emption flag	179
9.6.11	Priority level	180
9.6.12	Recent user priority flag	180
9.6.13	Requests bitmap	180
9.6.14	Requests flag	180
9.6.15	Reservation time remaining	181
9.6.16	SDS time remaining	181
9.6.17	SDS transaction type	181
9.6.18	Timing acceptance flag	182
9.6.19	Timing adjustment	182
9.6.20	Timing change announced	182
9.6.21	Timing change required	182
9.6.22	Timing flag	182
9.6.22A	Two-frequency call flag	183
9.6.23	Type of pre-emption	183
9.7	DM-SDU elements coding	183
9.7.1	Acknowledgement type	183
9.7.2	Additional addressing flag	183
9.7.3	Additional address type(s)	184
9.7.4	Calling party TSI	184
9.7.5	Call type flag	184
9.7.6	Cease cause	184
9.7.7	Disconnect cause	185
9.7.8	End-to-end encryption flag	185
9.7.9	External source flag	185
9.7.10	FCS	185
9.7.11	Information type	186
9.7.12	Length indicator	186
9.7.13	Pre-coded status	186
9.7.14	Reject cause	186
9.7.15	Release cause	187
9.7.15A	Release cause extension	187
9.7.16	Short Data Type Identifier (SDTI)	187
9.7.17	User defined data 1	187

iTech STANDARD PREVIEW
(standards.itech.ai)

SIST EN 300 396-3 V1.2.1:2006

[https://standards.itech.ai/catalog/standards/sist/8325077c-7a2f-45ea-ae10-](https://standards.itech.ai/catalog/standards/sist/8325077c-7a2f-45ea-ae10-3173e210/sist-en-300-396-3-v1-2-1-2006)

[3173e210/sist-en-300-396-3-v1-2-1-2006](https://standards.itech.ai/catalog/standards/sist/8325077c-7a2f-45ea-ae10-3173e210/sist-en-300-396-3-v1-2-1-2006)

9.7.18	User defined data 2	188
9.7.19	User defined data 3	188
9.7.20	User defined data 4	188
Annex A (normative):	Timers and constants in DM-MS	189
A.1	Layer 3 timers.....	189
A.2	Layer 3 constants.....	189
A.3	Layer 2 timers.....	189
A.4	Layer 2 constants.....	190
A.5	Maximum number of frame transmissions by DM-MAC.....	191
Annex B (normative):	Mathematical definition of FCS	192
Annex C (informative):	Limitations of Dual Watch operation	193
C.1	Energy saving economy mode	193
C.1.1	Idle Dual Watch without EG (i.e. EG0, receiving TMO in one slot every frame)	193
C.1.2	Idle Dual Watch with EG1 (i.e. receiving TMO in one slot every 2 frames)	194
C.1.3	Idle Dual Watch with EG2 and above	194
C.1.4	Drawbacks on EG usage.....	194
C.2	Small failures on dual watch surveillance	195
C.3	User's perception	195
C.4	Conclusions	195
Annex D (informative):	Use of threshold in channel surveillance procedures.....	196
Annex E (normative):	SDS-TL use in DMO.....	197
E.1	Use of SDS-TL PDUs in DM-SDS DATA/UDATA PDUs.....	197
E.1.1	SDS-TRANSFER.....	197
E.1.2	SDS-ACK.....	197
E.1.3	SDS-REPORT.....	198
E.1.4	SDS-SHORT REPORT.....	198
E.2	Use of SDS-TL Store and Forward in DMO.....	198
History	200

iTech STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 396-3 V1.2.1:2006

<https://standards.iteh.ai/catalog/standards/sist/8525077c-7a2f-45ca-acf0-18b93173e2f0/sist-en-300-396-3-v1-2-1-2006>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Project Terrestrial Trunked Radio (TETRA).

The present document is part 3 of a multi-part deliverable covering the Technical Requirements for Direct Mode Operation (DMO), as identified below:

- Part 1: "General network design";
- Part 2: "Radio aspects";
- Part 3: "Mobile Station to Mobile Station (MS-MS) Air Interface (AI) protocol";**
- Part 4: "Type 1 repeater air interface";
- Part 5: "Gateway air interface";
- Part 6: "Security"; <https://standards.iteh.ai/catalog/standards/sist/8325077c-7a2f-45ea-ae10-f8b93173e210/sist-en-300-396-3-v1-2-1-2006>
- Part 7: "Type 2 repeater air interface";
- Part 8: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 10: "Managed Direct Mode Operation (M-DMO)".

NOTE: Part 8 of this multi-part deliverable is of status "historical" and will not be updated according to this version of the standard.

National transposition dates	
Date of adoption of this EN:	17 December 2004
Date of latest announcement of this EN (doa):	31 March 2005
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2005
Date of withdrawal of any conflicting National Standard (dow):	30 September 2005

1 Scope

The multi-part deliverable EN 300 396 defines the TERrestrial Trunked RADio (TETRA) Direct Mode Operation (DMO). It specifies the basic air interface, the inter-working between Direct Mode (DM) groups via repeaters, and inter-working with the TETRA Voice plus Data (V+D) system via gateways. It also specifies the security aspects in TETRA DMO, and the intrinsic services that are supported in addition to the basic bearer and teleservices.

The present document applies to the TETRA DMO Mobile Station - Mobile Station (MS-MS) air interface and contains the specifications of the Data Link Layer (DLL) and the network layer according to the ISO model.

It establishes the services, messages and protocols used for voice and circuit mode data calls and short data transfer, starting with the upper layers:

- it defines and specifies the protocol used by the layer 3 entity to communicate across the air interface;
- it defines and specifies the services and protocol used in the DLL.

The normative annexes mainly specify the parameter values used in the protocol.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] ETSI ETS 300 396-1: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 1: General network design".
- [2] ETSI EN 300 396-2: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 2: Radio aspects".
- [3] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [4] ETSI EN 300 396-4: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 4: Type 1 repeater air interface".
- [5] ETSI ETS 300 396-5: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 5: Gateway air interface".
- [6] ETSI EN 300 396-6: "Terrestrial Trunked Radio (TETRA); Direct Mode Operation (DMO); Part 6: Security".
- [7] ETSI EN 300 396-7: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 7: Type 2 repeater air interface".
- [8] ETSI EN 300 392-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 1: General network design".
- [9] ETSI EN 300 396-10: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 10: Managed Direct Mode Operation (M-DMO)".

- [10] ETSI ETS 300 396-3: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 3: Mobile Station to Mobile Station (MS-MS) Air Interface (AI) protocol".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

call: complete sequence of related call transactions between DM-MSs

NOTE 1: There are two types of call, individual call or group call. An individual call is a complete sequence of related call transactions between two DM-MSs. A group call is a complete sequence of related call transactions involving two or more DM-MSs. The number of participants in a group call is not fixed. Participants may join (late entry) and leave an ongoing call.

NOTE 2: For calls without presence check there is no guaranty that anyone is listening.

call transaction: all of the functions associated with a complete unidirectional transmission of information

NOTE: A call is made up of one or more sequential call transactions.

called user application: user application which receives an incoming call

calling user application: user application which initiates an outgoing call

changeover: within a call, the process of effecting a transfer of the master role (and hence transmitting MS) at the end of one call transaction so that another can commence

Direct Mode Call Control (DMCC): layer 3 entity responsible for setting up and maintaining a call in DMO

Direct Mode GATEway (DM-GATE): device that provides gateway connectivity between DM-MS(s) and the TETRA TMO network

NOTE: The gateway provides the interface between TETRA DMO and TETRA TMO. A gateway may provide only the gateway function (DM-GATE) or may provide the functions of both a DM repeater and a DM gateway during a call (DM-REP/GATE).

Direct Mode Mobile Station (DM-MS): physical grouping that contains all of the mobile equipment that is used to obtain TETRA DM services

NOTE: A DM-MS may have one of three roles:

- **master:** if the DM-MS is either active in a call transaction transmitting traffic or control data, or is reserving the channel by means of channel reservation signalling;
- **slave:** if the DM-MS is receiving traffic and/or signalling in a call;
- **idle:** if the DM-MS is not in a call.

Direct Mode Operation (DMO): mode of simplex operation where mobile subscriber radio units may communicate using radio frequencies which may be monitored by, but which are outside the control of, the TETRA TMO network

NOTE: Direct Mode Operation is performed without intervention of any base station.

Direct Mode REPeater (DM-REP): device that operates in TETRA DMO and provides a repeater function to enable two or more DM-MSs to extend their coverage range

NOTE: It may be either a type 1 DM-REP, capable of supporting only a single call on the air interface, or a type 2 DM-REP, capable of supporting two calls on the air interface. A type 1 DM-REP may operate on either a single RF carrier (type 1A DM-REP) or a pair of duplex-spaced RF carriers (type 1B DM-REP). A type 2 DM-REP operates on a pair of duplex-spaced RF carriers.