# TECHNICAL SPECIFICATION

# **IEC** TS 62393

First edition 2005-05

Portable and hand-held multimedia equipment – Mobile computers – Battery run-time measurement

## iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC TS 62393:2005</u> https://standards.iteh.ai/catalog/standards/sist/2f8337b0-99b3-4201-ab30-28b781a46bc6/iec-ts-62393-2005



#### **Publication numbering**

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

#### **Consolidated editions**

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

#### Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- IEC Web Site (<u>www.iec.ch</u>)
- . Catalogue of IEC publications

The on-line catalogue on the IEC web site (<a href="www.iec.ch/searchpub">www.iec.ch/searchpub</a>) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

• IEC Just Publishedstandards.iteh.ai)

This summary of recently issued publications (<a href="www.iec.ch/online\_news/"www.iec.ch/online\_news/"justpub">www.iec.ch/online\_news/</a> justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information. TS 62393:2005

https://standards.iteh.ai/catalog/standards/sist/2f8337b0-99b3-4201-ab30-

• Customer Service Centre 1a46bc6/iec-ts-62393-2005

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

# TECHNICAL SPECIFICATION

### IEC TS 62393

First edition 2005-05

## Portable and hand-held multimedia equipment – Mobile computers – Battery run-time measurement

### iTeh STANDARD PREVIEW (standards.iteh.ai)

IEC TS 62393:2005 https://standards.iteh.ai/catalog/standards/sist/2f8337b0-99b3-4201-ab30-28b781a46bc6/iec-ts-62393-2005

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



PRICE CODE



#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

### PORTABLE AND HAND-HELD MULTIMEDIA EQUIPMENT – MOBILE COMPUTERS – BATTERY RUN-TIME MEASUREMENT

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international
  consensus of opinion on the relevant subjects since each technical committee has representation from all
  interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an EC Publication 337b0-99b3-4201-ab30-
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC 62393, which is a technical specification, has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
100/848/DTS	100/936/RVC

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · transformed into an International standard,
- reconfirmed;
- withdrawn;
- · replaced by a revised edition, or
- · amended.

A bilingual version of this document may be issued at a later date.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC TS 62393:2005</u> https://standards.iteh.ai/catalog/standards/sist/2f8337b0-99b3-4201-ab30-28b781a46bc6/iec-ts-62393-2005

#### INTRODUCTION

Adequate indication of the remaining battery level is crucial for mobile equipment, as its malfunction may lead to loss of user data. The wireless communication function of the mobile equipment causes the power dissipation to be larger and more irregular. A reliable indication of the remaining battery level is, therefore, strongly needed.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC TS 62393:2005</u> https://standards.iteh.ai/catalog/standards/sist/2f8337b0-99b3-4201-ab30-28b781a46bc6/iec-ts-62393-2005

### PORTABLE AND HAND-HELD MULTIMEDIA EQUIPMENT – MOBILE COMPUTERS – BATTERY RUN-TIME MEASUREMENT

#### 1 Scope

This Technical Specification defines the operation-mode mix of portable and hand-held multimedia equipment which can be driven by battery, especially mobile personal computers, in order to clarify the issues to be standardized on the battery run time.

#### 2 Battery run-time measurement methods for mobile PCs

#### 2.1 General

Current products have a variety of methods for setting power management as shown in Figure 1, and screens may differ from this example. If this is the case, the settings which most closely match the example should be used.

The battery run time should be calculated as follows.

iTeh STANDARD PREVIEW
[(measurement method a) + (measurement method b)]/2
(standards.iteh.ai)

The result should be rounded downward to one decimal point, and the result displaced as x.y. It is acceptable to use the term "approximately" or "about."

Example: https://standards.iteh.ai/catalog/standards/sist/2f8337b0-99b3-4201-ab30-28b781a46bc6/iec-ts-62393-2005


Measurement method (a) 3 h 15 min, measurement method (b) 8 h 7 min (195 min + 487 min)/2 = 5,683 h This should be rounded down to 5,6 h (or about 5,6 h).

It is necessary to disclose all information on settings which are different from the factory shipping default.

Examples of disclosure:

by the Web, by an information centre, or by brochure.

The margin on the measured value to the published value should not be defined.



IEC 582/05

Figure 1 - Power option properties

#### 2.2 Measurement method (a)

At a display luminance of 20 cd/m<sup>2</sup>, the continuous playback time of one MPEG moving image file read from a hard disk should be measured.

MPEG movie file

The MPEG movie file specified by this measuring method should be used.

• The sound should be set to the minimum (mute is acceptable as shown in Figure 2).




Figure 2 - Volume control

#### Luminance of LCD

While displaying white on the LCD, the luminance should be set to a minimum of 20 cd/m $^2$ . Any luminance exceeding 20 cd/m $^2$  (such as 25 cd/m $^2$ ) is acceptable. The luminance of the white area should not be reduced to less than 20 cd/m $^2$  during measurement. The white should be defined as the R, G and B data of each pixel at their maximum values.

- A fluctuating luminance is acceptable during measurement as long as it does not fall below 20 cd/m<sup>2</sup>.
- The way to set the values for the LCD to exceed the 20 cd/m² should be disclosed so that the luminance for measurement can be set without the need for an intensity meter (for example, two steps from the lower end of a five-step intensity range).
- Software used for movie playback is not defined. Software which is bundled in the shipping unit is preferred. Software which is used should be disclosed.

The user should be able to obtain the same playback software used for the measurement by downloading or purchasing.

- Playback size of the movie: one time (320 × 240).
- Percentage setting of battery remaining to be defined at the end of the test: not defined.
   It is acceptable to disable the percentage checking and run the test all the way down until the battery is empty
- Margin between measured results and value published in product catalogue: not defined.
   The guidelines of each PC manufacturer may be followed.
- Charging the battery for testing: charge the battery in the notebook PC itself.
- Condition of battery (degree of degradation, etc.): not defined.

Can be determined by each PC manufacturer.

Setting the other power management: not defined.

Power management should not cause any frame drops during playback of the movie.

· Location of movie file

The movie file should be stored on the hard disk, and the file always played back by reading it directly from the hard disk during playback. However, if there is no hard drive in the system, the movie file may be stored in a secondary memory source such as a flash card.

Storing or caching the entire moving image file in a main memory during measurement is prohibited.

In the case where the file is cached, the movie file should be linked many times so that the size for the file will exceed the main memory.

 Foreground applications and background applications running during measurement: not defined.

If the computer set-up has changed from the factory shipping default, the change should be disclosed.

#### 2.3 Measurement method (b)

The notebook PC should be set so that the desktop screen is displayed at the lowest luminance of the LCD. Power management settings are not defined in detail, but information on the settings should be disclosed.

#### Regulated items

- Luminance of LCD: set to the lowest possible value.
  - Neither the backlight nor the screen should be set to OFF. However, in the case of a system which has reflective type LCD, it may be measured without backlight.
- Margin between measured value and value published in product catalogue: not defined.
- May follow the guideline of each PC manufacturer
  - Foreground applications and background applications running during measurement: not defined.
    - If the computer set-up has changed from the factory shipping default, the change should be disclosed.
  - Percentage setting of battery remaining to be defined at the end of the test: not defined.
     https://standards.itch.ai/catalog/standards/sist/2f8337b0-99b3-4201-ab30 
     It is acceptable to disable the percentage checking and run the test all the way down until the battery is empty.
  - Powering-off of hard disk drive: not defined. Powering-off the hard disk drive during measurement is acceptable.

The power management value can be the lowest value that can be set.

Other power management: not defined.

As long as the screen and backlight are on during the measurement, no other regulation applies.

However, the power management settings should be disclosed.