

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**High-voltage switchgear and controlgear –
Part 100: Alternating-current circuit-breakers**

**Appareillage à haute tension –
Partie 100: Disjoncteurs à courant alternatif**

[IEC 62271-100:2008](https://standards.iteh.ai/catalog/standards/iec/e82756a0-fa3b-464a-89f6-60076020cd1b/iec-62271-100-2008)

<https://standards.iteh.ai/catalog/standards/iec/e82756a0-fa3b-464a-89f6-60076020cd1b/iec-62271-100-2008>





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



IEC 62271-100

Edition 2.2 2017-06
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE



High-voltage switchgear and controlgear –
Part 100: Alternating-current circuit-breakers

Appareillage à haute tension –
Partie 100: Disjoncteurs à courant alternatif

<https://standards.iteh.ai/>

<https://standards.iteh.ai/catalog/standards/iec/e82756a0-fa3b-464a-89f6-60076020cd1b/iec-62271-100-2008>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.130.10

ISBN 978-2-8322-4470-8

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

REDLINE VERSION

VERSION REDLINE



**High-voltage switchgear and controlgear –
Part 100: Alternating-current circuit-breakers**

**Appareillage à haute tension –
Partie 100: Disjoncteurs à courant alternatif**

[IEC 62271-100:2008](https://standards.iteh.ai/catalog/standards/iec/e82756a0-fa3b-464a-89f6-60076020cd1b/iec-62271-100-2008)

<https://standards.iteh.ai/catalog/standards/iec/e82756a0-fa3b-464a-89f6-60076020cd1b/iec-62271-100-2008>

CONTENTS

FOREWORD.....	13
INTRODUCTION to the Amendment	15
1 General.....	16
1.1 Scope.....	16
1.2 Normative references	17
2 Normal and special service conditions.....	18
3 Terms and definitions	18
3.1 General terms.....	18
3.2 Assemblies	22
3.3 Parts of assemblies	22
3.4 Switching devices.....	22
3.5 Parts of circuit-breakers.....	24
3.6 Operation	26
3.7 Characteristic quantities	29
3.8 Index of definitions	36
4 Ratings.....	40
4.1 Rated voltage (U_r).....	41
4.2 Rated insulation level	41
4.3 Rated frequency (f_r).....	42
4.4 Rated normal current (I_r) and temperature rise.....	43
4.5 Rated short-time withstand current (I_k).....	43
4.6 Rated peak withstand current (I_p).....	43
4.7 Rated duration of short circuit (t_k).....	43
4.8 Rated supply voltage of closing and opening devices and of auxiliary and control circuits (U_a).....	43
4.9 Rated supply frequency of closing and opening devices and auxiliary circuits.....	43
4.10 Rated pressures of compressed gas supply for insulation, operation and/or interruption controlled pressure systems	43
4.11 Rated filling levels for insulation and/or operation	43
4.101 Rated short-circuit breaking current (I_{sc}).....	44
4.102 Transient recovery voltage related to the rated short-circuit breaking current.....	44
4.102 Rated first-pole-to-clear factor	55
4.103 Rated short-circuit making current	56
4.104 Rated operating sequence	56
4.105 Characteristics for Short-line faults breaking capability	57
4.106 Rated out-of-phase making and breaking current.....	58
4.107 Rated capacitive switching currents	59
4.108 Inductive load switching.....	62
4.109 Rated time quantities Void	62
4.110 Number of mechanical operations.....	63
4.111 Classification of circuit-breakers as a function of electrical endurance	63
5 Design and construction	64
5.1 Requirements for liquids in circuit-breakers	64
5.2 Requirements for gases in circuit-breakers	64

5.3	Earthing of circuit-breakers.....	64
5.4	Auxiliary equipment	64
5.5	Dependent power-closing operation	65
5.6	Stored energy-closing operation	65
5.7	Independent manual or power operation	65
5.8	Operation of releases	65
5.9	Low- and high-pressure interlocking devices.....	66
5.10	Nameplates	66
5.11	Interlocking devices	68
5.12	Position indication	68
5.13	Degrees of protection by enclosures	68
5.14	Creepage distances.....	68
5.15	Gas and vacuum tightness.....	68
5.16	Liquid tightness	68
5.17	Fire hazard (flammability)	68
5.18	Electromagnetic compatibility	68
5.19	X-ray emission.....	69
5.20	Corrosion.....	69
5.101	Requirements for simultaneity of poles during single closing and single opening operations	69
5.102	General requirement for operation	69
5.103	Pressure limits of fluids for operation.....	70
5.104	Vent outlets	70
5.105	Time quantities	70
5.106	Static mechanical loads	71
6	Type tests	72
6.1	General	72
6.2	Dielectric tests.....	75
6.3	Radio interference voltage (r.i.v.) tests	80
6.4	Measurement of the resistance of the main circuit	80
6.5	Temperature-rise tests.....	80
6.6	Short-time withstand current and peak withstand current tests.....	81
6.7	Verification of the degree of protection	82
6.8	Tightness tests	82
6.9	Electromagnetic compatibility (EMC) tests	82
6.10	Additional tests on auxiliary and control circuits.....	82
6.11	X-radiation test procedure for vacuum interrupters	83
6.101	Mechanical and environmental tests	83
6.102	Miscellaneous provisions for making and breaking tests	95
6.103	Test circuits for short-circuit making and breaking tests	133
6.104	Short-circuit test quantities	135
6.105	Short-circuit test procedure.....	160
6.106	Basic short-circuit test-duties.....	162
6.107	Critical current tests	169
6.108	Single-phase and double-earth fault tests	169
6.109	Short-line fault tests	171
6.110	Out-of-phase making and breaking tests	177
6.111	Capacitive current switching tests.....	179

6.112	Special requirements for making and breaking tests on class E2 circuit-breakers	206
7	Routine tests	207
7.1	Dielectric test on the main circuit	207
7.2	Tests on auxiliary and control circuits	209
7.3	Measurement of the resistance of the main circuit	209
7.4	Tightness test	209
7.5	Design and visual checks	209
7.101	Mechanical operating tests	209
8	Guidance to the selection of circuit-breakers for service	211
8.101	General	211
8.102	Selection of rated values for service conditions	213
8.103	Selection of rated values for fault conditions	215
8.104	Selection for electrical endurance in networks of rated voltage above 1 kV and up to and including 52 kV	220
8.105	Selection for capacitive current switching	220
9	Information to be given with enquiries, tenders and orders	220
9.101	Information to be given with enquiries and orders	220
9.102	Information to be given with tenders	222
10	Rules for transport, storage, installation, operation and maintenance	224
10.1	Conditions during transport, storage and installation	224
10.2	Installation	224
10.3	Operation	230
10.4	Maintenance	230
11	Safety	230
12	Influence of the product on the environment	230
	Annex A (normative) Calculation of transient recovery voltages for short-line faults from rated characteristics	306
A.1	Basic approach	306
A.2	Transient voltage on line side	308
A.3	Transient voltage on source side	309
A.4	Examples of calculations	311
	Annex B (normative) Tolerances on test quantities during type tests	317
	Annex C (normative) Records and reports of type tests	326
C.1	Information and results to be recorded	326
C.2	Information to be included in type test reports	326
	Annex D (normative) Determination of short-circuit power factor	330
D.1	Method I – Calculation from d.c. component	330
D.2	Method II – Determination with pilot generator	330
	Annex E (normative) Method of drawing the envelope determination of the prospective TRV of a circuit and determining the representative parameters	332
E.1	Introduction General	332
E.2	Drawing the envelope	333
E.3	Determination of parameters	333
	Annex F (normative) Methods of determining prospective transient recovery voltage waves	337
F.1	Introduction General	337
F.2	General summary of the recommended methods	338

F.3	Detailed consideration of the recommended methods	339
F.4	Comparison of methods	343
Annex G (normative)	Rationale behind introduction of circuit-breakers class E2	353
Annex H (informative) Inrush currents of single and back-to-back capacitor banks		
H.1 — General		
H.2 — Example 1 — One capacitor to be switched in parallel (see Figure H.1)		
H.3 — Example 2 — Two capacitors to be switched in parallel (see Figure H.2)		
Annex I (informative) Explanatory notes		
I.1 — General		
I.2 — Explanatory note regarding the d.c. time constant of the rated short-circuit breaking current (4.101.2) — Advice for the choice of the appropriate time constant		
I.3 — Explanatory note regarding capacitive current switching tests (6.111)		
Annex J (informative) Test current and line length tolerances for short-line fault testing		
Annex K (informative) List of symbols and abbreviations used in this standard		
Annex L (informative) Explanatory notes on the revision of TRVs for circuit-breakers of rated voltages higher than 1 kV and less than 100 kV		
L.1 — General		
L.2 — Terminal fault		
L.3 — Short-line fault		
L.4 — Out-of-phase		
L.5 — Series reactor fault		
L.6 — TRV for last clearing poles / Tests circuit topology		
Annex M (normative informative)	Requirements for breaking of transformer-limited faults by circuit-breakers with rated voltage higher than 1 kV and less than 100 kV	376
M.1	General	376
M.2	Circuit-breakers with rated voltage less than 100 kV	377
M.3	Circuit-breakers with rated voltage from 100 kV to 800 kV	380
M.4	Circuit-breakers with rated voltage higher than 800 kV	380
Annex N (normative)	Use of mechanical characteristics and related requirements	382
Annex O (informative normative)	Guidance Requirements for short-circuit and switching test procedures for metal-enclosed and dead tank circuit-breakers	385
O.1	General	396
O.2	Reduced number of units for testing purposes	397
O.3	Tests for single pole in one enclosure	397
O.4	Tests for three poles in one enclosure	400
Annex P (normative) Calculation of the TRV parameters during asymmetrical fault condition (T100a)		
Annex Q (informative) Examples for the application of the asymmetry criteria during asymmetrical test-duty T100a		
Q.1 — Three-phase testing of a circuit-breaker with a rated d.c. time constant of the rated short-circuit breaking current constant longer than the test circuit time constant		
Q.2 — Single phase testing of a circuit-breaker with a rated d.c. time constant of the rated short-circuit breaking current shorter than the test circuit time constant		
Q.3 — Single phase testing of a circuit-breaker with a rated d.c. time constant of the rated short-circuit breaking current longer than the test circuit time constant		
Annex R (normative)	Requirements for circuit-breakers with opening resistors	415

R.1	General	415
R.2	Switching performance to be verified	415
R.3	Insertion time of the resistor	428
R.4	Current carrying performance	428
R.5	Dielectric performance	428
R.6	Mechanical performance	428
R.7	Requirements for the specification of opening resistors	428
R.8	Examples of recovery voltage waveshapes	428
Annex S (normative) Verification of capacitive current switching in presence of single or two-phase earth faults		432
S.1	General	432
S.2	Test voltage	432
S.3	Test current	432
S.4	Test-duty	433
S.5	Criteria to pass the tests	433
Bibliography		434
Figure 1 – Typical oscillogram of a three-phase short-circuit make-break cycle		232
Figure 2 – Circuit-breaker without switching resistors – Opening and closing operations.....		235
Figure 3 – Circuit breaker without switching resistors – Close-open cycle		237
Figure 4 – Circuit-breaker without switching resistors – Reclosing (auto-reclosing).....		239
Figure 5 – Circuit-breaker with switching resistors – Opening and closing operations		241
Figure 6 – Circuit-breaker with switching resistors – Close-open cycle.....		243
Figure 7 – Circuit-breaker with switching resistors – Reclosing (auto-reclosing).....		245
Figure 8 – Determination of short-circuit making and breaking currents, and of percentage d.c. component.....		246
Figure 9 – Percentage d.c. component in relation to the time interval from the initiation of the short-circuit for the standard different time constants τ_1 and for the special case time constants τ_2, τ_3 and τ_4		247
Figure 10 – Representation of a specified four-parameter TRV and a delay line for T100, T60, short-line fault and out-of-phase condition.....		248
Figure 11 – Representation of a specified TRV by a two-parameter reference line and a delay line		248
Figure 12 - ITRV circuit and representation of ITRV in relationship to TRV		249
Figure 13 – Three-phase short-circuit representation		251
Figure 14 – Alternative representation of Figure 13.....		252
Figure 15 – Basic short-line fault circuit		253
Figure 16 – Example of a line-side transient voltage with time delay and rounded crest showing construction to derive the values u_L^*, t_L and t_{dL}.....		254
Figure 16 – Examples of line side transient voltages		254
Figure 17 – Test sequences for low and high temperature tests		255
Figure 18 – Humidity test		256
Figure 19 – Static terminal load forces		256
Figure 20 – Directions for static terminal load tests		256
Figure 21 – Permitted number of samples for making, breaking and switching tests, illustrations of the statements in 6.102.2		256
Figure 22 – Definition of a single test specimen in accordance with 3.2.2 of IEC 62271-1		256

Figure 23a – Reference mechanical characteristics (idealised curve).....	262
Figure 23b – Reference mechanical characteristics (idealised curve) with the prescribed envelopes centered over the reference curve (+5 %, –5 %), contact separation in this example at time $t = 20$ ms	262
Figure 23c – Reference mechanical characteristics (idealised curve) with the prescribed envelopes fully displaced upward from the reference curve (+10 %, –0 %), contact separation in this example at time $t = 20$ ms	263
Figure 23d – Reference mechanical characteristics (idealised curve) with the prescribed envelopes fully displaced downward from the reference curve (+0 %, –10 %), contact separation in this example at time $t = 20$ ms	263
Figure 24 – Equivalent testing set-up for unit testing of circuit-breakers with more than one separate interrupter units	264
Figure 25 – Earthing of test circuits for three-phase short-circuit tests, first-pole-to-clear factor 1,5.....	265
Figure 26 – Earthing of test circuits for three-phase short-circuit tests, first-pole-to-clear factor 1,3.....	266
Figure 27 – Earthing of test circuits for single-phase short-circuit tests, first-pole-to-clear factor 1,5.....	267
Figure 28 – Earthing of test circuits for single-phase short-circuit tests, first-pole-to-clear factor 1,3.....	267
Figure 29 – Graphical representation of the three valid symmetrical breaking operations for three-phase tests in a non-effectively earthed neutral system (first-pole-to-clear factor 1,5) an example of the three valid symmetrical breaking operations for $k_{pp} = 1,5$	270
Figure 30 – Graphical representation of the three valid symmetrical breaking operations for three-phase tests in an effectively earthed neutral system (first-pole-to-clear factor 1,3) $k_{pp} = 1,2$ or $1,3$	272
Figure 31 – Graphical representation of an example of the three valid asymmetrical breaking operations for three-phase tests in a non-effectively earthed neutral system (first-pole-to-clear factor 1,5) for $k_{pp} = 1,5$	274
Figure 32 – Graphical representation of the three valid symmetrical breaking operations for single-phase tests in substitution of three-phase conditions in a non-effectively earthed neutral system (first-pole-to-clear factor 1,5) for $k_{pp} = 1,5$	276
Figure 33 – Graphical representation of the three valid symmetrical breaking operations for single-phase tests in substitution of three-phase conditions in a non-effectively earthed neutral system (first-pole-to-clear factor 1,5) for $k_{pp} = 1,5$	278
Figure 34 – Graphical representation of an example of the three valid asymmetrical breaking operations for single-phase tests in substitution of three-phase conditions in a non-effectively earthed neutral system (first-pole-to-clear factor 1,5) for $k_{pp} = 1,2$ or $1,3$	280
Figure 35 – Graphical representation of an example of the three valid asymmetrical breaking operations for single-phase tests in substitution of three-phase conditions in an effectively earthed neutral system (first-pole-to-clear factor 1,3) for $k_{pp} = 1,5$	282
Figure 36 – Graphical representation of an example of the three valid asymmetrical breaking operations for single-phase tests in substitution of three-phase conditions in an effectively earthed neutral system (first-pole-to-clear factor 1,3) for $k_{pp} = 1,2$ and $1,3$	284
Figure 37 – Graphical representation of the interrupting window and the voltage factor k_p , determining the TRV of the individual pole, for systems with a first-pole-to-clear factor of 1,3	286
Figure 38 – Graphical representation of the interrupting window and the voltage factor k_p , determining the TRV of the individual pole, for systems with a first-pole-to-clear factor of 1,5	287

Figure 39 – Example of prospective test TRV with four-parameter envelope which satisfies the conditions to be met during type test – Case of specified TRV with four-parameter reference line 288

Figure 40 – Example of prospective test TRV with two-parameter envelope which satisfies the conditions to be met during type test: case of specified TRV with two-parameter reference line 289

~~Figure 41 – Example of prospective test TRV with four-parameter envelope which satisfies the conditions to be met during type test – Case of specified TRV with two-parameter reference line 289~~

~~Figure 42 – Example of prospective test TRV with two-parameter envelope which satisfies the conditions to be met during type test – Case of specified TRV with four-parameter reference line 288~~

Figure 43 – Example of prospective test TRV-waves and their combined envelope in two-part test 291

Figure 44 – Determination of power frequency recovery voltage 292

Figure 45 – Necessity of additional single-phase tests and requirements for testing 293

Figure 46 – Basic circuit arrangement for short-line fault testing and prospective TRV-circuit-type a) according to 6.109.3: source side and line side with time delay 295

Figure 47 – Basic circuit arrangement for short-line fault testing – circuit type b1) according to 6.109.3: source side with ITRV and line side with time delay 297

Figure 48 – Basic circuit arrangement for short-line fault testing – circuit type b2) according to 6.109.3: source side with time delay and line side without time delay 299

Figure 49 – Flow-chart for the choice of short-line fault test circuits for class S2 circuit-breakers and for circuit-breakers having a rated voltage of 100 kV and above 300

Figure 50 – Compensation of deficiency of the source side time delay by an increase of the excursion of the line side voltage 301

Figure 51 – Test circuit for single-phase out-of-phase tests 302

Figure 52 – Test circuit for out-of-phase tests using two voltages separated by 120 electrical degrees 302

Figure 53 – Test circuit for out-of-phase tests with one terminal of the circuit-breaker earthed (subject to agreement of the manufacturer) 303

Figure 54 – Recovery voltage for capacitive current breaking tests 303

Figure 55 – Reclassification procedure for line and cable-charging current switching tests 304

Figure 56 – Reclassification procedure for capacitor bank current switching tests 305

Figure 58 – Graphical representation of the interrupting window and the voltage factor k_p , determining the TRV of the individual pole, for systems with a first-pole-to-clear factor of 1,2 285

Figure 59 – Example of wind velocity measurement 257

Figure 60 – Graphical representation of the time parameters for the demonstration of arcing times in three-phase tests of test-duty T100a 268

Figure A.1 – Typical graph of line and source side TRV parameters – Line side and source side with time delay 314

Figure A.2 – Typical graph of line and source side TRV parameters – Line side and source side with time delay, source side with ITRV 315

Figure A.3 – Actual course of the source side transient recovery voltage for short-line fault L₉₀, L₇₅ and L₆₀ 316

Figure E.1 – Representation by four parameters of a prospective transient recovery voltage of a circuit – Case E.2 c) 1) 335

Figure E.2 – Representation by four parameters of a prospective transient recovery voltage of a circuit – Case E.2 c) 2) 335

Figure E.3 – Representation by four parameters of a prospective transient recovery voltage of a circuit – Case E.2. c) 3) i)	336
Figure E.4 – Representation by two parameters of a prospective transient recovery voltage of a circuit – Case E.2. c) 3) ii)	336
Figure F.1 – Effect of depression on the peak value of the TRV	346
Figure F.2 – TRV in case of ideal breaking	346
Figure F.3 – Breaking with arc-voltage present	347
Figure F.4 – Breaking with pronounced premature current-zero	347
Figure F.5 – Breaking with post-arc current.....	347
Figure F.6 – Relationship between the values of current and TRV occurring in test and those prospective to the system.....	348
Figure F.7 – Schematic diagram of power-frequency current injection apparatus	349
Figure F.8 – Sequence of operation of power-frequency current injection apparatus	350
Figure F.9 – Schematic diagram of capacitance injection apparatus	351
Figure F.10 – Sequence of operation of capacitor-injection apparatus	352
Figure H.1 – Circuit diagram for example 1
Figure H.2 – Circuit diagram for example 2
Figure H.3 – Equations for the calculation of capacitor bank inrush currents
Figure M.1 – First example of transformer-limited fault (also called transformer-fed fault).....	376
Figure M.2 – Second example of transformer-limited fault (also called transformer-secondary fault)	377
Figure O.1 – Test configuration considered in Tables O.1, O.2 and O.3	398
Figure O.2 – Example showing the waveshapes of symmetrical currents, phase-to-ground and phase-to-phase voltages during three-phase interruption, as for Figure 25a.....
Figure O.3 – Example showing the waveshapes of symmetrical currents, phase-to-ground and phase-to-phase voltages during three-phase interruption, as for Figure 26a.....
Figure Q.1 – Three-phase testing of a circuit-breaker with a rated d.c. time constant of the rated short-circuit breaking current longer than the test circuit time constant
Figure Q.2 – Single phase testing of a circuit-breaker with a rated d.c. time constant of the rated short-circuit breaking current shorter than the test circuit time constant
Figure Q.3 – Single phase testing of a circuit-breaker with a rated d.c. time constant of the rated short-circuit breaking current longer than the test circuit time constant
Figure R.1 – Typical system configuration for interruption by a circuit-breaker with opening resistors	415
Figure R.2 – Test circuit for test duties T60 and T100	417
Figure R.3 – Test circuit for test duties T10, T30 and OP2	417
Figure R.4 – Example of an underdamped TRV for T100s(b), $U_r = 1\ 100\ \text{kV}$ $I_{SC} = 50\ \text{kA}$, $f_r = 50\ \text{Hz}$	420
Figure R.5 – Example of an overdamped TRV for T10, $U_r = 1\ 100\ \text{kV}$ $I_{SC} = 50\ \text{kA}$, $f_r = 50\ \text{Hz}$	421
Figure R.6 – Example of a test circuit for short-line fault test duty L_{90}	422
Figure R.7 – Example of real line simulation for short-line fault test-duty L_{90} based on $U_r = 1\ 100\ \text{kV}$, $I_{SC} = 50\ \text{kA}$ and $f_r = 50\ \text{Hz}$	423
Figure R.8 – Typical recovery voltage waveshape of capacitive current switching on a circuit-breaker equipped with opening resistors	425

Figure R.9 – Typical recovery voltage waveshape of T10 (based on $U_r = 1\ 100\text{ kV}$, $I_{sc} = 50\text{ kA}$ and $f_r = 50\text{ Hz}$) on the resistor interrupter of a circuit-breaker equipped with opening resistors 426

Figure R.10 – TRV waveshapes for high short-circuit current breaking operation 429

Figure R.11 – Currents in case of high short-circuit current breaking operation 429

Figure R.12 – TRV shapes for low short-circuit current breaking operation 430

Figure R.13 – Currents in case of low short-circuit current breaking operation 430

Figure R.14 – Voltage waveshapes for line-charging current breaking operation 431

Figure R.15 – Current waveshapes for line-charging current breaking operation 431

~~Table 1 – Standard values of transient recovery voltage for class S1 circuit-breakers – Rated voltage higher than 1 kV and less than 100 kV – Representation by two parameters 160~~

~~Table 2 – Standard values of transient recovery voltage^c for class S2 circuit-breakers – Rated voltage equal to or higher than 15 kV and less than 100 kV – Representation by two parameters 160~~

~~Table 3 – Standard values of transient recovery voltage^a – Rated voltages of 100 kV to 170 kV for effectively earthed systems – Representation by four parameters 160~~

~~Table 4 – Standard values of transient recovery voltage^a – Rated voltages of 100 kV to 170 kV for non-effectively earthed systems – Representation by four parameters 160~~

~~Table 5 – Standard values of transient recovery voltage^a – Rated voltages 245 kV and above for effectively earthed systems – Representation by four parameters 160~~

Table 6 – Standard multipliers for TRV values for second and third clearing poles for rated voltages above 1 kV 160

Table 7 – Standard values of ITRV – Rated voltages 100 kV and above 159

Table 8 – Values of line characteristics for short-line faults 173

Table 9 – Preferred values of rated capacitive switching currents 61

Table 10 – Nameplate information 67

Table 11 – Type tests 73

Table 12 – Invalid tests 75

Table 13 – Number of operating sequences 87

Table 14 – Examples of static horizontal and vertical forces for static terminal load test 71

~~Table 15 – Last current loop parameters for 50 Hz operation in relation with short-circuit test-duty T100a $\tau = 45\text{ ms}$ 71~~

~~Table 16 – Last current loop parameters for 50 Hz operation in relation with short-circuit test-duty T100a $\tau = 60\text{ ms}$ 71~~

~~Table 17 – Last current loop parameters for 50 Hz operation in relation with short-circuit test-duty T100a $\tau = 75\text{ ms}$ 71~~

~~Table 18 – Last current loop parameters for 50 Hz operation in relation with short-circuit test-duty T100a $\tau = 120\text{ ms}$ 71~~

~~Table 19 – Last current loop parameters for 60 Hz operation in relation with short-circuit test-duty T100a $\tau = 45\text{ ms}$ 71~~

~~Table 20 – Last current loop parameters for 60 Hz operation in relation with short-circuit test-duty T100a $\tau = 60\text{ ms}$ 71~~

~~Table 21 – Last current loop parameters for 60 Hz operation in relation with short-circuit test-duty T100a $\tau = 75\text{ ms}$ 71~~

~~Table 22 – Last current loop parameters for 60 Hz operation in relation with short-circuit test-duty T100a $\tau = 120\text{ ms}$ 71~~