

INTERNATIONAL STANDARD

NORME INTERNATIONALE

High-voltage switchgear and controlgear –
Part 100: Alternating-current circuit-breakers

Appareillage à haute tension –
Partie 100: Disjoncteurs à courant alternatif

STANDARD PREVIEW
(standards.iteh.ai)

IEC 62271-100:2008
<https://standards.iteh.ai/catalog/standards/sist/e82756a0-fa3b-464a-89f6-60076020cd1b/iec-62271-100-2008>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

[IEC 62271-100:2008](http://www.iec.ch/online_news/justpub)

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch

Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00



IEC 62271-100

Edition 2.0 2008-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE

High-voltage switchgear and controlgear –
Part 100: Alternating-current circuit-breakers

Appareillage à haute tension –
Partie 100: Disjoncteurs à courant alternatif

IEC 62271-100:2008

60076020cd1b/iec-62271-100-2008

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

XH

ICS 29.130.10

ISBN 2-8318-9714-9

CONTENTS

FOREWORD.....	19
1 General.....	21
1.1 Scope.....	21
1.2 Normative references.....	22
2 Normal and special service conditions.....	23
3 Terms and definitions.....	23
3.1 General terms.....	23
3.2 Assemblies.....	27
3.3 Parts of assemblies.....	27
3.4 Switching devices.....	27
3.5 Parts of circuit-breakers.....	29
3.6 Operation.....	31
3.7 Characteristic quantities.....	33
3.8 Index of definitions.....	39
4 Ratings.....	43
4.1 Rated voltage (U_r).....	44
4.2 Rated insulation level.....	44
4.3 Rated frequency (f_r).....	45
4.4 Rated normal current (I_r) and temperature rise.....	45
4.5 Rated short-time withstand current (I_k).....	45
4.6 Rated peak withstand current (I_p).....	45
4.7 Rated duration of short circuit (t_k).....	45
4.8 Rated supply voltage of closing and opening devices and of auxiliary and control circuits (U_a).....	45
4.9 Rated supply frequency of closing and opening devices and auxiliary circuits.....	45
4.10 Rated pressures of compressed gas supply for insulation, operation and/or interruption.....	46
4.101 Rated short-circuit breaking current (I_{SC}).....	46
4.101.1 AC component of the rated short-circuit breaking current.....	46
4.101.2 DC time constant of the rated short-circuit breaking current.....	46
4.102 Transient recovery voltage related to the rated short-circuit breaking current.....	47
4.102.1 Representation of TRV waves.....	47
4.102.2 Representation of TRV.....	48
4.102.3 Standard values of TRV related to the rated short-circuit breaking current.....	49
4.102.4 Standard values of ITRV.....	57
4.103 Rated short-circuit making current.....	57
4.104 Rated operating sequence.....	58
4.105 Characteristics for short-line faults.....	58
4.106 Rated out-of-phase making and breaking current.....	59
4.107 Rated capacitive switching currents.....	60
4.107.1 Rated line-charging breaking current.....	60
4.107.2 Rated cable-charging breaking current.....	60
4.107.3 Rated single capacitor bank breaking current.....	61
4.107.4 Rated back-to-back capacitor bank breaking current.....	62

4.107.5	Rated single capacitor bank inrush making current.....	62
4.108	Inductive load switching.....	62
4.109	Rated time quantities.....	62
4.109.1	Rated break-time.....	63
4.110	Number of mechanical operations.....	63
4.111	Classification of circuit-breakers as a function of electrical endurance.....	63
5	Design and construction.....	64
5.1	Requirements for liquids in circuit-breakers.....	64
5.2	Requirements for gases in circuit-breakers.....	64
5.3	Earthing of circuit-breakers.....	64
5.4	Auxiliary equipment.....	64
5.5	Dependent power closing.....	65
5.6	Stored energy closing.....	65
5.7	Independent manual operation.....	65
5.8	Operation of releases.....	65
5.8.101	Over-current release.....	65
5.8.101.1	Operating current.....	65
5.8.101.2	Operating time.....	65
5.8.101.3	Resetting current.....	66
5.8.102	Multiple releases.....	66
5.8.103	Operation limits of releases.....	66
5.8.104	Power consumption of releases.....	66
5.8.105	Integrated relays for self-tripping circuit-breakers.....	66
5.9	Low- and high-pressure interlocking devices.....	66
5.10	Nameplates.....	66
5.11	Interlocking devices.....	68
5.12	Position indication.....	68
5.13	Degrees of protection by enclosures.....	68
5.14	Creepage distances.....	68
5.15	Gas and vacuum tightness.....	68
5.16	Liquid tightness.....	68
5.17	Fire hazard (flammability).....	68
5.18	Electromagnetic compatibility.....	68
5.19	X-ray emission.....	69
5.20	Corrosion.....	69
5.101	Requirements for simultaneity of poles during single closing and single opening operations.....	69
5.102	General requirement for operation.....	69
5.103	Pressure limits of fluids for operation.....	69
5.104	Vent outlets.....	70
6	Type tests.....	70
6.1	General.....	72
6.1.1	Grouping of tests.....	72
6.1.2	Information for identification of specimens.....	72
6.1.3	Information to be included in type test reports.....	72
6.1.101	Invalid tests.....	72
6.2	Dielectric tests.....	73
6.2.1	Ambient air conditions during tests.....	73
6.2.2	Wet test procedure.....	73

6.2.3	Condition of circuit-breaker during dielectric tests.....	73
6.2.4	Criteria to pass the test.....	73
6.2.5	Application of test voltage and test conditions.....	73
6.2.6	Tests of circuit-breakers of $U_r \leq 245$ kV.....	74
6.2.7	Tests of circuit-breakers of $U_r > 245$ kV.....	74
6.2.8	Artificial pollution tests.....	75
6.2.9	Partial discharge tests.....	75
6.2.10	Tests on auxiliary and control circuits.....	75
6.2.11	Voltage test as a condition check.....	75
6.3	Radio interference voltage (r.i.v.) tests.....	76
6.4	Measurement of the resistance of the main circuit.....	76
6.5	Temperature-rise tests.....	76
6.5.1	Conditions of the circuit-breaker to be tested.....	76
6.5.2	Arrangement of the equipment.....	76
6.5.3	Measurement of the temperature and the temperature rise.....	77
6.5.4	Ambient air temperature.....	77
6.5.5	Temperature-rise tests of the auxiliary and control equipment.....	77
6.5.6	Interpretation of the temperature-rise tests.....	77
6.6	Short-time withstand current and peak withstand current tests.....	77
6.6.1	Arrangement of the circuit-breaker and of the test circuit.....	77
6.6.2	Test current and duration.....	77
6.6.3	Behaviour of the circuit-breaker during test.....	77
6.6.4	Conditions of the circuit-breaker after test.....	78
6.7	Verification of the degree of protection.....	78
6.7.1	Verification of the IP coding.....	78
6.7.2	Mechanical impact test.....	78
6.8	Tightness tests.....	78
6.9	Electromagnetic compatibility (EMC) tests.....	78
6.9.3.1	Ripple on d.c. input power port immunity test.....	78
6.9.3.2	Voltage dips, short interruptions and voltage variations on d.c. input power port immunity tests.....	78
6.10	Additional tests on auxiliary and control circuits.....	78
6.10.1	General.....	78
6.10.2	Functional tests.....	79
6.10.3	Electrical continuity of earthed metallic parts test.....	79
6.10.4	Verification of the operational characteristics of auxiliary contacts.....	79
6.10.5	Environmental tests.....	79
6.101	Mechanical and environmental tests.....	79
6.101.1	Miscellaneous provisions for mechanical and environmental tests.....	79
6.101.1.1	Mechanical characteristics.....	79
6.101.1.2	Component tests.....	80
6.101.1.3	Characteristics and settings of the circuit-breaker to be recorded before and after the tests.....	80
6.101.1.4	Condition of the circuit-breaker during and after the tests.....	81
6.101.1.5	Condition of the auxiliary and control equipment during and after the tests.....	81
6.101.2	Mechanical operation test at ambient air temperature.....	81
6.101.2.1	General.....	81
6.101.2.2	Condition of the circuit-breaker before the test.....	82

6.101.2.3	Description of the test on class M1 circuit-breakers	82
6.101.2.4	Extended mechanical endurance tests on class M2 circuit-breakers for special service requirements	83
6.101.2.5	Acceptance criteria for the mechanical operation tests.....	83
6.101.3	Low and high temperature tests	84
6.101.3.1	General	84
6.101.3.2	Measurement of ambient air temperature.....	85
6.101.3.3	Low temperature test.....	85
6.101.3.4	High-temperature test.....	86
6.101.4	Humidity test.....	87
6.101.4.1	General	87
6.101.4.2	Test procedure	88
6.101.5	Test to prove the operation under severe ice conditions	89
6.101.6	Static terminal load test	89
6.101.6.1	General	89
6.101.6.2	Tests	89
6.102	Miscellaneous provisions for making and breaking tests	90
6.102.1	General	91
6.102.2	Number of test specimens	91
6.102.3	Arrangement of circuit-breaker for tests	92
6.102.3.1	General	92
6.102.3.2	Common enclosure type	93
6.102.3.3	Multi-enclosure type	93
6.102.3.4	Self-tripping circuit-breakers	94
6.102.4	General considerations concerning testing methods	94
6.102.4.1	Single-phase testing of a single pole of a three-pole circuit-breaker	94
6.102.4.2	Unit testing	95
6.102.4.2.1	Identical nature of the units	96
6.102.4.2.2	Voltage distribution.....	96
6.102.4.2.3	Requirements for unit testing.....	97
6.102.4.3	Multi-part testing.....	97
6.102.5	Synthetic tests	98
6.102.6	No-load operations before tests	98
6.102.7	Alternative operating mechanisms	98
6.102.8	Behaviour of circuit-breaker during tests.....	99
6.102.9	Condition of circuit-breaker after tests	99
6.102.9.1	General	99
6.102.9.2	Condition after a short-circuit test-duty	100
6.102.9.3	Condition after a short-circuit test series.....	100
6.102.9.4	Condition after a capacitive current switching test series	101
6.102.9.5	Reconditioning after a short-circuit test-duty and other test series	102
6.102.10	Demonstration of arcing times	102
6.102.10.1	Three-phase tests	102
6.102.10.1.1	Test-duty T10, T30, T60, T100s, T100s(b), OP1 and OP2	102
6.102.10.1.2	Test-duty T100a	102
6.102.10.2	Single-phase tests in substitution for three-phase conditions.....	104
6.102.10.2.1	Non-effectively earthed neutral systems	104
6.102.10.2.1.1	Test-duties T10, T30, T60, T100s and T100s(b), OP1 and OP2	104

6.102.10.2.1.2	Test-duty T100a	105
6.102.10.2.2	Effectively earthed neutral systems including short-line fault tests	115
6.102.10.2.2.1	Test-duties T10, T30, T60, T100s and T100s(b), OP1 and OP2, L ₉₀ , L ₇₅ and L ₆₀	115
6.102.10.2.2.2	Test-duty T100a	115
6.102.10.2.3	Modified procedure in cases where the circuit-breaker failed to interrupt during a test with a medium arcing time	115
6.102.10.2.3.1	Breaking test with symmetrical current	115
6.102.10.2.3.2	Breaking test with asymmetrical current	116
6.102.10.2.4	Tests combining the conditions for effectively and non-effectively earthed neutral systems	116
6.102.10.2.5	Splitting of test-duties in test series taking into account the associated TRV for each pole-to-clear	116
6.103	Test circuits for short-circuit making and breaking tests	117
6.103.1	Power factor	117
6.103.2	Frequency	117
6.103.3	Earthing of test circuit	117
6.103.4	Connection of test circuit to circuit-breaker	119
6.104	Short-circuit test quantities	119
6.104.1	Applied voltage before short-circuit making tests	119
6.104.2	Short-circuit making current	119
6.104.2.1	General	119
6.104.2.2	Test procedure	120
6.104.2.2.1	Three-phase tests	120
6.104.2.2.2	Single-phase tests	120
6.104.3	Short-circuit breaking current	121
6.104.4	DC component of short-circuit breaking current	121
6.104.5	Transient recovery voltage (TRV) for short-circuit breaking tests	122
6.104.5.1	General	122
6.104.5.2	Test-duties T100s and T100a	124
6.104.5.3	Test duty T60	124
6.104.5.4	Test duty T30	124
6.104.5.5	Test duty T10	125
6.104.5.6	Test-duties OP1 and OP2	125
6.104.6	Measurement of transient recovery voltage during test	125
6.104.7	Power frequency recovery voltage	132
6.105	Short-circuit test procedure	132
6.105.1	Time interval between tests	132
6.105.2	Application of auxiliary power to the opening release – Breaking tests	133
6.105.3	Application of auxiliary power to the opening release – Make-break tests	133
6.105.4	Latching on short-circuit	133
6.106	Basic short-circuit test-duties	133
6.106.1	Test-duty T10	134
6.106.2	Test-duty T30	134
6.106.3	Test-duty T60	134
6.106.4	Test-duty T100s	134
6.106.4.1	Time constant of the d.c. component of the test circuit equal to the specified value	135

6.106.4.2	Time constant of the d.c. component of the test circuit less than the specified value	135
6.106.4.3	Time constant of the d.c. component of the test circuit greater than the specified value	136
6.106.4.4	Significant decay of the a.c. component of the test circuit	136
6.106.5	Test-duty T100a	137
6.106.6	Asymmetry criteria	138
6.106.6.1	Three-phase tests	139
6.106.6.1.1	Test current amplitude and last current loop duration	139
6.106.6.1.2	Percentage of d.c. component at current zero	139
6.106.6.2	Single-phase tests	139
6.106.6.2.1	Test current amplitude and last current loop duration	139
6.106.6.2.2	Percentage of the d.c. component at current zero	140
6.106.6.3	Adjustment measures	140
6.107	Critical current tests	140
6.107.1	Applicability	140
6.107.2	Test current	141
6.107.3	Critical current test-duty	141
6.108	Single-phase and double-earth fault tests	141
6.108.1	Applicability	141
6.108.2	Test current and recovery voltage	142
6.108.3	Test-duty	142
6.109	Short-line fault tests	143
6.109.1	Applicability	143
6.109.2	Test current	143
6.109.3	Test circuit	144
6.109.4	Test-duties	146
6.109.5	Short-line fault tests with a test supply of limited power	146
6.110	Out-of-phase making and breaking tests	147
6.110.1	Test circuit	147
6.110.2	Test voltage	147
6.110.3	Test-duties	147
6.111	Capacitive current switching tests	148
6.111.1	Applicability	148
6.111.2	General	148
6.111.3	Characteristics of supply circuits	149
6.111.4	Earthing of the supply circuit	149
6.111.5	Characteristics of the capacitive circuit to be switched	150
6.111.5.1	Line-charging and cable-charging current switching tests	150
6.111.5.2	Capacitor bank current switching tests	151
6.111.6	Waveform of the current	151
6.111.7	Test voltage	151
6.111.8	Test current	152
6.111.9	Test-duties	152
6.111.9.1	Test conditions for class C2 circuit-breakers	153
6.111.9.1.1	Class C2 test-duties	153
6.111.9.1.2	Three-phase line-charging and cable-charging current switching tests	156
6.111.9.1.3	Single-phase line-charging and cable-charging current switching tests	156

6.111.9.1.4	Three-phase capacitor bank (single or back-to-back) current switching tests	156
6.111.9.1.5	Single-phase capacitor bank (single or back-to-back) current switching tests	157
6.111.9.2	Test conditions for class C1 circuit-breakers	158
6.111.9.2.1	Class C1 test-duties	158
6.111.9.2.2	Single-phase and three-phase capacitive current switching tests	160
6.111.9.3	Test conditions corresponding to breaking in the presence of earth faults	160
6.111.10	Tests with specified TRV	161
6.111.11	Criteria to pass the test	161
6.111.11.1	General	161
6.111.11.2	Class C2 circuit-breaker	162
6.111.11.3	Class C1 circuit-breaker	162
6.111.11.4	Criteria for reclassification of a circuit-breaker tested to the class C2 requirements as a class C1 circuit-breaker	162
6.112	Special requirements for making and breaking tests on class E2 circuit-breakers	163
6.112.1	Class E2 circuit-breakers intended for use without auto-reclosing duty	163
6.112.2	Class E2 circuit-breakers intended for auto-reclosing duty	163
7	Routine tests	164
7.1	Dielectric test on the main circuit	164
7.2	Tests on auxiliary and control circuits	165
7.3	Measurement of the resistance of the main circuit	165
7.4	Tightness test	165
7.5	Design and visual checks	165
7.101	Mechanical operating tests	165
8	Guidance to the selection of circuit-breakers for service	167
8.101	General	167
8.102	Selection of rated values for service conditions	168
8.102.1	Selection of rated voltage	168
8.102.2	Insulation coordination	169
8.102.3	Rated frequency	169
8.102.4	Selection of rated normal current	169
8.102.5	Local atmospheric and climatic conditions	169
8.102.6	Use at high altitudes	170
8.103	Selection of rated values for fault conditions	170
8.103.1	Selection of rated short-circuit breaking current	170
8.103.2	Selection of transient recovery voltage (TRV) for terminal faults, first-pole-to-clear factor and characteristics for short-line faults	172
8.103.3	Selection of out-of-phase characteristics	173
8.103.4	Selection of rated short-circuit making current	173
8.103.5	Operating sequence in service	174
8.103.6	Selection of rated duration of short-circuit	174
8.103.7	Faults in the presence of current limiting reactors	174
8.104	Selection for electrical endurance in networks of rated voltage above 1 kV and up to and including 52 kV	175
8.105	Selection for capacitive current switching	175
9	Information to be given with enquiries, tenders and orders	175

9.101	Information to be given with enquiries and orders	175
9.102	Information to be given with tenders	177
10	Rules for transport, storage, installation, operation and maintenance	178
10.1	Conditions during transport, storage and installation.....	178
10.2	Installation.....	179
10.2.101	Commissioning tests.....	179
10.2.102	Commissioning checks and test programme	179
10.2.102.1	Checks after installation	179
10.2.102.1.1	General checks	179
10.2.102.1.2	Checks of electrical circuits	180
10.2.102.1.3	Checks of the insulation and/or extinguishing fluid(s)	180
10.2.102.1.4	Checks on operating fluid(s), where filled or added to on site	180
10.2.102.1.5	Site operations	180
10.2.102.2	Mechanical tests and measurements	180
10.2.102.2.1	Measurements of the characteristic insulating and/or interrupting fluid pressures (where applicable)	180
10.2.102.2.1.1	General	180
10.2.102.2.1.2	Measurements to be taken.....	180
10.2.102.2.2	Measurements of characteristic operating fluid pressures (if applicable)	181
10.2.102.2.2.1	General	181
10.2.102.2.2.2	Measurements to be taken.....	181
10.2.102.2.3	Measurement of consumption during operations (if applicable).....	181
10.2.102.2.4	Verification of the rated operating sequence.....	182
10.2.102.2.5	Measurement of time quantities	182
10.2.102.2.5.1	Characteristic time quantities of the circuit-breaker.....	182
10.2.102.2.6	Record of mechanical travel characteristics	183
10.2.102.2.7	Checks of certain specific operations	183
10.2.102.2.7.1	Auto-reclosing at the minimum functional pressure for operation (if applicable).....	183
10.2.102.2.7.2	Closing at the minimum functional pressure for operation (if applicable)	183
10.2.102.2.7.3	Opening at the minimum functional pressure for operation (if applicable)	183
10.2.102.2.7.4	Simulation of fault-making operation and check of anti- pumping device	184
10.2.102.2.7.5	Behaviour of the circuit-breaker on a closing command while an opening command is already present.....	184
10.2.102.2.7.6	Application of an opening command on both releases simultaneously (if applicable)	184
10.2.102.3	Electrical tests and measurements	184
10.2.102.3.1	Dielectric tests.....	184
10.2.102.3.2	Measurement of the resistance of the main circuit	184
10.3	Operation	185
10.4	Maintenance	185
11	Safety.....	185
12	Influence of the product on the environment	185
Annex A	(normative) Calculation of transient recovery voltages for short-line faults from rated characteristics	240
A.1	Basic approach.....	240

A.2	Transient voltage on line side	242
A.3	Transient voltage on source side	242
A.3.1	Rated voltages of 100 kV and above	242
A.3.2	Rated voltages equal and higher than 15 kV and below 100 kV	244
A.4	Examples of calculations	244
A.4.1	Source side and line side with time delay (L_{90} and L_{75} for 245 kV, 50 kA, 50 Hz)	245
A.4.2	Source side with ITRV, line side with time delay (L_{90} for 245 kV, 50 kA, 50 Hz)	246
A.4.3	Source side with time delay, line side without time delay (L_{90} for 245 kV, 50 kA, 50 Hz) – Calculation carried out using a simplified method	246
Annex B	(normative) Tolerances on test quantities during type tests	249
Annex C	(normative) Records and reports of type tests	256
C.1	Information and results to be recorded	256
C.2	Information to be included in type test reports	256
C.2.1	General	256
C.2.2	Apparatus tested	256
C.2.3	Rated characteristics of circuit-breaker, including its operating devices and auxiliary equipment	256
C.2.4	Test conditions (for each series of tests)	257
C.2.5	Short-circuit making and breaking tests	257
C.2.6	Short-time withstand current test	258
C.2.7	No-load operation	258
C.2.8	Out-of-phase making and breaking tests	258
C.2.9	Capacitive current switching tests	258
C.2.10	Oscillographic and other records	259
Annex D	(normative) Determination of short-circuit power factor	260
D.1	Method I – Calculation from d.c. component	260
D.1.1	Equation for the d.c. component	260
D.1.2	Phase angle φ	260
D.2	Method II – Determination with pilot generator	260
Annex E	(normative) Method of drawing the envelope of the prospective transient recovery voltage of a circuit and determining the representative parameters	262
E.1	Introduction	262
E.2	Drawing the envelope	262
E.3	Determination of parameters	263
Annex F	(normative) Methods of determining prospective transient recovery voltage waves	266
F.1	Introduction	266
F.2	General summary of the recommended methods	267
F.3	Detailed consideration of the recommended methods	268
F.3.1	Group 1 – Direct short-circuit breaking	268
F.3.2	Group 2 – Power-frequency current injection	269
F.3.3	Group 3 – Capacitor current injection	270
F.3.4	Groups 2 and 3 – Methods of calibration	270
F.3.5	Group 4 – Model networks	271
F.3.6	Group 5 – Calculation from circuit parameters	272
F.3.7	Group 6 – No-load switching of test circuits including transformers	272

F.3.8 Group 7 – Combination of different methods.....	272
F.4 Comparison of methods.....	272
Annex G (normative) Rationale behind introduction of circuit-breakers class E2	282
Annex H (informative) Inrush currents of single and back-to-back capacitor banks.....	283
H.1 General	283
H.2 Example 1 – One capacitor to be switched in parallel (see Figure H.1).....	284
H.2.1 Description of the capacitor banks to be switched.....	284
H.2.2 Calculation without any limitation device.....	284
H.2.3 Calculation of limitation devices.....	284
H.3 Example 2 – Two capacitors to be switched in parallel (see Figure H.2).....	285
H.3.1 Description of the capacitor banks to be switched.....	285
H.3.2 Calculation without any limitation device.....	285
H.3.3 Calculation of limitation devices.....	286
Annex I (informative) Explanatory notes.....	288
I.1 General	288
I.2 Explanatory note regarding the d.c. time constant of the rated short-circuit breaking current (4.101.2) – Advice for the choice of the appropriate time constant.....	288
I.2.1 Advice for the choice of the appropriate time constant.....	288
I.2.2 DC component during T100a testing.....	288
I.3 Explanatory note regarding capacitive current switching tests (6.111).....	290
I.3.1 Restrike performance.....	290
I.3.2 Test programme	290
I.3.3 Referring to Table 9.....	290
I.3.4 Referring to 6.111.1.....	290
I.3.5 Referring to 6.111.3.....	290
I.3.6 Referring to 6.111.5.....	291
I.3.7 Referring to 6.111.9.1.1.....	291
I.3.8 Referring to 6.111.9.1.1 and 6.111.9.2.1.....	291
I.3.9 Referring to 6.111.9.1.2 and 6.111.9.1.3.....	291
I.3.10 Referring to 6.111.9.1.2 to 6.111.9.1.5.....	291
I.3.11 Referring to 6.111.9.1.4 and 6.111.9.1.5.....	292
I.3.12 Referring to 6.111.9.2.....	292
Annex J (informative) Test current and line length tolerances for short-line fault testing.....	293
Annex K (informative) List of symbols and abbreviations used in this standard	295
Annex L (informative) Explanatory notes on the revision of TRVs for circuit-breakers of rated voltages higher than 1 kV and less than 100 kV.....	301
L.1 General	301
L.2 Terminal fault	301
L.2.1 TRV for circuit-breakers in line systems.....	301
L.2.2 Time delay.....	302
L.2.3 Amplitude factor for T100s and T100a	302
L.2.4 Amplitude factor for T60, T30 and T10.....	302
L.3 Short-line fault.....	303
L.4 Out-of-phase	303
L.5 Series reactor fault.....	303
L.6 TRV for last clearing poles / Tests circuit topology	304

Annex M (normative) Requirements for breaking of transformer-limited faults by circuit-breakers with rated voltage higher than 1 kV and less than 100 kV	305
Annex N (normative) Use of mechanical characteristics and related requirements	308
Annex O (informative) Guidance for short-circuit and switching test procedures for metal-enclosed and dead tank circuit-breakers	310
O.1 Introduction	310
O.2 General	310
O.2.1 Special features of metal-enclosed circuit-breakers with respect to making and breaking tests	310
O.2.2 Reduced number of units for testing purposes	310
O.2.3 General description of special features and possible interactions	311
O.3 Tests for single pole in one enclosure	312
O.3.1 Short-circuit making and breaking tests	312
O.3.2 Short-line fault tests	314
O.3.3 Capacitive current switching tests	314
O.3.4 Out-of-phase switching	316
O.4 Tests for three poles in one enclosure	317
O.4.1 Terminal fault tests	317
O.4.2 Short-line fault tests	319
O.4.3 Capacitive current switching tests	319
O.4.4 Out-of-phase switching test	319
Annex P (normative) Calculation of the TRV parameters during asymmetrical fault condition (T100a)	322
Annex Q (informative) Examples for the application of the asymmetry criteria during asymmetrical test-duty T100a	327
Q.1 Three-phase testing of a circuit-breaker with a rated d.c. time constant of the rated short-circuit breaking current constant longer than the test circuit time constant	327
Q.2 Single phase testing of a circuit-breaker with a rated d.c. time constant of the rated short-circuit breaking current shorter than the test circuit time constant	329
Q.3 Single-phase testing of a circuit-breaker with a rated d.c. time constant of the rated short-circuit breaking current longer than the test circuit time constant	330
Bibliography	335
Figure 1 – Typical oscillogram of a three-phase short-circuit make-break cycle	186
Figure 2 – Circuit-breaker without switching resistors. Opening and closing operations	188
Figure 3 – Circuit breaker without switching resistors – Close-open cycle	189
Figure 4 – Circuit-breaker without switching resistors – Reclosing (auto-reclosing)	190
Figure 5 – Circuit-breaker with switching resistors. Opening and closing operations	191
Figure 6 – Circuit-breaker with switching resistors – Close-open cycle	192
Figure 7 – Circuit-breaker with switching resistors – Reclosing (auto-reclosing)	193
Figure 8 – Determination of short-circuit making and breaking currents, and of percentage d.c. component	194
Figure 9 – Percentage d.c. component in relation to the time interval from the initiation of the short-circuit for the standard time constant τ_1 and for the special case time constants τ_2 , τ_3 and τ_4	195
Figure 10 – Representation of a specified four-parameter TRV and a delay line for T100, T60, short-line fault and out-of-phase condition	196

Figure 11 – Representation of a specified TRV by a two-parameter reference line and a delay line	197
Figure 12a – Basic circuit for terminal fault with ITRV	198
Figure 12b – Representation of ITRV in relationship to TRV	198
Figure 13 – Three-phase short-circuit representation	199
Figure 14 – Alternative representation of Figure 13	200
Figure 15 – Basic short-line fault circuit	201
Figure 16 – Example of a line-side transient voltage with time delay and rounded crest showing construction to derive the values u_{L^*} , t_L and t_{dL}	201
Figure 17 – Test sequences for low and high temperature tests	202
Figure 18 – Humidity test	203
Figure 19 – Static terminal load forces	204
Figure 20 – Directions for static terminal load tests	205
Figure 21 – Permitted number of samples for making, breaking and switching tests, illustrations of the statements in 6.102.2	206
Figure 22 – Definition of a single test specimen in accordance with 3.2.2 of IEC 62271-1	207
Figure 23a – Reference mechanical travel characteristics (idealised curve)	208
Figure 23b – Reference mechanical travel characteristics (idealised curve) with the prescribed envelopes centered over the reference curve (+5 %, –5 %), contact separation in this example at time $t = 20$ ms	208
Figure 23c – Reference mechanical travel characteristics (idealised curve) with the prescribed envelopes fully displaced upward from the reference curve (+10 %, –0 %), contact separation in this example at time $t = 20$ ms	209
Figure 23d – Reference mechanical travel characteristics (idealised curve) with the prescribed envelopes fully displaced downward from the reference curve (+0 %, –10 %), contact separation in this example at time $t = 20$ ms	209
Figure 24 – Equivalent testing set-up for unit testing of circuit-breakers with more than one separate interrupter units	210
Figure 25a – Preferred circuit	211
Figure 25b – Alternative circuit	211
Figure 25 – Earthing of test circuits for three-phase short-circuit tests, first-pole-to-clear factor 1,5	211
Figure 26a – Preferred circuit	212
Figure 26b – Alternative circuit	212
Figure 26 – Earthing of test circuits for three-phase short-circuit tests, first-pole-to-clear factor 1,3	212
Figure 27a – Preferred circuit	213
Figure 27b – Alternative circuit not applicable for circuit-breakers where the insulation between phases and/or to earth is critical (e.g. GIS or dead tank circuit-breakers)	213
Figure 27 – Earthing of test circuits for single-phase short-circuit tests, first-pole-to-clear factor 1,5	213
Figure 28a – Preferred circuit	214
Figure 28b – Alternative circuit, not applicable for circuit-breakers where the insulation between phases and/or to earth is critical (e.g. GIS or dead tank circuit-breakers)	214
Figure 28 – Earthing of test circuits for single-phase short-circuit tests, first-pole-to-clear factor 1,3	214
Figure 29 – Graphical representation of the three valid symmetrical breaking operations for three-phase tests in a non-effectively earthed neutral system (first-pole-to-clear factor 1,5)	215