

INTERNATIONAL STANDARD

IEC 60335-2-68

2002

AMENDMENT 1
2005-10

Amendment 1

**Household and similar electrical appliances –
Safety –**

**Part 2-68:
Particular requirements for spray extraction
appliances, for industrial and commercial use**

<https://standards.iteh.ai/catalog/standards/iec/b8cd2378-7203-47ac-92a7-5b4108aeb1db/iec-60335-2-68-2002-amd1-2005>

© IEC 2005 Droits de reproduction réservés — Copyright - all rights reserved

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

L

For price, see current catalogue

FOREWORD

This amendment has been prepared by subcommittee 61J: Electrical motor-operated cleaning appliances for industrial use, of IEC technical committee 61: Safety of household and similar electrical appliances.

The text of this amendment is based on the following documents:

FDIS	Report on voting
61J/197/FDIS	61J/210/RVD

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this amendment and the base publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

CONTENTS

Add, in the list of figures, the titles of the new Figures 102 to 105 as follows:

Figure 102 – Apparatus for testing the abrasion resistance of current-carrying hoses

Figure 103 – Apparatus for testing the resistance to flexing of current-carrying hoses

Figure 104 – Configuration of the hose for the freezing treatment

Figure 105 – Flexing positions for the hose after removal from the freezing cabinet

FOREWORD

Add to the list of differences existing in some countries the following new item:

- 7.12: No requirements for sound marking exist (USA).

INTRODUCTION

Replace the second sentence of the second paragraph by the following:

It also covers abnormal situations that can be expected in practice and takes into account the way in which electromagnetic phenomena can affect the safe operation of appliances.

2 Normative references

Add the following references:

IEC 60704-2-1, *Household and similar electrical appliances – Test code for the determination of airborne acoustical noise – Part 2-1: Particular requirements for vacuum cleaners*

ISO 6344-2, *Coated abrasives – Grain size analysis – Part 2: Determination of grain size distribution of macrogrits P12 to P220*

3 Definitions

3.1.9 Add, after the 1st paragraph, the following new paragraph:

Power outlets for accessories are loaded with a resistive load in accordance with the marking.

Add the following new definitions:

3.108

water-suction cleaning appliance

appliance for aspirating an aqueous solution that may contain foaming detergent

3.109

motorized cleaning head

accessory containing a motor that is supplied from the appliance and which is attached to the end of a hand-held hose or tube

NOTE The main cleaning head permanently attached is not regarded as a **motorized cleaning head**.

7 Marking and instructions

7.1 Add the following note:

NOTE The use of bar on the nameplate to designate the maximum rated operating pressure is allowed

Add the following subclause:

7.6 Addition:



[symbol IEC 60417-5935 (DB:2002-10)]

motorized cleaning head
for water-suction cleaning

7.12 Replace the existing text by the following new text:

Addition:

The front cover of the instruction manual shall include the substance of the following:

CAUTION Read the instruction manual before using the appliance.

This wording may be replaced by symbols ISO 7000-0434 (DB:2004-01) and ISO 7000-1641 (DB 2004-01). If these symbols are used, their meaning is to be explained in the instructions for use.

The instruction manual shall give details regarding the following, as applicable:

- the precautions to be taken when using the appliance under specific conditions such as handling flammable liquids or dust, and dust hazardous to health;
- a statement that the appliance is to be disconnected from its power source during cleaning or maintenance and when replacing parts or converting the appliance to another function,
 - for mains operated appliances, the plug is to be removed from the socket-outlet,
 - for battery operated appliances, the key of the supply switch is to be removed or an equivalent disconnection is to be made;

The instruction manual shall state the A-weighted sound pressure level L_{PA} in dB(A) emitted by the appliance, measured in accordance with IEC 60704-2-1. If the A-weighted sound pressure level exceeds 85 dB(A), it shall also state the sound power level L_{WA} in dB(A) and that appropriate ear protection has to be used.

The instruction manual shall include the substance of the following:

This appliance is suitable for commercial use, for example in hotels, schools, hospitals, factories, shops, offices and rental businesses.

The instruction manual for mains operated appliances shall include the substance of the following:

- do not allow the rotating brushes to come into contact with the supply cord;
- regularly examine the supply cord for damage, such as cracking or ageing. If damage is found, replace the cord before further use;
- only replace the supply cord with the type specified in the instruction manual;
- only use the socket outlet on the appliance for purposes specified in the instruction manual.

The instruction manual shall state the substance of the following:

- CAUTION If foam or liquid escapes from the appliance, switch off immediately;
- regularly clean the water level limiting device in accordance with the instructions and examine it for signs of damage.

If the symbol specified in 7.6, indicating that the **motorized cleaning head** can be used for water suction, is marked on the appliance its meaning shall be explained.

The instructions for appliances having a current-carrying hose operating at other than **safety extra-low voltage** shall include the substance of the following:

CAUTION: This hose contains electrical connections:

- do not use to collect water;
- do not immerse in water for cleaning;
- the hose should be checked regularly and must not be used if damaged.

If symbol IEC 60417-5935 (DB:2002-10) is used, its meaning shall be explained.

Add the following subclauses:

7.14 Addition:

The height of symbol IEC 60417-5935 shall be at least 15 mm.

Compliance is checked by measurement.

7.101 Motorized cleaning heads shall be marked with

- **rated voltage** or **rated voltage range** in volts;
- **rated power input** in watts;
- name, trade mark or identification mark of the manufacturer or responsible vendor;
- model or type reference.

Motorized cleaning heads for water-suction cleaning appliances, except those of **class III construction** having a working voltage up to 24 V shall be marked with symbol IEC 60417-5935.

NOTE This symbol is an information sign and, except for the colours, the rules of ISO 3864-1 apply.

Compliance is checked by inspection.

7.102 Appliance outlets for accessories shall be marked with the maximum load in watts.

NOTE This marking may be on the appliance close to the appliance outlet.

Compliance is checked by inspection.

10 Power input and current

Replace the existing text by the following:

This clause of Part 1 is applicable except as follows.

10.1 Addition:

The power input of **motorized cleaning heads** is measured separately.

15 Moisture resistance

15.2 *Replace the existing text after Note 101 by the following new text:*

*Nozzles and **motorized cleaning heads of water-suction cleaning appliances** are placed in a container, the base of which is level with the surface supporting the appliance. The container is filled with a detergent solution to a level of 5 mm above its base, this level being maintained throughout the test.*

The solution consists of 20 g of NaCl and 1 ml of a solution of 28 % by mass of dodecyl sodium sulphate in each 8 l of water.

The appliance is operated until its liquid container is completely full and for a further 5 min.

NOTE 102 The solution is to be stored in a cool atmosphere and used within seven days of its preparation.

NOTE 103 The chemical designation of dodecyl sodium sulphate is C₁₂H₂₅NaSO₄.

NOTE 104 If it is not possible to overfill the container for soiled liquid owing to the construction of the appliance, the test specified in 19.101 is considered to be adequate.

After each of these tests, the appliance shall withstand the electric strength test of 16.3.

*Inspection shall show that there is no trace of liquid on insulation that could result in a reduction of **clearances** or **creepage distances** below the values specified in Clause 29.*

NOTE 105 The appliance is allowed to stand in normal test room atmosphere for 24h before being subjected to the test of 15.3

Add the following subclause:

15.101 Motorized cleaning heads of water suction cleaning appliances shall be resistant to liquids that may come into contact with them.

Compliance is checked by the following tests.

The **motorized cleaning head** is subjected to an impact test as described in IEC 60068-2-75, the value of the impact being 2 J. The **motorized cleaning head** is rigidly supported and three blows are applied to every point of the enclosure that is likely to be weak.

It is then subjected to the free fall test procedure 1 of IEC 60068-2-32. It is dropped 4 000 times from a height of 100 mm onto a steel plate having a thickness of not less than 15 mm. It is dropped

- 1 000 times on its right side;
- 1 000 times on its left side;
- 1 000 times on its front face;
- 1 000 times on its cleaning surface.

The **motorized cleaning head** is then subjected to the test described in 14.2.7 of IEC 60529, the water containing approximately 1% NaCl.

The **motorized cleaning head** shall then withstand the electric strength test of 16.3, the voltage being applied between the **live parts** and the solution, and inspection shall show that there is no trace of saline solution on insulation which could result in a reduction of **clearances and creepage distances** below the values specified in Clause 29.

NOTE The test is not carried out on **motorized cleaning heads** of class III construction having a working voltage up to 24 V.

16 Leakage current and electric strength

Replace the existing text by the following:

This clause of Part 1 is applicable except as follows.

16.3 Addition:

Current-carrying hoses, except for their electrical connections, are immersed for 1 h in water containing approximately 1 % NaCl, at a temperature of 20 °C ± 5 °C. While the hose is still immersed, a voltage of 2 000 V is applied for 5 min between each conductor and all the other conductors connected together. A voltage of 3 000 V is then applied for 1 min between all the conductors and the saline solution.

19 Abnormal operation

19.7 Replace the last sentence of the addition by:

Motorized cleaning heads are tested with the rotating brush or similar device locked for 30 s.