

Edition 2.1 2010-09

# INTERNATIONAL STANDARD





# THIS PUBLICATION IS COPYRIGHT PROTECTED

# Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IFC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch

Web: www.iec.ch

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

# **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published

Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

IEC Just Published: www.iec.ch/online news/justpub/

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivarent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

■ Customer Service Sentre: www.iec.ch/webstore/custserv

If you wish to give us you feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us

Email: csc@iec.ch Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00

# A propos de la CEV

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'èlectricité, à l'électronique et aux technologies apparentées.

# A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

■ Catalogue des publications de la CEI: www.iec.ch/searchpub/cur\_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

Just Published CEI: www.iec.ch/online\_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

Service Clients: www.iec.ch/webstore/custserv/custserv\_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch Tél.: +41 22 919 02 11 Fax: +41 22 919 03 00



Edition 2.1 2010-09

colour

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



PUBLICATION FONDAMENTALE DE SÉCURITÉ

Fire hazard testing -

Part 6-1: Smoke obscuration - General guidance

Essais relatifs aux risques du feu -

Partie 6-1: Opacité des fumées - Lignes directrices générales



INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 13.220.99; 29.020 ISBN 978-2-88912-122-9

# CONTENTS

1 Scope 2 Normative references. 3 Terms, definitions and symbols 3.1 Terms and definitions 3.2 Symbols 4 General aspects of smoke test methods 4.1 Fire scenarios and fire models 4.2 Factors affecting smoke production 5 Principles of smoke measurement 5.1 Bouguer's law 5.2 Extinction area 5.3 Log <sub>10</sub> units 5.4 Light sources 5.5 Specific extinction area 5.6 Mass optical density 5.7 Visibility 6 Static and dynamic methods 6.2 Dynamic methods 6.2 Dynamic methods 7.1 Consideration of teshmethods 7.2 Selection of test specimen 8 Presentation of data 9 Relevance of data to hazard assessment.  Annex A (informative) Calculation of visibility. Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography  Figure 1 — Chart of Different phases in the development of a fire within a compartment Figure 2 — Attenuation of light by smoke. Figure 3 — Extinction area Figure 5 — Evaluation and consideration of smoke test methods	FO	REWORD	4
2 Normative references  3 Terms, definitions and symbols 3.1 Terms and definitions 3.2 Symbols 4 General aspects of smoke test methods 4.1 Fire scenarios and fire models 4.2 Factors affecting smoke production 5 Principles of smoke measurement 5.1 Bouguer's law 5.2 Extinction area 5.3 Log <sub>10</sub> units 5.4 Light sources 5.5 Specific extinction area 5.6 Mass optical density 5.7 Visibility 6 Static and dynamic methods 6.1 Static methods 6.2 Dynamic methods 7.1 Consideration of test specimen 8 Presentation of data 9 Relevance of data to hazard assessment  Annex A (informative) Relationships between D <sub>S</sub> and some other smoke parameters at measured in IEC 60695-6-30 and IEC 60695-6-31  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke Figure 3 – Extinction area Figure 4 – Dynamic smoke measurement Figure 5 – Evaluation and consideration of smoke test methods	INT	FRODUCTION	6
2 Normative references  3 Terms, definitions and symbols 3.1 Terms and definitions 3.2 Symbols 4 General aspects of smoke test methods 4.1 Fire scenarios and fire models 4.2 Factors affecting smoke production 5 Principles of smoke measurement 5.1 Bouguer's law 5.2 Extinction area 5.3 Log <sub>10</sub> units 5.4 Light sources 5.5 Specific extinction area 5.6 Mass optical density 5.7 Visibility 6 Static and dynamic methods 6.1 Static methods 6.2 Dynamic methods 7.1 Consideration of test specimen 8 Presentation of data 9 Relevance of data to hazard assessment  Annex A (informative) Relationships between D <sub>S</sub> and some other smoke parameters at measured in IEC 60695-6-30 and IEC 60695-6-31  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke Figure 3 – Extinction area Figure 4 – Dynamic smoke measurement Figure 5 – Evaluation and consideration of smoke test methods			
3.1 Terms and definitions 3.2 Symbols 4 General aspects of smoke test methods. 4.1 Fire scenarios and fire models 4.2 Factors affecting smoke production. 5 Principles of smoke measurement. 5.1 Bouguer's law. 5.2 Extinction area 5.3 Log <sub>10</sub> units 5.4 Light sources. 5.5 Specific extinction area. 5.6 Mass optical density 5.7 Visibility. 6 Static and dynamic methods 6.1 Static methods. 6.2 Dynamic methods. 7 Test methods. 7.1 Consideration of testmethods. 7.2 Selection of test specimen. 8 Presentation of data to hazard assessment  Annex A (informative) Calculation of visibility. Annex B (informative) Relationships between P <sub>3</sub> and some other smoke parameters at measured in IEC 60695-6-30 and IEC 60695-6-31. Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography.  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke. Figure 3 – Extinction area. Figure 4 – Dynamic smoke measurement. Figure 5 – Evaluation and consideration of smoke test methods.	1	Scope	7
3.1 Terms and definitions 3.2 Symbols 4 General aspects of smoke test methods. 4.1 Fire scenarios and fire models 4.2 Factors affecting smoke production. 5 Principles of smoke measurement. 5.1 Bouguer's law. 5.2 Extinction area. 5.3 Log <sub>10</sub> units 5.4 Light sources 5.5 Specific extinction area. 5.6 Mass optical density. 5.7 Visibility. 6 Static and dynamic methods 6.1 Static methods. 6.2 Dynamic methods. 6.3 Dynamic methods. 7 Test methods. 7.1 Consideration of test methods. 7.2 Selection of test specimen. 8 Presentation of data. 9 Relevance of data to hazard assessment  Annex A (informative) Relationships between D <sub>S</sub> and some other smoke parameters at measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography.  Figure 1 - Chart of Different phases in the development of a fire within a compartment Figure 2 - Attenuation of light by smoke. Figure 3 - Extinction area.  Figure 4 - Dynamic smoke measurement. Figure 5 - Evaluation and consideration of smoke test methods	2	Normative references	7
3.2 Symbols  4 General aspects of smoke test methods. 4.1 Fire scenarios and fire models 4.2 Factors affecting smoke production.  5 Principles of smoke measurement. 5.1 Bouguer's law. 5.2 Extinction area. 5.3 Log <sub>10</sub> units 5.4 Light sources 5.5 Specific extinction area 5.6 Mass optical density. 5.7 Visibility. 6 Static and dynamic methods 6.1 Static methods. 6.2 Dynamic methods. 7 Test methods. 7.1 Consideration of test methods. 7.1 Consideration of test methods. 9 Relevance of data to hazard assessment.  Annex A (informative) Calculation of visibility. Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters at measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography.  Figure 1 - Chart of Different phases in the development of a fire within a compartment Figure 2 - Attenuation of light by smoke.  Figure 3 - Extinction area Figure 4 - Dynamic smoke measurement Figure 5 - Evaluation and consideration of smoke test methods.	3	Terms, definitions and symbols	8
3.2 Symbols  4 General aspects of smoke test methods. 4.1 Fire scenarios and fire models 4.2 Factors affecting smoke production.  5 Principles of smoke measurement. 5.1 Bouguer's law. 5.2 Extinction area. 5.3 Log <sub>10</sub> units 5.4 Light sources 5.5 Specific extinction area 5.6 Mass optical density. 5.7 Visibility. 6 Static and dynamic methods 6.1 Static methods. 6.2 Dynamic methods. 7 Test methods. 7.1 Consideration of test methods. 7.1 Consideration of test methods. 9 Relevance of data to hazard assessment.  Annex A (informative) Calculation of visibility. Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters at measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography.  Figure 1 - Chart of Different phases in the development of a fire within a compartment Figure 2 - Attenuation of light by smoke.  Figure 3 - Extinction area Figure 4 - Dynamic smoke measurement Figure 5 - Evaluation and consideration of smoke test methods.		3.1 Terms and definitions	8
4.1 Fire scenarios and fire models 4.2 Factors affecting smoke production 5 Principles of smoke measurement. 5.1 Bouguer's law 5.2 Extinction area. 5.3 Log <sub>10</sub> units 5.4 Light sources. 5.5 Specific extinction area 5.6 Mass optical density 5.7 Visibility. 6 Static and dynamic methods 6.1 Static methods. 6.2 Dynamic methods. 7 Test methods. 7.1 Consideration of test methods. 7.1 Consideration of test methods. 8 Presentation of data. 9 Relevance of data to hazard assessment  Annex A (informative) Calculation of visibility. Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters at measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography.  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke. Figure 3 – Extinction area Figure 4 – Dynamic smoke measurement Figure 5 – Evaluation and consideration of smoke test methods		3.2 Symbols	16
4.2 Factors affecting smoke production.  5 Principles of smoke measurement.  5.1 Bouguer's law.  5.2 Extinction area.  5.3 Log <sub>10</sub> units.  5.4 Light sources.  5.5 Specific extinction area.  5.6 Mass optical density.  5.7 Visibility.  6 Static and dynamic methods.  6.1 Static methods.  6.2 Dynamic methods.  7.1 Consideration of test methods.  7.1 Consideration of test methods.  9 Relevance of data to hazard assessment.  Annex A (informative) Calculation of visibility.  Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography.  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke.  Figure 3 – Extinction area.  Figure 5 – Evaluation and consideration of smoke test methods.	4	General aspects of smoke test methods	17
4.2 Factors affecting smoke production.  5 Principles of smoke measurement.  5.1 Bouguer's law.  5.2 Extinction area.  5.3 Log <sub>10</sub> units.  5.4 Light sources.  5.5 Specific extinction area.  5.6 Mass optical density.  5.7 Visibility.  6 Static and dynamic methods.  6.1 Static methods.  6.2 Dynamic methods.  7.1 Consideration of test methods.  7.1 Consideration of test methods.  9 Relevance of data to hazard assessment.  Annex A (informative) Calculation of visibility.  Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography.  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke.  Figure 3 – Extinction area.  Figure 5 – Evaluation and consideration of smoke test methods.		4.1 Fire scenarios and fire models	17
5.1 Bouguer's law.  5.2 Extinction area.  5.3 Log <sub>10</sub> units  5.4 Light sources.  5.5 Specific extinction area.  5.6 Mass optical density.  5.7 Visibility.  6 Static and dynamic methods.  6.1 Static methods.  6.2 Dynamic methods.  7.1 Consideration of test specimen.  8 Presentation of data.  9 Relevance of data to hazard assessment.  Annex A (informative) Relationships between D <sub>S</sub> and some other smoke parameters at measured in IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography.  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke.  Figure 3 – Extinction area.  Figure 4 – Dynamic smoke measurement.  Figure 5 – Evaluation and consideration of smoke test methods.		4.2 Factors affecting smoke production	21
5.2 Extinction area  5.3 Log <sub>10</sub> units  5.4 Light sources  5.5 Specific extinction area  5.6 Mass optical density  5.7 Visibility.  6 Static and dynamic methods  6.1 Static methods  6.2 Dynamic methods  7.1 Consideration of test methods  7.1 Consideration of test methods  7.2 Selection of test specimen  8 Presentation of data  9 Relevance of data to hazard assessment  Annex A (informative) Relationships between D <sub>S</sub> and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement.  Figure 5 – Evaluation and consideration of smoke test methods	5		22
5.3 Log <sub>10</sub> units 5.4 Light sources 5.5 Specific extinction area		5.1 Bouguer's law	
5.4 Light sources 5.5 Specific extinction area. 5.6 Mass optical density 5.7 Visibility 6 Static and dynamic methods 6.1 Static methods 6.2 Dynamic methods 7 Test methods 7.1 Consideration of test methods 7.2 Selection of test specimen 8 Presentation of data. 9 Relevance of data to hazard assessment  Annex A (informative) Calculation of visibility.  Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography.  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke. Figure 3 – Extinction area Figure 4 – Dynamic smoke measurement Figure 5 – Evaluation and consideration of smoke test methods		5.2 Extinction area	23
6 Static and dynamic methods 6.1 Static methods 6.2 Dynamic methods 7 Test methods 7.1 Consideration of test methods 7.2 Selection of test specimen 8 Presentation of data 9 Relevance of data to hazard assessment  Annex A (informative) Calculation of visibility Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters at measured in IEC 60695-6-30 and IEC 60695-6-31  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement Figure 5 – Evaluation and consideration of smoke test methods		5.3 Log <sub>10</sub> units	24
6 Static and dynamic methods 6.1 Static methods 6.2 Dynamic methods 7 Test methods 7.1 Consideration of test methods 7.2 Selection of test specimen 8 Presentation of data 9 Relevance of data to hazard assessment  Annex A (informative) Calculation of visibility Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters at measured in IEC 60695-6-30 and IEC 60695-6-31  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement Figure 5 – Evaluation and consideration of smoke test methods		5.4 Light sources	24
6 Static and dynamic methods 6.1 Static methods 6.2 Dynamic methods 7 Test methods 7.1 Consideration of test methods 7.2 Selection of test specimen 8 Presentation of data 9 Relevance of data to hazard assessment  Annex A (informative) Calculation of visibility Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters at measured in IEC 60695-6-30 and IEC 60695-6-31  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement Figure 5 – Evaluation and consideration of smoke test methods		5.5 Specific extinction area	24
6.2 Dynamic methods		5.6 Mass optical density	25 26
6.2 Dynamic methods	6	Static and dynamic methods	26
6.2 Dynamic methods	Ü	6.1 Static methods	26
7.1 Consideration of test methods		6.2 Dynamic methods	26
7.1 Consideration of test specimen  8 Presentation of data.  9 Relevance of data to hazard assessment  Annex A (informative) Calculation of visibility.  Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography.  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke.  Figure 3 – Extinction area.  Figure 4 – Dynamic smoke measurement.  Figure 5 – Evaluation and consideration of smoke test methods	7	Test methods.	28
8 Presentation of data. 9 Relevance of data to hazard assessment  Annex A (informative) Calculation of visibility.  Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography.  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke.  Figure 3 – Extinction area.  Figure 4 – Dynamic smoke measurement.  Figure 5 – Evaluation and consideration of smoke test methods.		7.1 Consideration of test methods.	32
8 Presentation of data. 9 Relevance of data to hazard assessment  Annex A (informative) Calculation of visibility.  Annex B (informative) Relationships between D <sub>S</sub> and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography.  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke.  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement.  Figure 5 – Evaluation and consideration of smoke test methods		17.2 Selection of test specimen 178,8760,49fd,9af7,36775758435a/iac.60695	321-2
Annex A (informative) Calculation of visibility  Annex B (informative) Relationships between $D_{\rm S}$ and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31.  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area.  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods	8	Presentation of data	32
Annex B (informative) Relationships between $D_{\rm S}$ and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods	9	Relevance of data to hazard assessment	33
Annex B (informative) Relationships between $D_{\rm S}$ and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods			
Annex B (informative) Relationships between $D_{\rm S}$ and some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods	Anr	nex A (informative) Calculation of visibility	35
measured in IEC 60695-6-30 and IEC 60695-6-31  Annex C (informative) Relationships between percent transmission, as measured in a "three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods			
"three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods	me	asured in IEC 60695-6-30 and IEC 60695-6-31	37
"three metre cube" enclosure, and extinction area  Bibliography  Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods	Anr	nex C (informative) Relationships between percent transmission, as measured in a	
Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods	"thr	ree metre cube" enclosure, and extinction area	40
Figure 1 – Chart of Different phases in the development of a fire within a compartment Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods			
Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods	Bib	liography	42
Figure 2 – Attenuation of light by smoke  Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods			
Figure 3 – Extinction area  Figure 4 – Dynamic smoke measurement  Figure 5 – Evaluation and consideration of smoke test methods	_		
Figure 4 – Dynamic smoke measurement	_		
Figure 5 – Evaluation and consideration of smoke test methods	_		
	Fig	ure 4 – Dynamic smoke measurement	27
Figure 6 – Example SPRav versus t curve	Fig	ure 5 – Evaluation and consideration of smoke test methods	34
	Fig	ure 6 – Example $SPR_{av}$ versus $t$ curve	31
Figure 7 – SMOGRA curve derived from Figure 6	Fig	ure 7 – SMOGRA curve derived from Figure 6	31

Figure A.1 – Visibility (ω) versus extinction coefficient (k)	35
Figure B.1 – Smoke parameters related to $D_{\rm S}$ as measured in IEC 60695-6-30 and IEC 60695-6-31	39
Figure C.1 – Extinction area (amount of smoke) related to percent transmission as measured in the "three metre cube"	41
Table 1 – General classification of fires (ISO/TR 9122-1) Characteristics of fire stages (ISO 19706)	18
Table B.1 – Conversion from $D_{\rm S}$ to some other smoke parameters as measured in IEC 60695-6-30 and IEC 60695-6-31	38
Table C.1 – Conversions from percent transmission, as measured in the "three metre cube" to amount of smoke (extinction area)	40
iTex Sandards (https://sandards.iteh.ai) Dycun em Preview /standards.iteh.ai vano is xe/dx its 78-8260-49fd-9ef7-3672b7b8435e/iee-60699	

# INTERNATIONAL ELECTROTECHNICAL COMMISSION

# FIRE HAZARD TESTING -

# Part 6-1: Smoke obscuration – General guidance

## **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attack to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of IEC 60695-6-1 consists of the second edition (2005) [documents 89/692/FDIS and 89/696/RVD] and its amendment 1 (2010) [documents 89/905/CDV and 89/946A/RVC]. It bears the edition number 2.1.

The technical content is therefore identical to the base edition and its amendment and has been prepared for user convenience. A vertical line in the margin shows where the base publication has been modified by amendment 1. Additions and deletions are displayed in red, with deletions being struck through.

International Standard IEC 60695-6-1 has been prepared by IEC technical committee 89: Fire hazard testing.

The main changes with respect to the previous edition are listed below:

- Modified title.
- Updated normative references.
- Expanded terms and definitions.
- Numerous editorial changes of a technical nature throughout the publication.
- A flowchart has been added for the evaluation and consideration of smoke test methods.

It has the status of a basic safety publication in accordance with IEC Guide 104 and ISO/IEC Guide 51.

This standard is to be used in conjunction with IEC 60695-6-2.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The IEC 60695-6 series, under the general heading Fire hazard testing, consists of the following parts

Part 6-1: Smoke obscuration – General guidance

Part 6-2: Smoke obscuration – Summary and relevance of test methods

Part 6-30: Smoke obscuration – Guidance and test methods on the assessment of obscuration hazard of vision caused by smoke opacity from electrotechnical products involved in fires – Small scale static method - Determination of smoke opacity - Description of the apparatus

Part 6-31: Smoke obscuration - Small-scale static test - Materials

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

# INTRODUCTION

The risk of fire needs to be considered in any electrical circuit, and the objective of component, circuit and equipment design, as well as the choice of material, is to reduce the likelihood of fire, even in the event of foreseeable abnormal use, malfunction or failure.

Electrotechnical products, primarily victims of a fire, may nevertheless contribute to the fire. One of the contributing hazards is the release of smoke, which may cause loss of vision and/or disorientation which could impede escape from the building or fire fighting.

Smoke particles reduce the visibility due to light absorption and scattering. Consequently, people may experience difficulties in finding exit signs, doors and windows. Visibility is often determined as the distance at which an object is no longer visible. It depends on many factors, but close relationships have been established between visibility and the measurements of the extinction coefficient of smoke – see Annex A.

The production of smoke and its optical properties can be measured as well as other fire properties, such as heat release, flame spread, and the production of toxic gas and corrosive effluent. This part of IEC 60695-6 serves as a guidance document and focuses on obscuration of light by smoke.

iTex Syntaxos
(https://scandx/dx.iteh.ai)

Dycument Preview

10 06 5-6-1:2005
standards.iteh.ai

tandards.iteh.ai

tandards.iteh.ai

tandards.iteh.ai

tandards.iteh.ai

tandards.iteh.ai

tandards.iteh.ai

tandards.iteh.ai

# FIRE HAZARD TESTING -

# Part 6-1: Smoke obscuration – General guidance

# 1 Scope

This part of IEC 60695 gives guidance on:

- a) optical measurement of smoke obscuration;
- b) general aspects of optical smoke test methods;
- c) consideration of test methods;
- d) expression of smoke test data;
- e) relevance of optical smoke data to hazard assessment.

One of the responsibilities of a technical committee is, wherever applicable, to make use of basic safety publications in the preparation of its publications.

# 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60695-1-1, Fire hazard testing - Part 1-1: Guidance for assessing the fire hazard of electrotechnical products. General guidelines

https://IEC 60695-4:2001, Fire hazard testing - Rart 4: Terminology concerning fire tests 1ec-60695-6-1-1005

IEC 60695-6-2:2001) Fire hazard testing - Part 6-2: Smoke obscuration - Summary and relevance of test methods

IEC 60695 6-30, Fire hazard testing — Part 6: Guidance and test methods on the assessment of obscuration hazard of vision caused by smoke opacity from electrotechnical products involved in fires — Section 30: Small-scale static method — Determination of smoke opacity — Description of the apparatus

IEC 60695-6-31, Fire hazard testing - Part 6-31: Smoke obscuration - Small-scale static test - Materials

IEC Guide 104:1997, The preparation of safety publications and the use of basic safety publications and group safety publications

ISO/TR 9122-1:1989. Toxicity testing of fire effluents - Part 1: General

ISO 5659-2:1994, Plastics - Smoke generation - Part 2: Determination of optical density by a single-chamber test

ISO/IEC 13943:2000, Fire safety - Vocabulary

ISO/IEC Guide 51:1999. Safety aspects - Guidelines for inclusion in standards

IEC 60695-1-10, Fire hazard testing – Part 1-10: Guidance for assessing the fire hazard of electrotechnical products – General guidelines

IEC 60695-1-11<sup>1</sup>, Fire hazard testing – Part 1-11: Guidance for assessing the fire hazard of electrotechnical products – Fire hazard assessment

IEC 60695-4:2005, Fire hazard testing – Part 4: Terminology concerning fire tests for electrotechnical products

IEC 60695-6-2<sup>2</sup>, Fire hazard testing – Part 6-2: Smoke obscuration – Summary and relevance of test methods

IEC 60695-6-30:1996, Fire hazard testing — Part 6: Guidance and test methods on the assessment of obscuration hazard of vision caused by smoke opacity from electrotechnical products involved in fires — Section 30: Small-scale static method—Determination of smoke opacity — Description of the apparatus

IEC 60695-6-31:1999, Fire hazard testing – Part 6-31: Smoke obscuration – Small-scale static test – Materials

IEC Guide 104:1997, The preparation of safety publications and the use of basic safety publications and group safety publications

ISO/IEC Guide 51:1999. Safety aspects - Guidelines for inclusion in standards

ISO 5659-2:2006, Plastics – Smoke generation – Part 2. Determination of optical density by a single-chamber test

ISO 5660-2:2002, Reaction-to-fire tests – Heat release, smoke production and mass loss rate – Part 2: Smoke production rate (dynamic measurement)

ISO 13943:2008, Fire safety - Vocabulary

ISO 19706:2007, Guidelines for assessing the fire threat to people

NOTE ISO 9122-1:1989. Toxicity testing of fire effluents – Part 1: General, has been withdrawn and replaced by ISO 19706:2007.

ASTM E 1354:2008, Standard Test Method for Heat and Visible Smoke Release Rates for Materials and Products Using an Oxygen Consumption Calorimeter

EN 13823:2002, Reaction to fire tests for building products – Building products, excluding floorings, exposed to thermal attack by a single burning item

# 3 Terms, definitions and symbols

# 3.1 Terms and definitions

For the purpose of this document, the terms and definitions and symbols given in ISO/IEC 13943, some of which are reproduced below for the uses' convenience, as well as the following apply.

<sup>1</sup> To be published.

<sup>2</sup> To be published.

### 3.1.1

# combustion

exothermic reaction of a substance with an oxidizer

NOTE Combustion generally emits effluent accompanied by flames and/or visible light.

[ISO/IEC 13943, definition 23]

### 3.1.2

### extinction area of smoke

product of the extinction coefficient and the volume occupied by the smoke

NOTE It is a measure of the amount of smoke.

FIEC 60695-4, definition 2.1301

### 3.1.3

# extinction coefficient of smoke

natural logarithm of the opacity of smoke divided by the path length of the light used to measure the smoke opacity

[IEC 60695-4, definition 2.131]

# 3.1.4

### fire

a) process of combustion characterized by the emission of heat and effluent accompanied by smoke, and/or flame, and/or glowing:

8-8260-49fd-9ef7-3672b7b8435e/iec-60695-6-1-2005

b) rapid combustion spreading uncontrolled in time and space

[IEC 60695-4, definition 2.29]

## 3.1.<del>5</del>

# fire effluent

total gaseous, particulate or aerosol effluent from combustion or pyrolysis

https://[IEC 60695-4, definition 2,33]

### 3.1.6

# fire hazard

potential for injury or loss of life and/or damage to property by fire

FIEC 60605 4, definition 2.36

# 3.1.7

## fire model

a laboratory process, including both the apparatus and the mode of operation, intended to simulate a certain stage of a real fire

[IEC 60695-4, definition 2.120]

# 3.1.8

# fire scenario

detailed description of conditions, including environmental, of one or more stages from before ignition to after completion of combustion in an actual fire at a specific location or in a real-scale simulation

FISO/IEC 13943, definition 581

### 3.1.9

### flash-over

the rapid transition to a state of total surface involvement in a fire of combustible materials within an enclosure

[IEC 60695-4, definition 2.59]

### 3.1.10

### heat flux

amount of thermal energy emitted, transmitted or received per unit area and unit time

NOTE—It is expressed in watts per square metre.

[ISO/IEC 13943, definition 85]

### 3.1.11

### ignition

initiation of combustion

NOTE The term "ignition" in French has a very different meaning [state of body combustingn].

[ISO/IEC 13943, definition 96]

# 3.1.12

### large scale test

a test, the size of which exceeds that of a typical laboratory bench test

[IEC 60695-4, definition 2.122]

### 3.1.13

### mass optical density of smoke

optical density multiplied by a factor,  $V \times \Delta m$ , where V is the volume of the test chamber,  $\Delta m$  is the mass loss of the test specimen and L is the light path length

[IEC 60695-4, definition 2.133]

# 3.1.14

# opacity (of smoke)

the ratio (I/T) of insident luminous flux (X) to transmitted luminous flux (T) through smoke, under specified test conditions

[IEC 60695-4, definition 2.89]

### 3.1.15

# optical density (of smoke) [lg(I/T)]

common logarithm of the opacity of smoke (see also specific optical density)

[IEC 60695-4, definition 2.90]

# 3.1.16

### realscale test

a test which simulates an end-use situation in both size and surroundings

[IEC 60695-4, definition 2.123]

# 3.1.17

### small scale test

a test which may be made on a typical laboratory bench

[IEC 60695-4, definition 2.124]

# 3.1.18

### smoke

a visible suspension of solid and/or liquid particles in gases resulting from combustion or pyrolysis

[IEC 60695-4, definition 2.101]

### 3.1.19

### smoke obscuration

the reduction in visibility due to smoke

[IEC 60695-4, definition 2.102]

### 3.1.20

# smoke production rate

extinction area of smoke produced, per unit time, by the combustion of a material under specified test conditions

### 3.1.21

# smoke release rate

see "smoke production rate"

# 3.1.22

# specific extinction area of smoke

extinction area of smoke divided by the mass loss of the test specimen

[IEC 60695-4, definition 2.137]

### 3.1.23

# specific optical density (of smoke)

optical density multiplied by a geometric factor V/M, where V is the volume of the test chamber, A is the exposed surface area of the test specimen and L is the light path length

NOTE The use of the term 'specific' does not, in this case denote 'per unit mass' but rather denotes a dimensionless quantity associated with a particular test apparatus and exposed surface area of the test specimen.

## 3.1.24

# **visibility**

maximum distance at which an object of defined size, brightness and contrast can be seen and recognized

# 3.1.1

# combustion

exothermic reaction of a substance with an oxidizing agent

NOTE Combustion generally emits fire effluent accompanied by flames and/or glowing.

[ISO/IEC 13943, definition 4.46]

### 3.1.2

# extinction area of smoke

product of the volume occupied by smoke and the extinction coefficient of the smoke

NOTE It is a measure of the amount of smoke, and the typical units are square metres (m<sup>2</sup>).

[ISO /IEC 13943, definition 4.92]

# 3.1.3

# extinction coefficient

natural logarithm of the ratio of incident light intensity to transmitted light intensity, per unit light path length

NOTE Typical units are reciprocal metres (m<sup>-1</sup>).

[ISO/IEC 13943, definition 4.93]

# 3.1.4

#### fire

(general) process of combustion characterized by the emission of heat and fire effluent and usually accompanied by smoke, flame or glowing or a combination thereof

NOTE In the English language the term "fire" is used to designate three concepts, two of which, fire (3.1.5) and fire (3.1.6), relate to specific types of self-supporting combustion with different meanings and two of them are designated using two different terms in both French and German.

[ISO/IEC 13943, definition 4.96]

### 3.1.5

### fire

(controlled) self-supporting combustion that has been deliberately arranged to provide useful effects and is limited in its extent in time and space

[ISO/IEC 13943, definition 4.97]

# 3.1.6

#### fire

(uncontrolled) self-supporting combustion that has not been deliberately arranged to provide useful effects and is not limited in its extent in time and space

[ISO/IEC 13943, definition 4.98]

### 3.1.7

### fire effluent

totality of gases and aerosols, including suspended particles, created by combustion or pyrolysis in a fire

[ISO/IEC 13943, definition 4.105]

### 3.1.8

### fire hazard

physical object or condition with a potential for an undesirable consequence from fire-60695-6-1-2005

[ISO/IEC 13943, definition 4.112]

### 3.1.9

# fire model

# fire simulation

calculation method that describes a system or process related to fire development, including fire dynamics and the effects of fire

[ISO/IEC 13943, definition 4.116]

# 3.1.10

# fire scenario

qualitative description of the course of a fire with respect to time, identifying key events that characterise the studied fire and differentiate it from other possible fires

NOTE It typically defines the ignition and fire growth processes, the fully developed fire stage, the fire decay stage, and the environment and systems that impact on the course of the fire.

[ISO/IEC 13943, definition 4.129]

## 3.1.11

### flashover

 $\langle stage\ of\ fire \rangle$  transition to a state of total surface involvement in a fire of combustible materials within an enclosure

[ISO/IEC 13943, definition 4.156]