



Designation: F 1897 – 98

Standard Specification for Leg Protection for Chain Saw Users¹

This standard is issued under the fixed designation F 1897; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification specifies minimum requirements for the design, performance, testing, and certification of protective garments and protective devices designed to provide cut resistance protection to the legs of operators of power chain saws.

1.2 The objective of this specification is to prescribe fit, function, and performance criteria for protective garments and protective devices that, when worn by chain saw operators, that are intended to reduce leg injuries caused by contact with a running power saw chain.

1.3 This standard is not intended to serve as a detailed manufacturing or purchasing specification, but can be referenced in purchase contracts to ensure that minimum performance requirements are met.

1.4 Controlled laboratory tests used to determine compliance with the performance requirements of this standard shall not be deemed as establishing performance levels for all situations to which chain saw operators may be exposed.

1.5 Mandatory requirements are indicated by the use of shall; recommendations and advisory information is indicated by use of should.

2. Referenced Documents

2.1 ASTM Standards:

- D 1776 Practice for Conditioning Textiles for Testing²
- F 1414 Test Method for Measurement of Cut Resistance to Chain Saw in Lower Body (Legs) Protective Clothing³

2.2 AATCC Standards:⁴

- Test Method 96 - (1988) Dimensional Changes in Laundering of Woven and Knitted Fabrics, except Wool
- Test Method 158 - (1985) Dimensional Changes on Dry Cleaning in Perchloroethylene: Machine Method

¹ This specification is under the jurisdiction of ASTM Committee F-23 on Protective Clothing and is under the direct responsibility of Subcommittee F23.20 on Physical Properties.

Current edition approved June 10, 1998. Published August 1998.

² Annual Book of ASTM Standards, Vol 07.01.

³ Annual Book of ASTM Standards, Vol 11.03.

⁴ Available from American Association of Textile Chemists and Colorists, P. O. Box 12215, Research Triangle Park, NC 27709.

3. Terminology

3.1 Definitions:

3.1.1 *approve, v*—to be acceptable to the authority having jurisdiction.

3.1.2 *authority having jurisdiction, n*—the organization, office, or individual responsible for approving any equipment, installation, or procedure.

3.1.2.1 *Discussion*—The term *authority having jurisdiction* is used in this document in a broad manner since jurisdictions and the responsibilities of approval agencies vary.

3.1.3 *certification, n*—a system whereby an organization determines that a manufacturer has demonstrated the ability to make a product that complies with the requirements of the specification, authorizes the manufacturer to use a label on products that comply with the requirements of the specification, and conducts a follow-up to verify the methods the manufacturer uses to determine compliance with the requirements of this specification.

3.1.4 *certification organization, n*—an independent, third-party organization that determines product compliance with the requirements of the specification with a labeling and listing follow-up program.

3.1.5 *chain saw, n*—a portable power-operated tool used for cutting wood that has cutters linked in a chain.

3.1.6 *chain speed, n*—the velocity of synchronized movement of linked cutters around a guide bar and sprocket.

3.1.7 *chain stop, n*—for chain saw cut resistance, the resulting action when a material clogs (jams) the drive sprocket or slows the speed sufficiently to prevent advancement of the saw chain.

3.1.8 *cut resistance, n*—in textile testing for chain saws, the ability of a material, while in contact with the linked cutters, to resist penetration of the cutters of a moving saw chain, independent of either jamming or chain stop.

3.1.9 *cut-through time, n*—for chain saw cut resistance, the time required for a running saw chain to affect complete breakthrough of a protective garment or protective device.

3.1.9.1 *Discussion*—When a cutthrough is effected, speed of the saw chain and time required must be measured.

3.1.10 *follow-up program*, *n*—the sampling, inspection, tests, or other measures conducted by the certification organization on a periodic basis to determine the continued compliance of products that are being made by the manufacturer to the requirements of the standard specification.

3.1.11 *jamming*, *n*—for *chain saw cut resistance*, the clogging action manifested by a protective garment that can produce a chain stop.

3.1.12 *label*, *v*—for *protective clothing*, to attach a symbol or other identifying mark, the use of which has been authorized by a certification organization.

3.1.13 *list*, *v*—for *protective clothing*, to publish a register of equipment or materials that has been verified by a certification organization as being acceptable and meeting the requirements of standard specifications.

3.1.13.1 *Discussion*—The means for identifying listed equipment may vary for each organization concerned with product evaluation, some of which do not recognize equipment as listed unless it is also labeled. The authority having jurisdiction should utilize the system employed by the certification organization to identify a listed product.

3.1.14 *protective apron*, *n*—for *chain saw cut protection*, an oversized protective device worn outside the trousers that is secured around the waist and may be secured around the legs (see **protective chaps**).

3.1.15 *protective chaps*, *n*—for *chain saw cut protection*, a protective device normally worn outside the trousers that is secured around the legs and waist (see **protective apron**).

3.1.16 *protective clothing*, *n*—any material or combination of materials used in an item of clothing for the purpose of isolating parts of the body from a potential hazard.

3.1.16.1 *Discussion*—For this specification, the potential hazard is contact with a running chain saw.

3.1.17 *protective device*, *n*—for *chain saw cut resistance*, an article of personal protective equipment that augments other equipment and is worn for the purpose of providing limited protection from injury due to contact with a moving power saw chain (see **protective garment**).

3.1.17.1 *Discussion*—Examples of protective devices for leg protection include protective aprons and protective chaps.

3.1.18 *protective garment*, *n*—for *chain saw cut protection*, an article of personal protective equipment that is worn for the purpose of providing limited protection from injury due to contact with a moving power saw chain. (See **protective device**.)

3.1.18.1 *Discussion*—Examples of protective garments for leg protection include protective leggings and protective pants.

3.1.19 *protective legging*, *n*—for *chain saw cut resistance*, a protective garment with independent legs normally worn outside the trousers.

3.1.20 *protective pad*, *n*—for *chain saw cut protection*, a protective material permanently attached into or onto the protective garment or protective device, designed to reduce leg injuries in the event of contact with a moving power saw chain.

3.1.21 *protective pant*, *n*—for *chain saw cut resistance*, a trouser-style protective garment in which the protective material is permanently attached to the garment.

3.1.22 *saw chain*, *n*—closed loop of cutters linked together for use in a portable power-operated tool.

4. Materials and Manufacture

4.1 Protective garments and protective devices shall be constructed of materials that are sufficiently flexible to adapt to the shape of the leg. Protective garments or protective devices should remain functional and effective throughout seasonal climatic variations.

4.2 Protective garments and protective devices shall be constructed to be lightweight and flexible enough so as not to severely restrict movement of the leg.

4.3 Protective garments or protective devices shall be constructed of materials that offer protection as stipulated in Section 5 and that do not impede normal maneuverability or capability to perform the intended task. Protective garments or protective devices should retain their shape and function when wet.

4.4 The workmanship in the production and assembly of the protective garment or protective device, and any associated clothing or restraining material, shall be such that the protective pad is permanently attached to the protective clothing.

4.5 Protective garments or protective devices shall be free of defects or imperfections that could detract from their function or performance. All hardware on protective garments or protective devices should be free of rough spots, burrs, or sharp edges.

5. Areas of Protection

5.1 The means of maintaining the protective garment or protective device in the intended position is considered part of the protective clothing. Protective garments or protective devices shall have an adequate means to keep them securely fastened around the waist and legs.

5.2 After pretreating in accordance with Section 6, protective garments and protective devices shall protect a minimum area as described below:

5.2.1 *Pants/Trousers*:

5.2.1.1 The protective pad shall have a minimum length of 700 mm (28 in.) and extend from the crotch to a point no more than 75 mm (3 in.) above the bottom of the pant leg.

NOTE 1—Should the inseam length be less than 700 mm (28 in.), then the pad may extend above the crotch.

5.2.1.2 The protective pad shall cover at least 3.142 rad (180°) across the frontal arc of each leg plus an additional 0.524 rad (30°) or 100 mm (4 in.) on the left side of both legs. The top of the extended coverage area, adjacent to the crotch, may be trimmed to an angle, not to exceed 0.785 rad (45°) downwards in the back of the left leg, and at an angle not to exceed 1.134 rad (65°) in the back of the right leg. The protective pad should overlap the boot top by at least 50 mm (2 in.) as worn on the user (see Fig. 1a, 1b, and 1c).

5.2.2 *Chaps, Aprons, or Leggings*:

5.2.2.1 The protective pad shall have a minimum length of 700 mm (28 in.) and extend from the crotch to a point 25 mm (1 in.) above the bottom of the carrier garment.

5.2.2.2 The protective pad shall have a minimum width of 350 mm (14 in.) at the midpoint of the pad and a minimum