

INTERNATIONAL STANDARD



**Global maritime distress and safety system (GMDSS) –
Part 6: Narrowband direct-printing telegraph equipment for the reception
of navigational and meteorological warnings and urgent information to ships
(NAVTEX)**

Document Preview

[IEC 61097-6:2005](#)

<https://standards.iteh.ai/catalog/standards/iec/ae65e2b7-8edf-4c80-9bfa-d38458713f86/iec-61097-6-2005>





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

[IEC 61097-6:2005](http://standards.iteh.ai/catalog/standards/iec/ae65e2b7-8edf-4c80-9bfa-d38458713f86/iec-61097-6-2005)

<https://standards.iteh.ai/catalog/standards/iec/ae65e2b7-8edf-4c80-9bfa-d38458713f86/iec-61097-6-2005>



IEC 61097-6

Edition 2.2 2019-07
CONSOLIDATED VERSION

INTERNATIONAL STANDARD



**Global maritime distress and safety system (GMDSS) –
Part 6: Narrowband direct-printing telegraph equipment for the reception
of navigational and meteorological warnings and urgent information to ships
(NAVTEX)**

Document Preview

[IEC 61097-6:2005](https://standards.iteh.ai/catalog/standards/iec/ae65e2b7-8edf-4c80-9bfa-d38458713f86/iec-61097-6-2005)

<https://standards.iteh.ai/catalog/standards/iec/ae65e2b7-8edf-4c80-9bfa-d38458713f86/iec-61097-6-2005>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 47.020.70

ISBN 978-2-8322-7177-3

Warning! Make sure that you obtained this publication from an authorized distributor.

REDLINE VERSION



**Global maritime distress and safety system (GMDSS) –
Part 6: Narrowband direct-printing telegraph equipment for the reception
of navigational and meteorological warnings and urgent information to ships
(NAVTEX)**

Document Preview

[IEC 61097-6:2005](#)

<https://standards.iteh.ai/catalog/standards/iec/ae65e2b7-8edf-4c80-9bfa-d38458713f86/iec-61097-6-2005>



CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
INTRODUCTION to Amendment 1	8
INTRODUCTION to Amendment 2	8
1 Scope.....	9
2 Normative references	9
3 Definitions and abbreviations.....	10
3.1 Definitions	10
3.2 Abbreviations	10
4 Performance requirements	11
4.1 General.....	11
4.2 General characteristics.....	11
4.3 Specific characteristics.....	12
4.3.1 B_1 and B_2 characters	12
4.3.2 B_3 and B_4 characters	12
4.3.3 Preamble.....	12
4.3.4 Repetition of printing/display	12
4.3.5 Mandatory printing/display.....	13
4.3.6 Reception of messages with character errors	13
4.3.7 Controls and indicators.....	13
4.3.8 Programmable control memories	13
4.3.9 Alarms.....	13
4.3.10 Test facilities	14
4.4 Interfaces	15
4.5 Receiver.....	15
4.5.1 Number of receivers	15
4.5.2 Receive frequencies	15
4.5.3 Sensitivity.....	16
4.6 Display.....	16
4.6.1 General	16
4.7 Integral printer.....	17
4.7.1 General	17
4.8 NAVTEX message memory	18
4.8.1 Equipment without integral printers.....	18
4.8.2 Equipment with integral printer	18
4.9 Power supplies.....	19
4.10 Source of UTC	19
5 Test conditions	19
5.1 General.....	19
5.2 Performance test.....	20
5.3 Performance check.....	20
5.4 Normal and extreme conditions	20
5.4.1 Normal test conditions	20
5.4.2 Extreme test conditions	20
5.4.3 Excessive test conditions.....	21

5.5	Standard test signal	21
5.6	Standard test file	22
5.7	Arrangement for test signal applied to the receiver input	22
5.8	Artificial antennas.....	22
5.9	Measurement uncertainty	23
5.10	Interpretations of measurement results.....	23
5.11	Conducted and radiated RF immunity tests exclusion bands.....	23
5.11.1	Exclusion bands for receivers	23
5.12	Narrow band responses on receivers.....	23
6	Environmental tests required	24
7	Serial interface tests.....	24
7.1	INS input electrical tests.....	24
7.1.1	Method of test	24
7.1.2	Required results	24
7.2	INS input performance tests	24
7.2.1	Method of measurement	24
7.2.2	Required results	24
7.3	INS output electrical tests.....	24
7.3.1	Method of test	24
7.3.2	Required results	24
7.4	INS output performance tests	24
7.4.1	Method of measurement.....	24
7.4.2	Required results	25
7.5	Printer output electrical tests	25
7.5.1	Method of test	25
7.5.2	Required results	25
7.6	Printer output performance tests	25
7.6.1	Method of measurement	25
7.6.2	Required results	25
7.7	BAM interface performance tests.....	25
7.7.1	Method of measurement	25
7.7.2	Required results	25
8	General and signal processing tests	26
8.1	Exclusion of stations	26
8.1.1	Method of measurement	26
8.1.2	Results required	26
8.2	Exclusion of message categories.....	26
8.2.1	Method of measurement	26
8.2.2	Results required	26
8.3	Receiver test facility	26
8.3.1	Method of measurement	26
8.3.2	Results required	26
8.4	Search and rescue (SAR) alarm provision and reset.....	26
8.4.1	Method of measurement	26
8.4.2	Results required	27
8.5	Additional alarms.....	27
8.5.1	Method of measurement	27
8.5.2	Results required	27

9	Receiver tests	27
9.1	Call sensitivity	27
9.1.1	Definition	27
9.1.2	Method of measurement	27
9.1.3	Results required	27
9.2	Interference rejection and blocking immunity	27
9.2.1	Definition	27
9.2.2	Method of measurement	28
9.2.3	Results required	28
9.3	Co-channel rejection	28
9.3.1	Definition	28
9.3.2	Method of measurement	28
9.3.3	Results required	28
9.4	Intermodulation	28
9.4.1	Definition	28
9.4.2	Method of measurement	29
9.4.3	Results required	29
9.5	Off-frequency transmitter	29
9.5.1	Definition	29
9.5.2	Method of measurement	29
9.5.3	Results required	29
9.6	Simultaneous operation on several receive frequencies	29
9.6.1	Definition	29
9.6.2	Method of measurement	30
9.6.3	Results required	30
9.7	Protection of input circuits	30
9.7.1	Method of measurement	30
9.7.2	Results required	30
10	Printer tests	30
10.1	Basic requirements	30
10.1.1	Method of measurement	30
10.1.2	Results required	30
10.2	Paper roll end alarm and storage inhibition	30
10.2.1	Method of measurement	30
10.2.2	Results required	31
10.3	Automatic line feed indication and paper feed	31
10.3.1	Method of measurement	31
10.3.2	Results required	31
10.4	Mutilated character indication	31
10.4.1	Method of measurement	31
10.4.2	Results required	31
10.5	Tests of technical characteristics (ITU-R Recommendation M.540)	31
10.5.1	B_1/B_2 characters selection	31
10.5.2	Printer activation/error-free preamble B_1-B_4	31
10.5.3	Non-repetitive printing of a message	32
10.5.4	Message with $B_3B_4 = 00$	32
11	Memory tests	32
11.1	Internal storage, message tagging and erasure of oldest message identifications	32

11.1.1	Method of measurement	32
11.1.2	Results required	33
11.2	Erasure of message identifications/storage time	34
11.2.1	Method of measurement	34
11.2.2	Results required	34
11.3	Storage of message identifications	34
11.3.1	Method of measurement	34
11.3.2	Results required	35
11.4	Reception of messages with character errors	35
11.4.1	Method of measurement	35
11.4.2	Results required	35
11.5	Unsatisfactory reception	35
11.5.1	Method of measurement	35
11.5.2	Results required	35
11.6	Power-off check	36
11.6.1	Method of measurement	36
11.6.2	Results required	36
11.7	Brown-out test	36
11.7.1	Method of measurement	36
11.7.2	Results required	36
11.8	UTC handling check	36
11.8.1	Method of measurement	37
11.8.2	Results required	37
12	Miscellaneous tests	37
12.1	Spurious emissions	37
12.1.1	Method of measurement	37
12.1.2	Results required	37
12.2	Equipment manuals – checks of the manufacturer's documentation	37
12.3	Marking and identification	37
Annex A (informative)	Block diagrams of NAVTEX systems	39
Annex B (normative)	Definition of satisfactory reception of a message	41
Annex C (informative)	IEC 61162 sentences for NAVTEX operation	42
Annex D (normative)	Manufacturer's declarations/equipment manual	45
Figure A.1	– EUT with an integral printing device	39
Figure A.2	– EUT with an integral display device	39
Figure A.3	– EUT black box receiver	40
Table 1	– Alarm conditions signaled using the ALR sentence formatter	14
Table 2	– Extreme power supply variation	21
Table 3	– Unwanted signal levels	28
Table 4	– Intermodulation frequency pairs	29

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**GLOBAL MARITIME DISTRESS AND
SAFETY SYSTEM (GMDSS) –****Part 6: Narrowband direct-printing telegraph equipment
for the reception of navigational and meteorological warnings
and urgent information to ships (NAVTEX)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendments has been prepared for user convenience.

IEC 61097-6 edition 2.2 contains the second edition (2005-12) [documents 80/419/FDIS and 80/424/RVD], its amendment 1 (2011-12) [documents 80/619/CDV and 80/648/RVC] and its amendment 2 (2019-07) [documents 80/927/FDIS and 80/931/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendments 1 and 2. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 61097-6 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 61097 consists of the following parts under the general title *Global maritime distress and safety system (GMDSS)*:

- Part 1: Radar transponder – Marine search and rescue (SART) – Operational and performance requirements, methods of testing and required test results
- Part 2: COSPAS-SARSAT EPIRB – Satellite emergency position indicating radio beacon operating on 406 MHz – Operational and performance requirements, methods of testing and required test results
- Part 3: Digital selective calling (DSC) equipment – Operational and performance requirements, methods of testing and required testing results
- Part 4: INMARSAT-C ship earth station and INMARSAT enhanced group call (EGC) equipment – Operational and performance requirements, methods of testing and required test results
- Part 5: Inmarsat-E – Emergency position indicating radio beacon (EPIRB) operating through the Inmarsat system – Operational and performance requirements, methods of testing and required test results
- Part 6: Narrowband direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX)
- Part 7: Shipborne VHF radiotelephone transmitter and receiver – Operational and performance requirements, methods of testing and required test results
- Part 8: Shipborne watchkeeping receivers for the reception of digital selective calling (DSC) in the maritime MF, MF/HF and VHF bands – Operational and performance requirements, methods of testing and required test results
- Part 9: Shipborne transmitters and receivers for use in the MF and HF bands suitable for telephony, digital selective calling (DSC) and narrow band direct printing (NBDP) – Operational and performance requirements, methods of testing and required test results
- Part 10: Inmarsat-B ship earth station equipment – Operational and performance requirements, methods of testing and required test results
- Part 12: Survival craft portable two-way VHF radiotelephone apparatus – Operational and performance requirements, methods of testing and required test results
- Part 13: Inmarsat F77 ship earth station equipment – Operational and performance requirements, methods of testing and required test results

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

INTRODUCTION

NAVTEX provides shipping with navigational and meteorological warnings and urgent information by automatic display and/or print out from a dedicated receiver.

NAVTEX is a component of the IMO/IHO World-Wide Navigational Warning Service (WWNWS) defined by IMO Assembly Resolution A.706(17), as amended, and the WMO Manual on Marine Meteorological Services, Part *Ibis*, Provision of warnings and weather and sea bulletins (GMDSS application). It has been included as an element of the Global Maritime Distress and Safety System (GMDSS).

The original NAVTEX specification allowed for equipment with integral printers and precluded the fitting of equipment which relied on other ways of recording and displaying NAVTEX data. The use of Liquid Crystal Displays and other Visual Display Units is now ubiquitous on ships' bridges and this revision of the specification allows for their use in displaying NAVTEX data.

As a result of the final cessation of the distress watch on 500 kHz in 1999 the frequency 490 kHz became available for use as a national NAVTEX channel and this has now been widely implemented around the world. This NAVTEX specification therefore requires simultaneous operation on an additional channel to the international channel of 518 kHz.

IMO Resolution MSC.148(77) states that the equipment should comprise radio receivers, a signal processor and:

- a) an integrated printing device; or
- b) a dedicated display device, printer output port and a non-volatile message memory; or
- c) a connection to an integrated navigation system and a non-volatile message memory.

INTRODUCTION to Amendment 1

<http://standards.iteh.ai/catalog/standards/iec/61097-6-2005>

The amendment removes the description in Annex C of the sentences NRX and NRM. These sentences are now described in IEC 61162-1 (see NOTE below).

NOTE Applies as of edition 4 (2010).

INTRODUCTION to Amendment 2

This amendment adds a requirement to include an interface for alert management. This results from amendments to the performance standards for NAVTEX agreed by the International Maritime Organization in resolution MSC.430(98) in 2017.

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –

Part 6: Narrowband direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX)

1 Scope

This part of IEC 61097 specifies the minimum performance requirements, technical characteristics and type-testing requirements for narrowband telegraph equipment for the reception of navigational and meteorological information as required by Regulation IV/7.1.4 of the 1988 amendments to the 1974 International Convention for Safety of Life at Sea (SOLAS), and which is associated with IEC 60945. When a requirement in this standard is different from IEC 60945, the requirement in this standard takes precedence.

This standard incorporates the performance standards of IMO Resolution MSC.148(77), the technical characteristics of ITU-R Recommendation M.540, takes account of the IMO Resolution A.694(17) and conforms with the ITU Radio Regulations where applicable.

All text of this standard, whose meaning is identical to that in IMO Resolution MSC.148(77) and ITU-R Recommendation M.540 will be printed in *italics* and the Resolution/Recommendation and paragraph number indicated between brackets.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Marine navigation and radio communication equipment – General requirements – Methods of testing and required test results*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IEC 61162-2, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 2: Single talker and multiple listeners, high-speed transmission*

IEC 62923-1, *Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 1: Operational and performance requirements, methods of testing and required test results*

IEC 62923-2, *Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 2: Alert and cluster identifiers and other additional features*

IMO *Safety of Life at Sea (SOLAS) Convention* (1974), as amended (GMDSS)

IMO Resolution A.694(17) (1991) *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO Resolution MSC.148(77) (2003) *Revised performance standards for narrow-band direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX)*

IMO Publication – *NAVTEX Manual*

IMO Resolution MSC/Circ.1122 *Adoption of the revised NAVTEX manual*

IMO Resolution MSC.302(87) (2010), *Performance standards for bridge alert management*

ITU-R Recommendation M.540-2:1990, *Operational and technical characteristics for an automated direct printing telegraph system for promulgation of navigational and meteorological warnings and urgent information to ships*

ITU-R Recommendation M.625-3:1995, *Direct-printing telegraph equipment employing automatic identification in the maritime mobile service*

3 Definitions and abbreviations

For the purposes of this document, the following definitions and abbreviations apply.

3.1 Definitions

3.1.1

LORAN-C

long range radio-navigation system operating on an assigned frequency of 100 kHz

3.1.2

NAVTEX

system for the broadcast and automatic reception of maritime safety information by means of narrow-band telegraphy

<https://standards.iteh.ai/catalog/standards/iec/ae65e2b7-8edf-4c80-9bfa-d38458713f86/iec-61097-6-2005>

3.1.3

Test script

text file containing a number of NAVTEX messages formatted as defined in 5.5. The STF is a particular example of a test script

3.2 Abbreviations

ASCII	American Standard Code for Information Interchange
BAM	bridge alert management
CER	character error rate
EMC	electromagnetic compatibility
EUT	equipment under test
HMI	human-machine interface
INS	integrated navigation system
IMO	International Maritime Organization
ITU	International Telecommunication Union
PC	performance check
PT	performance test
RTC	real time clock
SAR	search and rescue