
International Standard



7007

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Woodworking machines — Table bandsawing machines — Nomenclature and acceptance conditions

Machines à bois — Machines à scier à ruban à table — Nomenclature et conditions de réception

First edition — 1983-04-15

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[ISO 7007:1983](https://standards.iteh.ai/catalog/standards/sist/238fd565-2002-4486-bc08-aecca20fad878/iso-7007-1983)

<https://standards.iteh.ai/catalog/standards/sist/238fd565-2002-4486-bc08-aecca20fad878/iso-7007-1983>

UDC 674.053 : 621.935

Ref. No. ISO 7007-1983 (E)

Descriptors : woodworking, woodworking machinery, nomenclature, acceptance, accuracy.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been authorized has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 7007 was developed by Technical Committee ISO/TC 39, *Machine tools*, and was circulated to the member bodies in April 1981.

It has been approved by the member bodies of the following countries :

Belgium	India	Romania
Brazil	Ireland	South Africa, Rep. of
China	Italy	Spain
Egypt, Arab Rep. of	Japan	Sweden
France	Korea, Dem. P. Rep. of	United Kingdom
Germany, F.R.	Korea, Rep. of	USSR
Hungary	Mexico	

No member body expressed disapproval of the document.

Woodworking machines — Table bandsawing machines — Nomenclature and acceptance conditions

iTeh STANDARD PREVIEW (standards.iteh.ai)

1 Scope and field of application

This International Standard specifies the terminology appropriate to each part of the machine and, with reference to ISO/R 230, the geometrical test for table bandsawing machines and gives the corresponding permissible deviations which apply to machines for general purpose use and normal accuracy.

NOTE — In addition to terms used in two of the three official ISO languages (English and French), this International Standard gives in the annex the equivalent terms in German, Spanish, Italian and Swedish; these have been included at the request of ISO Technical Committee TC 39 and are published under the responsibility of the member bodies for Germany, F.R. (DIN), Spain (IRANOR), Italy (UNI) and Sweden (SIS). However, only the terms and definitions given in the official languages can be considered as ISO terms and definitions.

This International Standard deals only with the verification of accuracy of the machine. It does not apply to the testing of the running of the machine (vibrations, abnormal noises, stick-slip motion of the components etc.), nor to its characteristics (speeds, feeds etc.) which should generally be checked before testing accuracy.

This International Standard does not impose any practical test for table bandsawing machines. Practical tests should be exceptions and have to be stated in a previous agreement between the producer and the user.

2 Reference

ISO/R 230, *Test code for machine tools*.

3 Preliminary remarks

ISO 7007:1983

<https://standards.iteh.ai/catalog/standards/sis/23861565-2007-4486-b-08>

3.1 In this International Standard all the dimensions and permissible deviations are expressed in millimetres.

3.2 To apply this International Standard, reference should be made to ISO/R 230, especially for installation of the machine before testing, the warming up of the bottom saw wheel and other moving parts and description of measuring methods. The measuring instruments shall not permit errors over 1/3 of the checked tolerances.

3.3 The sequence in which the geometrical tests are given is related to the sub-assemblies of the machine and this in no way defines the practical order of testing. In order to make mounting of instruments or gauging easier, tests may be applied in any order.


3.4 When inspecting a machine, it is not always possible or necessary to carry out all the tests given in this International Standard.

3.5 It is up to the user to choose, in agreement with the manufacturer, those tests relating to the properties which are of interest to him, but these tests are to be clearly stated when ordering a machine.


3.6 A movement is longitudinal when it takes place in the working direction of the piece.

3.7 When establishing the tolerance for a measuring range different from that given in this International Standard (see 2.311 in ISO/R 230), it should be taken into consideration that the minimum value of the tolerance is 0,01 mm.

4 Nomenclature






<https://standards.iteh.ai/catalog/standards/sist/238fd565-2002-4486-bc08-aeca20fad878/iso-7007-1983>



Ref.	English	French
	Table bandsawing machine	Machine à scier à ruban à table
1	Framework	Ossature
1.1	Main frame	Bâti
2	Feed of workpiece and/or tools	Déplacement des pièces et/ou outils
3	Workpiece support clamp and guide	Support, maintien et guidage des pièces
3.1	Table	Table
3.2	Fence	Guide longitudinal
4	Toolholders and tools	Porte-outils et outils
4.1	Sawblade	Lame (ruban)
4.2	Top saw wheel	Volant supérieur
4.3	Bottom saw wheel	Volant inférieur
4.4	Top saw guide	Guide-lame supérieur
4.5	Bottom saw guide	Guide-lame inférieur
5	Workheads and tool drives	Unité de travail et son entraînement
5.1	Top saw wheel bearing housing	Palier du volant supérieur
5.2	Sawblade tension device	Dispositif de tension du ruban
5.3	Bottom saw wheel bearing housing	Palier de volant inférieur
5.4	Bottom wheel pulley	Poulie d'entraînement
5.5	Driving motor	Moteur d'entraînement
6	Controls	Commandes
6.1	Starting switch	Commutateur de mise en route
6.2	Adjustment for sawblade tension	Réglage de tension
6.3	Saw tension indicator	Indicateur de tension
6.4	Saw tracking adjustment	Positionnement du ruban sur le volant
6.5	Saw guide lock	Blocage du guide ruban
7	Safety devices	Dispositifs de sécurité
7.1	Covers for wheels	Capot de protection
7.2	Adjustable guard for sawblade	Protecteur réglable de la lame
7.3	Brake	Frein
7.4	Wheel cleaning device	Dispositif de nettoyage du volant
8	Miscellaneous	Divers
8.1	Dust extraction outlet	Buse d'aspiration des copeaux
9	Free	Libre
10	Examples of work	Exemples de travail
10.1	Straight ripping	Déclignage
10.2	Curved cutting	Chantournage

5 Acceptance conditions and permissible deviations



No.	Diagram	Object	Permissible deviation	Measuring instruments	Observations and references in test code ISO/R 230
G1		<p>Checking flatness of the table (with it locked)</p> <p>a) transverse straightness</p> <p>b) longitudinal straightness</p> <p>c) diagonal straightness</p>	<p>a) and b)</p> <p>0,30 for $A < 630$</p> <p>0,40 for $630 < A < 1250$</p> <p>0,50 for $A > 1250$</p> <p>c)</p> <p>0,40 for $A < 630$</p> <p>0,50 for $630 < A < 1250$</p> <p>0,60 for $A > 1250$</p>	<p>Straightedge and feeler gauges</p>	<p>Clause 5.212 and 5.322</p>
G2		<p>Checking diagonal straightness of the fence</p>	<p>0,30 for $B < 630$</p> <p>0,40 for $B > 630$</p>	<p>Straightedge and feeler gauges</p>	<p>Clause 5.212</p>

No.	Diagram	Object	Permissible deviation	Measuring instruments	Observations and references in test code ISO/R 230
G3		<p>Checking squareness of the fence to the table</p> <p>ISO 7007:1983 https://standards.iteh.ai/catalog/standards/sist/238fd565-2002-4486-bc08-aeca20fad878/iso-7007-1983</p>	<p>0,20/100*</p>	<p>Square and feeler gauges</p>	<p>Clause 5.512.2</p> <p>* Distance C</p>

iTeh STANDARDS PREVIEW
 (standards.iteh.ai)

No.	Diagram	Object	Permissible deviation	Measuring instruments	Observations and references in test code ISO/R 230
G4		<p>Checking alignment of the wheels</p>	<p>0,30 for $D \leq 630$ 0,40 for $630 < D < 1000$ 0,50 for $D > 1000$</p>	<p>Plumb-line, or straightedge, or other instruments</p>	<p>Clause 5.412.2</p> <p>The straightedge shall be placed on the front surface of both wheels. The deviation between the straight-edge and the wheel surface shall be measured at two equidistant points from the vertical axis.</p>
G5		<p>Measuring run-out of the wheels</p>	<p>0,20 for $D \leq 630$ 0,30 for $D > 630$</p>	<p>Dial gauge</p>	<p>Clause 5.612.2</p> <p>Control on the wheels ready to operate.</p>

<https://standards.iteh.ai/catalog/standards/sist/238fd565-2002-4486-bc08-acc20fad878/iso-7007-1983>
 ISO 7007:1983
 iTeh STANDARDS PREVIEW
 (standards.iteh.ai)

No.	Diagram	Object	Permissible deviation	Measuring instruments	Observations and references in test code ISO/R 230
G6		Measuring camming of the wheels	<p>0,30 for $D < 630$ 0,40 for $630 < D < 1000$ 0,50 for $D > 1000$</p>	Dial gauge	Clause 5.632
G7		Measuring true running of the edge of the blade	<p>0,40 for $D < 630$ 0,60 for $630 < D < 1000$ 0,80 for $D > 1000$ for each turn of the test blade</p>	Dial gauge and test blade	<p>Clause 5.232.1</p> <p>The dial gauge shall be placed on the table with its stylus perpendicular to the test blade edge.</p> <p>The deviation is observed over three turns of the blade.</p>