PUBLICLY AVAILABLE SPECIFICATION

IEC PAS 62001

Pre-Standard

First edition 2004-07







Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

IEC Web Site (<u>www.iec.ch</u>)

. Catalogue of IEC publications

The on-line catalogue on the IEC web site (www.iec.ch/searchsub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

• IEC Just Published

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the customer Service Centre (see below) for further information.

Customer Service Centre

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: <u>custserv@iec.ch</u>
Tel: +41 22 919 02 11


Fax: \+41 22 919 03 00

PUBLICLY AVAILABLE SPECIFICATION

IEC PAS 62001

Pre-Standard

First edition 2004-07



© IEC 2004 - Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



PRICE CODE



CONTENTS

FOREWORD	5
1. INTRODUCTION AND OBJECTIVES	
1.2 Definitions	
1.3 Introduction	
1.4 Past experience	
1.5 Objectives	
1.0 Approach	11
2. GENERAL ASPECTS OF SPECIFICATIONS 2.1 General	12
2.1 General	
2.2 Boundaries of responsibility.	13
2.3 Scope of studies	
2.4 Scope of supply	16
2.5 Technical data to be supplied by Contractor	16
2.6 Alternative proposals by Bidders	1/
3. PERMISSIBLE DISTORTION LIMITS 3.1 General 3.2 Voltage distortion 3.3 Distortion limits pertaining to the HW and RHV network equipment	19
3.1 General	20
3.2 Voltage distortion	21
3.3 Distortion limits pertaining to the HV and EHV network equipment. 3.4 Telephone interference 3.5 Special criteria	27
3.4 Telephone interference	29
3.5 Special criteria	32
4 LIABMONIO OFNEDATION	40
4. HARMONIC GENERA NON	43
4. HARMONIC GENERATION 4.1 General 4.2 Converter harmonic generation 4.3 Calculation methodology	44
4.2 Colorletion methodology	44
4.4 Sensitivity of harmonic generation to various factors	40 51
4.5 Externally generated harmonics.	-pas-542
5. HARMONIC INTERACTION ACROSS CONVERTERS	57
5.1 Introduction	58
5.2 Interaction phenomena	
5.3 Interaction modelling	
5.4 Impact on a.c. filter design	
5.5 Study methods	
5.6 Possible countermeasures	
5.7 Recommendations for the Technical Specification	64
6. FILTER ARRANGEMENTS	65
6.1 Overview	
6.2 Advantages and disadvantages of typical filters	
6.3 Classification of filter types	
6.4 Tuned filters	
6.5 Damped filters	
6.6 Choice of filters	77

7. FILTER PERFORMANCE CALCULATION	/ 0
7.1 Calculation procedure	
7.2 Detuning and tolerances	
7.3 Network impedance for performance calculations	
7.4 Outages of filter banks / sub-banks	
7.5 Considerations of probability	
7.6 Flexibility regarding compliance	
1	
8. FILTER SWITCHING AND REACTIVE POWER MANAGEMENT	96
8.1 Introduction	
8.2 Reactive power interchange with a.c. network	
8.3 HVDC converter reactive power capability	
8.4 Bank / sub-bank definitions and sizing	
8 5 Hysteresis in switching points	102
8.5 Hysteresis in switching points	103
8.7 Operation at increased converter control angles	103
8.8 Filter switching sequence and harmonic performance	103
8.9 Demarcation of responsibilities	105
8.9 Demarcation of responsionities	103
9. STEADY STATE RATING	111
9.1 Introduction	112
9.2 Calculation method 9.3 A.C. network conditions 9.4 De-tuning effects. 9.5 Network impedance for rating calculations	112
9.3 A.C. network conditions	118
9.4 De-tuning effects	118
9.5 Network impedance for rating calculations.	119
9.6 Outages	119
10. TRANSIENT STRESSES AND RATING	120
10. TRANSIENT STRESSES AND TAXING	121
10.1 General	121
10.2 Switching impures studies 10.3 Fast fronted waveform studies 10.3 Fast fronted waveform studies 10.4 Fast fronted wa	121
10 4 Insulation co-ordination	
10.4 Insulation co-ordination	123
1XC \AS\\(\)2001:2004	
s://sta11. LOSSES	c-pas- 128 ¹
11.1 Background	
11.1 Background 11.2 A.C. filter component losses 11.3 Filter reactor losses 11.4 Criteria for loss evaluation 12. DESIGNISSUES AND SPECIAL APPLICATIONS	
11.1 Background 11.2 A.C. filter component losses 11.3 Filter reactor losses 11.4 Criteria for loss evaluation 12. DESIGNISSUES AND SPECIAL APPLICATIONS 12.1 Introduction	
11.1 Background	
11.1 Background	
11.1 Background 11.2 A.C. filter component losses 11.3 Filter reactor losses 11.4 Criteria for loss evaluation 12. DESIGNUSSUES AND SPECIAL APPLICATIONS 12.1 Introduction 12.2 Performance aspects 12.3 Rating aspects 12.4 Filters for special purposes	
11.1 Background	
11.1 Background 11.2 A.C. filter component losses 11.3 Filter reactor losses 11.4 Criteria for loss evaluation 12. DESIGNUSSUES AND SPECIAL APPLICATIONS 12.1 Introduction 12.2 Performance aspects 12.3 Rating aspects 12.4 Filters for special purposes 12.5 Impact of new HVDC station in vicinity of an existing station.	
11.1 Background	
11. LOSSES	
11.1 Background 11.2 A.C. filter componen losses 11.3 Filter reactor losses 11.4 Criteria for loss evaluation 12. DESIGNUSSUES AND SPECIAL APPLICATIONS 12.1 Introduction 12.2 Performance aspects 12.3 Rating aspects 12.4 Filters for special purposes 12.5 Impact of new HVDC station in vicinity of an existing station 12.6 Redundancy issues and spares 13. PROTECTION 13.1 Introduction 13.2 General 13.3 Bank and sub-bank overall protection	
11.1 Background	

14. SEISMIC REQUIREMENTS	165
14.1 General	166
14.2 Load specification	166
14.3 Method of qualification	167
14.4 Examples of improvements in the mechanical design	170
15. AUDIBLE NOISE	172
15.1 General	173
15.2 Sound active components of a.c. filters	
15.3 Sound requirements	
15.4 Noise reduction	
16. CUSTOMER SPECIFIED PARAMETERS AND REQUIREMENTS	178
16.1 Introduction	179
16.2 A.C. system parameters	179
16.3 Harmonic distortion requirements	
16.4 Environmental conditions	182
16.5 Electrical environment	184
16.6 Requirements for filter arrangements and components	184
16.6 Requirements for filter arrangements and components	185
16.8 Loss evaluation.	185
16.9 Field measurements and verifications	185
16.10 General requirements	
16.10 General requirements	
17 EOLUDMENT DESIGN AND TEST DESCUIDEMENTS	106
17. EQUIPMENT DESIGN AND TEST REQUIREMENTS	100
17.1 General	18/
17.2 Capacitors	190
1/3 Reactors	193
17.4 Resistors 17.5 Arresters	196
17.5 Arresters.	199
17.6 Instrument transformers	202
17.7 Filter switching equipment	204
110 140 70 2001 2004 110 140 70 70 70 70 70 70 70 70 70 70 70 70 70	00 200 6
18. FIELD MEASUREMENTS AND VERIFICATION	
18.1 Introduction	
18.2 Equipment and subsystem tests	
18.3 System tests	211
18.3 System tests	215
18.5 Measurements of pre-existing harmonic levels for design purposes	215
19. FUTURE DEVELOPMENTS	217
19.1 Introduction	
19.2 New filter technology	
19.3 New converter technology	
19.4 Changing external environment.	
27. Camagang Oncernal on Homeon	
0. REFERENCES	224
.U. INLI LINLINGLO	∠ು ।

INTERNATIONAL ELECTROTECHNICAL COMMISSION

GUIDE TO THE SPECIFICATION AND DESIGN EVALUATION OF AC FILTERS FOR HVDC SYSTEMS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsbever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or revance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is a technical specification not fulfilling the requirements for a standard but made available to the public.

IEC-PAS 62001 was submitted by the CIGRÉ (International Council on Large Electric Systems) and has been processed by subcommittee 22F: Power electronics for electrical transmission and distribution systems, of IEC technical committee 22: Power electronic systems and equipment.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
22F/97/NP	22F/102/RVN

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned will transform it into an International Standard.

An IEC-PAS licence of copyright and assignment of copyright has been signed by the IEC and CIGRÉ and is recorded at the Central Office.

This PAS shall remain valid for an initial maximum period of three years starting from 2004-07. The validity may be extended for a single three-year period, following which it shall be revised to become another type of normative document or shall be withdrawn.

HOW TO USE THIS GUIDE

The principal purpose of this document is to give guidance to those responsible for:

- preparing the a.c. filtering aspects of Technical Specifications for HVDC projects,
- · evaluating the proposed designs, and
- monitoring the subsequent project.

The main objective is to enable informed judgements to be made and future Technical Specifications to be written, such that the resulting a.c. filters are effective yet economical, and are not under- or over designed.

The Guide has been written by a diverse group including engineers from various manufacturers, utilities and consultants, and the recommendations respect the interests of all parties.

This Guide can be used in different ways by different readers:

- The Guide provides sufficient instructional material so that it can be used as an introduction by those involved in HVDC technology for the first time. An initial reader can omit certain sections and concentrate on core aspects.
- An engineer preparing a Technical Specification can find the key points, which must be considered, highlighted throughout the Quide, and summarised in Section 16.
- The Guide emphasises aspects where the specified requirements can, perhaps unintentionally, have a significant impact on filter design and costs. A user issuing a Technical Specification should consider how these aspects apply to that Specification.
- For evaluating proposed designs and technically monitoring the project, a deeper understanding of many aspects will be required. This document contains guidance reflecting the accumulated knowledge of many HVDC projects, and so will be of value even to highly experienced users. It should help Customers to understand the reasons for differences among filter designs offered by Bidders.
- While making specific recommendations, it has also been necessary to provide a considerable amount of background material. Much of this information has never been brought together under one cover before, and so the Guide will provide a valuable source of reference.
- Additionally, the Guide also contains material which will be of relevance in power industry
 applications other than HVDC, for example in industrial filtering, switched capacitor
 applications and general power quality issues.

The Guide has been clearly set-out in sections, each covering specific aspects of a.c. filter design. For guidance on any particular subject, each section may be read individually. Cross-references to other sections are made where necessary.

The brief description below of the contents of each section is intended to assist the reader to use the Guide in the most appropriate way.


• For any reader, it is recommended to start with the short introductory Sections 1 and 2, which explain the justification for the production of this document and also discuss what a Technical Specification must attempt to achieve and the optional approaches regarding what should be included.

- Section 3 tackles the difficult and controversial problem of defining what harmonic distortion
 limits should be specified. This is a complex subject and one where it is difficult to make
 unambiguous recommendations, due to the vastly different local circumstances applying to
 different HVDC projects. The options and implications are covered in detail. However, a nonspecialised reader need not go too deeply into this section before proceeding.
- In Section 4, various aspects of converter harmonic generation are discussed, concentrating on those points which could be defined in the Technical Specification, and making recommendations intended to avoid difficulties encountered in previous projects. This section contains essential introductory material.
- In Section 5, the impact of harmonic interaction across the converter is discussed. Recommendations are made as to how this phenomenon should be treated in the practical context of an HVDC project design.
- A brief review of many different a.c. filter configurations is given in Section 6, along with lists of advantages and disadvantages. As well as being of value as a reference, this information may be used in the evaluation of proposed filter solutions.
- The central question of how to calculate a.c. filter performance is treated in Section 7, which brings together various strands from other sections. The definition of a.c. system harmonic impedance is of crucial importance to the filter design, and this section shows the various options available and discusses the relative merits of each.
- The specification and design of a.c. filtering equipment is closely linked to the other main function of a.c. filters, which is to provide reactive compensation. The specified requirements on reactive compensation, and how these will influence the cost and complexity of the filter design, are covered in Section 8.
- Sections 9, 10 and 11 define how the steady-state rating, the transient rating, and the losses of a.c. filters are to be calculated, and what should be specified in this respect.
- Numerous aspects of valuable practical experience are brought together in Section 12, which discusses special areas of design not covered elsewhere in the document and what influence these aspects could have on a Specification. This section will be of value particularly to those with an in-depth knowledge of the subject
- Section 13 covers aspects of a.c. filter protection, providing sufficient information to enable an evaluation to be made of particular proposed protection schemes
 - Sections 14 and 15 deal with the specialised areas of seismic design and audible noise, which in some instances can have a significant impact on the physical design, cost and layout of an a.c. filter installation.
 - A summary of all the important parameters and requirements which must be specified by the Customer in a Technical Specification, is given in Section 16. This summary lists the key points which have been discussed in depth elsewhere in the Guide, and makes suitable cross-references.
 - Section 17 contains a detailed description of what should be specified regarding the detailed design and testing of each item of filter equipment.
 - Field measurements, and verification that the specified performance is achieved in service, are discussed in Section 18, which concentrates on those aspects which need to be clearly defined in the Technical Specification in order to avoid subsequent contractual conflict.
 - Finally, the expected impacts of new technologies in the fields of HVDC converters and a.c. filters are discussed in Section 19.

In some sections, detailed background material and equations have been set aside in small Appendices.

A substantial list of references is included, in Section 20.

1. INTRODUCTION AND OBJECTIVES



1.1 General

This document is a Guide to the specification and design evaluation of a.c. side harmonic performance and a.c. side filters for HVDC schemes. It is intended to be primarily for the use of the utilities and consultants who are responsible for issuing the Technical Specifications for new HVDC projects and evaluating designs proposed by prospective suppliers.

1.2 Definitions

The term "Technical Specification" or "Specification" used in this Guide is taken to mean the document which defines the overall system requirements for the a.c. filters and the a.c. system environment in which they have to operate. Such a document is normally issued by utilities to the prospective HVDC manufacturers. It also ensures the uniformity of proposals and sets guidelines for the evaluation of bids. The term as used here does not refer to the detailed engineering specifications relating to individual items of equipment, which are prepared by the HVDC manufacturer as a result of the filter tesign process.

The Technical Specification defines the technical basis for a contract between two parties, who in this Guide will be referred to as the "Customer" and the "Contractor".

- The "Customer" is the organisation which is purchasing the HVDC converter station, including the a.c. filters. The term "Customer" is taken to cover similar terms which may be used in specifications, such as Owner, Client, Buyer, Utility, User, Employer and Purchaser, and also covers a Consultant representing the Customer.
- The "Contractor" has the overall responsibility for delivery of the HVDC converter station, including the a.c. filters, as a system, and may in turn contract one or more sub-suppliers of individual items of equipment. The term "Contractor" is taken to cover similar terms which may be used in specifications, such as Manufacturer, or Supplier.

Where the context clearly refers to the pre-contract stage of a project, the word "Bidder" has been used instead of "Contractor", to indicate a prospective Contractor or Tenderer.

1.3 Introduction

When installing an HVDC converter station in an a.c. system, the way in which it may affect the quality of power supply in that system is always an important issue. One of the main power quality topics is that of harmonic performance

The a.c. side current of an HVDC converter has a highly non-sinusoidal waveform, and, if allowed to flow in the connected a.c. system, might produce unacceptable levels of distortion. A.C. side filters are therefore required as part of the total HVDC converter station, in order to reduce the harmonic distortion of the a.c. side current and voltage to acceptably low levels.

HVDC converters also consume substantial reactive power, a large proportion of which must normally be supplied locally within the converter station. Shunt connected a.c. filters appear as capacitive sources of reactive power at fundamental frequency, and normally in conventional HVDC schemes the a.c. filters are used to compensate most or all of the reactive consumption of the converter. Additional shunt capacitors and reactors may also be used to ensure that the desired reactive balance is maintained within specified limits under defined operational conditions.

The design of the a.c. filters therefore normally has to satisfy these two requirements of harmonic filtering and reactive power compensation, for various operational states and load levels. Optimisation of this design is the task of the a.c. filter designer, and the constraints under which the design is made are defined in the Technical Specification.

The a.c. filters form a substantial part of a conventional HVDC converter station. The fundamental reactive power rating of the a.c. filters (including shunt capacitors where applicable) at each converter station has

typically been in the range of 50% - 60% of the active power rating of the scheme. Together with the required switchyard equipment, the a.c. filters can occupy over half of the total land requirements of an HVDC scheme. The cost of manufacture, installation and commissioning of the a.c. filter equipment is significant, being typically in the approximate range of 10% of the total station costs. In addition, the filter design studies can be extensive and may have an impact on many other aspects of station design [Ref. 1-1, 1-2] and on the total project schedule. Once in operation, the a.c. filters will continue to have a major importance due to requirements for switching, maintenance, component spares, and reliability.

It is therefore important that the way in which the requirements for the a.c. filters are specified is such as to allow the design to be optimised in terms of all the above factors, while fulfilling the essential functions of disturbance mitigation and reactive power compensation.

The scope of this Guide covers a.c. side filtering for the frequency range of interest in terms of harmonic distortion and audible frequency disturbances. It excludes filters designed to be effective in the PLC and radio interference spectra.

1.4 Past experience

In practice, there have been few problems of harmonic disturbance from HVDC schemes and few problems relating to a.c. filter equipment in operation. Section 12 discusses some application problems, while analyses of some filter reactor failures may be found in Ref. 1-3. Further information on experience with existing a.c. filter schemes is available through the "HVDC Users' Group".

This past experience indicates that designs in general have been at least adequate. However, it is not obvious to what extent this satisfactory experience might indicate that a.c. filters in some instances may have been over-designed, and that a more economical design might have been possible.

One of the fundamental problems in specifying a.c. filters is that some of the essential design data is not readily available. The harmonic impedance of the a.c. system is of paramount importance to the design, and yet is difficult to measure or calculate for all operational conditions, both at present and during the future operational life of the scheme. The level of existing harmonic distortion to be considered is another factor which is difficult to measure or predict, as is the extent to which existing or future telecommunication systems may be affected by harmonic currents flowing in the a.c. network. The tolerance to harmonics of existing and future equipment such as motors and electronic loads, connected to the power system itself, is also difficult to evaluate.

Other factors affecting the filter design have, in the past, been difficult to calculate accurately with the available tools. Most prominent of these is the effect of the harmonic interaction between the a.c. and d.c. sides of the converter which, while well understood in theory, has been difficult to incorporate consistently into the design process.

One important aspect of the filtering scheme is the eventual ease of operation. Complex switching schemes with several different types and sizes of a.c. filter bank may fulfil rigorous requirements on performance and reactive power exchange, but the practical consequences and costs of lifetime operation should also be considered.

Historically, there has been a wide variation in the content and requirements of Technical Specifications of a.c. filters for different HVDC projects. There have developed several near-standard types of specification, associated with certain utilities and consultants, but even these are adapted to suit individual projects.

1.5 Objectives

In preparing this Guide, CIGRÉ Working Group 14.30 has attempted to:

- examine previous a.c. filter specifications and consider relative merits,
- consider field experience and draw conclusions,
- review results of previous and current CIGRÉ work on voltage and current limits, on a.c. system modelling, and on a.c./d.c. harmonic interaction and consider how the recommendations resulting from this work can usefully be incorporated in future specifications for HVDC projects,
- take note of other relevant work in CIGRÉ and the IEEE,
- examine how particular aspects of specification can have a significant influence on the design and costs,
- look forward to the likely impact of new technologies, both in the HVDC field and in related areas such as telephone technology,
- make recommendations based on all of the above,
- provide information to facilitate reasoned decisions in the preparation of future Technical Specifications and the evaluation of prospective designs.

In doing so, the Working Group sought to bring together the experience, and consider the interests, of all sectors of the HVDC community and to produce a Guide which, while primarily intended for the use of utilities and consultants, will be of interest to all parties.

1.6 Approach

The Guide attempts to review all possible aspects to be covered in a specification and the subsequent design evaluation, and to give a more detailed analysis of critical or contentious points.

The technical background to each subject area is described briefly, and reference made to further sources of information, in order to provide the background and context for the decisions to be made.

Where it is possible to make clear recommendations, these are given in the Guide. In other instances, where there may be different ways to approach some aspect, then the different approaches and their consequences are described. The intention in such instances is to enhance awareness of the implications of different possible approaches.

The Guide gives a comprehensive treatment of most aspects of the subject. This does not imply that a Technical Specification needs to mention all the aspects included in this Guide. In some circumstances a simple and open Specification may be preferable. However, while preparing any Specification, those responsible should at least be aware of, and consider, all the points discussed in this Guide. In the eventual design evaluation phase, most of the material included in this Guide will be of relevance.

New technologies which are currently being introduced into HVDC systems will, where applied, substantially alter many aspects of a.c. filter design. Foremost of these are the series compensated converter, the automatically continuously tuned reactor, and active filters.

To introduce throughout this Guide the radically different approaches which such new technologies require, would have led to a clumsy presentation. Instead, the bulk of the Guide concentrates on the "conventional" a.c. filter technology and current-source line-commutated HVDC converters. Discussion of the changes entailed by new technologies is treated exclusively in Section 19. Other unusual applications, such as series filters, which use conventional technology but are only employed in very specific circumstances, are discussed in Section 12.

2. GENERAL ASPECTS OF SPECIFICATIONS

2.3 Scope of	ries of responsibilityf studies	
2.5 Technic	f supplyal data to be supplied by Contractortive proposals by Bidders	
Appendix 2.1	Alternative type of procurement procedure	
	iTexxn(aco	
	(https://stapakkax.i	teh.ai)
	Culled Previ	
	1 C A.S 62001:2004 of estanded size / 5 942183-673a-4202-	
^		
_ (`		