
Razprševalna in brizgalna oprema za prekrivne materiale - Varnostne zahteve

Atomising and spraying equipment for coating materials - Safety requirements

Spritz- und Sprühgeräte für Beschichtungsstoffe - Sicherheitsanforderungen

Equipements d'atomisation et de pulvérisation pour produits de revêtement - Exigences de sécurité

(standards.iteh.ai)

Ta slovenski standard je istoveten z: EN 1953:1998

<https://standards.iteh.ai/catalog/standards/sist/e31ac8e6-afed-4ed2-bfe6-a2a35c52016d/sist-en-1953-2000>

ICS:

87.100	Oprema za nanašanje premazov	Paint coating equipment
--------	------------------------------	-------------------------

SIST EN 1953:2000**en**

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

SIST EN 1953:2000

<https://standards.iteh.ai/catalog/standards/sist/e31ac8e6-afed-4ed2-bfe6-a2a35c52016d/sist-en-1953-2000>

ICS 87.100

Descriptors: safety of machines, sprayers, coatings, liquids, pastes, powdery materials, safety requirements, accident prevention, definitions, hazards, safety measures, utilization, information, marking

English version

Atomising and spraying equipment for coating materials - Safety requirements

Equipements d'atomisation et de pulvérisation pour
produits de revêtement - Exigences de sécurité

Spritz- und Sprühgeräte für Beschichtungsstoffe -
Sicherheitsanforderungen

This European Standard was approved by CEN on 4 September 1998.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 1953:2000

<https://standards.iteh.ai/catalog/standards/sist/c31ac8e6-afed-4ed2-bfe6-a2a35c52016d/sist-en-1953-2000>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Contents	Page
Foreword	4
0 Introduction	4
1 Scope	4
2 Normative References	5
3 Definitions	6
3.1 General	6
3.2 atomising and spraying equipment	6
3.3 safety devices	6
3.4 electrostatic atomising and spraying equipment	6
3.5 hand-held atomising and spraying equipment	6
3.6 automatic atomising and spraying equipment	6
3.7 coating material	7
3.8 flammable coating material	7
3.9 non-flammable coating material	7
3.10 fire	7
3.11 explosion	7
3.12 explosion range	7
3.13 lower explosion limit (LEL)	7
3.14 chemical reaction	7
3.15 maximum working pressure	7
3.16 burst pressure	7
3.17 proof pressure	7
3.18 functional test	7
3.19 type test	8
4 List of Hazards	8
4.1 General	8
4.2 Mechanical hazards	8
4.3 Electrical hazards	8
4.4 Thermal hazards	8
4.5 Noise hazards	8
4.6 Vibration hazards	8
4.7 Fire and explosion hazards created by atomised and sprayed coating materials	9
4.8 Health hazards created by atomised and sprayed coating materials	9
4.9 Hazards created by malfunction of any part of the equipment	9
4.10 Hazards created by missing safety relevant measures	9
5 Safety Requirements	10
5.1 General	10
5.2 Mechanical Safety Requirements	10
5.3 Electrical Safety Requirements	10
5.4 Safety Requirements Relating to Thermal Effects	10
5.5 Safety Requirements Relating to Noise	11
5.6 Safety Requirements Relating to Vibration	11
5.7 Safety Requirements Relating to Fire and Explosion due to Atomised Coating Materials	11
5.8 Safety Requirements Related to Health due to Atomised and Sprayed Materials	11
5.9 Safety Requirements Relating to Malfunction	11
5.10 Requirements Relating to Missing Safety Relevant Measures	11
6 Compliance with the Safety Requirements	11
6.1 General	11
6.2 Compliance with mechanical safety requirements	11
6.3 Compliance with electrical safety requirements	12
6.4 Compliance with thermal safety requirements	12
6.5 Compliance with safety requirements relating to noise	12
6.6 Compliance with safety requirements relating to vibration	12
6.7 Compliance with safety requirements relating to fire and explosion due to atomised coating materials	12



6.8 Compliance with safety requirements relating to health due to atomised and sprayed coating materials	12
6.9 Compliance with safety requirements relating to malfunction.....	12
6.10 Compliance with the requirements relating to missing safety relevant measures	12
7 Information for Use	12
7.1 Operation Manual	12
7.2 Marking	13
Annex A (informative) Literature.....	14
Annex B (informative) National references to exposure limit values	15
Annex ZA (informative) Relationship of the European Standard with EU Directives.....	16

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 1953:2000

<https://standards.iteh.ai/catalog/standards/sist/e31ac8e6-afed-4ed2-bfe6-a2a35c52016d/sist-en-1953-2000>

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 271 "Surface treatment equipment - Safety", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 1999, and conflicting national standards shall be withdrawn at the latest by March 1999.

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this standard.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

0 Introduction

This European Standard is a type C standard as stated in ENV1070.

This European Standard forms part of a series of standard specifying the health , safety and environmental protection requirements for devices , units and equipment for surface coating .

- Atomising and Spraying Equipment for Coating Materials
- Machinery for the Supply and Circulation of Coating Materials Under Pressure
- Mixing machinery for Coating Materials

The equipment concerned and the extent to which hazards are covered is indicated in the scope of this standard . The equipment shall comply , as appropriate , with EN292-1 and EN292-2 for hazards which are not covered by this standard .

1 Scope

This European Standard applies to the design and construction of spraying equipment for both manual and automatic application of liquid , paste (semi-solid) and powder coating materials . The manual equipment is hand-held and the automatic equipment is operated by auxiliary signals and mounted either rigidly or onto automated devices such as robots , or reciprocating or rotary machines .

The coating material may be atomised by air , by airless , by airless with the assistance of air or mechanically by centrifugal force . With atomisation by centrifugal force , the atomised coating material may be assisted towards the workpiece by controlled air veils .

The atomising and spraying equipment may also be electrostatically supported .

This standard specifically refers to hazards created by or resulting from the use of atomising and spraying equipment, if it is used as determined and in accordance with the foreseeable conditions of the manufacturer (see clause 4) .

Atomising and spraying equipment may be linked with supply systems , control circuits , spray booths and/or automated machinery , none of which are covered by the scope of this standard . This may result in the overlapping of some hazards or risks . Such hazards or risks should be taken into consideration when specifying and installing the atomising and spraying equipment .

Further topics for this standard are minimum user information :

- Operation manuals
- Marking

This standard excludes :

- Flocking machines
- Equipment related to the atomising and spraying of foodstuffs and pharmaceuticals
- Artists airbrushes
- Machinery for the supply and/or circulation of coating materials under pressure
- Automated devices such as robots , reciprocating or rotary machines .

This standard applies to equipment constructed after the date of issue of this standard .

2 Normative References

This European Standard incorporates , by dated or undated reference , provisions from other publications . These normative references are cited at appropriate places in the text and the publications are listed hereafter .

For dated references , subsequent revisions of any of these publications apply to the European Standard only when incorporated in it by amendment or revision . For undated references , the latest edition of the publication referred to applies .

EN292-1:1991	Safety of Machinery - Basic Concepts , General Principles for Design Part 1 : Basic Terminology , Methodology .
EN292-2:1991 +A1:1995	Safety of Machinery - Basic Concepts , General Principles for Design Part 2 : Technical Principles and Specification
EN349	Safety of Machinery - Minimum gaps to avoid crushing of parts of the humanbody
EN563	Safety of Machinery - Temperature of touchable surfaces : Ergonomic data to establish limit values for hot surfaces
EN614-1	Safety of Machinery - Ergonomic design principles Part 1 : Terminology and General Principles
EN971-1	Paints and Varnishes : Terms and definitions for coating materials Part1: General Terms
CR1030-1	Hand-arm vibration : Guidelines for vibration hazard reduction Part 1 : Engineering methods by design of machinery
ENV1070	Safety of Machinery - Terminology
EN1127-1	Safety of Machinery - Fire and explosion Part1: Explosion prevention and protection
ISO/TR11688-1	Acoustics - Recommended practice for the design of low noise machinery and equipment - Part 1: Planning
ENV26385	Safety of Machinery - Ergonomic principles of the design of work systems
EN50050	Electrical apparatus for potentially explosive atmospheres - Electrostatic hand-held spraying equipment
EN50053-1	Regulations for selection , installation and use of electrostatic atomising and spraying equipment for flammable coating materials - Part 1 : Electrostatic hand-held atomising and spraying equipment for liquid spraying materials with an energy limit of 0.24 mJ including accessories .
EN50053-2	Regulations for selection , installation and use of electrostatic atomising and spraying equipment for flammable coating materials - Part 2 : Electrostatic hand-held atomising and spraying equipment for powder materials with an energy limit of 5 mJ including accessories .
EN50059:1990	Electrostatic hand-held atomising and spraying equipment for non-flammable liquid coating materials

EN50176	Automatic electrostatic spraying installations for flammable liquid coating materials
EN50177	Automatic electrostatic spraying installations for flammable powder spraying materials
EN60204-1	Safety of Machinery :Electrical equipment of machines Part 1 : General Requirements
EN60335-1	Safety of household and similar electrical appliances : Part 1 : General requirements

3 Definitions

For the purposes of this standard , the definitions apply from EN971-1 and ENV1070. For the purposes of this standard , the following definitions also apply :

3.1 General

The coating materials for use with the atomising and spraying equipment can either be delivered to the equipment by a pump or a pressure vessel via a supply hose or by an integrated gravity or suction cup .

For atomising and spraying equipment fitted with a gravity or suction cup only compressed air is supplied to the equipment and the coating material either flows from the gravity cup or is sucked from the suction cup .

Atomising and spraying equipment which has the coating material supplied via a hose from a pump or pressure vessel may also be supplied with compressed air .

The coating material is emitted from the atomising and spraying equipment via a valve which is controlled either manually by the trigger or automatically by auxiliary energy from an actuator system .

3.2 atomising and spraying equipment

Any type of device which can be used to atomise coating materials . Atomisation may be achieved by air , hydromechanically (airless) with or without air assistance , or by centrifugal forces such as rotating bells or discs .

Note : Atomising and spraying equipment (either manual or automatically operated) normally consists of a gun body , a coating material valve either located inside the body or integrated with it and a trigger mechanism which operates the valve .

3.3 safety devices

Devices for atomising and spraying equipment which aim to prevent the unintended spraying of a coating material . Safety devices of this type are such as , but not limited to :

- Trigger guards
- Trigger locking devices
- Fluid needle locking mechanisms

3.4 electrostatic atomising and spraying equipment

Equipment used for the atomising and spraying of coating materials with the assistance of an electrostatic charge .

Such equipment can be fitted with a high voltage generator ,located either outside the equipment or integrated with it , a high voltage electrode , power lines and an earth connection .

For powder coating materials the electrostatic charge can be achieved by flow friction (tribocharging) only .

3.5 hand-held atomising and spraying equipment

Equipment operated manually and triggered by hand for the application of coating materials onto a workpiece .

3.6 automatic atomising and spraying equipment

Equipment operated by auxiliary signals which may be electrical , pneumatic or hydraulic , excluding any other equipment associated with automated devices .

These auxiliary signal normally trigger a valve which operates the equipment .

Note : Automatic atomising and spraying equipment may be mounted either rigidly or on automated equipment such as robots or reciprocating or rotary machines . They may spray continuously or be rapid triggered for a specific time when either the workpiece passes in front of it or it passes over the workpiece .

3.7 coating material

In accordance with EN971-1, a liquid , paste (semi-solid) or powdered product which , if applied to a substrate , forms a film which has protective , decorative or other specific properties. Such coating materials may consist of binding agents , pigments , colourings , fillers , solvents and other additives .

Such coating materials can be :

- varnishes
- paints
- synthetic resins
- patching compounds
- fillers
- floor coatings
- sealers and adhesives

3.8 flammable coating material

A substance which can be ignited by a sufficient ignition source and which can continue to burn after the ignition source has been removed or which can react in the form of an explosion

3.9 non-flammable coating material

In accordance with EN50059:1990 , a substance which , in any mixture with air , cannot be ignited by an ignition source of less than 500mJ

3.10 fire

A process of combustion , characterised by the emission of heat accompanied by the formation of smoke and/or flames

3.11 explosion

An abrupt oxidisation or decompression reaction producing an increase in temperature , pressure or in both simultaneously [EN 1127-1].

3.12 explosion range

The range of the concentration of a flammable substance in air within which an explosion can occur [EN 1127-1].

3.13 lower explosion limit (LEL)

The lower limit of the explosion range [EN 1127-1].

3.14 chemical reaction

Process where the coating material or any part of the coating material reacts with the materials of construction of the atomising and spraying equipment .

3.15 maximum working pressure

The highest pressure , indicated by the manufacturer , to which the equipment should be subjected during normal operation .

3.16 burst pressure

A pressure at which any part of the equipment may fail or crack .

3.17 proof pressure

A pressure which can be applied to the equipment without creating any deformation , leakage or other failure and which allows normal operation of the equipment after testing .

3.18 functional test

When the equipment is operated under normal operating conditions as laid down in the operation manual .