SLOVENSKI STANDARD

SIST EN 61966-8:2003

december 2003

Multimedia systems and equipment - Colour measurement and management - Part 8: Multimedia colour scanners (IEC 61966-8:2001)

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 61966-8:2003</u> https://standards.iteh.ai/catalog/standards/sist/57751635-a590-4556-97b4-7d2d4582a70e/sist-en-61966-8-2003

ICS 17.180.20; 33.160.60

Referenčna številka SIST EN 61966-8:2003(en)

© Standard je založil in izdal Slovenski inštitut za standardizacijo. Razmnoževanje ali kopiranje celote ali delov tega dokumenta ni dovoljeno

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 61966-8:2003</u> https://standards.iteh.ai/catalog/standards/sist/57751635-a590-4556-97b4-7d2d4582a70e/sist-en-61966-8-2003

EUROPEAN STANDARD

EN 61966-8

NORME EUROPÉENNE

EUROPÄISCHE NORM

May 2001

ICS 33.160.60; 35.180

English version

Multimedia systems and equipment -Colour measurement and management Part 8: Multimedia colour scanners (IEC 61966-8:2001)

Systèmes et appareils multimédia -Mesure et gestion de la couleur Partie 8: Numériseurs couleur (CEI 61966-8:2001) Multimediasysteme und -geräte -Farbmessung und Farbmanagement Teil 8: Multimedia-Farbscanner (IEC 61966-8:2001)

This European Standard was approved by CENELEC on 2001-04-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

https://standards.iteh.ai/catalog/standards/sist/57751635-a590-4556-

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

© 2001 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

Foreword

The text of document 100/192/FDIS, future edition 1 of IEC 61966-8, prepared by IEC TC 100, Audio, video and multimedia systems and equipment, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 61966-8 on 2001-04-01.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement
 (don) 2002-01-01
- latest date by which the national standards conflicting with the EN have to be withdrawn
 (dow) 2004-04-01

Annexes designated "normative" are part of the body of the standard. Annexes designated "informative" are given for information only. In this standard, annexes A, B and ZA are normative and annex C is informative. Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 61966-8:2001 was approved by CENELEC as a European Standard without any modification. (standards.iteh.ai)

<u>SIST EN 61966-8:2003</u> https://standards.iteh.ai/catalog/standards/sist/57751635-a590-4556-97b4-7d2d4582a70e/sist-en-61966-8-2003

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

Publication	Year	Title	<u>EN/HD</u>	Year
IEC 60050-845	1987	International Electrotechnical Vocabulary (IEV) Chapter 845: Lighting	-	-
IEC 61966-2-1	1999 iT	Multimedia systems and equipment - Colour measurement and management Part 2-1: Colour management - Default RGB colour space - sRGB (standards.iteh.ai)	EN 61966-2-1 EW	2000
CIE 15.2	1986	Colorimetry	-	-
ISO 5-4	1995 https:/	Photography - Density measurements Part 4: Geometric conditions for reflection density	0-4556-	-
ISO 9241-8	1997	Ergonomic requirements for office work with visual display terminals (VDTs) Part 8: Requirements for displayed colours	EN ISO 9241-8	1997
ISO 12641	1997	Graphic technology - Prepress digital data exchange - Colour targets for input scanners calibration	-	-
ISO 13655	1996	Graphic technology - Spectral measurement and colorimetric computation for graphic arts images	-	-
ISO/CIE 10527	1991	CIE standard colorimetric observers	-	-

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 61966-8:2003</u> https://standards.iteh.ai/catalog/standards/sist/57751635-a590-4556-97b4-7d2d4582a70e/sist-en-61966-8-2003

INTERNATIONAL STANDARD



First edition 2001-02

Multimedia systems and equipment – Colour measurement and management –

Part 8: Multimedia colour scanners iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 61966-8:2003</u> https://standards.iteh.ai/catalog/standards/sist/57751635-a590-4556-97b4-7d2d4582a70e/sist-en-61966-8-2003

© IEC 2001 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission3, rue de Varembé Geneva, SwitzerlandTelefax: +41 22 919 0300e-mail: inmail@iec.chIEC web site http://www.iec.ch



Commission Electrotechnique Internationale International Electrotechnical Commission Международная Электротехническая Комиссия





For price, see current catalogue

CONTENTS

Page

FO	REWO)RD	. 4			
INT	RODI	JCTION	. 6			
1	Scop	e and object	. 9			
2	Norm	ative references	9			
3	Terms and definitions					
4	Lette	rs and symbols	11			
5		litions				
5	5.1	General conditions				
	5.1 5.2					
6		Output digital image data				
0						
	6.1	Spectrophotometer				
	6.2	Spectroradiometer				
7	6.3	Specification of the target				
7	-	tral power distribution of the built-in light source				
	7.1	Characteristics to be measured				
	7.2	Measurement conditions. A.N.D.A.R.D. P.R.E.V.I.E.W.	15			
•	7.3 T	Presentation of results characteristics (standards.iteh.ai)	15			
8						
	8.1	Characteristics to be measured. <u>SIST EN 61966-8:2003</u>	17			
	8.2	Measurement conditions https://standards.iteh.ai/catalog/standards/sist/57751635-a590-4556-	17			
	8.3	Method of measurement 7d2d4582a70c/sist-en-61966-8-2003				
	8.4	Calculation of results				
	8.5	Presentation of results				
9	Inver	se tone characteristics	19			
9.1	Char	acteristics to be calculated	19			
	9.2	Method of calculation	19			
	9.3	Presentation of results	20			
10	Spec	tral responsivity characteristics	20			
	10.1	Characteristics to be measured	20			
	10.2	Measurement conditions	21			
	10.3	Method of measurement	21			
	10.4	Presentation of results	21			
11	Spati	al non-uniformity	25			
	11.1	Characteristics to be measured	25			
	11.2	Measurement conditions	25			
	11.3	Method of measurement	25			
	11.4	Presentation of results	27			
12	Mid-t	erm instability	28			
	12.1	Characteristics to be measured	28			
		Measurement conditions				
	12.3	Method of measurement	29			
	12.4	Presentation of results	29			
13	Large	e area spatial crosstalk	29			

13.1 Characteristics to be measured				
13.2 Measurement conditions				
13.3 Method of measurement				
13.4 Presentation of results				
Annex A (normative) Estimation of multiband of wavelength sensitivities				
A.1 Quantities to be estimated				
A.2 Input to the algorithm				
A.3 Output to the algorithm				
A.4 Internal variables of the algorithmA.5 Estimation algorithm				
A.5 Estimation algorithm Annex B (normative) Scanner model output data from estimated multiband	აა			
sensitivities	36			
Annex C (informative) Examples for the application of the spectral characteristics	37			
C.1 Calculation of the ICC profiles	37			
C.2 Calculation of an optimized conversion for sRGB colour space	37			
Bibliography	38			
Figure 1 – Specification of the target for characterization of multimedia colour				
scanners	13			
Figure 2 – Example of graphical representation of multiband spectral reflection of a colour patch	14			
Figure 3 – Scanning area and the points of measurement	15			
Figure 4 – Example of the normalized spectral power distribution of the built-in light				
source	10			
data	19			
Figure 6 – An example of multiband spectral responsivity, $s_{\rm R}$, $s_{\rm G}$ and $s_{\rm B}$				
Figure 7 – Example of reporting form of the overall multiband spectral responsitivity,				
$S_n s_{R_n}$, $S_n s_{G_n}$ and $S_n s_{B_n}$	25			
Figure 8 – Measurement points for spatial non-uniformity				
Figure 9 – Example of report of mid-term instability				
Figure 10 – Target for the measurement of spatial crosstalk				
rigule to - rarger for the measurement of spatial crosstalk	50			
Table 1 – Example of reporting form of a spectral table	14			
Table 2 – Example of multiband spectral characteristics of the light source	16			
Table 3 – Example of reporting form of the polynomial coefficients of the red, green				
and blue channel	10			
Table 4 – Example of reporting form of the polynomial coefficients of the red, green and blue channels	20			
Table 5 – Example of reporting form of the multiband responsitivity characteristics	22			
Table 6 – Reporting form for the measurement of spatial non-uniformity	28			
Table 7 – Reporting form for the measurement of spatial crosstalk				
Table 8 – Reporting form of average data and maximum crosstalk given by relative				
maximum differences and relative standard deviations of data in red, green and blue channels (8 bits per channel)	31			

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MULTIMEDIA SYSTEMS AND EQUIPMENT – COLOUR MEASUREMENT AND MANAGEMENT –

Part 8: Multimedia colour scanners

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense reh STANDARD PREVIEW
- Committees in that sense ch STANDARD PREVIEW
 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards 57751635-a590-4556-
- 6) Attention is drawn to the possibility that some of the elements of this international standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61966-8 has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/192/FDIS	100/218/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

IEC 61966 consists of the following parts, under the general title: Multimedia systems and equipment – Colour measurement and management:

- Part 1: General¹
- Part 2-0: Colour management in multimedia systems¹
- Part 2-1: Colour management Default RGB colour space sRGB
- Part 2-2: Colour management Extended RGB colour space sRGB64¹
- Part 2-3: Colour management Default YCC colour space sYCC¹
- Part 3: Equipment using cathode ray tubes
- Part 4: Equipment using liquid crystal display panels
- Part 5: Equipment using plasma display panels¹
- Part 6: Equipment used for digital image projection¹
- Part 7-1: Colour printers Reflective prints RGB inputs¹
- Part 7-2: Colour printers Reflective prints CMYK input¹
- Part 7-3: Colour printers Transparent prints¹
- Part 8: Multimedia colour scanners¹
- Part 9: Digital cameras
- Part 10: Quality assessment Colour image in network systems¹
- Part 11: Quality assessment Impaired video in network systems

Annexes A and B form integral parts of this standard.

Annex C is for information only. https://standards.iteh.ai/catalog/standards/sist/57751635-a590-4556-

The committee has decided that the contents of this publication will remain unchanged until 2003. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

¹ To be published.

INTRODUCTION

This introduction is intended to distinguish the field of application of ISO 12641 and IEC 61966-8.

In order to standardize the calibration procedure for input scanners used in the printing and prepress industry, ISO 12641 was published in 1997. This part of IEC 61966 targets colour scanners for multimedia applications by providing characterization data necessary for colour management in open multimedia systems. It characterizes any multimedia colour scanners for consumer use, typically being connected to personal computers so as to capture colour images and display the colour information, either locally or distributed worldwide.

In such applications, colour management is important. Any red – green – blue data should have their colorimetric attributes clearly specified. The characterization data reported from this part of IEC 61966 will be used for the calculation of equipment specific colorimetric characterization so that colour management in open systems can be conducted.

The capture of colour information in a prepress input scanner usually assumes that the source is a positive film (transparent) original. The second most common type of original is positive photographic printing paper (reflective). Recently, prepress input scanners can support various types of reflective originals in addition to printing paper and can also capture an image directly from a negative film, although this is not yet very common. Due to these circumstances, ISO 12641 was established for prepress digital data exchange corresponding to transparent and reflective originals. However, a standard colour target for transparent film negative originals has not yet been established.

Spectral sensitivity characteristics of prepress scanners are not derived from the calculation based on a special colour system or the spectral distribution of printing ink; but are base signals relatively close to the three primary colours (red, green, blue) acquired for calibration purposes. The characteristics ds of the tapte press ds in put 7 scanners -4 are guaranteed by the experience of the operator or the sophistication of the colour processing application so that subtle variations among the colours appear in the printed result. In fact, printing and prepress scanners have many settings that are made available to professional users, and the operator can control the input scanner characteristics in a non-linear fashion to suit their objectives. In older input scanners, these controls were part of the stand-alone scanner system itself. For the scanners of the printing industry, these controls are typically part of the colour processing application software which processes the signals after capture and transfers them to the general purpose computer (workstation or server). In other words, a highly experienced and skilled operator can adjust the settings to freely change scanner characteristics such as tone and colour separation as he desires. Furthermore, scanner characteristics can be changed to correct and compensate for the characteristics of the original image target, such as colour fogging, as well as absorb them, and the operator can even change scanner colour separation conditions (typically cyan, yellow, magenta and black) in anticipation of the later printing process so as to obtain the most feasible printed result. As such, on the site of the prepress scanner, good colour separation (reproduction) is and has been dependent on the skill of the operator.

All prepress input scanners show variation in colour sensitivity characteristics depending on types, manufacturers, manufactured time and condition. Prepress input scanners tend to show less variation than other general-purpose multimedia colour scanners because of their usage in critical colour capturing in a closed system in comparison with the worldwide open system such as the Internet. There has never been an attempt to standardize the colour characteristics of prepress input scanners put on the market by different manufacturers.

61966-8 © IEC:2001(E)

However, it is demanded that the printing process should produce essentially the same results from the same original regardless of the input scanner used. This demand has been accomplished by the skill of the operator. For this reason, the process of scanning, including colour processing for the raw data, should involve the human operator, and the total system be considered as one system. In this human-machine interaction system, the characteristics can be understood as unified or standardized.

Under these circumstances, and in consideration of the actual work process, ISO/TC 130 (Graphic technology) has established a method using a colour target as stipulated in ISO 12641 for prepress input scanner calibration that includes functions capable of handling colour changes accompanying local distortions in colour regions. These targets for both positive reflective material (photographic printing paper) and positive transmission material (photographic film) are implemented by the photographic manufacturers on their specific materials of their particular products.

Multimedia colour scanners for general use which are much less expensive in comparison with prepress input scanners, are available for small office/home office personal computers. Targets for scanning are not specified as in prepress input scanners. Images of natural objects such as the petals of violets, green plants or human skin will be most important. As many of the users of multimedia colour scanners are not colour experts, it is preferable to have an automatic system requiring minimal adjustment. The manufacturers of this type of colour scanner do not provide colorimetric specifications of the red – green – blue data obtained from their scanner on one hand. On the other hand, the data obtained from the multimedia colour scanner are easily compressible and compatible to the World Wide Web and anonymous users will use the colour information in colour reproduction without having available the specific features of the original generator.

(standards.iteh.ai)

Prepress scanners have been used for many years in the printing and prepress industry and an environment has already been created in which only prepress scanners meeting certain critical criteria are selected. This being the case, there is no need for a new evaluation of prepress input scanner performance. In such an environment, however, the maintenance of input scanner quality is important and it is necessary and sufficient to calibrate a scanner using the appropriate target. The internationally standardized target in ISO 12641 exists for this purpose.

However, open multimedia systems and composing equipment creates a new environment different from the conventional printing industry, and the colour scanners used for multimedia systems have not undergone a similar evaluation process in related industries. In the multimedia environment, it is assumed that multimedia colour scanners will be used for a variety of purposes. This means that the initially assumed environment will vary and the functions required for individual multimedia colour scanners will also vary. In other words, the multimedia colour scanners supplied to the market and bought by general users might be designed for different purposes and will not all assure the same quality and characteristics. This will not be the case if multimedia colour scanner specifications are unified in the future; however, there is currently no movement in this direction.

Therefore, it would be a great advantage to the general user, if he could evaluate the characteristics of the multimedia colour scanner he is about to buy and judge whether it suits his purpose. In other words, knowing the colour reproduction characteristics of each scanner before making a decision, would allow the user to select a multimedia colour scanner having characteristics suited to his purpose.

While there is hope that scanners used in a multimedia environment will undergo critical evaluation in the market over time, the ability to quantitatively evaluate the colour reproduction of such multimedia colour scanners would be of direct benefit to the critical issue of colour management that we now face.