

SLOVENSKI STANDARD SIST EN 12312-12:2003

01-november-2003

Podporna oprema na tleh za letalski promet – 12. del: Servisna oprema za pitno vodo

Aircraft ground support equipment - Specific requirements - Part 12: Potable water service equipment

Luftfahrt-Bodengeräte - Besondere Anforderungen - Teil 12: Trinkwasser-Servicegeräte (standards.iteh.ai)

Matériel au sol pour aéronefs - Exigences particulieres - Partie 12: Matériel d'alimentation en eau potable 9c2b134cf627/sist-en-12312-12-2003

Ta slovenski standard je istoveten z: EN 12312-12:2002

<u>ICS:</u>

49.100 Oprema za servis in vzdrževanje na tleh Ground service and maintenance equipment

SIST EN 12312-12:2003

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 12312-12:2003</u> https://standards.iteh.ai/catalog/standards/sist/93bfc59c-b8d1-445c-a1fa-9c2b134cf627/sist-en-12312-12-2003

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 12312-12

August 2002

ICS 49.100

English version

Aircraft ground support equipment - Specific requirements - Part 12: Potable water service equipment

Matériel au sol pour aéronefs - Exigences particulières -Partie 12: Matériel d'alimentation en eau potable Luftfahrt-Bodengeräte - Besondere Anforderungen - Teil 12: Trinkwasser-Servicegeräte

This European Standard was approved by CEN on 29 May 2002.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

SIST EN 12312-12:2003 https://standards.iteh.ai/catalog/standards/sist/93bfc59c-b8d1-445c-a1fa-9c2b134cf627/sist-en-12312-12-2003



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

© 2002 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. EN 12312-12:2002 E

Contents

		page	
Forewo	ord	3	
Introduction		4	
1	Scope	4	
2	Normative references	4	
3	Terms and definitions	5	
4	List of hazards	5	
5	Safety requirements and/or measures	5	
5.1	General requirements		
5.2 5.3	Tanks Water systems	••••••	
5.4	Workplaces		
6	Information for use	8	
6.1	Marking	8	
6.2	Additional marking	8	
6.3 6.4	Warnings	8 8	
7	Verification of requirements		
Anney	SIST EN 12312-12:2003 A (informative) Examples of potable water service equipment - 18d1-445e-al fermion	10	
	Annex B (normative) List of hazard 9c2b134cf627/sist-en-12312-12-2003		
Annex	Annex ZA (informative) Relationship of this document with EC Directives		
Bibliography		14	

Foreword

This document EN 12312-12:2002 has been prepared by Technical Committee CEN/TC 274 "Aircraft ground support equipment", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by February 2003, and conflicting national standards shall be withdrawn at the latest by February 2003.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EC Directive(s).

For relationship with EC Directives, see informative annex ZA, which is an integral part of this document.

The Parts of EN 12312 — Aircraft ground support equipment — Specific requirements — are:

- Part 1: Passenger stairs
- Part 2: Catering vehicles
- Part 3: Conveyor belt vehicles
- Part 4: Passenger boarding bridges
- Part 5: Aircraft fuelling equipment STANDARD PREVIEW Part 6: Deicers and deicing/antiicing equipment
- Part 7: Aircraft movement equipment (standards.iteh.ai)
- Part 8: Maintenance stairs and platforms
- Part 9: Container/Pallet loaders
- Part 10: Container/Pallet transfer transportersSIST EN 12312-12:2003
- Part 11: Container/Pallet dollies and loose load trailers dards/sist/93bfc59c-b8d1-445c-a1fa-
- Part 12: Potable water service equipment^{2b134ct627/sist-en-12312-12-2003}
- Part 13: Lavatory service equipment
- Part 14: Disabled/Incapacitated passenger boarding equipment
- Part 15: Baggage and equipment tractors
- Part 16: Air start equipment
- Part 17: Air conditioning equipment
- Part 18: Nitrogen or Oxygen units
- Part 19: Aircraft jacks, axle jacks and hydraulic tail stanchions
- Part 20: Ground power equipment

Annex A is informative and annex B is normative.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

Introduction

This European Standard specifies health and safety requirements, as well as some functional and performance requirements for potable water service equipment intended for servicing all aircraft types commonly in service in civil air transport.

The minimum essential criteria are considered to be of primary importance in providing safe, serviceable, economical, and practical potable water service equipment. Deviations from the recommended criteria should occur only after careful consideration, extensive testing, risk assessment and thorough service evaluation have shown alternative methods or conditions to be satisfactory.

This European Standard is a Type C standard as stated in EN 1070:1998.

1 Scope

This European Standard specifies the technical requirements to minimise the hazards listed in clause 4 which can arise during the commissioning, operation and maintenance of potable water service equipment when carried out in accordance with the specifications given by the manufacturer or his authorised representative. It also takes into account some requirements recognised as essential by authorities, aircraft and ground support equipment (GSE) manufacturers as well as airlines and handling agencies.

This standard applies to:

- self-propelled potable water vehicles; eh STANDARD PREVIEW
- towable potable water vehicles;
- moveable parts of ramp integrated systems,

designed for servicing aircraft and intended to be used under the conditions given in clause 1 of EN 1915-1:2001 (Examples see annex A). 9c2b134cf627/sist-en-12312-12-2003

(standards.iteh.ai)

This standard does not establish requirements for hazards caused by noise and vibration.

This Part of EN 12312 is not applicable to potable water service equipment which is manufactured before the date of publication of this standard by CEN.

Normative references 2

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text, and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

EN 292-2:1991/A1:1995, Safety of machinery - Basic concepts, general principles for design - Part 2: Technical principles and specifications.

EN 954-1:1996, Safety of machinery - Safety-related parts of control systems - Part 1: General principles for design.

EN 1050:1996, Safety of machinery - Principles for risk assessment.

EN 1070:1998, Safety of machinery - Terminology.

EN 1837:1999, Safety of machinery - Integral lighting of machines.

EN 1915-1:2001, Aircraft ground support equipment - General requirements - Part 1: Basic safety requirements.

EN 1915-2:2001, Aircraft ground support equipment - General requirements - Part 2: Stability and strength requirements, calculations and test methods.

EN 10088-1:1995, Stainless steels - Part 1: List of stainless steels.

ISO/DIS 17775:-¹⁾, Aircraft — Ground service interfaces — Potable water, toilet flush water and toilet drain.

3 Terms and definitions

For the purposes of this European Standard, the terms and definitions given in EN 1070:1998 and EN 1915-1:2001 together with the following apply.

3.1

potable water service equipment

ground support equipment (GSE) for servicing aircraft with potable water by means of a pump

3.2

potable water vehicle

self-propelled or towable potable water service equipment

3.3

open work material flooring material for standing areas with openings to allow self-draining and cleaning (standards.iteh.ai)

4 List of hazards

SIST EN 12312-12:2003

The list of risks and hazards (see annex B) is based on EN 1050 1996 and contains the hazards and hazardous situations, as far as they are dealt with in this European Standard, identified by risk assessment as significant for potable water service equipment and which require action to eliminate or reduce risks. Not covered are risks and hazards due to a standard automotive chassis, the traffic, maintenance and repair and general misuse.

5 Safety requirements and/or measures

5.1 General requirements

5.1.1 Potable water service equipment shall conform to the relevant requirements of EN 1915-1:2001, unless otherwise specified in this standard. They shall also conform to the specific requirements of this standard.

5.1.2 Stability and strength calculations shall be carried out in accordance with EN 1915-2:2001.

5.1.3 The connection to the aircraft system shall meet the requirements of ISO/DIS 17775:-¹).

5.1.4 Where the potable water service equipment is intended to be moved on public roadways, the dimensions, laden mass and other characteristics shall meet all applicable governmental regulations.

NOTE Applicable governmental regulations are dependent on the airport of use.

¹⁾ First edition in preparation at time of publication of this standard

5.1.5 The ground clearance shall allow without interference the transversing of two surfaces intersecting at an angle of \pm 3° (5 %) either in bridging or creating.

5.1.6 The height of the potable water vehicle shall allow the servicing of aircraft as intended by the manufacturer.

NOTE Parts of potable water vehicles intended to be driven underneath the aircraft should not be more than 1,60 m (63 in) above the ground (see clause 0 of EN 1915-1:2001 — negotiation). This might cause problems in fulfilling the requirements in ISO 3411:1995.

5.1.7 All parts of the water system shall be made of materials acceptable for use in connection with potable water. Where stainless steel is used, the material shall be acid resistant like quality No 1.4404 according to EN 10088-1:1995. All inside surfaces shall be pickled.

5.1.8 Self-propelled potable water vehicles shall be equipped with driver accommodation.

5.1.9 A working light shall be provided, e.g. for connection of hoses to the aircraft during night operations. The design and installation of the light shall conform to EN 1837:1999. The minimum electrical power of the lamp shall be 25 W.

5.1.10 Where it is intended to climb upon the vehicle during filling the tanks of the potable water vehicle adequate safety measures to prevent falling shall be taken. Where fixed guard rails cannot be installed, alternative safety measures shall be taken, e.g. filling from ground level, use of foldable or collapsible guard rails.

5.2 Tanks

5.2.1 For easy cleaning and disinfecting, tanks shall have the following features:

- a) all inside fittings, welds, joints and rivets shall have a smooth finishal)
- b) cylindrical ends shall be dished; <u>SIST EN 12312-12:2003</u>

https://standards.iteh.ai/catalog/standards/sist/93bfc59c-b8d1-445c-a1fa-

c) all inside corners of the tank shell shall have a radius of at least 10 mm (0,4 in);

d) the bottom of the tank shall have a minimum slope of 1° towards the drain point.

NOTE 1 Tanks can be equipped with system insulation and/or heating to protect water from freezing.

NOTE 2 An easily readable tank content level indicator, protected against mechanical damage can be installed.

5.2.2 Baffles shall be installed inside the tank, if the capacity is over 1 000 I to prevent surge of load while the potable water vehicle is driven.

5.2.3 Tanks shall have at least one raintight inspection hole with a minimum diameter of 400 mm (16 in) in the upper region to facilitate cleaning, disinfecting and inspection.

5.2.4 Tanks shall be fitted with raintight ventilating means.

5.2.5 Tanks shall be securely fitted to the chassis of the potable water vehicle, to avoid relative movement between tank and chassis, working loose, wear and tear.

5.3 Water systems

5.3.1 Where the pump is driven by a power take-off, it shall not be possible to operate the pump unless the vehicle's transmission is in neutral or park position and vice versa. The corresponding safety circuit shall be according to EN 954-1:1996, category B.

5.3.2 A shut-off valve shall be installed between tank and pump.

NOTE A filter can be installed between pump and water outlet and/or between tank and pump.

5.3.3 There shall be a relief valve to allow the pressure to be regulated according to the requirements of different aircraft types. The relief valve shall be adjustable easily, e.g. without using tools.

NOTE 1 Different types of pressure gauges can be fitted and should be easily readable.

NOTE 2 An aircraft water tank draining system can be installed.

5.3.4 Control devices shall be provided to allow the pump to be operated from the ground and, where fitted, from the work platform.

5.3.5 A meter, equipped with a zero reset, shall be provided to indicate the amount of water delivered to the aircraft.

5.3.6 Water hoses shall:

- be flexible;
- have an inside diameter of at least 19 mm (¾ in);
- enable servicing of the intended aircraft (see also clause 0 of EN 1915-1:2001 negotiation) and shall be equipped with a coupler at the delivery end;
- be made of material acceptable for use in connection with potable water.

NOTE A hose emptying system can be installed.

5.4 Workplaces

(standards.iteh.ai)

5.4.1 Fixed or vertically moving lifting/work platforms shall be provided on the potable water vehicle. This is not applicable for vehicles where it is possible to reach the service connections from ground level (see clause 0 of EN 1915-1:2001 — negotiation) standards. itch ai/catalog/standards/sist/93bfc59c-b8d1-445c-alfa-

9c2b134cf627/sist-en-12312-12-2003

5.4.2 The minimum load capacity of work platforms shall be 200 kg (441 lb).

5.4.3 The floor of work platforms shall be made of open-work material.

5.4.4 Control devices for raising and lowering of the platform and for filling shall be reachable from the platform.

5.4.5 Storage locations for hoses shall be installed close to the workplace, e.g. control devices.

NOTE 1 A self-rewinding or powered reel for the water hose can be installed.

NOTE 2 An interlock can be installed to prevent self-propelled vehicles from being moved when the hose coupling is not in a stowed position.

5.4.6 On potable water vehicles with lifting/work platform, the hoses shall be located so as to prevent risk of hose damage caused by the movement of the platform.

5.4.7 For lifting/work platforms an emergency lowering system with controls accessible from ground level shall be fitted, e.g. manually operated pump, manually activated valve.

5.4.8 An interlock shall be fitted to prevent the potable water vehicle from being moved with the lifting/work platform in an elevated position. The corresponding safety circuit shall be according to EN 954-1:1996, category 1 with galvanic separation switches or category 2 with proximity switches.