

7C 29

International Standard



7226

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Dimensions of hexagonal die nuts

Filières hexagonales de filetage à main

First edition — 1985-05-15

UDC 621.992.31

Ref. No. ISO 7226-1985 (E)

Descriptors : tools, hand tools, cutting tools, threading dies, dimensions.

Price based on 3 pages

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 7226 was prepared by Technical Committee ISO/TC 29, *Small tools*.

Dimensions of hexagonal dienuts

0 Introduction

Circular screwing dies are specified for certain thread forms in ISO 2568, ISO 4230 and ISO 4231. For certain sizes of these threads, it is convenient for some purposes to use hexagonal dienuts instead of circular dies and, for purposes connected with their manufacture and use, it is desirable that certain dimensions of the dienuts should be standardized.

1 Scope and field of application

This International Standard specifies the general dimensions of hexagonal dienuts for certain sizes of ISO metric threads (coarse and fine pitch series — see ISO 68 and ISO 261), ISO inch threads (UNC and UNF — see ISO 68 and ISO 263), and pipe threads (G and R series — see ISO 7/1 and ISO 228/1), as well as the non-preferred thread series BSW, BSF and BA.

2 References

ISO 7/1, *Pipe threads where pressure-tight joints are made on the threads — Part 1: Designation, dimensions and tolerances.*

ISO 68, *ISO general purpose screw threads — Basic profile.*

ISO 228/1, *Pipe threads where pressure-tight joints are not made on the threads — Part 1: Designation, dimensions and tolerances.*

ISO 261, *ISO general purpose metric screw threads — General plan.*

ISO 263, *ISO inch screw threads — General plan and selection for screws, bolts and nuts — Diameter range 0,06 to 6 in.*

ISO 2568, *Hand- and machine-operated circular screwing dies and hand-operated die stocks.*

ISO 4230, *Hand- and machine-operated circular screwing dies for taper pipe threads — R series.*

ISO 4231, *Hand- and machine-operated circular screwing dies for parallel pipe threads — G series.*

3 Dimensions and tolerances

See the figure, and tables 1 and 2.





Figure — Dimensions

Table 1 – General table of dimensional characteristics of hexagonal die nuts for metric and inch threads
(except R series pipe threads)

Range of thread diameter, <i>d</i>				<i>s</i> h13 mm	Metric pitches												
mm		in			0,35 0,70	0,73 0,81	0,90 1,00	1,25	1,50	1,75	2,00	2,50	3,00	3,50	4,00 4,50	5,00 5,50	
Over	Up to and including	Over	Up to and including		Number of threads per inch												
					48 40	36 32	28 24	22 18	16	14	13 12	11 10	9 8	7	6	5 4 1/2	
Cutting width, <i>E</i> (mm) <i>j</i> _s 13																	
2,65	4,00	0.104 3	0.157 5	18	5*	7											
4,00	6,35	0.157 5	0.250 0		7	7	7										
6,35	9,00	0.250 0	0.354 3	21	9	9	9										
9,00	11,20	0.354 3	0.440 9	27		11	11	11	11								
11,20	15,00	0.440 9	0.590 6	36			10*	10*	14	14							
15,00	21,20	0.590 6	0.834 6	41			14*	14*	14*	18	18						
21,20	26,50	0.834 6	1.043 3	50				16*	16*	16*	22	22					
26,50	37,50	1.043 3	1.476 4	60				18*	18*	18*	18*	25	25	25			
37,50	42,50	1.476 4	1.673 2	70				20*		20*	20*	30		30			
42,50	53,00	1.673 2	2.086 6	85				22*		22*	22*	36	36	36	36		
53,00	63,00	2.086 6	2.480 3	100				22*		22*	22*	36		36	36		

* These cutting widths, which are the lower of the two values specified for each range of thread diameter, may be increased to the higher value at the discretion of the manufacturer.