

# **SLOVENSKI STANDARD**

## **SIST EN ISO 2870:1997**

**01-december-1997**

---

**Površinsko aktivne snovi - Detergenti - Določanje anionsko aktivnih snovi, odpornih in neodpornih pri hidrolizi pod kislimi pogoji (ISO 2870:1986)**

Surface active agents - Detergents - Determination of anionic-active matter hydrolyzable and non-hydrolyzable under acid conditions (ISO 2870:1986)

Tenside - Waschmittel - Bestimmung von sauer hydrolysierbaren und nicht-hydrolysierbaren anionaktiven Anteilen (ISO 2870:1986)

Agents de surface - Détergents - Détermination de la matière active anionique hydrolysable et non hydrolysable en milieu acide (ISO 2870:1986)

<https://standards.iteh.ai/catalog/standards/sist/b1bcd164-19ce-4602-b564-60968f7bf681/sist-en-iso-2870-1997>

**Ta slovenski standard je istoveten z: EN ISO 2870:1994**

---

**ICS:**

71.100.40      Površinsko aktivna sredstva      Surface active agents

**SIST EN ISO 2870:1997**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN ISO 2870:1997

<https://standards.iteh.ai/catalog/standards/sist/b1bcd164-19ce-4602-b564-60968f7bf681/sist-en-iso-2870-1997>

EUROPEAN STANDARD

EN ISO 2870

NORME EUROPÉENNE

EUROPÄISCHE NORM

August 1994

UDC 661.185:543

Descriptors: surfactants, detergents, chemical analysis, determination of content, anionic-active matter, volumetric analysis

English version

**Surface active agents - Detergents -  
Determination of anionic-active matter  
hydrolyzable and non-hydrolyzable under acid  
conditions (ISO 2870:1986)**

Agents de surface - Détergents - Détermination  
de la matière active anionique hydrolysable et  
non hydrolysable en milieu acide  
(ISO 2870:1986)

Tenside - Waschmittel - Bestimmung von sauer  
hydrolysierbaren und nicht-hydrolysierbaren  
anionaktiven Anteilen (ISO 2870:1986)

(standards.iteh.ai)

SIST EN ISO 2870:1997

<https://standards.iteh.ai/catalog/standards/sist/b1bcd164-19ce-4602-b564-60968f7bf681/sist-en-iso-2870-1997>

This European Standard was approved by CEN on 1994-08-22. CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

The European Standards exist in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

**CEN**

European Committee for Standardization  
Comité Européen de Normalisation  
Europäisches Komitee für Normung

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

## Foreword

This European Standard has been taken over by the Technical Committee CEN/TC 276 "Surface active agents" from the work of ISO/TC 91 "Surface active agents" of the International Organization for Standardization (ISO).

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by February 1995, and conflicting national standards shall be withdrawn at the latest by February 1995.

According to the CEN/CENELEC Internal Regulations, the following countries are bound to implement this European Standard: Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom.

## Endorsement notice

The text of the International Standard ISO 2870:1986 was approved by CEN as a European Standard without any modification.

**(standards.iteh.ai)**

SIST EN ISO 2870:1997

<https://standards.iteh.ai/catalog/standards/sist/b1bcd164-19ce-4602-b564-60968f7bf681/sist-en-iso-2870-1997>

# International Standard



# 2870

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

## Surface active agents — Detergents — Determination of anionic-active matter hydrolyzable and non-hydrolyzable under acid conditions

*Agents de surface — Détergents — Détermination de la matière active anionique hydrolysable et non hydrolysable en milieu acide*

Second edition — 1986-05-01

(standards.iteh.ai)

SIST EN ISO 2870:1997

<https://standards.iteh.ai/catalog/standards/sist/b1bcd164-19ce-4602-b564-60968f7bf681/sist-en-iso-2870-1997>

UDC 661.185 : 543

Ref. No. ISO 2870-1986 (E)

Descriptors : surfactants, detergents, chemical analysis, determination of content, anionic-active matter, volumetric analysis.

Price based on 3 pages

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 2870 was prepared by Technical Committee ISO/TC 91, *Surface active agents*.

This second edition cancels and replaces the first edition (ISO 2870:1973), of which it constitutes a minor revision.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

# Surface active agents — Detergents — Determination of anionic-active matter hydrolyzable and non-hydrolyzable under acid conditions

## 1 Scope and field of application

This International Standard specifies a method for the determination, in detergents, of anionic-active matter hydrolyzable and non-hydrolyzable under acid conditions.

This active matter includes alkyl sulfates and hydroxysulfates and alkylphenol and fatty alcohol ethoxysulfates.

The mean relative molecular mass of the two types of active matter must be known or previously determined, if their content is expressed as a percentage by mass. If the detergent contains perborate, this must be destroyed before the hydrolysis.

## 2 References

ISO 607, *Surface active agents — Detergents — Methods of sample division*.

ISO 2271, *Surface active agents — Detergents — Determination of anionic-active matter (direct two-phase titration procedure)*.

## 3 Principle

Titration of an aliquot portion of a sample solution with benzethonium chloride solution according to the direct two-phase titration procedure specified in ISO 2271.

Hydrolysis, by refluxing under acid conditions, of a second aliquot portion of the sample solution after destruction, if necessary, of any perborate in the sample by the addition of sodium sulfite.

Titration of unhydrolyzed anionic-active matter with benzethonium chloride solution as before.

Calculation of the contents of hydrolyzable and non-hydrolyzable anionic-active matter from the results obtained.

## 4 Reagents

During the analysis, use only reagents of recognized analytical grade and only distilled water or water of equivalent purity.

In addition to the reagents mentioned in ISO 2271 and given below as a reminder:

**4.1 Chloroform**,  $\rho_{20}$  1,48 g/ml, distilling between 59,5 and 61,5 °C.

**4.2 Sulfuric acid**, 245 g/l solution.

**4.3 Sulfuric acid**, 49 g/l solution.

**4.4 Sodium hydroxide**, standard volumetric solution,  $c(\text{NaOH}) = 1,0 \text{ mol/l}$ .

**4.5 Sodium lauryl sulfate**, standard volumetric solution,  $c[\text{CH}_3(\text{CH}_2)_{11}\text{OSO}_3\text{Na}] = 0,004 \text{ mol/l}$ .

**4.6 Benzethonium chloride**, standard volumetric solution,  $c(\text{C}_{27}\text{H}_{42}\text{ClNO}_2 \cdot \text{H}_2\text{O}) = 0,004 \text{ mol/l}$ .

**4.7 Phenolphthalein**, 10 g/l ethanolic solution.

**4.8 Mixed indicator solution**.

the following reagents are necessary:

**4.9 Sulfuric acid**, 490 g/l solution.

**4.10 Sodium hydroxide**, 400 g/l solution.

**4.11 Sodium hydroxide**, 40 g/l solution.

**4.12 Sodium sulfite**, 20 g/l solution.

## ISO 2870-1986 (E)

## 5 Apparatus

Ordinary laboratory apparatus and

**5.1 Conical flask**, of capacity 250 ml, with a conical ground glass joint.

**5.2 Reflux condenser**, water-cooled, with a conical ground glass joint at the bottom, fitting on to the conical flask (5.1).

## 6 Sampling

The laboratory sample of detergents shall be prepared and stored in accordance with the instructions given in ISO 607.

## 7 Procedure

## 7.1 Test portion and test solution

Weigh, to the nearest 0,001 g, a sample which contains 3 to 5 milli-equivalents of anionic-active matter, and dissolve in 100 ml of water. Transfer the solution quantitatively to a 1 000 ml one-mark volumetric flask and dilute to the mark (test solution A).

## 7.2 Determination of total anionic-active matter

Carry out the determination of total anionic-active matter present in the sample by the procedure described in ISO 2271 on an aliquot portion of 25 ml of test solution A (7.1).

## 7.3 Determination of hydrolyzable anionic-active matter

By means of a pipette, transfer a second aliquot portion of 25 ml of the solution A (7.1) to the conical flask (5.1). Add, by means of a pipette, 5 ml of the sulfuric acid solution (4.9) and a few anti-bumping granules. [If the sample contains perborate, also add to the conical flask 10 ml of the sodium sulfite solution (4.12).]

Attach the water-cooled reflux condenser (5.2), well washed with water, to the conical flask and reflux for 3 h. Apply heat cautiously at the start to avoid excessive foaming.

At the end of the reflux period of 3 h, allow to cool, wash down the water-cooled reflux condenser well with at least 5 ml of water, detach the conical flask and wash the ground glass joint with a little water, collecting the washings in the conical flask.

Add a few drops of the phenolphthalein solution (4.7) and neutralize with the sodium hydroxide solution (4.10); add most of the sodium hydroxide solution at once and then complete the neutralization drop by drop with the sodium hydroxide solution (4.11).

Transfer 15 ml of the chloroform (4.1) and 10 ml of the mixed indicator solution (4.8) to the conical flask, stopper and shake well.

Titrate with the benzethonium chloride solution (4.6), as described in ISO 2271.

NOTE — The absence of non-hydrolyzable anionic-active matter after the hydrolysis may be checked by the addition of 1 ml of the benzethonium chloride solution (4.6). The pink coloured chloroform layer should not appear.

## 8 Expression of results

## 8.1 Calculations

## 8.1.1 Anionic-active matter hydrolyzable under acid conditions

The content, expressed as a percentage by mass, is given by the formula

$$\frac{(V_0 - V_1) \times c \times 1\,000 \times M_{r1} \times 100}{1\,000 \times 25 \times m}$$

$$= \frac{(V_0 - V_1) \times c \times M_{r1} \times 4}{m}$$

The molality, expressed in milli-equivalents per gram, is given by the formula

$$\frac{(V_0 - V_1) \times c \times 1\,000}{25 \times m}$$

$$= \frac{(V_0 - V_1) \times c \times 40}{m}$$

where the symbols have the meanings given in 8.1.2.

## 8.1.2 Anionic-active matter non-hydrolyzable under acid conditions

The content, as a percentage by mass, is given by the formula

$$\frac{V_1 \times c \times 1\,000 \times M_{r2} \times 100}{1\,000 \times 25 \times m}$$

$$= \frac{V_1 \times c \times M_{r2} \times 4}{m}$$

The molality, expressed in milli-equivalents per gram, is given by the formula

$$\frac{V_1 \times c \times 1\,000}{25 \times m}$$

$$= \frac{V_1 \times c \times 40}{m}$$