

SLOVENSKI STANDARD SIST EN 1791:1999

01-marec-1999

Površinsko aktivne snovi - Maščobni alkil dimetil amin oksidi - Določevanje vsebnosti amin oksida

Surface active agents - Fatty alkyl dimethyl amine oxides - Determination of the amine oxide content

Agents de surface - Oxydes d'alkyldiméthylamine grasses - Détermination de la teneur en oxyde d'amine

SIST EN 1791:1999

https://standards.iteh.ai/catalog/standards/sist/5438f794-7278-4a7c-80ec-

Ta slovenski standard je istoveten z: EN 1791-1999

ICS:

71.100.40 Površinsko aktivna sredstva Surface active agents

SIST EN 1791:1999 en

SIST EN 1791:1999

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 1791:1999

https://standards.iteh.ai/catalog/standards/sist/5438f794-7278-4a7c-80ec-64a504c4ba38/sist-en-1791-1999

EUROPEAN STANDARD

EN 1791

NORME EUROPÉENNE

EUROPÄISCHE NORM

February 1997

ICS 71.100.40

Descriptors:

surfactants, chemical analysis, determination of content, oxides, tertiary amines, titration, potentiometric methods

English version

Surface active agents - Fatty alkyl dimethyl amine oxides - Determination of the amine oxide content

Agents de surface - Oxydes d'alkyldiméthylamine archen aktive stoffe grasses - Détermination de la teneur en oxyde archen aktive stoffe - Bestimmung des d'amine

(standards.iteh.ai)

<u>SIST EN 1791:1999</u> https://standards.iteh.ai/catalog/standards/sist/5438f794-7278-4a7c-80ec-64a504c4ba38/sist-en-1791-1999

This European Standard was approved by CEN on 1997-01-05. CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

The European Standards exist in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization Comité Européen de Normalisation Europäisches Komitee für Normung

Central Secretariat: rue de Stassart,36 B-1050 Brussels

Page 2 EN 1791:1997

Contents

8.1 8.2	Calculation Precision	7
7.2 8	Polonovski reaction and titration of tertiary amine Expression of results	6
7 7.1	Procedure Titration of the sum : Amine oxide and tertiary amine	6
6	Sampling	5
5	Apparatus	
4	Reagents	
2	Normative references Principle	
1 .	Scope	
1.010	word	3

SIST EN 1791:1999 https://standards.iteh.ai/catalog/standards/sist/5438f794-7278-4a7c-80ec-64a504c4ba38/sist-en-1791-1999

Page 3 EN 1791:1997

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 276 "Surface active agents", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 1997, and conflicting national standards shall be withdrawn at the latest by August 1997.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

Annexes A and B are informative.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 1791:1999</u> https://standards.iteh.ai/catalog/standards/sist/5438f794-7278-4a7c-80ec-64a504c4ba38/sist-en-1791-1999 Page 4 EN 1791:1997

1 Scope

This draft European Standard specifies a method for the determination of up to approximately 2 milli-equivalents of tertiary amine oxide. Components which lose their basicity in reaction with acetic anhydride by forming an amide (e.g. primary and secondary amines) interfere. If present, these primary and secondary amines should be determined by a different procedure e.g. reaction with carbonsulfide.

The method is applicable to solids or to aqueous solutions of the active material. The molecular mass of the amine oxide shall be known if its content is expressed as a percentage of mass.

2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

ISO 607 Surface active agents and detergents. Methods of sample division

ISO 1042 1983 Laboratory glassware - One-mark volumetric flasks

3 Principle SIST EN 1791:1999 https://standards.iteh.ai/catalog/standards/sist/5438f794-7278-4a7c-80ec-

This draft European Standard is based on the Polonovski reaction in which the fatty alkyldimethylamine oxide reacts with acetic anhydride to form a N,N-disubstituted acetamide and an aldehyde (see equation 1). Free tertiary amine, residual raw material of technical amine oxide, remains unreacted and after dissolution of the sample in mixture of acetic acid and acetic anhydride 2:1 (as a volume fraction) is titrated with a perchloric acid solution (see equation 2). In this medium the acetamide is not titrated.

In a second titration the sum of amine oxide and tertiary amine is determined by potentiometric titration in acetic acid medium with a perchloric acid solution (see equation 3).

$$R - N(CH_3)_2 0 + (CH_3CO)_2 0 \rightarrow R - N(CH_3)COCH_3 + HCHO + CH_3COOH$$
 ...(1)

$$R - N(CH_3)_2 + HCIO_4 \rightarrow R - NH(CH_3)_2^+ CIO_4^-$$
 ...(2)

$$R - N(CH_3)_2 0 + R - N(CH_3)_2 + 2HCI0_4 \rightarrow R - N (CH_3)_2 0H^+CIO_4^- + R - NH(CH_3)_2^+CIO_4^- \qquad ...(3)$$

The difference between these two titrations (3 - 2) gives the amine oxide content.

4 Reagents

During the analysis, use only reagents of recognized analytical grade and only distilled water or water of equivalent purity.

- **4.1** Perchloric acid standard volumetric solution of known titre, c = 0,1 mol/l in acetic acid.
- 4.2 Acetic acid, glacial (purity 99 % as a mass fraction (minimum), density 1,05 g/ml at 20 °C).
- 4.3 Acetic anhydride (purity 99 % as a mass fraction (minimum), density 1,08 g/ml at 20 °C).

5 Apparatus

Ordinary laboratory apparatus and the following:

5.1 Recording potentiometer equipped with a 20 ml plunger burette and stirrer.

NOTE: An example of instrument settings is given in annex A. (standards.iteh.ai)

5.2 Combined glass electrode. SISTEN 1791:1999

https://standards.iteh.ai/catalog/standards/sist/5438f794-7278-4a7c-80ec-64a504c4ba38/sist-en-1791-1999

- **5.3 Magnetic stirrer** with electrically heated hot plate, capable of maintaining a temperature of (100 ± 5) °C.
- **5.4** Beaker, 150 ml capacity.
- 5.5 Measuring cylinder, 100 ml capacity.
- 5.6 Conical flask, 100 ml capacity.
- 5.7 Reflux condenser.
- 5.8 Analytical balance.

6 Sampling

The laboratory sample of the detergent shall be prepared and stored in accordance with instructions given in ISO 607.

Page 6 EN 1791:1997

7 Procedure

7.1 Titration of the sum : Amine oxide and tertiary amine

Weigh (m_1) , to the nearest 0,1 mg, a portion of the laboratory sample containing approximately 1,5 milli-equivalent of amine oxide into a 150 ml beaker (see 5.4).

Add 50 ml acetic acid (see 4.2) with a measuring cylinder (see 5.5) and dissolve the sample.

Place the beaker on the potentiometer (see 5.1) and insert a stirring bar.

Insert the combined glass electrode (see 5.2) and start stirring.

Titrate with the perchloric acid standard volumetric solution (see 4.1) until slightly beyond the potential jump and record the volume of perchloric acid solution necessary to reach equivalent point (V_1) (see annex B).

7.2 Polonovski reaction and titration of tertiary amine

Weigh (m_2), approximately 5 g to the nearest 10 mg of the laboratory sample into a conical flask (see 5.6). **Teh STANDARD PREVIEW**

Add 25 ml of acetic anhydride (see 4.3) with a measuring cylinder and dissolve the sample.

Insert a stirring bar, place the flask on the the hot plate (see 5.3) and connect the reflux condenser (see 5.7). SISTEN 1791:1999 https://standards.iteh.ai/catalog/standards/sist/5438f794-7278-4a7c-80ec-

Heat to the boiling point and maintain a moderate reflux for 10 min while stirring.

Cool to room temperature and add 50 ml of acetic acid.

Place the flask on the potentiometer (see 5.1).

Insert the combined glass electrode (see 5.2) and start stirring.

Titrate with the perchloric acid standard volumetric solution (see 4.1) until slightly beyond the potential jump and record the volume of perchloric acid solution necessary to reach the equivalent point (V_2) (see annex B).

8 Expression of results

8.1 Calculation

The amine oxide content (A) expressed as a percentage by mass is given by the following equation :

$$A = \left(\frac{V_1}{m_1} - \frac{V_2}{m_2}\right) \times C \times \frac{M \times 100}{1000} \%$$
 ...(4)

where:

- V₁ is the volume of the perchloric acid standard volumetric solution (see 4.1) necessary to reach the equivalence point in 7.1, in millilitres;
- V₂ is the volume of the perchloric acid standard volumetric solution necessary to reach the equivalence point in 7.2, in millilitres;
- m_1 is the mass of the laboratory sample, weighed in 7.1, in grams;
- m_2 is the mass of the laboratory sample, weighed in 7.2, in grams;
- C is the concentration of the perchloric acid standard volumetric solution;
- M is the mean molecular mass of the amine oxide.

8.2 Precision

8.2.1 Repeatability

0,8 % at a level of approximately 31 % tertiary amine oxide.

In the normal and correct operation of the method, the difference between two individual results obtained within the shortest feasible time interval by the same operator using the same apparatus and identical test material will exceed the repeatability value on average not more than once in 20 cases.

8.2.2 Reproducibility

0,9 % at a level of approximately 31 % tertiary amine oxide.

In the normal and correct operation of the method, individual results obtained by two different laboratories using identical test material will differ by more than reproducibility value on average not more than once in 20 cases.