

INTERNATIONAL STANDARD

ISO
7319

Second edition
1992-12-15

Aerospace — Fluid systems — Interface of 24° cone metric couplings

*Aéronautique et espace — Systèmes de fluides — Interface des
raccordements métriques à cône de 24°*
(standards.iteh.ai)

ISO 7319:1992

<https://standards.iteh.ai/catalog/standards/sist/c5238f05-3ca7-4856-88cb-9a62fcc757cc/iso-7319-1992>



Reference number
ISO 7319:1992(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 7319 was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Sub-Committee SC 10, *Aerospace fluid systems and components*.

This second edition cancels and replaces the first edition (ISO 7319:1982), the figure of which has been technically revised.

Annex A of this International Standard is for information only.

© ISO 1992

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Aerospace — Fluid systems — Interface of 24° cone metric couplings

1 Scope

This International Standard defines the geometry of the interface of removable 24° cone couplings for fluid systems in aircraft. The connection with the pipe of each one of the connecting elements may be of different design.

This International Standard specifies the dimensions which allow the interchangeability of the male and female elements and of the nut used for the connection.

The dimensions define the maximum volume of the male fitting.

2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 5855-3:1988, *Aerospace — MJ threads — Part 3: Limit dimensions for fittings for fluid systems.*


3 Coupling assembly and sealing principle

The coupling comprises three elements as follows.

- a) A female element including a frustum with a cone angle equal to 24°, with which the male element comes into contact to provide sealing. The contact line is a circle with a theoretical diameter, E .
- b) A male element, included inside a shell composed of two frustums connected by a spherical section with which the female element comes into contact to provide sealing. The contact line is a circle with a theoretical diameter, E .
- c) A nut allowing assembly of the male and female elements of the coupling.

4 Dimensions


The dimensions shall be as shown in figure 1 and given in table 1.



Female element

Nut

Male element



- Key**
- Point a: origin at $E/2$ from the XX' axis
 - Point b: point located at a distance R from point a, on the perpendicular to the line tilted 12° relative to XX' and passing through point a
 - Point c: located at $B/2$ from the XX' axis and at a distance P from point a
 - Line cd: tangent drawn from c to the arc of the circle with centre at b and radius R
 - Line ef: tangent tilted $12^\circ 50'$ relative to the XX' axis on the arc to the circle with centre at b and radius R . The point of tangency thus obtained is designated e.

NOTE — The profile involves exclusively those machined male elements which do not lose their shape. Nevertheless, the male element may be in the form of a sleeve fitted over the end of the pipe and which, during coupling to the female element, is compressed onto the pipe and changes its shape such that the correct profile is obtained.

Figure 1 — Dimensions

Table 1 — Dimensions

Dimensions in millimetres

DN ¹⁾	N ²⁾		F	G	H	L	M	P	R	S		T	U	V
	external 4g6g	internal 4H5H								min.	max.			
5	1,38	MJ10 x 1	5,06	5,26	12	3,88	7,18	2,58	6,13	0,56	0,92	3,88	2,8	4,7
6	1,38	MJ12 x 1,25	6,06	6,26	14	4,38	8,18	2,58	6,13	0,56	0,92	4,38	3,8	4,7
8	1,38	MJ14 x 1,5	8,06	8,26	17	4,38	9,18	2,58	6,13	0,56	0,92	4,38	3,8	5,2
10	1,38	MJ16 x 1,5	10,06	10,26	19	4,38	10,18	2,58	6,13	0,56	0,92	4,38	4,1	5,9
12	2,28	MJ18 x 1,5	12,06	12,26	22	4,48	9,28	3,48	12,13	0,96	1,32	4,48	4,1	6,4
14	2,28	MJ20 x 1,5	14,06	14,26	24	4,48	9,28	3,48	12,13	0,96	1,32	4,48	4,1	6,4
16	2,28	MJ22 x 1,5	16,06	16,26	27	4,48	9,28	3,48	12,13	0,96	1,32	4,48	4,4	6,1
20	2,28	MJ27 x 1,5	20,08	20,28	32	4,48	9,28	3,48	12,13	0,96	1,32	4,48	3,9	6,1
25	2,28	MJ33 x 1,5	25,08	25,28	41	4,48	10,28	3,48	13,61	0,96	1,32	4,48	4,2	5,8
32	2,28	MJ42 x 2	32,1	32,3	46	4,98	11,28	3,48	17,24	0,96	1,32	4,98	4,1	5,9
40	2,28	MJ50 x 2	40,1	40,3	60	4,98	11,28	3,48	21,32	0,96	1,32	4,98	4,4	7,6

1) Nominal size (outside diameter of the corresponding tube).

2) Threads are in accordance with ISO 5855-3.

3) Tolerance for the proof gauge: ± 0,002 5

4) L min. = S

5) The radius R shall have a sufficient minimum value in order to prevent a deterioration of the seats during assembly of the male and female elements.

Annex A
(informative)

Bibliography

- [1] ISO 5855-1:1988, *Aerospace — MJ threads — Part 1: General requirements.*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 7319:1992](https://standards.iteh.ai/catalog/standards/sist/c5238f05-3ca7-4856-88cb-9a62fcc757cc/iso-7319-1992)

<https://standards.iteh.ai/catalog/standards/sist/c5238f05-3ca7-4856-88cb-9a62fcc757cc/iso-7319-1992>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This page intentionally left blank

[ISO 7319:1992](#)

<https://standards.iteh.ai/catalog/standards/sist/c5238f05-3ca7-4856-88cb-9a62fcc757cc/iso-7319-1992>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 7319:1992

<https://standards.iteh.ai/catalog/standards/sist/c5238f05-3ca7-4856-88cb-9a62fcc757cc/iso-7319-1992>

UDC 621.643.414:629.7.064.2/.3

Descriptors: aircraft industry, aircraft equipment, hydraulic fluid power, pneumatic fluid power, fluid circuits, pipes (tubes), pipe fittings, couplings, interfaces, dimensions, interchangeability.

Price based on 4 pages
