INTERNATIONAL STANDARD



First edition 2005-10





Reference number IEC 62002-1:2005(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- IEC Web Site (<u>www.iec.ch</u>)
- Catalogue of IEC publications

The on-line catalogue on the IEC web site (www.iec.ch/search.ub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

IEC Just Published

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

Customer Service Centre

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

le6-25f1-468c-9b2a-667da9d0eb7e/iec-62002-1-2005

Email: <u>custeerv@iec.df</u> Tel: +41 22 919 02 11 Fax: +41 22 919 03 00

INTERNATIONAL STANDARD



First edition 2005-10



© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale International Electrotechnical Commission Международная Электротехническая Комиссия



XA

For price, see current catalogue

CONTENTS

1	Scope	7	
2	Normative references		
3	Abbreviations		
4	Terminal categories		
5	Definition of receiving conditions	11	
-	5.1 Portable reception	11	
	5.2 Mobile reception		
6	Frequencies and channel bandwidths		
	6.1 Channel frequencies	<u>)</u>	
	6.2 Supported frequency ranges.		
	6.3 Supported bandwidths	13	
7	DVB-T modes	13	
	7.1 Supported DVB-T modes		
	7.2 Change of modulation parameters	13	
	7.3 Tuning procedure	13	
8	Transmitter performance	14	
	8.1 Transmitter noise-like impairments	14	
	8.2 Further transmitter impairments		
	8.3 Spectrum masks	16	
9	Receiver antenna characteristics	17	
	9.1 Antennas for terminal category a	17	
	9.2 Antennas for terminal category by		
	9.3 Antennas for terminal category b2 and c		
	9.4 External antennas		
10	Receiver performance	19	
	10.1 Reference model	19	
	10.2 Noise model	20	
	10.3 Degradation criteria	21	
	10.4 Diversity receivers	22	
	10.5 DVB-H receivers	23	
	10.6 Channel models	24	
	10.7 <i>C</i> / <i>N</i> performance	25	
	10.8 Receiver minimum and maximum signal input levels		
	10.9 Immunity to analogue and/or digital signals in other channels		
	10.10 Immunity to co-channel interference from analogue TV signals	35	
	10.11 Guard interval utilization		
	10.12 Tolerance to impulse interference		
	10.13 EMC characteristics		
11	Interoperability with other radio systems	40	

62002-1 © IEC:2005(E)

Annex A (informative) Active external antennas	45
Annex B (informative) An example of C/N performance with a practical transmitter	48
Annex C (informative) Multi-path reception in a DVB-T system	49
Annex D (informative) C/N performance of DVB-H receivers	52
Bibliography	54
Figure 1 – Reference model	19
Figure 2 – Noise model	20
Figure 3 – Antenna diversity receiver	22
Figure 4 – Receiver behaviour in a mobile channel	
Figure 5 – PAL interfering signals	
Figure 6 – SECAM L interfering signal	
Figure 7 – Pattern S1 in case of $N + 1$ or $N - 1$,
Figure 8 – Pattern S2 in case of $N + 1$ or $N - 1$	33
Figure 9 – Pattern L1	
Figure 10 – Pattern L2	
Figure 11 – Pattern L3	
Figure 12 – Echo outside guard interval mask	
Figure 13 – Mask for echo outside GI for $GI = 1/4$	
Figure 14 – Definition of the impulse interference test pattern	
Figure 15 – Terminal architectures	41
Figure 16 – Frequency bands	
Figure 17 – GSM Tx block diagram	
SFigure 18 - Tx PA-poise mask in DVB-T/H receiver input. Sauthan 667.dan.dan.dan.dan.dan.dan.dan.dan.dan.dan	iee.62002 4 4
Figure C.1 – Theoretical limits of out-of-guard delay	
Figure C.2 – DVB T model – Splitting of the signal power into contributing and	
interfering companents	
Figure C.3 – Theoretical echo power profile for 8k, 64QAM, 2/3	51
Figure D.1 – DVB-H reference receiver C/N behaviour in mobile channel	53
Table 1 – Supported frequency ranges	13
Table 2 – Conversion of MER to END	15
Table 3 – Typical antenna gain for terminal category b2 and c	
Table 4 – Delta values between picture failure point and reference BER	21
Table 5 – Approximation of the DVB-T specified Rayleigh channel	24
Table 6 – Typical urban profile (TU6) constitution	24
Table 7 – C/N (dB) for reference BER in Gaussian channel	26
Table 9 C/N (dP) for reference <i>PEP</i> in pertable channel	26

Table 8 – C/N (dB) for reference BER in portable channel	26
Table 9 – C/N (dB) for $PER = 10^{-4}$ in typical urban channel for single antenna receiver	27
Table 10 – C/N (dB) for $PER = 10^{-4}$ in typical urban channel for diversity receiver	27
Table 11 – Maximum input levels for terminal category a and b1	29
Table 12 – Maximum input levels for terminal category b2 and c	29

Table 13 – Immunity to pattern S1	. 32
Table 14 – Immunity to pattern S2	. 33
Table 15 – Immunity to pattern L1	. 34
Table 16 – Immunity to pattern L2	. 35
Table 17 – Immunity to pattern L3	. 35
Table 18 – Immunity to co-channel interference from analogue signals	. 36
Table 19 – C/N for echo within guard interval	.36
Table 20 – Timing of the corner point Tc	. 37
Table 21 – Definition of the value Δ	. 37
Table 22 – Definition of the inflection point	. 38
Table 23 – Impulse interference test patterns	.40
Table 24 – GSM reject filter attenuation	.43
Table B.1 – C/N (dB) for reference BER	.48
Table D.1 – C/N (dB) for 5 % MFER in Gaussian channel	. 52
Table D.2 – C/N (dB) for QEFIP in portable channel	. 53
Table D.3 – C/N (dB) in mobile channel	. 53

https://standards.iteh.a

6-25f1-468c-9b2a-667da9d0eb7e/iec-62002-1-2005

eview

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MOBILE AND PORTABLE DVB-T/H RADIO ACCESS -

Part 1: Interface specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter (referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as hearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.

7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or

- other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62002-1 has been prepared by Technical Area 1: Terminals for audio, video and data services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

CDV	Report on voting
100/920/CDV	100/1012/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 62002 consists of the following parts, under the general title *Mobile and portable DVB-T/H Radio access:*

Part 1: Interface specification

Part 2: Interface conformance testing

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- · replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date

https://standards.iteh.a

MOBILE AND PORTABLE DVB-T/H RADIO ACCESS -

Part 1: Interface specification

1 Scope

This part of IEC 62002 is a radio access specification for mobile, portable and hand-held portable devices capable of receiving DVB-T/H services. It includes informative system aspects as well as specifications for minimum RF performance. It covers terminals in three main classes, namely integrated car terminals, portable digital TV sets and hand-held portable convergence terminals. Interoperability with integrated cellular radios is also considered. The specification covers the following areas.

- Frequency ranges
- Supported modes
- Definition of receiving conditions
- Definition of the receiver RF reference model
- Definition of QoS criteria
- Antenna characteristics
- Channel models
- C/-performance with different channels
- Minimum and maximum input levels
- Immunity to interfering signals
- Definition of an ensemble of interference patterns

Tolerance to impulse interference

- SFN performance
- Transmitter minimum performance
- Interoperability of cellular radios
- EMC aspects

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 13, Sound and television broadcast receivers and associated equipment – Radio disturbance characteristics – Limits and methods of measurement

CISPR 20, Sound and television broadcast receivers and associated equipment – Immunity characteristics – Limits and methods of measurement

IEC 60169-2, Radio-frequency connectors – Part 2: Coaxial unmatched connector

ETSI EN 300 744:2004, Digital Video Broadcasting (DVB); Framing structure, Channel coding and modulation for digital terrestrial television, V1.5.1

ETSI ETS 300 342-1, Radio Equipment and Systems (RES); ElectroMagnetic Compatibility (EMC) for European digital cellular telecommunications system (GSM 900 MHz and DCS 1 800 MHz) – Part 1: Mobile and portable radio and ancillary equipment

ETSI EN 300 607-1, Digital cellular telecommunications system (Phase 2+) (GSM) – Mobile Station (MS) conformance specification; Part 1: Conformance specification

ETSI EN 302 304:2004, Digital Video Broadcasting (DVB); Transmission System for Handheld Terminals (DVB-H), V1.1.1

3 Abbreviations

For the purposes	of this document, the following abbreviations apply.
λ	Lambda, wavelength ($\lambda = c/f$)
A2	German analogue TV stereo system
A_A	Coupling between antennas
AGC	Automatic gain control
A gsm	Stop band attenuation of the GSM reject filter
В	Bandwidth
BER	Bit error ratio
С	Carrier power (In band carrier power including any echoes)
С	Speed of light $c = 3(0 \times 10^8 \text{ m/s})$
Ci	Power contribution from the <i>i</i> -th signal
Ct	Total useful carrier power
C/N	Carrier to-noise ratio
s: C/N _{min} ards.iteh.a	Minimum C/W col 0424e6-25f1-468c-9b2a-667da9d0eb7e/iec-62002-1-2005
CPE	Common phase error
CR	Code rate
dB	Decibel
dBc	dB compared to carrier power C
dBd	Antenna gain in dB compared to reference dipole (0 dBd = $-2,14$ dBi)
dBi	Antenna gain in dB compared to isotropic antenna (0 dBi = 2,14 dBd)
dB(mW)	Power in dB compared to 1 mW
DVB, DVB-T	Digital video broadcasting, terrestrial digital video broadcasting
DVB-H	Digital video broadcasting to hand held terminals
DVB-RCT	DVB terrestrial return channel
Ε	Field strength V/m
$E(dB\mu V/m)$	Field strength in dB compared to 1 μ V
EDGE	Enhanced data rates for GSM/global evolution
EMC	Electromagnetic compatibility
END	Equivalent noise degradation
ENF	Equivalent noise floor
ESR	Erroneous second ratio

F	Frequency in Hz
f (MHz)	Frequency in MHz
fc	Centre frequency
F	Noise factor
fd, Fd	Doppler frequency
Fd _{3dB}	Doppler frequency with minimum C/N requirement raised by 3dB
FER	Frame error rate
G	Gain
Ga	Antenna gain
GI	Guard interval
GPRS	General packet radio service
GSM	Global system for mobile communications
Ι	Interfering power
ICI	Intercarrier interference
J	joule
К	Boltzmann's constant k = $1,38 \times 10^{-26}$ J/K
К	kelvin
L1, L2, L3	Linearity patterns
L _{GSM}	Insertion loss of the GSM reject filter
LNA	Low noise amplifier
MER	Modulation error ratio
MFER	MPE-FEC frame error rate
MHz	Megahertz Megahertz
MPEG-2	Motion pictures expert group, video compression standard
N, m, N	Changelindexes
NF	Noise figure in dB
	Additional sound carrier for analogue TV, modulated with a near instantaneous compended audio multiplex
PA	Power amplifier
PAL, PAL B, PAL G, PAL I, PAL I1	Phase alternation line, TV-systems using PAL
PER	Packet error ratio
P _{in}	Input power W
P_{in} (dB(mW))	Input power dB compared to 1 mW
P _{max}	Maximum power
P _{min}	Minimum power
ppm	Parts per million
PSI/SI	Program specific information, service information
P _{TX}	Transmission power
Px	Excess noise power dBc
QAM16, QAM64	Quadrature amplitude modulation, 16-level and 64-level versions

QEF	Quasi error free
QoS	Quality of service
QPSK	Quaternary phase shift keying
RF	Radiofrequency
RS	Reed solomon
Rx	Receiver
S1,S2	Selectivity patterns
SECAM, SECAM L	Sequential à mémoire, TV system using SECAM
SFN	Single frequency network
SFP	Subjective failure point
Т	Temperature in kelvins
Тс	Corner point
Te	Total duration of the gating pulses
ti	Time of arrival for the <i>i</i> -th signal
TS	Transport stream
Tg	Guard interval duration
Ти	Active symbol duration
Тх	Transmitter
UHF	Ultra high frequency
UMTS	Universal mobile telecommunications system
VHF	Very high frequency
W	watt
WCDMA	Wide-band code division multiple access
Wi	Weighting coefficient for the <i>i</i> -th component
$\langle \rangle$	$\setminus \setminus \setminus$

4 Terminal categories

In this specification three different terminal categories are considered. The requirements cover all categories unless otherwise stated.

The terminal categories are:

a) Integrated car terminals

This category covers DVB-T terminals installed in a car and where the antenna is integral with the car.

b) Portable digital TV sets

This category covers terminals, which are intended for receiving normal MPEG-2 based digital TV services indoors and outdoors with terminal attached antennas. This category is divided into two subcategories.

 The receiver screen size is typically greater than 25 cm and the receiver may be battery- or mains-powered. Typically, the terminal is stationary during the reception. An example of the antenna construction may be an adjustable telescope or wideband design, either active or passive, attached to the receiver.

- 2) Pocketable digital TV-receiver. The terminal is battery operated and can be moved during use. Usually the antenna is integral with the terminal.
- c) Hand-held portable convergence terminals

This category covers small battery powered hand held convergence terminals with built in cellular radio like GSM, GPRS or UMTS. The terminals have the functionality of a mobile phone and can receive IP-based services using DVB-H over DVB-T physical layer. The DVB-T antenna and the cellular antenna are both integral with the terminal.

5 Definition of receiving conditions

5.1 **Portable reception**

This is when a portable receiver (terminal category b1) with an attached or integral antenna is used indoors or outdoors at a minimum height of 1,5 m above floor or ground level. It is assumed that the receiving antenna is omni-directional. It is also assumed that the antenna and any nearby large objects are stationary. Extreme cases, such as reception in completely shielded rooms, are disregarded. [1]¹⁾

As a special case of portable reception a small hand-held portable receiver (terminal category b2 or c) is used indoors or outdoors at a minimum height of 1,0 m above floor or ground level. It is assumed that the receiving antenna is omni-directional. It is also assumed that the channel conditions can change due to slow movements (≤ 3 km/h) of the antenna and any nearby large objects. Extreme cases, such as reception in completely shielded rooms, are disregarded.

The main difference between portable and hand-held portable reception is the antenna gain of the terminal.

5.2 Mobile reception

This applies to the use of integrated car terminals (terminal category a) with speeds higher than 3 km/h. It is assumed that the receiving antenna is omni directional with a minimum height above ground level of 1,5 m. Other vehicles such as buses or high-speed trains could be considered as special cases.

A small hand-held portable receiver (terminal category b2 or c) used within a car or train could also be considered as a case of mobile reception. [2]

6 Frequencies and channel bandwidths

6.1 Channel frequencies

The channel frequencies of bands III, IV and V are given below 6 MHz, 7 MHz and 8 MHz channel rasters used in various countries. The centre frequencies fc of the incoming DVB-T RF signals are as follows.

¹⁾ Figures in square brackets refer to the Bibliography.

VHF III

For countries using 8 MHz channel raster

fc = 178 MHz + (N - 6) x 8 MHz +f offset

 $N = \{6, \dots, 12\}$ (VHF channel number)

For countries using 7 MHz channel raster

 $fc = 177,5 \text{ MHz} + (N-5) \times 7 \text{ MHz} + f \text{ offset}$

 $N = \{5, ..., 12\}$ (VHF channel number)

For countries using 6 MHz channel raster

 $fc = 177,0 \text{ MHz} + (N - 7) \times 6 \text{ MHz} + f \text{ offset}$

 $N = \{7, \dots, 13\}$ (VHF channel number)

In some countries offsets may be used

Preferred offset is $\pm n \ge 1/6$ MHz. $n = \{1, 2, ...\}$

UHF IV and V

For countries using 8 MHz channel raster

 $fc = 474 \text{ MHz} + (N - 21) \times 8 \text{ MHz} + f \text{ offset}$

 $n = \{21, \dots, 69\}$ (UHF channel number)

For countries using 7 MHz channel raster

 $fc = 529,5 \text{ MHz} + (N - 28) \times 7 \text{ MHz} + f \text{ offset}$

 $n = \{28, \dots, 67\}$ (UHF channel number)

For countries using 6 MHz channel raster

 $fc = 473,0 \text{ MHz} + (N - 14) \times 6 \text{ MHz} + f \text{ offset}$

 $n = \{14, ..., 83\}$ (UHF channel number)

In some countries offsets may be used

https://Preferred offset is ± n x 1/6 MHz. n = { 1, 2,...} In the UK n = 1

The error in the centre frequency (fc) of the transmitted RF signal should not exceed 500 Hz in MFN. In SFN the error in the centre frequency (fc) of the transmitted RF signal should not exceed 1 Hz.

6.2 Supported frequency ranges

The receivers in terminal categories a and b1 shall be able to receive all channels in the VHF band III and UHF bands IV and V. VHF III can be left out in market areas, where it is not used. The receivers in terminal category b2 shall be able to receive all channels in UHF bands IV and V, VHF III is an option depending on the market area needs. The receivers in terminal category c shall be able to receive all channels in UHF band IV and V, provided that the terminal does not support GSM 900.

In the case where GSM 900 is used in a convergence terminal (category c), the usable frequency range is limited to channel 49 (698 MHz) due to the interoperability considerations. Supported frequency ranges are shown in Table 1.