

# INTERNATIONAL STANDARD

**Fixed resistors for use in electronic equipment –  
Part 8: Sectional specification – Fixed surface mount resistors**

ITeC Standards  
(<https://standards.iteh.ai>)  
Document Preview

IEC 60115-8:2009

<https://standards.iteh.ai/catalog/standards/iec/06351a0e-8ed2-4597-a121-cf37501837c4/iec-60115-8-2009>

Withhold



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.


- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00



<http://www.standards.iteh.ai/>  
IEC 60115-8-2009  
<http://standards.iec.org/06/51a0e-8ed2-4597-a121-cb37501837c4/iec-60115-8-2009>

# INTERNATIONAL STANDARD

**Fixed resistors for use in electronic equipment –  
Part 8: Sectional specification – Fixed surface mount resistors**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE



ICS 31.040.10

ISBN 978-2-88910-060-6

## CONTENTS

|  |    |
|--|----|
| FOREWORD.....  | 4  |
| 1 General.....   | 6  |
| 1.1 Scope.....   | 6  |
| 1.2 Object.....  | 6  |
| 1.3 Normative references.....                                  | 6  |
| 1.4 Information to be specified in a detail specification..... | 7  |
| 1.4.1 Outline drawing.....                                     | 7  |
| 1.4.2 Style and dimensions.....                                | 7  |
| 1.4.3 Climatic category.....                                   | 7  |
| 1.4.4 Limits of resistance change after testing.....           | 7  |
| 1.4.5 Resistance range.....                                    | 7  |
| 1.4.6 Tolerances on nominal resistance.....                    | 7  |
| 1.4.7 Temperature coefficient of resistance.....               | 7  |
| 1.4.8 Rated dissipation.....                                   | 7  |
| 1.4.9 Limiting element voltage.....                            | 8  |
| 1.4.10 Insulation voltage.....                                 | 8  |
| 1.4.11 Insulation resistance.....                              | 8  |
| 1.4.12 Marking.....  | 8  |
| 1.4.13 Ordering information.....                               | 8  |
| 1.4.14 Mounting.....   | 8  |
| 1.5 Product classification.....                                | 8  |
| 2 Preferred characteristics, ratings and test severities.....  | 9  |
| 2.1 Preferred characteristics.....                             | 9  |
| 2.1.1 Style and dimensions.....                                | 9  |
| 2.1.2 Preferred climatic categories.....                       | 11 |
| 2.1.3 Variation of resistance with temperature.....            | 11 |
| 2.1.4 Limits for change in resistance.....                     | 12 |
| 2.2 Preferred values of ratings.....                           | 13 |
| 2.2.1 Resistance.....  | 13 |
| 2.2.2 Tolerances on resistance.....                            | 13 |
| 2.2.3 Rated dissipation $P_{70}$ .....                         | 13 |
| 2.2.4 Limiting element voltage $U_{max}$ .....                 | 14 |
| 2.2.5 Insulation resistance.....                               | 14 |
| 2.2.6 Insulation voltage.....                                  | 14 |
| 2.3 Preferred test severities.....                             | 14 |
| 2.3.1 Short time overload.....                                 | 14 |
| 2.3.2 Solderability.....                                       | 15 |
| 2.3.3 Resistance to soldering heat.....                        | 15 |
| 2.3.4 Shear (adhesion) test.....                               | 16 |
| 2.3.5 Periodic pulse overload test.....                        | 17 |
| 2.3.6 Resistance to electrostatic discharge (ESD).....         | 17 |
| 2.3.7 Component solvent resistance.....                        | 18 |
| 2.3.8 Solvent resistance of marking.....                       | 18 |
| 2.4 Preparation of specimen.....                               | 18 |
| 2.4.1 Drying.....  | 18 |
| 2.4.2 Mounting of components.....                              | 18 |
| 3 Quality assessment procedures.....                           | 21 |

|         |  |    |
|---------|--|----|
| 3.1     | General .....  | 21 |
| 3.2     | Definitions .....  | 21 |
| 3.2.1   | Primary stage of manufacture .....   | 21 |
| 3.2.2   | Structurally similar components .....  | 21 |
| 3.2.3   | Assessment level EZ .....  | 21 |
| 3.3     | Formation of inspection lots.....  | 21 |
| 3.4     | Qualification approval.....  | 22 |
| 3.4.1   | Qualification approval on the basis of the fixed sample size<br>procedure .....  | 22 |
| 3.4.2   | Qualification approval on the basis of lot-by-lot and periodic testing .....   | 23 |
| 3.5     | Quality conformance inspection.....  | 23 |
| 3.6     | Technology approval procedures.....  | 23 |
| 3.7     | Delayed delivery.....  | 23 |
| Annex A | (normative) 0 Ω resistors (Jumper) .....   | 36 |
| A.1     | Information to be specified in a detail specification.....   | 36 |
| A.2     | Preferred characteristics.....   | 36 |
| A.3     | Preferred ratings .....  | 36 |
| A.4     | Preferred severities .....   | 36 |
| A.5     | Test schedule for qualification approval.....  | 37 |
| A.6     | Test schedule for quality conformance inspection.....  | 37 |
| Annex B | (informative) Letter symbols and abbreviations .....   | 38 |
| B.1     | Letter symbols.....  | 38 |
| B.2     | Abbreviations .....  | 39 |
|         | Bibliography.....  | 40 |
|         | Figure 1 – Shape and dimensions of rectangular (RR) resistors .....  | 10 |
|         | Figure 2 – Shape and dimensions of cylindrical (RC) resistors .....  | 10 |
|         | Figure 3 – Derating curve .....  | 14 |
|         | Figure 4 – Basic layout for mechanical, environmental and electrical tests, Kelvin (4<br>point) connections .....                        | 19 |
|         | Figure 5 – Attachment of the sense line for Kelvin (4 point) connections for specimen<br>with nominal resistance lower than 100 mΩ ..... | 19 |
|         | Figure 6 – Basic layout for mechanical, environmental and electrical tests.....  | 20 |
|         | Table 1a – Preferred styles for rectangular (RR) resistors.....  | 9  |
|         | Table 1b – Preferred styles for cylindrical (RC) resistors.....  | 10 |
|         | Table 2 – Permitted change of resistance .....   | 11 |
|         | Table 3a – Limits for change of resistance .....   | 12 |
|         | Table 3b – Limits for change of resistance.....  | 13 |
|         | Table 4 – Shear test force.....  | 17 |
|         | Table 5 – Soldering pad dimensions .....   | 20 |
|         | Table 6 – Test schedule for qualification approval.....  | 24 |
|         | Table 7a – Test schedule for quality conformance inspection: Lot-by-lot tests.....   | 30 |
|         | Table 7b – Test schedule for quality conformance inspection: Periodic tests.....   | 32 |

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## FIXED RESISTORS FOR USE IN ELECTRONIC EQUIPMENT –

**Part 8: Sectional specification –  
Fixed surface mount resistors**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60115-8 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This second edition cancels and replaces the first edition, published in 1989, and its Amendment 1 (2000). This second edition constitutes a technical revision and includes test conditions and requirements for lead-free soldering and assessment procedures meeting the requirements of a "zero defect" approach.

The major technical changes with regard to the first edition are the following:

- introduction of a product classification based on application requirements;
- extension of the list of styles and dimensions;
- use of an extended scope of stability class definitions;
- extension of the lists of preferred values of ratings
- inclusion of test conditions and requirements for lead-free soldering, for periodic overload and for resistance to electrostatic discharge (ESD);

- inclusion of a new set of severities for a shear test;
- inclusion of definitions for a test board;
- replacement of assessment level E and possible others by the sole assessment level EZ, meeting the requirements of a “zero defect” approach;
- inclusion of an extended endurance test, a flammability test, a temperature rise test, vibration tests, an extended rapid change of temperature test, and a single pulse high-voltage overload test;
- inclusion of requirements applicable to 0  $\Omega$  resistors (jumpers).

The text of this standard is based on the following documents:

| FDIS         | Report on voting |
|--------------|------------------|
| 40/1933/FDIS | 40/1970/RVD      |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts of the IEC 60115 series, under the general title *Fixed resistors for use in electronic equipment*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

# FIXED RESISTORS FOR USE IN ELECTRONIC EQUIPMENT –

## Part 8: Sectional specification – Fixed surface mount resistors

### 1 General

#### 1.1 Scope

This part of IEC 60115 is applicable to fixed surface mount resistors for use in electronic equipment.

These resistors are typically described according to types (different geometric shapes) and styles (different dimensions). They have metallized terminations and are primarily intended to be mounted directly on to a circuit board.

#### 1.2 Object

The object of this standard is to prescribe preferred ratings and characteristics and to select from IEC 60115-1, the appropriate quality assessment procedures, tests and measuring methods and to give general performance requirements for this type of resistor.

Test severities and requirements prescribed in detail specifications referring to this sectional specification shall be of equal or higher performance level, because lower performance levels are not permitted.

#### 1.3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60062:2004, *Marking codes for resistors and capacitors*

IEC 60068-1:1988, *Environmental testing – Part 1: General and guidance*  
Amendment 1(1992)

IEC 60068-2-58:2004, *Environmental testing – Part 2-58: Tests – Test Td: Test methods for solderability, resistance to dissolution of metallization and to soldering heat of surface mounting devices (SMD)*

IEC 60115-1:2008, *Fixed resistors for use in electronic equipment – Part 1: Generic specification*

IEC 61193-2:2007, *Quality assessment systems – Part 2: Selection and use of sampling plans for inspection of electronic components and packages*

IEC 61340-3-1, *Electrostatics – Part 3-1: Methods for simulation of electrostatic effects – Human body model (HBM) electrostatic discharge test waveforms*

IEC 61760-1:2006, *Surface mounting technology – Part 1: Standard method for the specification of surface mounting components (SMDs)*



#### 1.4 Information to be specified in a detail specification

Detail specifications shall be derived from the relevant blank detail specification.

Detail specifications shall not specify requirements inferior to those of the generic specification, sectional specification or blank detail specification. When severer requirements are included, they shall be listed in a subclause of the detail specification and indicated in the test schedules, for example by a note.

The following information shall be given in each detail specification and the values quoted shall preferably be selected from those given in the appropriate clause of this sectional specification.

##### 1.4.1 Outline drawing

There shall be an illustration of the resistor as an aid to easy recognition and for comparison of the resistor with others.

##### 1.4.2 Style and dimensions

See 2.1.1.

Dimensions and their associated tolerances, which affect interchangeability and mounting, shall be given in the detail specification.

##### 1.4.3 Climatic category

See 2.1.2.

##### 1.4.4 Limits of resistance change after testing

See 2.1.4.

##### 1.4.5 Resistance range

See 2.2.1.

NOTE When products approved according to the detail specification have different ranges, the following statement should be added: "The range of values available in each style, together with the associated tolerance and temperature coefficient, is given in the register of approvals, available for example on the website [www.iecq.org](http://www.iecq.org)".

##### 1.4.6 Tolerances on nominal resistance

See 2.2.2.

##### 1.4.7 Temperature coefficient of resistance

See 2.1.3.

##### 1.4.8 Rated dissipation

See 2.2.3.

The mounting conditions are as described in 2.4.2.

The detail specification shall state the maximum dissipation at temperatures other than 70 °C, for example the derating, either in a diagram or in the form of a statement. All break points shall be verified by test.

#### **1.4.9 Limiting element voltage**

See 2.2.4.

#### **1.4.10 Insulation voltage**

This information is required only for insulated resistors.

See 2.2.6 and the definition in IEC 60115-1, 2.2.10

For small size resistors where the dimensions of the test jig given in IEC 60115-1, 4.6 are not adequate, they shall be specified in the detail specification.

#### **1.4.11 Insulation resistance**

This information is required only for insulated resistors.

See 2.2.5.

For small size resistors where the dimensions of the test jig given in IEC 60115-1, 4.6 are not adequate, they shall be specified in the detail specification.

#### **1.4.12 Marking**

Surface mount resistors are generally not marked on the body. However, if some marking is applied to the body, the resistor shall be marked with the resistance according to IEC 60062, Clause 3 and as many of the remaining items listed in IEC 60115-1, 2.4. All the required information shall be marked on the packaging.

#### **1.4.13 Ordering information**

The detail specification shall specify that the following information is required when ordering resistors:

The number of the detail specification and style reference.

Resistance, tolerance on resistance and temperature coefficient of resistance according to IEC 60062.

#### **1.4.14 Mounting**

The detail specification shall give guidance on methods of mounting for normal use, preferably based on the specification of assembly process conditions of IEC 61760-1, Clause 5. Mounting for test and measurement purposes (when required) shall be in accordance with 2.4.2 of this specification and IEC 60115-1, 4.31.

The detail specification may include additional information (which is not normally required to be verified by the inspection procedure), such as circuit diagrams, curves, drawings and notes needed for the clarification of the detail specification.

### **1.5 Product classification**

The introduction of a product classification permits the user to select performance requirements according to the conditions of the intended end-use application.

Two general end product levels have been established to reflect characteristic differences in functional, performance and reliability requirements and to permit the use of suitable inspection and test schedules. It should be recognized that there may be overlaps of applications between the levels.

**Level G** – General electronic equipment, typically operated under benign or moderate environmental conditions, where the major requirement is function. Examples for level G include consumer products and telecommunication user terminals.

**Level P** – High-performance electronic equipment, where one or more of the following criteria applies:

- uninterrupted performance is desired or mandatory;
- operation in harsh environmental conditions;
- extended lifetime.

Examples for level P include professional equipment, telecommunication transmission systems, industrial control and measurement systems and most automotive applications operated outside the passenger compartment.

Level P is the suitable basis for detail specifications aiming for the approval of components with established reliability.

Each level shall be used in individual detail specifications.

## 2 Preferred characteristics, ratings and test severities

### 2.1 Preferred characteristics

The values given in detail specifications shall preferably be selected from the following.

#### 2.1.1 Style and dimensions


The preferred styles and dimensions are given in Table 1a and Table 1b.

**Table 1a – Preferred styles for rectangular (RR) resistors**

| Style   |                       | Dimensions            |                      |                                       |
|---------|-----------------------|-----------------------|----------------------|---------------------------------------|
| Metric  | Imperial <sup>a</sup> | Length <i>L</i><br>mm | Width <i>W</i><br>mm | Height <i>T</i><br>mm                 |
| RR0603M | RR0201                | 0,6 ± 0,03            | 0,3 ± 0,03           | 0,23 ± 0,03                           |
| RR1005M | RR0402                | 1,0 ± 0,05            | 0,5 ± 0,05           | 0,35 ± 0,05                           |
| RR1608M | RR0603                | 1,6 ± 0,1             | 0,8 ± 0,1            | 0,45 ± 0,1                            |
| RR2012M | RR0805                | 2,0 ± 0,1             | 1,25 ± 0,15          | 0,5 <sup>+0,15</sup> <sub>-0,10</sub> |
| RR3216M | RR1206                | 3,2 ± 0,2             | 1,6 ± 0,15           | 0,55 ± 0,1                            |
| RR3225M | RR1210                | 3,2 ± 0,2             | 2,5 ± 0,2            | 0,55 ± 0,1                            |
| RR3245M | RR1218                | 3,2 ± 0,2             | 4,6 ± 0,2            | 0,55 ± 0,1                            |
| RR4532M | RR1812                | 4,6 ± 0,2             | 3,2 ± 0,2            | 0,55 ± 0,1                            |
| RR5025M | RR2010                | 5,0 ± 0,2             | 2,5 ± 0,2            | 0,55 ± 0,2                            |
| RR6332M | RR2512                | 6,3 ± 0,2             | 3,2 ± 0,2            | 0,55 ± 0,2                            |

NOTE Figure 1 shows the shape and dimensions of rectangular resistors.

<sup>a</sup> Historical style codes, for information only.



IEC 2353/08

Figure 1 – Shape and dimensions of rectangular (RR) resistors


Table 1b – Preferred styles for cylindrical (RC) resistors

| Style                | Dimensions                            |                                       |
|----------------------|---------------------------------------|---------------------------------------|
|                      | Length <i>L</i><br>mm                 | Diameter <i>D</i><br>mm               |
| RC1610M              | 1,6 <sup>+0,10</sup> <sub>-0,05</sub> | 1,0 <sup>+0,15</sup> <sub>-0,05</sub> |
| RC2012M              | 2,0 ± 0,1                             | 1,25 <sup>+0,2</sup> <sub>-0,1</sub>  |
| RC2211M              | 2,2 <sup>0</sup> <sub>-0,3</sub>      | 1,1 <sup>0</sup> <sub>-0,10</sub>     |
| RC3514M <sup>a</sup> | 3,5 ± 0,2                             | 1,4 ± 0,2                             |
| RC5922M <sup>b</sup> | 5,9 ± 0,2                             | 2,2 ± 0,2                             |

NOTE Figure 2 shows the shape and dimensions of cylindrical resistors.

<sup>a</sup> Comparable to historical style: RC3715M ( $L = 3,7<sup>0</sup><sub>-0,2</sub>$  mm;  $D = 1,5<sup>+0,1</sup><sub>-0,3</sub>$  mm).

<sup>b</sup> Comparable to historical style: RC6123M ( $L = 6,1<sup>0</sup><sub>-0,9</sub>$  mm;  $D = 2,3<sup>+0,2</sup><sub>-0,4</sub>$  mm).



IEC 2354/08

Figure 2 – Shape and dimensions of cylindrical (RC) resistors

When the component style is other than described above, for example for surface mount wirewound resistors, the detail specification shall state such dimensional information as will adequately describe the resistor.