



SLOVENSKI STANDARD
SIST EN 300 757 V1.3.1:2003
01-december-2003

8][]HbY]nVc`ýUbYVfYnj fj] bYHfY_ca i b]_UWfYfB97HLËB]n_c\]fcbgUgfcf]Hfj
gdcfc Ub^Ufl@FAGžj_`^ bc`g`gfcf]h]]c`_fUh_] `gdcfc]`fGAGL

Digital Enhanced Cordless Telecommunications (DECT); Low Rate Messaging Service (LRMS) including Short Messaging Service (SMS)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: ^{SIST EN 300 757 V1.3.1:2003} EN 300 757 Version 1.3.1
<https://standards.iteh.ai/catalog/standards/sist/58b0c1bc-5516-4365-a255-db343d0f367f/sist-en-300-757-v1-3-1-2003>

ICS:

33.070.30 Öä åæ } ^ Å à [|zæ ^ Digital Enhanced Cordless
à!^: ç|çã } ^ Å | ^ \ [{ ~ } å æ å Telecommunications (DECT)
ÇÖÓVD

SIST EN 300 757 V1.3.1:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 757 V1.3.1:2003](https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-db343d0f367f/sist-en-300-757-v1-3-1-2003)

[https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-
db343d0f367f/sist-en-300-757-v1-3-1-2003](https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-db343d0f367f/sist-en-300-757-v1-3-1-2003)

ETSI EN 300 757 V1.3.1 (2002-01)

European Standard (Telecommunications series)

**Digital Enhanced Cordless Telecommunications (DECT);
Low Rate Messaging Service (LRMS)
including Short Message Service (SMS)**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 300 757 V1.3.1:2003](https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-db343d0f367f/sist-en-300-757-v1-3-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-db343d0f367f/sist-en-300-757-v1-3-1-2003>



Reference

REN/DECT-A0203

Keywords

data, DECT, profile, SMS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 757 V1.3.1:2003

<https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-db343d0f367f/sist-en-300-757-v1-3-1-2003>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

Contents

Intellectual Property Rights	8
Foreword.....	8
Introduction	8
1 Scope	9
2 References	10
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols.....	11
3.3 Abbreviations	11
4 Description of services	13
4.1 General	13
4.2 Low Rate Messaging Service (LRMS).....	13
4.2.1 Point-To-Point (PTP).....	13
4.2.2 Point-To-Multipoint (PTM).....	14
4.3 Short Message Service (SMS).....	14
4.4 Service objectives.....	14
5 Low Rate Messaging Service (LRMS)	15
5.1 Reference configuration.....	15
5.2 Functional description.....	15
5.2.1 General.....	15
5.2.2 Exceptions for Point-To-Multipoint (PTM) service	16
5.2.2.1 MMS relations to outside networks (horizontal model).....	16
5.2.2.2 Architecture.....	16
5.2.2.3 MMS relations to the upper/lower layers (vertical model).....	16
5.2.2.4 Phases of the horizontal interactions.....	16
5.3 Physical layer requirements.....	16
5.4 MAC layer requirements	17
5.4.1 Requirements Point-To-Point (PTP) service.....	17
5.4.2 Requirements Point-To-Multipoint (PTM) service.....	17
5.4.3 Capabilities	18
5.4.3.1 Services	18
5.4.3.2 Protocol parameters.....	18
5.4.3.3 Messages	19
5.4.3.4 Message parameters	21
5.4.3.5 Functions implemented	22
5.4.3.6 Timer support.....	23
5.4.3.7 Procedure support	23
5.5 DLC layer requirements	24
5.5.1 Requirements C-plane Point-To-Point (PTP) service	24
5.5.2 Requirements C-plane Point-To-Multipoint (PTM) service	25
5.5.3 Requirements U-plane	25
5.5.4 Capabilities	25
5.5.4.1 C-plane services	25
5.5.4.2 C-plane procedures.....	25
5.5.4.2.1 Point to point acknowledged operation	25
5.5.4.2.2 Unacknowledged operation	27
5.5.4.2.3 Broadcast operation	27
5.5.4.2.4 Management procedures.....	28
5.5.4.3 C-plane PDU frame structure.....	29
5.5.4.4 C-plane messages.....	29
5.5.4.5 C-plane timers	34
5.5.4.6 C-plane protocol error handling	34
5.6 Network layer requirements	35

5.6.1	Requirements Point-To-Point (PTP) service.....	35
5.6.2	Requirements Point-To-Multipoint (PTM) service.....	35
5.7	Management entity requirements	36
5.8	Generic interworking conventions	36
5.8.1	MMSP procedures	36
5.8.2	Multimedia Messaging Service - Service Access Point (MMS-SAP)	36
5.8.3	MMSP primitives Point-To-Point (PTP) service	37
5.8.3.1	C-MMS primitives	37
5.8.3.2	M-MMS primitives	37
5.8.3.3	Parameters	37
5.8.4	MMSP primitives Point-To-Multipoint (PTM) Service	37
5.8.4.1	M-MMS primitives	37
5.8.4.2	Parameters	37
6	MMSP protocol definition.....	38
6.1	General	38
6.2	Functional description	38
6.2.1	General.....	38
6.2.2	MMS relations to outside networks (horizontal model).....	39
6.2.3	Architecture	40
6.2.3.1	General.....	40
6.2.3.2	MMSP call control part (C-MMS).....	40
6.2.3.3	MMSP messaging part (M-MMS)	40
6.2.4	MMS relations to the upper/lower layers (vertical model)	40
6.2.4.1	General	40
6.2.4.2	MMS relation to the DECT upper layers	41
6.2.4.2.1	General	41
6.2.4.2.2	M-MMS	41
6.2.4.2.3	C-MMS.....	42
6.2.5	MMS relations to outside networks (vertical and horizontal model).....	42
6.2.5.1	General	42
6.2.5.2	Phases of the horizontal interactions	42
6.2.5.2.1	General	42
6.2.5.2.2	PP originated outgoing MMS call	42
6.2.5.2.3	Example of a typical PP initiated message	44
6.2.5.2.4	PP terminated incoming MMS call.....	44
6.3	MMSP protocol messages and procedures.....	45
6.3.1	C-MMS messages and procedures.....	45
6.3.2	M-MMS	45
6.3.2.1	Summary of the M-MMS messages.....	45
6.3.2.2	MMS SEND procedure.....	45
6.3.2.2.1	{MMS-SEND} message contents	46
6.3.2.2.2	{MMS-SEND-RPY} message contents	46
6.3.2.3	MMS SEND-REQ procedure.....	47
6.3.2.3.1	{MMS-SEND-REQ} message contents	47
6.3.2.3.2	{MMS-SEND-RPY} message contents	48
6.3.2.4	MMS RETRIEVE procedure	48
6.3.2.4.1	{MMS-RETRIEVE} message contents.....	49
6.3.2.4.2	{MMS-RETRIEVE-RPY} message contents.....	49
6.3.2.5	MMS RETRIEVE-HDR procedure	49
6.3.2.5.1	{MMS-RETRIEVE-HDR} message contents	50
6.3.2.5.2	{MMS-RETRIEVE-RPY} message contents.....	50
6.3.2.6	MMS-EXT-CMD procedure	51
6.3.2.6.1	{MMS-EXT-CMD} message contents.....	51
6.3.2.6.2	{MMS-EXT-CMD-RPY} message contents.....	52
6.3.2.7	MMS-STATUS procedures	52
6.3.2.7.1	{MMS-STATUS} message contents.....	53
6.3.2.7.2	{MMS-STATUS-RPY} message contents.....	53
6.3.2.8	MMS-ESC-CMD procedure	53
6.3.2.8.1	{MMS-ESC-CMD} message contents	54
6.3.2.8.2	{MMS-ESC-CMD-RPY} message contents	54
6.3.2.8.3	Generic interworking conventions for the {MMS-ESC-CMD} command and reply.....	54

6.3.2.9	Procedures for the use of the MMS-message identifier	55
6.3.2.10	Multi-part message procedures	55
6.3.2.10.1	Multi-part send procedures	55
6.3.2.10.2	Multi-part retrieve procedures	56
6.3.2.11	Unsupported MMS command and IE compatibility procedures	56
6.3.2.11.1	Unsupported MMS commands procedure	56
6.3.2.11.2	Unsupported Information elements procedure	56
6.4	MMSP information elements	56
6.4.1	Summary of M-MMSP information elements	56
6.5	Parameters of M-MMSP service primitives	57
6.5.1	M_MMS_SEND- {req, ind}	57
6.5.2	M_MMS_SEND_REQ- {req, ind}	58
6.5.3	M_MMS_SEND_RPY- {req, ind}	58
6.5.4	M_MMS_RETRIEVE- {req, ind}	59
6.5.5	M_MMS_RETRIEVE_RPY- {req, ind}	59
6.5.6	M_MMS_EXT_CMD- {req, ind}	60
6.5.7	M_MMS_EXT_CMD_RPY- {req, ind}	60
6.5.8	M_MMS_STATUS- {req, ind}	61
6.5.9	M_MMS_STATUS_RPY- {req, ind}	61
6.5.10	M_MMS_ESC_CMD- {req, ind}	62
6.5.11	M_MMS_ESC_CMD_RPY- {req, ind}	62
7	Short Message Service (SMS).....	63
7.1	Feature and service definitions.....	63
7.1.1	Application features.....	63
7.1.2	MMS features	63
7.1.3	NWK features	63
7.1.4	DLC services	63
7.2	General requirements	63
7.2.1	Reference configurations	63
7.2.2	Protocol architecture	63
7.3	Interoperability requirements	64
7.3.1	Application features.....	64
7.3.2	MMS features	65
7.3.3	NWK features	65
7.3.4	DLC services	65
7.3.5	MAC services	65
7.3.6	PHL services.....	65
7.3.7	Application feature to procedure mapping.....	66
7.3.8	MMS feature to procedure mapping	66
7.3.9	NWK feature to procedure mapping.....	66
7.3.10	DLC feature to procedure mapping	67
7.4	Application procedures.....	67
7.4.1	Incoming message storage	67
7.4.2	Message encapsulation	67
7.4.3	General interworking requirements	67
7.4.3.1	Mapping of SMS message transfers onto CC- transactions	67
7.4.3.2	Authentication and ciphering	67
7.4.4	Message/primitive interworking	68
7.5	MMS procedures	68
7.5.1	Messaging send procedure.....	68
7.6	NWK layer procedure descriptions	70
7.6.1	Summary of outgoing call messages, normal case.....	70
7.6.2	Outgoing messaging call request	70
7.6.3	Outgoing messaging call connect	70
7.6.4	Summary of incoming call messages, normal case.....	71
7.6.5	Incoming messaging call request	71
7.6.6	Incoming messaging call connect	72
7.6.7	Message transfer	72
7.6.8	Terminal capability indication	73
7.7	DLC layer procedures	73
7.7.1	Class B link establishment.....	73

7.7.1.1	Associated procedures.....	75
7.7.1.1.1	Timer <DL.02> management	75
7.7.1.1.2	Re-transmission counter management	75
7.7.1.1.3	Multiple frame operation variables management	75
7.7.1.2	Exceptional cases	76
7.7.1.2.1	Timer <DL.02> expiry	76
7.7.1.2.2	Receipt of a request for link release	76
7.7.1.2.3	Receipt of an indication for a connection release	76
7.7.2	Class B multiple frame operation	76
7.7.2.1	Class B multiple frame operation with segment reassemble	79
7.7.2.2	Associated procedures.....	79
7.7.2.2.1	Timer <DL.04> management	79
7.7.2.2.2	Re-transmission counter management	79
7.7.2.2.3	Multiple frame operation variables management	79
7.7.2.2.4	Exception handling	79
7.7.2.3	Exceptional cases	79
7.7.2.3.1	Timer <DL.04> expiry	79
7.7.2.3.2	Receipt of a request for link release	79
7.7.2.3.3	Receipt of an indication for a connection release	80
7.7.2.3.4	DLC wants to make a connection handover	80
7.7.3	Class B link release.....	80
7.7.3.1	Associated procedures.....	82
7.7.3.1.1	LLME U-plane release	82
7.7.3.1.2	LLME release a MAC connection.....	82
7.7.3.1.3	Timer <DL.00> management	82
7.7.3.2	Exceptional cases	82
7.7.3.2.1	Timer <DL.00> expiry	82
7.7.3.2.2	Receipt of an indication for a connection release	83
7.7.3.2.3	Collision of identical transmitted and received commands	83
7.7.4	Class B link suspension and resumption	83
7.7.4.1	Unacknowledged suspend	83
7.7.4.2	Class B link resumption	83
7.7.4.3	Associated procedures.....	83
7.7.4.3.1	Timer <DL.03> management	83
7.7.4.4	Exceptional cases	83
7.7.4.4.1	Timer <DL.03> expiry	83
7.7.4.4.2	Receipt of an indication for a connection release	84
7.7.5	Class B link re-establishment.....	84
7.7.5.1	Associated procedures.....	86
7.7.5.1.1	Timer <DL.02> management	86
7.7.5.2	Exceptional cases	86
7.7.5.2.1	Timer <DL.02> expiry	86
7.7.5.2.2	Receipt of a request for link release	86
7.7.5.2.3	Receipt of an indication for a connection release	86
7.7.5.2.4	Collision of identical transmitted and received commands	86
7.8	MAC layer procedures	87
7.9	PHY layer requirements.....	87
7.10	Management procedures.....	87
7.10.1	Broadcast attribute management.....	87

Annex A (normative): Support of MMSP by the DECT lower layers.....88

A.1	Profile-specific information elements	88
A.1.1	MMS Generic Header information element	88
A.1.2	MMS Object Header information element	92
A.1.3	MMS Extended Header information element.....	97
A.2	MMSP message implementation.....	98
A.2.1	General	98
A.2.2	C-MMS primitives mapping rules.....	98
A.2.2.1	LRMS PTP C-MMS primitives	98
A.2.2.2	LRMS PTM C-MMS primitives.....	98
A.2.3	M-MMS message mapping rules.....	98

A.2.3.1	General rules for LRMS PTP.....	98
A.2.3.2	General rules for LRMS PTM	99
A.2.3.3	Information element mapping rules	99
A.3	Network layer segmentation rules for LRMS PTP.....	99
A.3.1	Procedure at the sending side	99
A.3.2	Procedure at the receiving side.....	100
Annex B (informative):	Profile selection coding.....	101
B.1	<<BASIC SERVICE>> coding.....	101
B.2	<<IWU-ATTRIBUTES>> coding	101
B.3	<<CONNECTION ATTRIBUTES>> coding.....	101
Annex C (informative):	Typical message mapping sequences.....	102
C.1	Summary of SMS-RP requirements	102
C.2	Message sequences.....	102
Annex D (informative):	Bibliography.....	104
History	105

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 757 V1.3.1:2003](https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-db343d0f367f/sist-en-300-757-v1-3-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-db343d0f367f/sist-en-300-757-v1-3-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Project Digital Enhanced Cordless Telecommunications (DECT).

National transposition dates	
Date of adoption of this EN:	4 January 2001
Date of latest announcement of this EN (doa):	30 April 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 October 2001
Date of withdrawal of any conflicting National Standard (dow):	31 October 2001

[SIST EN 300 757 V1.3.1:2003](https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-db343d0f367f/sist-en-300-757-v1-3-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-db343d0f367f/sist-en-300-757-v1-3-1-2003>

Introduction

The present document replaces the former ETS 300 757, known as the E.2 profile, and the former ETS 301 678 (never published), known as CTM FP2. It defines profiles for Digital Enhanced Cordless Telecommunications (DECT) systems conforming to EN 300 175 parts 1 [1] to 8 [8]. It is part of a family of profiles aimed at the general connection of terminals supporting non-voice services to a fixed infrastructure, private and public.

1 Scope

The Low Rate Messaging Service (LRMS), specified in the present document, provides a means for the slow, acknowledged or unacknowledged, transfer of multimedia message objects, including the Short Message Service (SMS). It provides both point-to-point and point-to-multipoint messaging. This service may be used for private and public roaming applications.

The present document defines the requirements on the Physical (PHY), Medium Access Control (MAC), Data Link Control (DLC) and Network (NWK) layers of DECT. The standard also specifies management entity requirements and generic interworking conventions, which ensure the efficient use of the DECT spectrum.


The present document further mandates how to implement a GSM like Short Message Service (SMS), Point to Point (PTP), which uses a sub-set of the Low Rate Messaging Service (LRMS) mentioned before as a bearer service. SMS-PTP includes the following two services:

- SMS Mobile Originated (SMS-MO), for transport of short messages from PT to FT;
- SMS Mobile Terminated (SMS-MT), for transport of short messages from FT to PT.

The Short Message Service, Cell Broadcast is outside the scope of the present document.

In order to facilitate re-use of existing GSM Service Centres, the present document applies the upper GSM protocols up-to and including the GSM SMS-RP protocol. Therefore, interworking functions handling the encapsulation of GSM SMS-RP messages are specified.

The following picture shows the protocols defined in the present document.



The SMS or LRMS applications are outside the scope of the present document. So is the network behind the FP. Any information provided concerning applications or the network behind the FP is provided for informative, descriptive reasons only.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".
- [3] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
- [5] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [6] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [7] ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
- [8] ETSI EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech coding and transmission".
- [9] ETSI EN 300 444: "Digital Enhanced Cordless Telecommunications (DECT); Generic Access Profile (GAP)".
- [10] ETSI ETS 300 559: "European digital cellular telecommunications system (Phase 2); Point-to-Point (PP) Short Message Service (SMS) support on mobile radio interface (GSM 04.11)".
- [11] ISO/IEC 8073: "Information technology - Open Systems Interconnection - Protocol for providing the connection-mode transport service".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

multiframe: repeating sequence of 16 successive Time Division Multiple Access (TDMA) frames, that allows low rate or sporadic information to be multiplexed (e.g. basic system information or paging)

service class 1: local area applications, for which terminals are pre-registered off-air with one or more specific fixed parts, and establishment of service and user parameters is therefore implicit, according to a profile-defined list

service class 2: private and public roaming applications for which terminals may move between fixed parts within a given domain and for which association of service parameters is explicit at the time of service request

SMS-SC: SMS Short Message Center

NOTE: It is the logical entity able to store and forward short messages.

TDMA frame: time-division multiplex of 10 ms duration, containing 24 successive full slots

NOTE: A TDMA frame starts with the first bit period of full slot 0 and ends with the last bit period of full slot 23.

3.2 Symbols

The symbols defined in this clause are applied for procedures, features, services in the present document if not explicitly otherwise stated. The interpretation of status columns in all tables is as follows:

C	for conditional to support (process mandatory);
I	for out-of-scope (provision optional, process optional) not subject for testing;
M	for mandatory to support (provision mandatory, process mandatory);
N/A	for non-applicable (in the given context the specification makes it impossible to use this capability).
O	for optional to support (provision optional, process mandatory);

Provision mandatory, process mandatory means that the indicated feature, service or procedure shall be implemented as described in the present document, and may be subject to testing.

Provision optional, process mandatory means that the indicated feature, service or procedure may be implemented, and if implemented, the feature, service or procedure shall be implemented as described in the present document, and may be subject to testing.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACK	Acknowledgement
ADPCM	Adaptive Pulse Code Modulation
CC	Call Control
C _F	higher layer signalling Channel (Fast)
CL _F	higher layer Connectionless channel (Fast) - a logical channel to the MAC layer
CL _S	higher layer Connectionless channel (Slow) - a logical channel to the MAC layer
CLMS	Connectionless Message Service
C-plane	Control plane
CTM	Cordless Terminal Mobility
C _S	higher layer signalling Channel (Slow)
DAM	DECT Authentication Module
DLC	Data Link Control
FP	Fixed Part

FT	Fixed radio Termination
FTP	File Transfer Protocol
GAP	Generic Access Profile
G _F	higher layer information control channel - a logical channel to the MAC layer
GSM	Global System for Mobile communication
HTTP	Hyper Text Transfer Protocol
IE	Information Element
I _p	higher layer Information channel (Protected)
IWF	Interworking Functions
IWU	Interworking Unit
LAP	Link Access Procedure
LAP-C	Link Access Procedure (Control)
LCE	Link Control Entity
LLN	Logical Link Number (DLC layer)
LRMS	Low Rate Messaging Service
M	MAC control channel
MAC	Medium Access Control
MCE	Message Control Entity
MMSP	Multimedia Messaging Service Protocol
MNCC	Mobile Network Call Control
MO	Mobile Originated
MT	Mobile Terminated
NLF	New Link Flag
NWK	Network
P	Paging channel
PDU	Protocol Data Unit
PHL	Physical Layer
PHY	Physical
PP	Portable Part
PT	Portable radio Termination
PTM	Point-To-Multipoint
PTP	Point-To-Point
Q	system information channel
RFP	Radio Fixed Part
RFPI	Radio Fixed Part Identifier
SAP	Service Access Point
SAPI	Service Access Point Identifier
SC	Service Center
SDU	Service Data Unit
SI _N	higher layer connectionless channel (Unprotected)
SIM	Subscriber Identity Module
SM	Short Message
SM-RP	Short Message Relay layer Protocol
SM-TP	Short Message Transfer layer Protocol
SMS	Short Message Service
SMS-MO	SMS Mobile Originated
SMS-MT	SMS Mobile Terminated
TDMA	Time Division Multiple Access
UI	Unnumbered Information (Frame)
U-plane	User plane
WWW	World Wide Web

Tech STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 757 V1.3.1:2003](https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-d0345d0b67f/sist-en-300-757-v1-3-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/58b0efbe-33f6-4565-a255-d0345d0b67f/sist-en-300-757-v1-3-1-2003>

4 Description of services

4.1 General

The DECT data profile defined in the present document has been intended for message transfer or paging and is optimized for small SDUs, low PP complexity and ultra-low power consumption. Two service types are defined: Low Rate Messaging Service Point-To-Point (LRMS PTP) which may be unacknowledged or acknowledged used for point-to-point messaging and Low Rate Messaging Service Point-To-Multipoint (LRMS PTM) used for point-to-multipoint messaging. The LRMS PTM is an optional feature while LRMS PTP support is mandatory if this profile is supported.

The LRMS PTP and PTM may co-exist with other profiles and their existence should not have any effect on the functionality of the other existing profiles. That is, the LRMS functionality should have a secondary priority in respect to the profile relations.

The present document also mandates how LRMS PTP is to be used for transfer of GSM like SMS messages.

4.2 Low Rate Messaging Service (LRMS)

4.2.1 Point-To-Point (PTP)

The objectives of the LRMS PTP profile are as follows:

The LRMS PTP is a generic set of commands, information elements and functionality for file/messaging service. In most of the cases LRMS can be regarded as a DECT internal teleservice that can interwork with the similar services in external networks. In addition LRMS PTP provides means to convey transparently application specific upper layer protocol frames thus facilitating the usage of this profile as a bearer service. It provides a generic file handling/messaging services over the DECT air interface by utilizing the transportation mechanism of the DECT C-plane in the best way possible while offering a general set of functions to the applications using its services. The LRMS procedures can be accessed in a standardized way through a set of primitives. The LRMS point-to-point service may be acknowledge or unacknowledged.

LRMS provides a compact subset of functions to messaging servers with the advantage that a single terminal with LRMS support can use a wide variety of messaging services with minimum amount of application layer complexity. If a complete set of services is needed an escape sequence has to be used or some other means such as transparent protocol transportation mechanism should be used.

The Multimedia Messaging Service Protocol (MMSP) fulfils these objectives.

MMSP that is used for the provision of LRMS services and functionality is a stateless protocol which defines a set of messages, framing rules and information elements each containing optional and mandatory information fields.

MMSP utilizes the services of the DECT Call Control (CC) entity. It could be regarded as a supplementary service type of service that provides signalling/control and application specific information related to the teleservices provided by the DECT data profiles.

The MMSP layer functionality is provided by a set of specific DECT network layer CC information elements. Therefore the MMSP is not from DECT layer viewpoint a separate real protocol layer but a service provided to the application. However, from the application perspective the MMSP can be seen as a protocol layer. Therefore, the MMSP can be regarded as a virtual protocol layer.

The support of MMSP protocol in LRMS PTP is mandatory.

In general the LRMS PTP may receive or send messages during an on-going other profile based call but this requires a separate CC instance.