

IEC 60384-22

(First edition – 2004-06)

**Fixed capacitors for use in electronic equipment –**

**Part 22: Sectional specification: Fixed surface mount multilayer capacitors**

**of ceramic dielectric, Class 2**

**CORRIGENDUM 1**

Page 8

**1.5.6  
rated voltage (DC)**

*Replace, in the note, 'AC' by 'a.c.'.*

Page 8

**1.5.6  
rated voltage (DC)**

*Replace, in the title and text, 'DC' by 'd.c.'.*

Page 9

**1.6.1**

*Replace, in item b), 'DC' by 'd.c.'.*

Page 10

**2.2.5 Temperature characteristic of capacitance**

*Replace, in the first paragraph, 'DC' by 'd.c.'.*

Page 11

**Table 3 – Temperature characteristic of capacitance**

*Replace, throughout the table, 'DC' by 'd.c.'.*

**Table 4 – Fixed sample size test plan for qualification approval, assessment level EZ**

Replace the column headers by the following:

Group No.	Test	Subclause of this publication	Number of specimens <i>n</i> <sup>e</sup>	Permissible number of non conforming items <i>c</i>
-----------	------	-------------------------------	--	--

**Table 5 – Tests schedule for qualification approval**

Replace GROUP 1 A by the following:

GROUP 1A	D	See Table 4	
4.15 Robustness of termination (if applicable)		Test Ua1, force: 2,5 N Test Ub, method 1, force: 2,5 N Number of bends: 1 Visual examination	No visible damage
4.9.2 Initial measurement		Capacitance	
4.9 Resistance to soldering heat		Special preconditioning as in 4.1 See detail specification for the method Recovery: (24 ± 2) h	
4.9.5 Final measurement		Visual examination Capacitance	As in 4.9.5 As in 4.9.5
4.16 Component solvent resistance (if applicable)		Solvent: ... Solvent temperature: ... Method 2 Recovery: ...	See detail specification