



IEC 60794-2-50

Edition 1.0 2008-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Optical fibre cables –

Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies

Câbles à fibres optiques –

Partie 2-50: Câbles intérieurs – Spécification de famille pour les câbles simplex et duplex utilisés dans les ensembles de câbles équipés

<https://standards.itech.ai/cstd/g/standards/icc/386f3d4e-996c-430d-90bd-fd81862bd98c/iec-60794-2-50-2008>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch

Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00



IEC 60794-2-50

Edition 1.0 2008-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Optical fibre cables –

Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies

Câbles à fibres optiques –

Partie 2-50: Câbles intérieurs – Spécification de famille pour les câbles simplex et duplex utilisés dans les ensembles de câbles équipés

<https://standards.itech.ai/cstdn/standards/icc/386f3d4e-996c-430d-90bd-fd81862bd98c/iec-60794-2-50-2008>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

V

ICS 33.180.10

ISBN 2-8318-9902-8

CONTENTS

FOREWORD	4
1 Scope	6
2 Normative references	6
3 Terms and definitions	7
4 Construction	7
4.1 General	7
4.2 Optical fibres and primary coating	7
4.3 Buffer	7
4.4 Tube	8
4.5 Strength and anti-buckling members	8
4.6 Sheath	8
4.7 Sheath marking	8
4.8 Examples of cable constructions	8
5 Tests	8
5.1 Dimensions	9
5.2 Mechanical requirements	9
5.2.1 Tensile performance	9
5.2.2 Crush	9
5.2.3 Impact	10
5.2.4 Repeated bending	10
5.2.5 Bend	10
5.2.6 Torsion	11
5.2.7 Bend at low temperature	11
5.2.8 Kink	11
5.2.9 Sheath pull-off force	11
5.2.10 Buffered fibre movement in compression	12
5.3 Environmental requirements	12
5.3.1 Temperature cycling	12
5.3.2 Sheath shrinkage	13
5.4 Transmission requirements	13
5.5 Fire performance	13
Annex A (informative) Examples of some types of cable construction	14
Annex B (normative) METHOD E21 – Sheath pull-off force for optical fibre cable for use in patch cords	17
Annex C (normative) METHOD F11 – Sheath shrinkage for optical fibre cable for use in patchcords	22
Annex D (normative) METHOD E22 – Buffered fibre movement under compression in optical fibre cables for use in patchcords	24
Annex E (normative) METHOD F12 – Temperature cycling for optical fibre cable for use in patchcords	26
Annex F (normative) Guidance on the selection of tests applicable to optical fibre cables for use in patchcords	28
Bibliography	31
Figure A.1 – Simplex loose non-buffered fibre cable	14

Figure A.2 – Simplex ruggedized fibre cable	14
Figure A.3 – Duplex loose non-buffered fibre cable.....	14
Figure A.4 – Duplex ruggedized fibre cable.....	15
Figure A.5 – Duplex ruggedized fibre zip cord.....	15
Figure A.6 – Duplex ruggedized flat cable.....	15
Figure A.7 – Duplex ruggedized round cable.....	16
Figure B.1 – Schematic of test arrangement	19
Figure B.2 – Example of pulling jig.....	20
Figure B.3 – Cable sample preparation	21
Figure D.1 – Test set up for fibre movement under compression.....	25
Table 1 – Dimensions of buffered fibres	8
Table 2 – Temperature cycling severities	12
Table F.1 – Cable test method summary	28
Table F.2 – Cable testing agreement	30

iTech Standards
(<https://standards.itech.ai>)

Document Preview

[IEC 60794-2-50:2008](https://standards.itech.ai/cstdng/standards/icc/386f3d4e-996c-430d-90bd-fd81862bd98c/iec-60794-2-50-2008)

<https://standards.itech.ai/cstdng/standards/icc/386f3d4e-996c-430d-90bd-fd81862bd98c/iec-60794-2-50-2008>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

OPTICAL FIBRE CABLES –

Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60794-2-50 has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

This standard cancels and replaces IEC/PAS 60794-2-50 published in 2004. This first edition constitutes a technical revision.

This standard is to be used in conjunction with IEC 60794-1-1, IEC 60794-1-2 and IEC 60794-2.

This bilingual version, published in 2008-07, corresponds to the English version.

The text of this standard is based on the following documents:

FDIS	Report on voting
86A/1204/FDIS	86A/1223/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 60794 series, under the general title *Optical fibre cables*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

<https://standards.itech.ai/ctn/g/standards/ics/386f3d4e-996c-430d-90bd-fd81862bd98c/iec-60794-2-50-2008>

OPTICAL FIBRE CABLES –

Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies

1 Scope

This part of IEC 60794 is a family specification that covers requirements for simplex and duplex optical fibre cables for use in terminated cable assemblies or for termination with optical fibre passive components.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

They complete the normative references already listed in the generic specification (IEC 60794-1-1 and IEC 60794-1-2) or in the sectional specification (IEC 60794-2 series).

IEC 60068-2-14, *Environmental testing – Part 2: Tests. Test N: Change of temperature*

IEC 60189-1, *Low-frequency cables and wires with PVC insulation and PVC sheath – Part 1: General test and measuring methods*

IEC 60793-1-1:2008, *Optical fibres – Part 1-1: Measurement methods and test procedures – General and guidance* <https://www.iec.ch/standards/ics/386f3d4e-996c-430d-90bd-fd81862bd98c/iec-60794-2-50-2008>

IEC 60793-1-20, *Optical fibres – Part 1-20: Measurement methods and test procedures – Fibre geometry*

IEC 60793-1-21, *Optical fibres – Part 1-21: Measurement methods and test procedures – Coating geometry*

IEC 60793-1-40, *Optical fibres – Part 1-40: Measurement methods and test procedures – Attenuation*

IEC 60793-1-46, *Optical fibres – Part 1-46: Measurement methods and test procedures – Monitoring of changes in optical transmittance*

IEC 60793-2-10, *Optical fibres – Part 2-10: Product specifications – Sectional specification for category A1 multimode fibres*

IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 60794-1-1, *Optical fibre cables – Part 1-1: Generic specification – General*

IEC 60794-1-2:2003, *Optical fibre cables – Part 1-2: Generic specification – Basic optical cable test procedures*

IEC 60794-2, Optical fibre cables – Part 2: Indoor cables – Sectional specification

IEC 60811-1-3, *Common test methods for insulating and sheathing materials of electric and optical cables – Part 1-3: General application – Methods for determining the density – Water absorption tests – Shrinkage test*

IEC 60811-1-4:1985, *Common test methods for insulating and sheathing materials of electric cables – Part 1: Methods for general application – Section Four: Tests at low temperature*

Amendment 1 (1993)

Amendment 2 (2001)

ISO/IEC 11801, *Information technology – Generic cabling for customer premises*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

terminated cable assembly

short length of cable provisioned with a connector at both ends

NOTE Examples from ISO/IEC 11801 are:

Patch cords are used to establish connections on a patch panel. Typical length of the patch cord 1 m to 10 m.

Work area cords are used to connect outlet to the terminal equipment. Typical length of the work area cords according to this specification is between 1 m and 35 m.

Equipment cords should fulfill the requirements of patch cords or work area cords depending on their application.

4 Construction

4.1 General

In addition to the constructional requirements in IEC 60794-2, the following considerations apply to simplex and duplex indoor cables for use in terminated cable assemblies.

It is not the intention of this standard to specify the finished terminated cable assembly complete with terminations.

The cable shall be designed and manufactured for an expected operating lifetime of 15 years. The materials in the cable shall not present a health hazard within its intended use.

There shall be no fibre splice in a delivery length. It shall be possible to identify each individual fibre throughout the length of the cable.

4.2 Optical fibres and primary coating

Multimode or single-mode optical fibres meeting the requirements of IEC 60793-2-10, type A1a and A1b, and IEC 60793-2-50, type B, shall be used.

4.3 Buffer

If a tight or semi-tight (loosely applied) buffer is required, it shall consist of one or more layers of inert material. Semi-tight tubes may be filled. Unless otherwise specified, the buffer shall be removable in one operation over a length of 15 mm.

Buffer dimensions are shown in Table 1.

Table 1 – Dimensions of buffered fibres

Nominal diameter (mm)	0,3 – 1,3
Tolerances (mm)	± 0,05

4.4 Tube

One or two primary coated or buffered fibres are packaged (loosely or not) in a tube construction which may be filled. The tube may be reinforced with a composite wall.

If required the suitability of the tube shall be determined by an evaluation of its kink resistance in accordance with IEC 60794-1-2, Method G7.

4.5 Strength and anti-buckling members

The cable shall be designed with sufficient strength members to meet the requirements of this standard.

The strength and/or anti-buckling member may be either metallic or non-metallic and may be located in the cable core and/or under the sheath and/or in the sheath.

4.6 Sheath

The cable shall have a uniform overall protective sheath. The cable diameter shall be specified in the relevant detail specification (or product specification). Sheath removal is an important feature of these cables. This is tested by the method E21 described in Annex B of this standard.

4.7 Sheath marking

If required, the cable shall be marked as agreed between the customer and supplier. The marking shall be resistant to abrasion.

<https://standards.itec.ai/ctryg/standards/iec/386f3d4e-996c-430d-90bd-fd81862bd98c/iec-60794-2-50-2008>

4.8 Examples of cable constructions

Examples of some main types of cable construction are shown in Figures A.1 to A.7.

Other configurations are not excluded if they meet the mechanical, environmental, transmission and termination requirements given in this standard.

5 Tests

Compliance with the specification requirements shall be verified by carrying out tests selected from the following subclauses. It is not intended that all tests be carried out in all cases, and Annex F provides guidance on the selection of tests. The tests to be applied and the frequency of testing shall be agreed between the customer and supplier.

Some of the following tests can be performed on a short sample length of cable which is still an integral part of a longer length, thus making it possible to detect permanent changes in attenuation.

Single-mode cables shall be measured at 1 550 nm and 1 625 nm and multimode¹⁾ cables shall be measured at 1 300 nm unless otherwise agreed. Measurements shall be carried out according to IEC 60793-1-40.

If loops are used within a test to fix the ends of a cable, the diameter shall not be so small as to cause excessive mode filtering in multimode fibre.

Unless otherwise specified, all tests shall be carried out at ambient temperature, as described in IEC 60793-1-1, Clause 5.

5.1 Dimensions

The fibre dimensions and tolerances shall be checked in accordance with test method of IEC 60793-1-20 or IEC 60793-1-21. The diameter of the buffer and of the cable, as well as the thickness of the sheath, shall be measured in accordance with the methods of IEC 60189-1.

5.2 Mechanical requirements

5.2.1 Tensile performance

Method: IEC 60794-1-2-E1A.

Diameter of chuck drums and transfer devices: not less than the minimum dynamic bending diameter specified for the cable, at least 250 mm diameter.

Rate of transfer device: either 100 mm/min or 100 N/min.

Load: 100 N applied for 5 min for simplex cables, 200 N for 5 min for duplex cables.

Length of sample: sufficient to achieve the desired accuracy of measurement of attenuation change and shall be agreed between the customer and the supplier.

<https://standards.iteh.ai/ctm/g/standards/icc/386f3d4e-996c-430d-90bd-fd81862bd98c/iec-60794-2-50-2008>

Requirements: the maximum increase in attenuation during the test shall be specified in the product specification, there shall be no change in attenuation after the test, and there shall be no damage to the cable elements.

5.2.2 Crush

Method: IEC 60794-1-2-E3.

Force: 500 N.

Duration: 1 min.

Length between test locations: 500 mm.

Requirements: the maximum increase in attenuation during the test shall be specified in the product specification, there shall be no change in attenuation after the test, and there shall be no damage to the cable elements.

NOTE For cables having a non-circular cross section, the force should be applied in the direction of the minor axis (perpendicular to the major axis).

¹⁾ OM3 multimode cables should be tested at 850 nm and may be tested at 1 300 in addition, all other multimode cables should be tested at 1 300 nm.

5.2.3 Impact

Method: IEC 60794-1-2-E4.

Radius of striking surface: 12,5 mm.

Impact energy: 1,0 J.

Number of impacts: at least 3, each separated at least 500 mm.

Requirements: the maximum increase in attenuation after the test shall be specified in the product specification and there shall be no fibre breakage or damage to the cable elements. Any imprint of the striking surface on the cable sheath is not considered as a mechanical damage.

NOTE For cables having a non-circular cross section, the force should be applied in the direction of the minor axis (perpendicular to the major axis).

5.2.4 Repeated bending

Method: IEC 60794-1-2-E6.

Bending radius: 30 mm for simplex, 20 times cable diameter for duplex (for non-circular cables, the cable diameter is the minor dimension).

Number of cycles: 200.

Mass of weights: sufficient to contour the apparatus e.g. 1 kg to 2 kg.

Requirements: the maximum increase in attenuation during the test shall be specified in the product specification, there shall be no change in attenuation after the test, and there shall be no damage to the cable elements.

NOTE For cables having a non-circular cross section, the bend requirements are determined using the minor axis as the cable diameter with bending in the direction of the preferential bend.

5.2.5 Bend

Method: IEC 60794-1-2-E11A.

Mandrel diameter: 60 mm.

Number of turns per helix: 6.

Number of cycles: 3.

Length of sample: sufficient to carry out the test.

Prior to bending: at both ends of the sample all the cable components shall be fixed together, e.g. by loops or glue.

Requirements: the maximum increase in attenuation during the test shall be specified in the product specification, there shall be no change in attenuation after the test, and there shall be no damage to the cable elements.

NOTE For cables having a non-circular cross section, the bend requirements are determined using the minor axis as the cable diameter with bending in the direction of the preferential bend.

5.2.6 Torsion

Method: IEC 60794-1-2-E7.

Number of cycles: 10.

Distance between fixed and rotating clamps: 250 mm.

Tension load: according to Table 1 of IEC 60794-1-2-E7.

Length of sample: sufficient to carry out the test.

Requirements: the maximum increase in attenuation during the test shall be specified in the product specification, there shall be no change in attenuation after the test, and there shall be no damage to the cable elements.

5.2.7 Bend at low temperature

Method: IEC 60794-1-2-E11A (see IEC 60811-1-4, Clause 8)

Bending radius: 10 times cable diameter (for non-circular cables, the cable diameter is the minor dimension) but not less than 30 mm.

Number of cycles: 2.

Test temperature: 0 °C, -10 °C or -15 °C depending on application and customer requirements.

Number of turns per helix: according to Clause 8 of IEC 60811-1-4.

Requirements: in addition to the requirement of Clause 8 of IEC 60811-1-4, no fibre shall break during the test and there shall be no damage to the cable elements.

5.2.8 Kink

Method: IEC 60794-1-2-E10.

Minimum loop, horizontal inner dimension: (for non-circular cables, the cable diameter is the minor dimension), see Figure E.10.

- For cables outer diameter \leq 3,0 mm, to be 10 mm.
- For cables outer diameter $>$ 3,0 mm, to be $5 \times$ the cable diameter.

NOTE This is not an operational parameter; this is to address short-term installation/handling performance.

Requirement: no kink shall occur.

5.2.9 Sheath pull-off force

Method: see Annex B.

Rate of separation: \leq 200 mm/min.

Strip length: 50 mm.

Requirement: the force to strip the sheath shall not be greater than 15 N.

5.2.10 Buffered fibre movement in compression

Method: See Annex D.

Compression distance: 1 mm.

Number of movements: 5.

Requirement: the maximum increase in attenuation during the test shall be specified in the product specification and the reaction force shall be less than 1 N at 0,4 mm.

5.3 Environmental requirements

5.3.1 Temperature cycling

Method: See Annex E.

Severity taken from Table 2 below.

Period: t_1 sufficient that the cable has reached, and stabilised to, the specified temperature.

Number of cycles: 4.

Length of sample: 10 m.

Requirements: maximum increase in attenuation shall be as shown in Table 2 below.

Measurement uncertainty:

- 0,05 dB for cables with single-mode fibres;
- 0,10 dB for cables with multimode fibres.

<https://standards.itech.ai/cstdn/g/standards/iec/386f3d4e-996c-430d-90bd-fd81862bd98c/iec-60794-2-50-2008>

Table 2 – Temperature cycling severities

	Low temperature T_A °C	High temperature T_B °C	Maximum increase in attenuation at 1 300 nm dB	Maximum increase in attenuation at 1 550 nm dB	Maximum increase in attenuation at 1 625 nm dB
a)	0	+50	0,1	0,1	0,2
b)	-5	+50	0,1	0,2	0,3
c)	-20	+60	0,3	0,5	1,0
d)	-45	+60	0,3	0,5	1,0
e)	-25	+70	0,3	0,5	1,0
f)	-40	+85	0,3	0,5	1,0

NOTE Condition a), b), c), d) e) or f) should be selected depending on application and user requirements, for example condition c) is appropriate for applications to ISO/IEC 11801. The low temperature requirement for the completed patchcord assembly is -10 °C.