

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Multicore and symmetrical pair/quad cables for digital communications –
Part 1: Generic specification**

**Câbles multiconducteurs à paires symétriques et quartes pour transmissions
numériques –
Partie 1: Spécification générique**

[IEC 61156-1:2007](https://standards.iteh.ai/standards/iec/13466288-b607-403c-a813-3419295b0bc8/iec-61156-1-2007)

<https://standards.iteh.ai/standards/iec/13466288-b607-403c-a813-3419295b0bc8/iec-61156-1-2007>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Multicore and symmetrical pair/quad cables for digital communications –
Part 1: Generic specification**

**Câbles multiconducteurs à paires symétriques et quartes pour transmissions
numériques –
Partie 1: Spécification générique**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.120.20

ISBN 978-2-8891-0417-8

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	9
4 Installation considerations	12
5 Materials and cable construction	13
5.1 General remarks.....	13
5.2 Cable construction	13
5.2.1 Conductor.....	13
5.2.2 Insulation.....	13
5.2.3 Cable element	14
5.2.4 Cable make-up	14
5.2.5 Screening of the cable core	14
5.2.6 Sheath.....	15
5.2.7 Identification.....	15
5.2.8 Finished cable	15
6 Characteristics and requirements	15
6.1 General remarks – Test configurations	15
6.2 Electrical characteristics and tests	16
6.2.1 Conductor resistance.....	16
6.2.2 Resistance unbalance	16
6.2.3 Dielectric strength	17
6.2.4 Insulation resistance.....	17
6.2.5 Mutual capacitance.....	17
6.2.6 Capacitance unbalance	17
6.2.7 Transfer impedance.....	18
6.2.8 Coupling attenuation.....	18
6.2.9 Current-carrying capacity.....	18
6.3 Transmission characteristics	18
6.3.1 Velocity of propagation (phase velocity)	18
6.3.2 Phase delay and differential delay (delay skew)	19
6.3.3 Attenuation.....	19
6.3.4 Unbalance attenuation.....	22
6.3.5 Near-end crosstalk	27
6.3.6 Far-end crosstalk.....	29
6.3.7 Alien (exogenous) near-end crosstalk.....	32
6.3.8 Alien (exogenous) far-end crosstalk.....	37
6.3.9 Alien (exogenous) crosstalk of bundled cables	37
6.3.10 Impedance.....	38
6.3.11 Return loss.....	39
6.4 Mechanical and dimensional characteristics and requirements	40
6.4.1 Measurement of dimensions	40
6.4.2 Elongation at break of the conductor	40
6.4.3 Tensile strength of the insulation	40
6.4.4 Elongation at break of the insulation.....	40
6.4.5 Adhesion of the insulation to the conductor	40

6.4.6	Elongation at break of the sheath	40
6.4.7	Tensile strength of the sheath	40
6.4.8	Crush test of the cable	40
6.4.9	Impact test of the cable	40
6.4.10	Bending under tension.....	40
6.4.11	Repeated bending of the cable	43
6.4.12	Tensile performance of the cable.....	44
6.4.13	Shock test of the cable	44
6.4.14	Bump test of the cable.....	44
6.4.15	Vibration test of the cable.....	44
6.5	Environmental characteristics.....	44
6.5.1	Shrinkage of the insulation	44
6.5.2	Wrapping test of the insulation after thermal ageing.....	44
6.5.3	Bending test of the insulation at low temperature.....	45
6.5.4	Elongation at break of the sheath after ageing.....	45
6.5.5	Tensile strength of the sheath after ageing.....	45
6.5.6	Sheath pressure test at high temperature.....	45
6.5.7	Cold bend test of the cable.....	45
6.5.8	Heat shock test.....	46
6.5.9	Damp heat steady state.....	46
6.5.10	Solar radiation.....	46
6.5.11	Solvents and contaminating fluids.....	46
6.5.12	Salt mist and sulphur dioxide.....	46
6.5.13	Water immersion.....	46
6.5.14	Hygroscopicity.....	46
6.5.15	Wicking.....	47
6.5.16	Flame propagation characteristics of a single cable.....	48
6.5.17	Flame propagation characteristics of bunched cables.....	48
6.5.18	Halogen gas evolution.....	48
6.5.19	Smoke generation.....	48
6.5.20	Toxic gas emission.....	48
6.5.21	Integrated fire test method for cables in environmental air handling spaces	48
	Bibliography.....	49
	Figure 1 – Test set-up for the measurement of attenuation, velocity of propagation and phase delay	20
	Figure 2 – Test set-up for the measurement of the differential-mode loss of the baluns	24
	Figure 3 – Test set-up for the measurement of the common-mode loss of the baluns.....	24
	Figure 4 – Test set-up for unbalance attenuation at near end (<i>TCL</i>).....	26
	Figure 5 – Test set-up for unbalance attenuation at far end (<i>TCTL</i>)	26
	Figure 6 – Test set-up for near-end crosstalk.....	28
	Figure 7 – Test set-up for far-end crosstalk.....	30
	Figure 8 – Test set-up for alien (exogenous) near-end crosstalk	33
	Figure 9 – Test assembly cross-section; six cables around one cable	35
	Figure 10 – Test assembly layout; six cables around one cable	35

Figure 18 – Schematic diagram representing the position of the 9 cables on a wooden drum 36

Figure 19 – Arrangement of the cables on the drum..... 36

Figure 20 – Preparation of one end..... 37

Figure 13 – Test set-up for characteristic impedance and return loss..... 38

Figure 14 – U-bend test configuration 41

Figure 15 – S-bend test configuration 42

Figure 16 – Repeated bending test configuration 43

Figure 17 – Wicking test configuration 47

Table 1 – Test balun performance characteristics 23

Withheld

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES
FOR DIGITAL COMMUNICATIONS –****Part 1: Generic specification**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 61156-1 edition 3.1 contains the third edition (2007) [documents 46C/815/FDIS and 46C/823/RVD], its amendment 1 (2009) [documents 46C/897/FDIS and 46C/899/RVD] and its corrigendum 1 (2015-08).

A vertical line in the margin shows where the base publication has been modified by amendment 1.

The cables are classified in the study of generic cabling for information technology being produced by ISO/IEC JTC1/SC 25.

International Standard IEC 61156-1 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories.

This edition includes the following significant technical changes with respect to the previous edition:

- a) inclusion of definitions and test methods in support of the MICE table in ISO 24702;
- b) inclusion of definitions and test methods in support of new cable categories 6_A and 7_A;
- c) inclusion of definitions in support of PoEP.

This bilingual version (2008-02) replaces the English version.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 61156 series, under the general title *Multicore and symmetrical pair/quad cables for digital communication*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 1: Generic specification

1 Scope

This part of IEC 61156 is applicable to communication systems such as ISDN, local area networks and data communication systems and specifies the definitions, requirements and test methods of multicore, symmetrical pair and quad cables.

This standard is also applicable to cables used for customer premises wiring.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60028, *International standard of resistance for copper*

IEC 60050-726, *International Electrotechnical Vocabulary (IEV) – Part 726: Transmission lines and wave guides*

IEC 60068-2-1, *Environmental testing – Part 2: Tests – Tests A: Cold*

IEC 60169-22, *Radio-frequency connectors – Part 22: RF two-pole bayonet coupled connectors for use with shielded balanced cables having twin inner conductors (Type BNO)*

IEC 60189-1:1986, *Low-frequency cables and wires with PVC insulation and PVC sheath – Part 1: General test and measuring methods*¹⁾

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 60332-1-1, *Tests on electric and optical fibre cables under fire conditions – Part 1-1: Test for vertical flame propagation for a single insulated wire or cable – Apparatus*

IEC 60332-2-1, *Tests on electric and optical fibre cables under fire conditions – Part 2-1: Test for vertical flame propagation for a single small insulated wire or cable – Apparatus*

IEC 60332-3-10, *Tests on electric cables under fire conditions – Part 3-10: Test for vertical flame spread of vertically-mounted bunched wires or cables – Apparatus*

IEC 60332-3-24, *Tests on electric cables under fire conditions – Part 3-24: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category C*

IEC 60708, *Low-frequency cables with polyolefin insulation and moisture barrier polyolefin sheath*

¹⁾ There exists a 2007 edition of 60189-1.

IEC 60754-2, *Test on gases evolved during combustion of electric cables – Part 2: Determination of the degree of acidity of gases evolved during the combustion of materials taken from electric cables by measuring pH and conductivity*

IEC 60794-1-2:2003, *Optical fibre cables – Part 1-2: Generic specification – Basic optical cable test procedures*

IEC 60811-1-1:1993, *Common test methods for insulating and sheathing materials of electric cables and optical cables – Part 1: Methods for general application – Section 1: Measurement of thickness and overall dimensions – Tests for determining the mechanical properties*

IEC 60811-1-2:1985, *Common test methods for insulating and sheathing materials of electric and optical cables – Part 1: Methods for general application – Section Two: Thermal ageing methods*

IEC 60811-1-3:1993, *Common test methods for insulating and sheathing materials of electric and optical cables – Part 1: Methods for general application – Section Three: Methods for determining the density – Water absorption tests – Shrinkage test*

IEC 60811-1-4:1985, *Common test methods for insulating and sheathing materials of electric and optical cables – Part 1: Methods for general application – Section Four: Test at low temperature*

IEC 60811-3-1:1985, *Common test methods for insulating and sheathing materials of electric and optical cables – Part 3: Methods specific to PVC compounds – Section One: Pressure test at high temperature – Tests for resistance to cracking*

IEC 60811-4-2:2004, *Insulating and sheathing materials of electric cables – Common test methods – Part 4-2: Methods specific to polyethylene and polypropylene compounds – Tensile strength and elongation at break after conditioning at elevated temperature – Wrapping test after conditioning at elevated temperature – Wrapping test after thermal ageing in air – Measurement of mass increase – Long-term stability test – Test method for copper-catalyzed oxidative degradation*

IEC 61034 (all parts), *Measurement of smoke density of cables burning under defined conditions*

IEC 61196-1-105, *Coaxial communication cables – Part 1-105: Electrical test methods – Test for withstand voltage of cable dielectric*

IEC 62012-1:2004, *Multicore and symmetrical pair/quad cables for digital communications to be used in harsh environments – Part 1: Generic specification*

IEC 62153-4-3, *Metallic communication cables test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

IEC 62153-4-4, *Metallic communication cables test methods – Part 4-4: Electromagnetic compatibility (EMC) – Shielded screening attenuation, test method for measuring of the screening attenuation a_s up to and above 3 GHz*

IEC 62153-4-5, *Metallic communication cables test methods – Part 4-5: Electromagnetic compatibility (EMC) – Coupling or screening attenuation – Absorbing clamp method*

IEC 62255 (all parts), *Multicore and symmetrical pair/quad cables for broadband digital communications (high bit rate digital access telecommunication networks) – Outside plant cables*

ITU-T Recommendation G.117:1996, *Transmission aspects of unbalance about earth*

ITU-T Recommendation O.9:1999, *Measuring arrangements to assess the degree of unbalance about earth*

3 Terms and definitions

For the purposes of this document, the following terms and definitions, as well as those given in IEC 60050-726, apply.

3.1

resistance unbalance

difference in resistance of the conductors within a pair or one side of a quad or between pairs or quads

NOTE Resistance unbalance is expressed as a percentage (%).

3.2

capacitance unbalance to earth

arithmetic difference of the capacitance to earth of the conductors of a pair or one side of a quad

NOTE Capacitance unbalance is expressed in pF/m.

3.3

mutual capacitance

electrical charge storage parameter of a pair of conductors (or with respect to the side of a quad)

NOTE 1 Mutual capacitance is one of the four primary transmission line parameters: mutual capacitance, mutual inductance, resistance and conductance.

NOTE 2 Mutual capacitance is expressed in pF/m.

3.4

velocity of propagation (phase velocity)

speed at which a sinusoidal signal propagates on a pair in the cable

NOTE Velocity of propagation is expressed in m/s.

3.5

delay (phase delay)

time duration between the instants that the wave front of a sinusoidal travelling wave, defined by a specified phase, passes two given points in a cable

NOTE Phase delay is expressed in s/m.

3.6

differential phase delay (skew)

difference in phase delay between any two pairs in the cable

NOTE Differential phase delay (skew) is expressed in s.

3.7

attenuation

decrease in magnitude of power of a signal that propagates along a pair of a cable

NOTE Attenuation is expressed in dB/m.

3.8

unbalance attenuation

magnitude of power of a signal that propagates between the common-mode circuit and the differential-mode circuit of a cable

NOTE Unbalance attenuation is expressed in dB.

3.9

near-end crosstalk

NEXT

magnitude of the signal power coupling from a disturbing pair at the near end to a disturbed pair measured at the near end

NOTE Near-end crosstalk is expressed in dB.

3.10

far-end crosstalk

FEXT

magnitude of the signal power coupling from a disturbing pair at the near end to a disturbed pair measured at the far end

NOTE Far-end crosstalk is expressed in dB.

3.11

power sum of crosstalk

PS

summation of the crosstalk power from all disturbing pairs into a disturbed pair

NOTE 1 The summation is applicable to near-end and far-end crosstalk.

NOTE 2 The power sum of crosstalk is expressed in dB.

3.12

attenuation to crosstalk ratio, near-end

ACR-N

arithmetic difference between the near-end crosstalk and the attenuation of the disturbed pair

NOTE Attenuation to crosstalk ratio, near-end, is expressed in dB.

3.13

attenuation to crosstalk ratio, far-end

ACR-F

arithmetic difference between the far-end crosstalk and the attenuation of the disturbed pair

NOTE Attenuation to crosstalk ratio, far-end, is expressed in dB.

3.14

alien (exogenous) near-end crosstalk

ANEXT

near-end crosstalk where the disturbing and disturbed pairs are contained in different cables

NOTE Alien (exogenous) near-end crosstalk is expressed in dB.

3.15

alien (exogenous) far-end crosstalk

AFEXT

far-end crosstalk where the disturbing and disturbed pairs are contained in different cables

NOTE Alien (exogenous) far-end crosstalk is expressed in dB.

3.16**power sum of alien (exogenous) crosstalk****PSA**

summation of the alien (exogenous) crosstalk power from all disturbing pairs into a disturbed pair in different cables

NOTE 1 The summation is applicable to near-end and far-end alien (exogenous) crosstalk.

NOTE 2 The power sum of alien (exogenous) crosstalk is expressed in dB.

3.17**characteristic impedance** **Z_c**

impedance at the input of a homogeneous line of infinite length

The impedance value is expressed in Ω , calculated, at relevant frequencies, as the square root of the product of the impedances measured at the near end (input) of a cable pair when the far end is terminated by a short-circuit load and then an open circuit load.

NOTE 1 The asymptotic value at high frequencies is denoted as Z_∞ .

NOTE 2 The characteristic impedance of a homogeneous cable pair is given by the quotient of a voltage wave and current wave which are propagating in the same direction, either forwards or backwards.

NOTE 3 For homogeneous ideal cables, this method yields a flat smooth curve over the whole frequency range. Real cables with distortions give curves with some roughness.

3.18**terminated input impedance** **Z_{in}**

impedance value, expressed in Ω , at relevant frequencies, measured at the near end (input) when the far end is terminated with the system nominal impedance, Z_R

(See IEC/TR 62152.)

3.19**fitted characteristic impedance** **Z_m**

impedance value, expressed in Ω , calculated by applying a least squares function fitting algorithm to the measured characteristic impedance values

3.20**mean characteristic impedance** **Z_∞**

asymptotic value at which the characteristic impedance approaches at sufficiently high frequencies (≈ 100 MHz) such that the imaginary part (phase angle) is insignificant

NOTE 1 Normally measured from the capacitance and time delay.

NOTE 2 Applicable for cables with frequency independence of mutual capacitance.

3.21**return loss****RL**

ratio of reflected power to input power at the input terminals of a cable pair

NOTE Return loss is expressed in dB.

3.22**balun**

balanced to unbalanced impedance matching transformer

3.23

bundled cable

grouping or assembly of several individual cables that are systematically laid up

NOTE Bundled cables are also referred to as speed-wrap, whip, or loomed cables.

3.24

current carrying capacity

maximum current a cable circuit (one or several conductors) can support resulting in a specified increase of the surface temperature of the conductor beyond the ambient temperature, not exceeding the maximum allowed operating temperature of the cable

3.25

hygroscopic

characteristic of a material to absorb moisture from the atmosphere

3.26

wicking

longitudinal flow of a liquid in a material due to capillary action

3.27

coupling attenuation

ratio between the transmitted power through the conductors and the maximum radiated peak power, conducted and generated by the excited common-mode currents

3.28

ambient temperature

the temperature of the room or space surrounding the cable

3.29

operating temperature

the surface temperature of the conductors of a cable

The operating temperature is the sum of ambient temperature and of the temperature increase due to the carried power.

4 Installation considerations

The cables shall be designed to meet the installation conditions encountered for each area as follows.

a) Equipment cables

The cables are used between work stations and peripheral equipment (for example, printer).

b) Work area cables

The cables are used between the work station and the communication outlets.

c) Horizontal floor wiring cables

The cables are used between the work area communication outlet and the communication closet.

d) Riser cables and building back-bone cables

The cables are used for horizontal installation or vertically between floors.

e) Campus cables

These cables are used to interconnect buildings and shall be suitable for outdoor installation. The cables should be sheathed and protected in accordance with IEC 62255.