

SLOVENSKI STANDARD SIST EN ISO 787-9:1997

01-december-1997

Splošne metode preskušanja pigmentov in polnil - 9. del: Določanje pH vrednosti vodnih suspenzij (ISO 787-9:1981)

General methods of test for pigments and extenders - Part 9: Determination of pH value of aqueous suspension (ISO 787-9:1981)

Allgemeine Prüfverfahren für Pigmente und Füllstoffe - Teil 9: Bestimmung des pH-Wertes einer wäßrigen Suspension (ISO 787-9:1981) REVIEW

(standards.iteh.ai)
Méthodes générales d'essai des pigments et matieres de charge - Partie 9:
Détermination du pH d'une suspension aqueuse (ISO 787-9:1981)

https://standards.iteh.ai/catalog/standards/sist/f54499a2-43c9-4516-ace5-

Ta slovenski standard je istoveten z: 55a72fee94d5/sist_en-iso-787-9-1997

ICS:

87.060.10 Pigmenti in polnila Pigments and extenders

SIST EN ISO 787-9:1997 en

SIST EN ISO 787-9:1997

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN ISO 787-9:1997</u> https://standards.iteh.ai/catalog/standards/sist/f54499a2-43c9-4516-ace5-55a72fee94d5/sist-en-iso-787-9-1997 **EUROPEAN STANDARD**

EN ISO 787-9

NORME EUROPÉENNE

EUROPÄISCHE NORM

March 1995

ICS 87.060.10

Descriptors:

paints, pigments, tests, chemical analysis, determination of content, pH

English version

General methods of test for pigments and extenders - Part 9: Determination of pH value of aqueous suspension (ISO 787-9:1981)

Méthodes générales d'essai des pigments et ARD PRE Allgemeine Prüfverfahren für Pigmente und matières de charge - Partie 9: Détermination du ARD PRE Allgemeine Prüfverfahren für Pigmente und Füllstoffe - Teil 9: Bestimmung des pH-Wertes pH d'une suspension aqueuse (ISO 787-9:1981) einer wäßrigen Suspension (ISO 787-9:1981)

<u>SIST EN ISO 787-9:1997</u> https://standards.iteh.ai/catalog/standards/sist/f54499a2-43c9-4516-ace5-55a72fee94d5/sist-en-iso-787-9-1997

This European Standard was approved by CEN on 1994-10-17. CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

The European Standards exist in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization Comité Européen de Normalisation Europäisches Komitee für Normung

Central Secretariat: rue de Stassart,36 B-1050 Brussels

Page 2 EN ISO 787-9:1995

Foreword

This European Standard has been taken over by the Technical Committee CEN/TC 298 "Pigments and extenders" from the work of ISO/TC 35 "Paints and varnishes" of the International Organization for Standardization (ISO).

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 1995, and conflicting national standards shall be withdrawn at the latest by September 1995.

According to the CEN/CENELEC Internal Regulations, the following countries are bound to implement this European Standard: Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom.

Endorsement notice

The text of the International Standard ISO 787-9:1981 has been approved by CEN as a European Standard without any modification.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN ISO 787-9:1997</u> https://standards.iteh.ai/catalog/standards/sist/f54499a2-43c9-4516-ace5-55a72fee94d5/sist-en-iso-787-9-1997

International Standard



787/9

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION●MEЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ●ORGANISATION INTERNATIONALE DE NORMALISATION

General methods of test for pigments and extenders — Part 9: Determination of pH value of an aqueous suspension

Méthodes générales d'essai des pigments et matières de charge — Partie 9 : Détermination du pH d'une suspension aqueuse ITEN STANDARD PREVIEW

First edition - 1981-09-15

(standards.iteh.ai)

<u>SIST EN ISO 787-9:1997</u> https://standards.iteh.ai/catalog/standards/sist/f54499a2-43c9-4516-ace5-55a72fee94d5/sist-en-iso-787-9-1997

UDC 667.622:543.257.1

Ref. No. ISO 787/9-1981 (E)

O 787/9-1981 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 787/9 was developed by Technical Committee ISO/TC 35, Paints and varnishes, and was circulated to the member bodies in November 1979.

It has been approved by the member bodies of the following countries:

SIST EN ISO 787-9:1997

httpqr/standlards.iteh.ai/catalog/standards/sist/f54499a2-43c9-4516-ace5-Australia 55a72fee94d5/sisouthisAfrica, Rep.96f Austria Israel Brazil Italy Spain Canada Kenya Sweden Korea, Rep. of Switzerland China Netherlands United Kingdom France **USSR** Germany, F. R. Norway Poland India

.....

No member body expressed disapproval of the document.

This International Standard cancels and replaces ISO Recommendation R 787/9-1970, of which it constitutes a technical revision.

International Organization for Standardization, 1981

Printed in Switzerland

The purpose of this International Standard is to establish a series of general test methods for pigments and extenders which are suitable for all or many of the individual pigments and extenders for which specifications might be required. In such cases, a cross-reference to the general method should be included in the International Standard relating to that pigment or extender, with a note of any detailed modifications which might be needed in view of the special properties of the product in question.

Technical Committee ISO/TC 35, Paints and varnishes, decided that all the general methods should be published as they become available, as parts of a single International Standard, in order to emphasize the relationship of each to the whole series.

iTeh

The Technical Committee also decided that, where two or more procedures were widely used for determining the same or a similar characteristic of a pigment or extender, there would be no objection to including more than one of them in the ISO series. In such cases it will, however, be essential to state clearly in a specification which method is to be used and, in the test report, which method has been used.

Parts of the series already published are as follows:

https://standards.iteh.ai/catalog/standards/sist/f54499a2-43c9-4516-ace5-

55 Part 194 Comparison of colour of pigments

Part 2 : Determination of matter volatile at 105 °C

Part 3: Determination of matter soluble in water - Hot extraction method

Part 4 : Determination of acidity or alkalinity of the aqueous extract

Part 5 : Determination of oil absorption value

Part 6 : Determination of residue on sieve - Oil method

Part 7 : Determination of residue on sieve — Water method — Manual procedure

Part 8 : Determination of matter soluble in water — Cold extraction method

Part 9 : Determination of pH value of an aqueous suspension

Part 10: Determination of density - Pyknometer method

Part 11: Determination of tamped volume and apparent density after tamping

Part 13: Determination of water-soluble sulphates, chlorides and nitrates

Part 14: Determination of resistivity of aqueous extract

Part 15: Comparison of resistance of coloured pigments of similar types to light from a specified light source

Part 16: Comparison of relative tinting strength (or equivalent colouring value) and colour on reduction in linseed stand oil using the automatic muller

Part 17: Comparison of lightening power of white pigments

Part 18: Determination of residue on sieve — Water method — Mechanical flushing procedure

Part 19: Determination of water-soluble nitrates — Salicylic acid method

Part 20: Comparison of ease of dispersion - Oscillatory shaking method

Part 21: Comparison of heat stability of pigments using a stoving medium

Part 22: Comparison of resistance to bleeding of pigments

Part 23: Determination of density (using a centrifuge to remove entrained air)

Part 24: Determination of relative tinting strength of coloured pigments and relative scattering power of white pigments — Photometric method

SIST EN ISO 787-9:1997

iTeh This page intentionally left blank FVIEW (standards.iteh.ai)

<u>SIST EN ISO 787-9:1997</u> https://standards.iteh.ai/catalog/standards/sist/f54499a2-43c9-4516-ace5-55a72fee94d5/sist-en-iso-787-9-1997

General methods of test for pigments and extenders — Part 9: Determination of pH value of an aqueous suspension

Introduction

This document is a part of ISO 787, General methods of test for pigments and extenders.

Scope and field of application

This part of ISO 787 specifies a general method of test for determining the pH value of an aqueous suspension of a sample of pigment or extender.

NOTE — When this general method is applicable to a given pigment of R described in ISO 842. extender, only a cross-reference to it should be included in the International Standard relating to that pigment or extender, with a note of any detailed modification which may be needed in view of the special properties of the material in question. Only when this general method is not applicable to a particular material should a special method for 786-9 Procedure determination of pH value be specified. https://standards.iteh.ai/catalog/standards/sist/f54499a2-43c9-4516-ace5-

4.2 pH measuring device, capable of measurement to 0,1 unit, calibrated against buffer solutions of known pH value at the temperature of the test.

Balance, with an appropriate accuracy.

5 Sampling

Take a representative sample of the material to be tested as

55a72fee94d5/sist-en-isCarry out the determination in duplicate at room temperature.

2 Reference

ISO 842, Raw materials for paints and varnishes — Sampling.

3 Reagent

Freshly distilled water, boiled before use to remove carbon dioxide, or water otherwise prepared of at least equivalent purity.

The water shall be boiled and cooled in a vessel made of chemically resistant glass, immediately before use. It shall be boiled for 5 to 10 min only, in order to avoid an increase of its pH value due to alkali dissolved from the glass vessel. Because water rapidly absorbs carbon dioxide, the cooled water shall be protected from access to the atmosphere and shall be stored for not more than 30 min. The closed container should be protected by a soda asbestos tube or similar device.

Apparatus

4.1 Glass container, of capacity 50 ml, made of chemically resistant glass, fitted with a ground glass or rubber stopper.

Before using the container for the first time, boil dilute hydrochloric acid placed in the container and then rinse it thoroughly with distilled water. The rubber stopper shall not have been used for any other purpose.

Prepare a 10 % (m/m) suspension of the material under test, using the distilled water (clause 3), in the glass container (4.1). Stopper the container and shake it vigorously for 1 min. Allow it to stand for 5 min, remove the stopper and determine, to the nearest 0,1 unit, the pH value of the suspension.

If the material does not disperse easily in water, a wetting agent should be used; in the case of materials not soluble in ethanol, up to 5 ml of ethanol may be used but care should be taken to ensure that the minimum quantity is used and that it is neutral and free from pyridine. In the case of pigments soluble in ethanol, a neutral non-ionic wetting agent such as 10 ml of a 0.01 % (m/m) solution of an ethylene oxide condensate should be used. The neutrality of the wetting agent should be checked by making a blank determination. If a wetting agent is used, the volume of the water should be reduced so that a 10 % (m/m)suspension is obtained.

The type and quantity of wetting agent used shall be stated in the test report.

NOTE - With pigments and extenders of relatively low density, it may be necessary to use a suspension of less than 10 % (m/m). In such cases the concentration of the suspension used should be stated in the test report.

Record the pH values to the nearest 0,1 unit and record the temperature of the suspension to the nearest 1 °C. If the duplicate determinations of pH differ by more than 0,3 unit, the procedure shall be repeated.