

Edition 4.0 2008-07

# INTERNATIONAL STANDARD





## THIS PUBLICATION IS COPYRIGHT PROTECTED

#### Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch

Email: inmail@iec.ch
Web: www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Rease make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: www.iec.ch/online news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

■ Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

■ Customer Service Centre: www.ies.ch/webstore/custserv

If you wish to give us your feedback on this publication of need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

Tel.: +41 22 919 02 11 // stan ard lec 1563214-5f20-4fca-99af-cf47bb2a4bf5/iec-60384-1-200 Fax: +41 22 919 03 00



Edition 4.0 2008-07

## INTERNATIONAL STANDARD

Fixed capacitors for use in electronic equipment –
Part 1: Generic specification

ten.ai

typs://standards.itch.au

typs:/

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE XC

ICS 31.060 ISBN 2-8318-9907-9

## CONTENTS

FOF	REW	ORD	7
1	Gene	eral	9
	1.1	Scope	9
	1.2	Normative references	9
2	Tech	nnical data	10
	2.1	Units and symbols	10
	2.2	Terms and definitions	11
	2.3	Preferred values	17
		2.3.1 General	17
		2.3.2 Preferred values of nominal capacitance	17
		2.3.3 Preferred values of rated voltage	,17
	2.4	Marking	17
		2.4.1 General	17
		2.4.2 Coding	17
3	Qual	ity assessment procedures	17
			18
	4.1	General	19
	4.2	Standard atmospheric conditions	19
		4.2.1 Standard atmospheric conditions for testing	
		4.2.2 Recovery conditions	19
		4.2.2 Recovery conditions 4.2.3 Referee conditions	20
		4.2.4 Reference conditions	20
	4.3	Drying	20
	4.4	Visual examination and check of dimensions	
	•••	4.4.1 Visual examination	
		4.4.2 Dimensions (gauging)	
		4.4.3 Dimensions (detail)	
	4.5	Insulation resistance	
	1.0	4.5.1 Preconditioning	
		4.5.2 Measuring conditions	
	<	4.5.3 Test points	
		4.5.4 Test methods	
		4.5.5 Temperature compensation	
		4.5.6 The relevant specification shall prescribe:	
	4.6	Voltage proof	
	1.0	4.6.1 Test circuit (for the test between terminations)	
		4.6.2 Test	
		4.6.3 Requirements	
		4.6.4 Conditions to be prescribed in the relevant specification	
	4.7	Capacitance	
		4.7.1 Measuring frequency and measuring voltage	
		4.7.2 Measuring equipment	
		4.7.3 Conditions to be prescribed in the relevant specification	
	4.8	Tangent of loss angle and equivalent series resistance (ESR)	
	4.0	4.8.1 Tangent of loss angle	
		4.8.2 Equivalent series resistance (FSR)	27

4.9	Leakage current	27
	4.9.1 Preconditioning	
	4.9.2 Test method	
	4.9.3 Power source	
	4.9.4 Measuring accuracy	28
	4.9.5 Test circuit	
	4.9.6 Conditions to be prescribed in the relevant specification	
4.10	Impedance	
	Self-resonant frequency and inductance	
	4.11.1 Self-resonant frequency ( $f_r$ )	
	4.11.2 Inductance	
	4.11.3 Conditions to be prescribed in the relevant specification	
4.12		32
		33
	4.13.1 Test Ua <sub>1</sub> – Tensile	33
	4.13.2 Test Ub – Bending (half of the sample)	33
	4.13.3 Test Uc – Torsion (remaining sample)	33
	4.13.4 Test Ud – Torque (for terminations with threaded studs or screws	
	and for integral mounting devices)	33
	4.13.5 Visual examination	34
4.14	Resistance to soldering heat	34
	4 14 1 Preconditioning	34
	4.14.2 Test procedure	34
	4.14.3 Recovery	34
	4.14.4 Final inspection, measurement and requirements	
4.15	Soldorability	24
	4.15.1 Preconditioning	34
	4.15.2 Test procedure	35
	4.15.3 Final inspection, measurements and requirements	35
4.16	Rapid change of temperature	
	4.16.1 Initial measurement	
	4.16.2 Test procedure	
/	4.16.3 Final inspection, measurements and requirements	
4.17	Vibration	
	4.17.1 Initial measurement	
	4.17.2 Test procedure	36
	4.17.3 Electrical test	
	4.17.4 Final inspection, measurements and requirements	
4.18	Bump	
	4.18.1 Initial measurement	
	4.18.2 Test procedure	
	4.18.3 Final inspection, measurements and requirements	
4.19	Shock	
	4.19.1 Initial measurement	
	4.19.2 Test procedure	
	4.19.3 Final inspection, measurements and requirements	
4 20	Container sealing	
	Climatic sequence	
	4.21.1 Initial measurements	

	4.21.2 Dry heat	37
	4.21.3 Damp heat, cyclic, test Db, first cycle	37
	4.21.4 Cold	37
	4.21.5 Low air pressure	38
	4.21.6 Damp heat, cyclic, test Db, remaining cycles	38
	4.21.7 Final measurements	38
4.22	Damp heat, steady state	38
	4.22.1 Initial measurement	38
	4.22.2 Test procedure	38
	4.22.3 Final inspection, measurements and requirements	
4.23	Endurance	
	4.23.1 Initial measurements	39
		39
	4.23.3 Conditions to be prescribed in the relevant specification	39
	4.23.4 Test voltage	39
	4.23.5 Placement in the test chamber.	40
	4.23.6 Recovery	40
	4.23.7 Final inspection, measurements and requirements	
4.24		
	4 24 1 Static method	41
	4.24.2 Dynamic method	41
	4.24.3 Methods of calculation	42
4.25	Storage	43
	4.25.1 Storage at high temperature	43
	4.25.2 Storage at low temperature	43
4.26	Surge	43
	4.26.1 Initial measurement	
	4.26.2 Test procedure	
	4.26.3 Final inspection, measurements and requirements	
	4.26.4 Information to be given in the relevant detail specification	
4.27	Charge and discharge tests and inrush current test	
	4.27.1 Initial measurement	
<	4.27.2 Test procedure	
	4.27.3 Charge and discharge	
	4.27.4 Inrush current	
	4.27.5 Final inspection, measurements and requirements	
4.28	Pressure relief (for aluminium electrolytic capacitors)	
	4.28.1 a.c. test	
	4.28.2 d.c. test	
	4.28.3 Pneumatic test	
	4.28.4 Final inspection, measurements and requirements	
4.29	Characteristics at high and low temperature	
	4.29.1 Test procedure	
	4.29.2 Requirements	
4.30	Thermal stability test	
4.31	Component solvent resistance	
	4.31.1 Initial measurements	
	4.31.2 Test procedure	
	4.31.3 Final inspection, measurements and requirements	
	- process of the second	

4.32	Solvent resistance of marking	49
	4.32.1 Test procedure	49
	4.32.2 Final inspection, measurements and requirements	49
4.33	Mounting (for surface mount capacitors only)	
	4.33.1 Substrate	49
4.34	Shear test	52
	4.34.1 Test procedure	
	4.34.2 Final inspection, measurements and requirements	
4.35	Substrate bending test	
	4.35.1 Test procedure	
	4.35.2 Recovery	52
	4.35.3 Final inspection and requirements	
4.36		52
	4.36.1 Test procedure	52
	4.36.2 Requirement	
4.37	Accelerated damp heat, steady state (for multilayer seramic capacitors only)	53
	4.37.1 Mounting of capacitors	53
	4.37.2 Initial measurement	53
	4.37.2 Illitial measurement 4.37.3 Test procedure 4.37.4 Recovery	53
	4.37.4 Recovery	54
	4.37.5 Final inspection, measurements and requirements	54
4.38	Passive flammability	54
4.00	4.38.2 Final inspection, measurements and requirements  High surge current test	54
4.39	4.39.1 Initial measurements	55
	4.39.2 Test procedure	
	4.39.3 Requirements for the charging circuit	
4.40	4.39.4 Nonconforming items	50
4.40	solid electrolyte)	
	4.40.1 Initial measurement	56
<	4.40 2 Test procedure	56
	4.40.3 Final inspection, measurements and requirements	57
	4.40.4 Conditions to be prescribed in the relevant specification	57
	(normative) Interpretation of sampling plans and procedures as described in 0 for use within the IECQ system	58
	(normative) Rules for the preparation of detail specifications for capacitors tors for electronic equipment for use within the IECQ system	50
	(normative) Layout of the first page of a PCP/CQC specification	
	(normative) Requirements for capability approval test report	
	(informative) Guide for pulse testing of capacitors	
Annex F	(informative) Guidance for the extension of endurance tests on fixed s	
Annex G	(normative) Damp heat, steady state with voltage applied, for metallized film s only	
·	(normative) Quality assessment procedures	
Figure 1	– Reactive power against frequency	13

Figure 2 – Relation between category temperature range and applied volta	ge16
Figure 3 – Voltage-proof test circuit	24
Figure 4 – Schematic diagram of the impedance measuring circuit	28
Figure 5 – Capacitor mounting arrangement	30
Figure 6 – Capacitor mounting arrangement	30
Figure 7 – Typical diagram of an absorption oscillator-wavemeter	31
Figure 8 – Schematic diagram of the measuring circuit	31
Figure 9 – Test circuit	32
Figure 10 – Test circuit for electrolytic capacitors	
Figure 11 – Relay circuit	44
Figure 12 – Thyristor circuit	
Figure 13 – Voltage waveform across capacitor	45
Figure 14 – Voltage and current waveform	
Figure 15 – Suitable substrate for mechanical tests (may not be suitable to measurements)	r impedance 51
	51
	55
Figure 18 – Voltage transient overload test circuit	56
	57
Figure Q.1 – General scheme for capability approval	70
Table 1 – Referee conditions	20
Table 2 – Measurement of insulation resistance	21
Table 3 – Measuring points	23
Table 4 – Tensile force	1 <del>04bf5/icc.60384</del> . <b>33</b> 2008
Table 5 – Torque	33
Table 6 – Number of cycles	38
Table 7 – Severities and requirements	54

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

### FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT -

## Part 1: Generic specification

### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an EC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatspever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60384-1 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment

This fourth edition cancels and replaces the third edition issued in 1999 and constitutes a technical revision, including minor revisions related to tables, figures and references.

This edition contains the following significant technical changes with respect to the previous edition:

implementation of Annex Q which replaces Clause 3.

The text of this standard is based on the following documents:

FDIS	Report on voting
40/1915/FDIS	40/1924/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The QC number that appears on the front cover of this publication is the specification number in the IECQ Quality Assessment System for Electronic Components (IECQ).

A list of all the parts of the IEC 60384 series, under the general title *Fixed capacitors for use in electronic equipment*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed.
- · withdrawn,
- replaced by a revised edition, or
- · amended.

A bilingual version of this publication may be issued at a later stage.

The contents of the corrigendum of November 2008 have been included in this copy.

iTex San (a cas (https://standardx.dx.iteh.ai)

Lycurer Preview

F25024-1:2008

https://standards.iteh.avg.y/standardx/eev/s003214-5f20-4fca-99af-cf47bb2a4bf5/iec-60384-1-2008

## FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT -

## Part 1: Generic specification

#### 1 General

#### 1.1 Scope

This part of IEC 60384 is a generic specification and is applicable to fixed capacitors for use in electronic equipment.

It establishes standard terms, inspection procedures and methods of test for use in sectional and detail specifications of electronic components for quality assessment or any other purpose.

#### 1.2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60027, Letter symbols to be used in electrical technology

IEC 60050 (all parts), International Electrotechnical Vocabulary (IEV)

IEC 60062, Marking codes for resistors and capacitors

IEC 60063, Preferred number series for resistors and capacitors

IEC 60068-1:1988, Environmental testing - Part 1: General and guidance

IEC 60068-2-1-2007, Environmental testing - Part 2-1: Tests - Tests A: Cold

IEC 60068-2-2:2067, Environmental testing – Part 2-2: Tests – Tests B: Dry heat

IEC 60068-2-6:2007, Environmental testing – Part 2: Tests – Test Fc: Vibration (sinusoidal)

IEC 60068-2-13:1983, Environmental testing - Part 2: Tests - Test M: Low air pressure

IEC 60068-2-14:1984, Environmental testing – Part 2: Tests – Test N: Change of temperature

IEC 60068-2-17:1994, Environmental testing - Part 2-17: Tests - Test Q: Sealing

IEC 60068-2-20:1979, Environmental testing – Part 2-20: Tests – Test T: Soldering

IEC 60068-2-21:2006, Environmental testing – Part 2-21: Tests – Test U: Robustness of terminations and integral mounting devices

IEC 60068-2-27:2008, Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock

IEC 60068-2-29:1987, Environmental testing – Part 2-29: Tests – Test Eb and guidance: Bump

IEC 60068-2-30:2005, Environmental testing – Part 2-30: Tests – Test Db: Damp heat, cyclic (12 h + 12 h cycle)

IEC 60068-2-45:1980, Environmental testing – Part 2-45: Tests – Test XA and guidance: Immersion in cleaning solvents

IEC 60068-2-54:2006, Environmental testing – Part 2-54: Tests – Test Ta: Solderability testing of electronic components by the wetting balance method

IEC 60068-2-58:2004, Environmental testing – Part 2-58: Tests – Test Td: Test methods for solderability, resistance to dissolution of metallization and to soldering heat of surface mounting devices (SMD)

IEC 60068-2-69:2007, Environmental testing – Part 2: Tests – Test Te Solderability testing of electronic components for surface mounting devices (SMD) by the wetting balance method

IEC 60068-2-78:2001, Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state

IEC 60294, Measurement of the dimensions of a cylindrical component having two axial terminations

IEC 60410:1973, Sampling plans and procedures for inspection by attributes

IEC 60617, Graphical symbols for diagrams

IEC 60695-11-5:2004, Fire hazard testing – Part 11-5: Test flames – Needle-flame test method – Apparatus, confirmatory test arrangement and guidance

IEC 60717, Method for the determination of the space required by capacitors and resistors with unidirectional terminations 15 60 34-12008

IEC 61193-2, Quality assessment systems – Part 2: Selection and use of sampling plans for inspection of electronic components and packaging<sup>1</sup>

IEC 61249-2-7:2002, Materials for printed boards and other interconnecting structures – Part 2-7: Reinforced base materials clad and unclad – Epoxide woven E-glass laminated sheet of defined flammability (vertical burning test), copper-clad

IEC QC 001002-3, Rules of Procedure - Part 3: Approval procedures

ISO 3, Preferred numbers – Series of preferred numbers

ISO 1000, SI units and recommendations for the use of their multiples and of certain other units

ISO 9000, Quality management systems – Fundamentals and vocabulary

#### 2 Technical data

## 2.1 Units and symbols

Units, graphical symbols and letter symbols should, whenever possible, be taken from the following publications:

<sup>1</sup> To be published.

- IEC 60027;
- IEC 60050 (series);
- IEC 60617;
- ISO 1000.

When further items are required, they should be derived in accordance with the principles of the publications listed above.

#### 2.2 Terms and definitions

For the purposes of this document, the following terms and definitions apply, in alphabetical order.

#### 2.2.1

#### a.c. capacitor

capacitor designed essentially for application with alternating voltages

#### 2.2.2

#### **bipolar capacitor** (for electrolytic capacitors)

electrolytic capacitor designed to withstand an alternating voltage and/or reversal of the applied direct voltage

#### 2.2.3

## category of passive flammability

category of passive flammability is given by the maximum burning time after a specified time of flame application

#### 2.2.4

## category temperature range

range of ambient temperatures for which the capacitor has been designed to operate continuously; this is given by the lower and upper category temperature

#### 2.2.5

#### category voltage (V)

maximum voltage which may be applied continuously to a capacitor at its upper category temperature

#### 2.2.6

#### d.c. capacitor

capacitor designed essentially for application with direct voltage

NOTE A d.c. capacitor may not be suitable for use on a.c. supplies.

#### 2.2.7

## family (of electronic components)

group of components which predominantly displays a particular physical attribute and/or fulfils a defined function

## 2.2.8

#### grade

term to indicate an additional general characteristic concerning the intended application of the component

#### 2.2.9

#### insulated capacitor

capacitor in which all terminations of a section may be raised to a potential different (but not less than the rated voltage) from that of any conducting surface with which the case is liable to come into contact in normal use

#### 2.2.10

#### lower category temperature

minimum ambient temperature for which a capacitor has been designed to operate continuously

#### 2.2.11

## maximum storage temperature

maximum ambient temperature which the capacitor withstands in the port-operating condition without damage

#### 2.2.12

#### maximum temperature of a capacitor

temperature at the hottest point of its external surface

NOTE The terminations are considered to be part of the external surface.

#### 2.2.13

#### minimum storage temperature

minimum ambient temperature which the capacitor withstands in the non-operating condition without damage

#### 2.2.14

## minimum temperature of a capacitor

temperature at the coldest point of the external surface

NOTE The terminations are considered to be part of the external surface.

#### s://standards.iteh.

## 2.2.15 nominal capacitance $(C_N)$

designated capacitance value usually indicated on the capacitor

#### 2.2.16

## passive flammability

ability of a capacitor to burn with a flame as a consequence of the application of an external source of heat

#### 2.2.17

#### polar capacitor (for electrolytic capacitors)

capacitor intended for use with a unidirectional voltage connected according to the polarity indication

#### 2.2.18

#### pulse capacitor

capacitor for use with pulses of current or voltage

NOTE The definitions of IEC 60469-1 and IEC 60469-2 apply.

#### 2.2.19

#### pulse equivalent circuit of a capacitor

equivalent circuit consisting of an ideal capacitor in series with its residual inductance and the equivalent series resistance (ESR)