

# INTERNATIONAL STANDARD

Consumer audio/video equipment – Digital interface –  
Part 8: Transmission of ITU-R BT.601 style digital video data  
(standards.iteh.ai)

[IEC 61883-8:2008](https://standards.iteh.ai/catalog/standards/sist/d68bb05d-bb8e-464f-b9b6-bc7b213caa38/iec-61883-8-2008)

<https://standards.iteh.ai/catalog/standards/sist/d68bb05d-bb8e-464f-b9b6-bc7b213caa38/iec-61883-8-2008>



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00



IEC 61883-8

Edition 1.0 2008-11

# INTERNATIONAL STANDARD

---

**Consumer audio/video equipment – Digital interface –  
Part 8: Transmission of ITU-R BT.601 style digital video data**

<https://standards.iteh.ai/catalog/standards/sist/d68bb05d-bb8e-464f-b9b6-bc7b213caa38/iec-61883-8-2008>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE



---

ICS 33.160.40

ISBN 978-2-88910-583-0

## CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references .....	6
3 Abbreviations and conventions .....	7
3.1 Abbreviations .....	7
3.2 Notation .....	8
3.2.1 Numeric values.....	8
3.2.2 Bit, byte and quadlet ordering.....	8
4 Reference model for data transmission.....	9
4.1 Model overview .....	9
4.2 Compression .....	10
4.3 Isochronous packet header .....	10
4.4 CIP header.....	10
4.5 Stream definition .....	11
4.6 Packetization.....	15
4.6.1 Source packet format .....	15
4.6.2 Type 0 <sub>16</sub> source packet – Video data source packet.....	16
4.6.3 Type 1 <sub>16</sub> source packet – Stream information and metadata (SIM) source packet.....	20
4.6.4 Type 2 <sub>16</sub> source packet – Audio source packet.....	27
4.7 Packet transmission method.....	27
4.7.1 Packet transmission for compression mode 0 <sub>16</sub> .....	27
4.7.2 Packet transmission for compression mode 1 <sub>16</sub> .....	30
4.7.3 Packet transmission for compression mode 2 <sub>16</sub> .....	30
4.7.4 Packet transmission for compression mode FF <sub>16</sub> .....	30
Annex A (informative) Audio/video synchronization.....	31
Annex B (normative) Additional video mode parameters .....	32
Annex C (informative) Using IEC 61883-1 plug control registers beyond S400.....	36
Annex D (normative) Compliance annex .....	37
Annex E (informative) Typical SIM source packet .....	38
Annex F (informative) Derivation of TRANSFER_DELAY .....	39
Annex G (normative) 1394 trade association CCI descriptor block .....	40
Bibliography.....	42
Figure 1 – Bit ordering within a byte.....	8
Figure 2 – Byte ordering within a quadlet.....	9
Figure 3 – Quadlet ordering within an octlet.....	9
Figure 4 – Isochronous packet header .....	10
Figure 5 – CIP header.....	10
Figure 6 – FDF field.....	11
Figure 7 – General format of a source packet .....	15
Figure 8 – Video data source packet.....	16
Figure 9 – Compression mode 0 <sub>16</sub> specific information .....	17
Figure 10 – Color space 0 <sub>16</sub> video data packetization .....	19

Figure 11 – Color space 1 <sub>16</sub> video data packetization .....	19
Figure 12 – Color space 2 <sub>16</sub> video data packetization .....	20
Figure 13 – Stream information and metadata source packet .....	21
Figure 14 – Stream information field definitions .....	22
Figure 15 – Auxiliary data field definitions .....	24
Figure E.1 – Typical SIM source packet .....	38
Figure G.1 – CCI descriptor block .....	40
Table 1 – Video mode .....	12
Table 2 – Compression mode .....	15
Table 3 – Color space .....	15
Table 4 – Source packet type encoding .....	16
Table 5 – References for video data definition .....	17
Table 6 – Frame rate .....	22
Table 7 – Aspect ratio .....	23
Table 8 – Progressive/interlace mode .....	23
Table B.1 – Additional video mode parameters, 1 of 2 .....	32
Table B.2 – Additional video mode parameters, 2 of 2 .....	34

iteh STANDARD PREVIEW  
(standards.iteh.ai)

[IEC 61883-8:2008](https://standards.iteh.ai/catalog/standards/sist/d68bb05d-bb8e-464f-b9b6-bc7b213caa38/iec-61883-8-2008)

<https://standards.iteh.ai/catalog/standards/sist/d68bb05d-bb8e-464f-b9b6-bc7b213caa38/iec-61883-8-2008>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**CONSUMER AUDIO/VIDEO EQUIPMENT –  
DIGITAL INTERFACE –**

**Part 8: Transmission of ITU-R BT.601 style digital video data**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61883-8 has been prepared by technical area 4: Digital system interfaces and protocols, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/1446/FDIS	100/1476/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61883 series, under the general title *Consumer audio/video equipment – Digital interface*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## **iTeh STANDARD PREVIEW (standards.iteh.ai)**

[IEC 61883-8:2008](#)

<https://standards.iteh.ai/catalog/standards/sist/d68bb05d-bb8e-464f-b9b6-bc7b213caa38/iec-61883-8-2008>

## CONSUMER AUDIO/VIDEO EQUIPMENT – DIGITAL INTERFACE –

### Part 8: Transmission of ITU-R BT.601 style digital video data

#### 1 Scope

This part of IEC 61883 specifies a protocol for the transport of uncompressed or compressed video data in the 4:2:2 format of recommendation ITU-R BT.601 (including compatible extensions to this format for the higher and lower resolutions of other commonly used video resolutions) over high performance serial bus, as specified by IEEE Std 1394-1995 as amended by IEEE Std 1394a-2000 and IEEE Std 1394b-2002 (collectively IEEE 1394). The data formats for the encapsulation of video data are compatible with those specified by IEC 61883-1. Associated audio data, if any, should be formatted as specified by IEC 61883-6.

There are many commonly used video formats unsupported by IEC 61883, such as MPEG-4, Windows Media Format (WMF) and the format used by automotive navigation applications. Support for all or most of these formats in rendering devices would require implementation of multiple video codecs. This is an undue burden that may be avoided if the source device converts to ITU-R BT.601 4:2:2 format and, if necessary, compresses the data with a codec supported by all destination devices. An additional advantage is that on-screen display (OSD) information may be mixed with video data prior to transmission to the rendering device.

Because ITU-R BT.601 4:2:2 format is widely used internally in contemporary AV equipment, this specification permits straight-forward integration of IEEE 1394 into these devices and enables markets whose usage scenarios include single video sources transmitting to one or more video displays, such as:

- consumer electronic STB or DVD video rendered by multiple displays in the home;
- automotive navigation and entertainment; and
- aeronautical in-flight entertainment.

For the sake of interoperability and bounded implementation complexity, it is essential that the specification provide the following:

- a 1394 TA controlled list of compression codecs; and
- at a minimum, a reference to one video compression codec.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61883 (all parts), *Consumer audio/video equipment – Digital interface*

IEC 61883-1, *Consumer audio/video equipment – Digital interface – Part 1: General*

ISO/IEC 11172-2:1993, *Information technology – Coding of moving pictures and associated audio for digital storage media at up to about 1,5 Mbit/s – Part 2: Video*

IEEE Std 1394-1995, *Standard for a high performance serial bus*



IEEE Std 1394a-2000, *Standard for a high performance serial bus Amendment 1*

IEEE Std 1394b-2002, *Standard for a high performance serial bus Amendment 2*

Throughout this document, the term IEEE 1394 refers to IEEE Std 1394-1995 as amended by IEEE Std 1394a-2000 and IEEE Std 1394b-2002.

1394 Trade Association 2004006, *AV/C Digital Interface Command Set General Specification Version 4.2*

1394 Trade Association 2003017, *IIDC 1394-based Digital Camera Specification Ver.1.31*

EIA/CEA-861-B 2002, *A DTV Profile for Uncompressed High Speed Digital Interfaces*

IEEE Std 1394.1-2004, *Standard for High Performance Serial Bus Bridges*

ITU-R BT.601-5 1995, *Studio encoding parameters of digital television for standard 4:3 and wide-screen 16:9 aspect ratios*

ITU-R BT.656-4 1998, *Interfaces for digital component video signals in 525-line and 625-line television systems operating at the 4:2:2 level of recommendation ITU-R BT.601*

ITU-R BT.709-4 2000, *Parameter values for the HDTV standards for production and international programme exchange*

ITU-R BT.1358 1998, *Studio parameters of 625 and 525 line progressive scan television systems*

ITU-T H.263 1998, *Video coding for low bit rate communication*

SMPTE 267M-1995, *Television – Bit-Parallel Digital Interface – Component Video Signal 4:2:2 16x9 Aspect Ratio*

SMPTE 274M-1998, *Television – 1920 × 1080 Scanning and Analog and Parallel Digital Interfaces for Multiple Picture Rates*

SMPTE 293M-1996, *Television – 720 × 483 Active Line at 59.94-Hz Progressive Scan Production – Digital Representation*

SMPTE 296M-2001, *Television – 1280 × 720 Progressive Image Sample Structure – Analog and Digital Representation and Analog Interface*

*VESA Monitor Timing Specifications*, VESA and Industry Standards and Guidelines for Computer Display Monitor Timing, Version 1.0, Revision 0.8

### **3 Abbreviations and conventions**

#### **3.1 Abbreviations**

For the purposes of this document, the abbreviations given in IEC 61883-1, as well as the following, apply.

AV/C Audio Video Control

BCD	Binary Coded Decimal
BT.601	ITU-R BT.601-5 1995
CIP	Common Isochronous Packet
CSR	Control and status register
DAC	Digital Analog Converter
DCT	Discrete Cosine Transform
DV	Digital Video
ND	No Data
OSD	Onscreen Display
OUI	Organizationally Unique Identifier
r	Reserved
MPEG	Moving Picture Experts Group
SIM	Stream Information & Metadata
VDSP	Video Data Source Packet
WMF	Windows Media Format

### 3.2 Notation

#### 3.2.1 Numeric values

Decimal and hexadecimal are used within this standard. By editorial convention, decimal numbers are most frequently used to represent quantities or counts. Addresses are uniformly represented by hexadecimal numbers. Hexadecimal numbers are also used when the value represented has an underlying structure that is more apparent in a hexadecimal format than in a decimal format.

<https://standards.iteh.ai/catalog/standards/sist/d68bb05d-bb8e-464f-b9b6-1e7b213ca38/iec-61883-8-2008>


Decimal numbers are represented by Arabic numerals without subscripts or by their English names. Hexadecimal numbers are represented by digits from the character set 0 – 9 and A - F followed by the subscript 16. When the subscript is unnecessary to disambiguate the base of the number it may be omitted. For the sake of legibility hexadecimal numbers are separated into groups of four digits separated by spaces.

As an example, 42 and 2A<sub>16</sub> both represent the same numeric value.

#### 3.2.2 Bit, byte and quadlet ordering

This specification uses the facilities of Serial Bus, IEEE 1394, and therefore uses the ordering conventions of Serial Bus in the representation of data structures. In order to promote interoperability with memory buses that may have different ordering conventions, this specification defines the order and significance of bits within bytes, bytes within quadlets and quadlets within octlets in terms of their relative position and not their physically addressed position.


Within a byte, the most significant bit, msb, is that which is transmitted first and the least significant bit, lsb, is that which is transmitted last on serial bus, as illustrated below. The significance of the interior bits uniformly decreases in progression from msb to lsb.



IEC 2117/08

**Figure 1 – Bit ordering within a byte**


Within a quadlet, the most significant byte is that which is transmitted first and the least significant byte is that which is transmitted last on serial bus, as shown below.



IEC 2118/08

**Figure 2 – Byte ordering within a quadlet**

Within an octlet, which is frequently used to contain 64-bit serial bus addresses, the most significant quadlet is that which is transmitted first and the least significant quadlet is that which is transmitted last on serial bus, as the figure below indicates.



IEC 2119/08

**Figure 3 – Quadlet ordering within an octlet**

When block transfers take place that are not quadlet aligned or not an integral number of quadlets, no assumptions can be made about the ordering (significance within a quadlet) of bytes at the unaligned beginning or fractional quadlet end of such a block transfer, unless an application has knowledge (outside of the scope of this specification) of the ordering conventions of the other bus.

(standards.iteh.ai)

#### 4 Reference model for data transmission

[IEC 61883-8:2008](#)

##### 4.1 Model overview [standards.iteh.ai/catalog/standards/sist/d68bb05d-bb8e-464f-b9b6-bc7b213caa38/iec-61883-8-2008](#)

The presently defined compression standards for IEEE 1394 transport, DV and MPEG2, have difficulties at the system level in a practical consumer AV network. Both offer excessive compression for simple transport over a wide bandwidth network and carry the associated complexity of coding and decoding signals. Each are fine for their intended purpose, but have excessive cost for simple video transport. Conventional video equipment is interfaced with analog cables carrying a number of signal formats, and it is this low cost and universal connection capability which digital interfaces need to emulate. Thus the analog output from any DVD player will connect to any TV, and this is seen as adequate by equipment manufacturers. Digital interfaces would allow many additional features, but providing every input with the capability of decoding both DV and MPEG2 in all available standards and resolutions is unnecessarily expensive. Inside equipment variations on the broadcast equipment ITU-R BT.601-5/BT.656-4 interface are common and provide a universal interface standard for digital video transport. The coding system in ITU-R BT.601-5 sends YUV data across an 8 bit interface between integrated circuits, for example an MPEG decoder and DAC. If the decoder and DAC are separated by 1394 in their separate boxes there will be a reduction in cost at the source device and the sink device will be independent from the video encoding mechanism.

This standard describes the method of passing YUV video signals across IEEE 1394 based upon the formats defined by ITU-R BT.601-5. Familiarity with the specifications ITU-R BT.601-5, ITU-R BT.656-4 and IEC 61883 is necessary to follow the technical details.

There is also the capability to transfer data in YUV 4:4:4 and 24 bit RGB formats. This allows video to be transferred without the need for color space sub-sampling.

It is valid to transmit all video modes as uncompressed data as long as the IEEE 1394 bus bandwidth is available. In practice some video modes will not be transportable in an uncompressed state.

This model also allows for the future development of video codecs. Since the transport of the video data is independent of the original source encoding as new codecs are deployed, such as MPEG-4, the transport mechanism described in this document will not need to change.

### 4.2 Compression

To allow the transport of high definition video signals at bus speeds less than S1600 or to allow the transport of multiple video streams it is essential that the video stream is compressed. This compression need not be more than about 10:1 and should have minimal discernable impact on the displayed image. Since compression is required to transport some of the video modes it is necessary to reference at least one compression codec in this specification. A suitable video compression codec is referenced for this purpose in Table 2. There is no requirement that a source or sink device implement this codec. Other suitable video compression codecs may be added in the future.

### 4.3 Isochronous packet header

The header quadlet of an IEEE 1394 isochronous packet (tcode A<sub>16</sub>) is shown in the Figure 4 below.




Figure 4 – Isochronous packet header

The tag field shall be set to 1<sub>16</sub> indicating that the packet has the Common Isochronous Packet (CIP) Header as defined in IEC 61883-1. The contents of the CIP Header are described in 4.4.


IEC 61883-8:2008

<https://standards.iteh.ai/catalog/standards/sist/d68bb05d-bb8e-464fb9b6-0c70215caa38/iec-61883-8-2008>

The definition of the remaining fields is outside of the scope of this specification.

### 4.4 CIP header

The definition of the CIP header is shown in Figure 5 below.



IEC 2121/08

Figure 5 – CIP header

- SID denotes the source node ID. This is bus configuration dependent.
- DBS value depends upon the video mode being transported and the color space used. This value is dependent upon the compression mode, color space and video mode. The DBS value for compression mode 0<sub>16</sub> can be calculated from the source packet size given in Table 1 by dividing the value by 4. For other compression modes refer to the documentation available from the codec vendor.
- FN shall always have a value of 0<sub>16</sub>. There shall only be 1 data block per source packet.
- QPC shall always have a value of 0<sub>16</sub>. There shall be no padding.
- SPH shall be 0<sub>16</sub>. The source packet header is not present.
- Since FN is 0<sub>16</sub> the value of DBC shall always increment by the number of source packets present in the Isochronous packet. This field indicates the count value of the first data block in the current isochronous packet.

- The value of FMT shall be  $000001_2$ . This value indicates that the source packet format is as defined in this specification. This also indicates that the SYT field is present in the CIP header.
- The FDF field is encoded as shown in Figure 6 below.
- The SYT field is encoded as defined in IEC 61883-1.



IEC 2122/08

**Figure 6 – FDF field**

The ND field is used to signify whether the data payload of the isochronous packet after the CIP header is valid. If ND is set to  $1_2$  it indicates that the data is not valid and shall be ignored, this setting is only used in blocking transmission mode (see 4.7.1.3). The DBC field in the CIP header of a packet which has ND set to  $1_2$  shall be the count value of the next valid data block. The transmission of an isochronous packet with this bit set shall not cause the value of DBC to increment. If ND is set to  $0_2$  it indicates that the data payload of the isochronous packet after the CIP header is valid. In non-blocking transmission mode, see 4.7.1.2, ND shall be set to  $0_2$  for all isochronous packets.

#### 4.5 Stream definition

A stream that conforms to this specification is governed by three key parameters:

- video mode, see Table 1 below. Additional information for each video mode is given in Annex B.
- compression mode, see Table 2 below.
- color space, see Table 3 below.

Each of these parameters includes an unconstrained mode that allows modes not explicitly defined to be transmitted. The use of these unconstrained modes is beyond the scope of this standard. However, it is expected that their use will be determined by negotiation before transmission.

For transmission of compression mode  $0_{16}$  data the packetization and timing characteristics are defined in this specification.

For transmission of compression mode  $1_{16}$  and  $2_{16}$  data the packetization and timing characteristics are defined in the applicable specification document referenced in Table 2.