
Akustika - Ocena emisije hrupa v zraku z merjenjem vibracij naprav

Acoustics -- Estimation of airborne noise emitted by machinery using vibration measurement

Acoustique -- Détermination du bruit aérien émis par les machines par mesurage des vibrations

STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **ISO/TR 7849:1987**
<https://standards.iteh.ai/catalog/standards/sist/65101765-298c-4a56-9663-8ad8b98f5977/sist-iso-tr-7849-1997>

ICS:

17.140.20	Emisija hrupa naprav in opreme	Noise emitted by machines and equipment
17.160	Vibracije, meritve udarcev in vibracij	Vibrations, shock and vibration measurements

SIST ISO/TR 7849:1997**en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO/TR 7849:1997](https://standards.iteh.ai/catalog/standards/sist/b5f0f7b3-298c-4a56-9663-8ad8b98f5977/sist-iso-tr-7849-1997)

<https://standards.iteh.ai/catalog/standards/sist/b5f0f7b3-298c-4a56-9663-8ad8b98f5977/sist-iso-tr-7849-1997>



TECHNICAL REPORT 7849

Published 1987-12-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Acoustics — Estimation of airborne noise emitted by machinery using vibration measurement

Acoustique — Estimation du bruit aérien émis par les machines par mesurage des vibrations

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

The main task of ISO technical committees is to prepare International Standards. In exceptional circumstances a technical committee may propose the publication of a technical report of one of the following types:

- type 1, when the necessary support within the technical committee cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still under technical development requiring wider exposure;
- type 3, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art" for example).

Technical reports are accepted for publication directly by ISO Council. Technical reports types 1 and 2 are subject to review within three years of publication, to decide if they can be transformed into International Standards. Technical reports type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

ISO/TR 7849 was prepared by Technical Committee ISO/TC 43, *Acoustics*.

The reasons which led to the decision to publish this document in the form of a technical report type 2 are explained in the Introduction.

0 Introduction

0.1 Reasons for publication as a technical report type 2

The proposal to prepare an International Standard on measurement and characterization of noise radiated by structure-borne components of machinery was initiated in 1979 at the ISO/TC 43/SC 1 meeting. A draft proposal was prepared for discussion. However, in 1982 it was decided that the text of this DP should be amended on the basis of the member body comments, and as the subject had not sufficiently advanced to prepare an International Standard, the amended text should be submitted for adoption as a Technical Report. This proposal to publish as a Technical Report was supported by the majority of participating members of TC 43.

This document is published in the form of a technical report type 2 as the subject cannot yet be considered suitable for an International Standard because of the lack of present knowledge on some measurement characteristics; the accuracy of the method remains, for example, uncertain when applied to specific families of machines which are most relevant in noise radiation. The subject is still under study and this Technical Report may encourage further practical investigation in this field, producing basic data to change this Technical Report into an International Standard in future.

UDC 534.647 : 621

Ref. No. ISO/TR 7849 : 1987 (E)

Descriptors: acoustics, vibration, machinery, tests, acoustic tests, determination, noise (sound), airborne sound.

© International Organization for Standardization, 1987 ●

Printed in Switzerland

Price based on 20 pages

ISO/TR 7849 : 1987 (E)

0.2 General

The determination of airborne noise emission of a machine by measuring vibrations of the machine's outer surface may be of interest in the following cases :

- when undesired background noise (e.g. noise from other machines or sound reflected by room boundaries) is high compared with the noise radiated directly by the machine under test;
- when the noise radiated by structural vibration is to be separated from noise of aerodynamic origin (also in cases where the new noise intensity measuring technique cannot easily be applied);
- where the structure-borne noise from only a part of a machine, or from a component of a machine set, is to be determined in the presence of noise from the other parts of the whole source.

This Technical Report gives a procedure for estimating the sound power of the airborne noise emitted by machinery from vibration measurements. Under certain conditions, the measurement procedure can be applied without great difficulty if

- the shape of the machine's outer surface is more or less simple;
- vibrations at different measurement locations are not significantly correlated, and a large number of resonant modes of vibration are found within the frequency band.

Certain well correlated sources of simple shape can also be treated (vibration of a source of zero order, piston vibration). If these conditions are not fulfilled, some problems arise as described in 0.3. For such cases it is not yet possible to give exact requirements for the measurement procedures, but some measurement procedures are put forward in this Technical Report.

0.3 Assumptions and problems in determining the sound power from a knowledge of the mean square value of the surface velocity of vibration of machines

0.3.1 The airborne sound power radiated by a machine or equipment caused by structural vibrations of its outer surface only, P_S , can be estimated by using the following equation : [SIST ISO/TR 7849:1997](https://standards.iteh.ai/catalog/standards/sist/b5f0f7b3-298c-4a56-9663-8ad8b98f5977/sist-iso-tr-7849-1997)

<https://standards.iteh.ai/catalog/standards/sist/b5f0f7b3-298c-4a56-9663-8ad8b98f5977/sist-iso-tr-7849-1997>

$$P_S = \rho c \bar{v}^2 S_S \sigma$$

where

ρc is the fluid characteristic impedance,

where

ρ is the mean density of the fluid (i.e. air),

c is the velocity of sound in the fluid (i.e. air);

\bar{v}^2 is the mean square value of the normal vibratory velocity averaged over the surface area S_S ;

S_S is the area of the defined outer surface of the machine;

σ is the radiation factor.

As the characteristic impedance ρc is a constant for known meteorological conditions, the formula given above requires the three quantities \bar{v}^2 , S_S and σ to be determined.

0.3.2 The value of \bar{v}^2 is obtained from measurements of the r.m.s. vibratory velocity component perpendicular to the machine's outer surface and taken for a sufficient number of measurement locations distributed over the relevant outer surface of the machine. The array and number of measurement locations can be regarded as sufficient if the value of \bar{v}^2 remains stable within the precision of the method for an increasing number and changed array of measurement locations. A random distribution of vibration pick-ups appears to be desirable. Guidelines on a practical approach are given in 7.2 and 7.3.

It may be desirable to subdivide the machine's surface area in order to rank the sound power radiated from different components. The implication of this subdivision is that each area radiated sound independently.

The spatial variation of vibration velocity depends on

- a) the number of resonant modes excited simultaneously in the frequency band;
- b) the degree of non-uniformity of the structure (e.g. presence of stiffness, holes variation and thickness of material);
- c) the spatial distribution of the exciting forces.

The major problem occurs when very few modes are excited at resonance in a frequency band.

0.3.3 The area of the relevant outer surface of the machine, S_S , can be calculated easily if the shape of the outer surface of the machine is simple (e.g. cylindrical, spherical, composition of flat plates, etc.).

One problem is the radiation from connected structures, such as pipes, mounts, supports, etc., and the radiation from grid-work, rib surfaces, perforated surfaces and supporting structures.

It is recommended to define S_S for specific kinds of machinery in connection with the relevant radiation factor (see the "Bibliography").

0.3.4 The radiation factor, σ , depends on the following factors:

- a) The dimension of the radiating surface compared with the wavelength of the sound in air for the relevant frequencies.
- b) The shape of the radiating surface.
- c) The modal pattern in the frequency band.

The value of σ is determined not only by the structure, but also by the distribution and manner of excitation and by the internal loss factor. So for a certain machine, σ may vary if the field of exciting forces changes (e.g. between idling and load).

The radiation factor of individual modes of certain idealized uniform structures, such as spheres, flat plates and circular cylinders, is known. The modal-average radiation factor of such structures is also known on the assumption of equal modal energy. Certain kinds of excitation may result in non-uniform modal energy, e.g. airborne excitation, single excitation, impulsive excitation.

- d) The time characteristics of the process (stationary or non-stationary).

The radiation factor can be determined as follows:

- a) Theoretically, as described above (see the "Bibliography").
- b) Experimentally from measurements on one or more structures being representative of a certain family of machines or equipment.

This method uses the equation given in 0.3.1 in the following form:

$$\sigma = \frac{P_S}{\rho c S_S \bar{v}^2}$$

where

P_S is the airborne sound power determined either in accordance with ISO 3741, ISO 3742, ISO 3743, ISO 3744, ISO 3745 or ISO 3746 or by using sound intensity measurement;

ρc , S_S and \bar{v}^2 are determined as described previously.

- c) By assuming estimated σ -values as a function of frequency.

Such values may be derived for machines having similar acoustical behaviour as compared with sound sources being investigated carefully according to methods a) and b).

According to some investigations the radiation factor $\sigma(f)$ of a spherical source of zero order (see 8.3.2) approximates, for example, the radiation factor of a large number of sound sources (machines, equipment).

A very rough estimation of σ is given by the value $\sigma = 1$. In general, this assumption allows one to estimate an upper value for the radiated sound power, P_S .

ISO/TR 7849 : 1987 (E)

1 Scope and field of application

This Technical Report gives basic requirements for reproducible methods for estimating the sound power emitted by machines or equipment by using surface vibration measurements. The method is especially applicable in cases where accurate direct airborne noise measurements as specified in ISO 3741, ISO 3742, ISO 3743, ISO 3744 and ISO 3745 are not possible because of high background noise or other parasitic environmental influences. The methods are only applicable to noise which is emitted by vibrating surfaces of solid structures and not to noise generated aerodynamically. The method described in this Technical Report applies mainly to processes which are stationary with respect to time. Research into the possibility of extending these techniques to non-stationary processes is, however, encouraged.

Guidelines for the estimation of the radiation factor variation with frequency are given in annex D. Recommendations on the selection of frequency bands are given in annex E.

This Technical Report specifies procedures by which the sound power radiated from individual parts of the whole of the vibrating surface of large machines can be estimated by vibration measurements.

2 References

ISO 1683, *Acoustics — Preferred reference quantities for acoustic levels.*

ISO 3741, *Acoustics — Determination of sound power levels of noise sources — Precision methods for broad-band sources in reverberation rooms.*

ISO 3742, *Acoustics — Determination of sound power levels of noise sources — Precision methods for discrete-frequency and narrow-band sources in reverberation rooms.*

ISO 3743, *Acoustics — Determination of sound power levels of noise sources — Engineering methods for special reverberation test rooms.*

ISO 3744, *Acoustics — Determination of sound power levels of noise sources — Engineering methods for free-field conditions over a reflecting plane.*

ISO 3745, *Acoustics — Determination of sound power levels of noise sources — Precision methods for anechoic and semi-anechoic rooms.*

ISO 3748, *Acoustics — Determination of sound power levels of noise sources — Engineering method for small, nearly omnidirectional sources under free-field conditions over a reflecting plane.*¹⁾

ISO 5348, *Mechanical vibration and shock — Mechanical mounting of accelerometers.*¹⁾

IEC Publication 225, *Octave, half-octave and third-octave band filters intended for the analysis of sounds and vibrations.*

IEC Publication 651, *Sound level meters.*

3 Definitions

For the purposes of this Technical Report, the following definitions apply.

3.1 structure-borne sound: Vibration transmitted through solid structures of a machine in the frequency range of audible sound. It is determined either from the vibratory velocity or the vibratory acceleration of the surface of the solid structure.

3.2 machine:

- (1) Item of equipment which incorporates a single noise source.
- (2) Assembly of items of equipment which incorporates several noise sources.

3.3 vibratory velocity: Component of the velocity of the vibrating surface in the direction normal to the surface. The root-mean square (r.m.s.) value of the vibratory velocity is designated by the symbol v .

NOTE — The vibratory displacement is the time integral of the vibratory velocity. The r.m.s. displacement for sinusoidal vibration, s , with frequency f is given by the following equation:

$$s = \frac{v}{2\pi f} \quad \dots (1)$$

The vibratory acceleration is the time derivative of the vibratory velocity. The r.m.s. acceleration for sinusoidal vibration, a , with frequency f is given by the following equation:

$$a = 2\pi f v \quad \dots (2)$$

1) At present at the stage of draft.

3.4 vibratory velocity level, L_v : Velocity level, in decibels, given by the following equation :

$$L_v = 10 \lg \frac{v^2}{v_0^2} \quad \dots (3)$$

where

v is the r.m.s. value of the vibratory velocity within the frequency band of interest;

v_0 is the reference velocity¹⁾ and is equal to 5×10^{-8} m/s (= 50 nm/s).

NOTES

- 1 For airborne and structure-borne sound, the reference velocity, v_0 , has the property that the intensity level, the sound pressure level and the vibratory velocity level for a progressive plane wave in air are almost equal in magnitude (see ISO 1683).
- 2 The determination of the vibratory velocity level, L_v , from the vibratory acceleration level, L_a , is described in annex F.

3.5 radiation factor, σ : Factor expressing the efficiency of sound radiation and given by the following equation :

$$\sigma = \frac{P_S}{\rho c S_S \bar{v}^2} \quad \dots (4)$$

where

P_S is the airborne sound power emitted by the vibrating surface of the machine;

ρc is the characteristic impedance of air,

where

ρ is the mean density of air,

c is the velocity of sound in air;

S_S is the area of the vibrating surface (vibrating measurement surface; see 3.8);

\bar{v}^2 is the squared r.m.s. value of the vibratory velocity averaged over the area S_S .

The three quantities σ , P_S and \bar{v}^2 relate to the same period of time.

3.6 radiation index: Index defined by the expression $10 \lg \sigma$.

3.7 airborne sound power level, L_{WS} : Ten times the logarithm to the base 10 of the ratio of a given sound power to the reference sound power. The width of a restricted frequency band is indicated, e.g. octave-band power level, one-third octave-band power level, etc. The airborne sound power level is expressed in decibels (reference sound power : 1 pW). The airborne sound power level for a particular part of the surface of the machine, L_{WS} , is given by the following equation :

$$L_{WS} = 10 \lg \frac{P_S}{P_0} \quad \dots (5)$$

where

P_S is the sound power radiated by the relevant part of the surface of the machine;

P_0 is the reference sound power (= 10^{-12} W = 1 pW).

3.8 vibrating measurement surface: The surface or parts of the surface of the machine on which the measurement positions lie; its area is designated by the symbol S_S .

1) The choice of $v_0 = 10^{-9}$ m/s (as specified in ISO 1683) would result in a vibratory velocity level which is 34 dB higher than the level used in this Technical Report. In equations (6), (10), (11) and (17) 34 dB shall, therefore, be subtracted from the right-hand side.

ISO/TR 7849 : 1987 (E)

3.9 extraneous structure-borne vibratory velocity level: Vibratory velocity level determined when the machine is not working or caused by other undesired sources. Extraneous structure-borne sound originates from structures other than the machine under consideration, e.g. from coupled assemblies.

3.10 spherical source of zero order: Sphere vibrating with uniform phase and the same amplitude over the whole surface.

4 Principle

4.1 General

The method described in this Technical Report is based on the assumption that the airborne sound power output of a vibrating surface is directly proportional to the mean-square vibratory velocity averaged over the vibrating surface and directly proportional to the area of the vibrating surface.

4.2 Method

Vibratory velocity levels in frequency bands are determined at a specified number of locations on the measurement surface of the vibrating structure (the sound source), using vibration measurement equipment. The average vibratory velocity level in frequency bands plus a term for the area of the measurement surface plus a term for the efficiency of sound radiation of the structure gives the airborne sound power level in frequency bands.

Three ways of estimating the radiation factor, σ , and hence the airborne sound power level are described as follows:

- a) If a radiation factor $\sigma = 1$ is assumed, an approximate upper limit to the radiated airborne sound power is obtained. Thus an upper limit for the A-weighted airborne sound power level can be estimated from the A-weighted vibratory velocity level.
- b) If, for a given structure, the sound radiation model of a spherical source of zero order can be justified (e.g. for compact machines), the frequency-dependent radiation factor σ can be obtained from a theoretical curve. By using vibratory velocity levels determined in frequency bands, airborne sound power levels in frequency bands can be determined; from these levels the A-weighted airborne sound power levels may be calculated.
- c) For more accurate determination, the frequency-dependence of the radiation factor σ for the structure or family of machines under test is determined. This also requires the determination of vibratory velocity levels in frequency bands and results in band sound power levels and, if required, the A-weighted airborne sound power level.

5 Measuring instrumentation

5.1 General

In this clause, measuring instrumentation using vibration pick-ups is described. In most cases it will be convenient to make use of light accelerometers; however, for special purposes, other kinds of equipment and measuring techniques may be needed (e.g. non-contact devices, laser-doppler methods).

5.2 Vibration pick-up

The vibration pick-up can load the vibrating surface.

For vibration measurements covering a wide frequency range, piezoelectric accelerometers should be preferred. When selecting an accelerometer for a particular application, allowance should be made for the parameters of the transducer and the environmental conditions in which it is to be used.

Measurements are normally confined to using the linear portion of the frequency-response curve of the accelerometer which, at the high frequency end, is limited by the resonance of the transducer. As a rule-of-thumb the upper frequency limit for measurements can be set to one-third of the resonance frequency of the accelerometer so that vibration components measured at this limit will deviate by no more than 1 dB.

Small, low-mass accelerometers may have high resonance frequencies but in general they have low sensitivity (dynamic range). So a compromise has to be made because high sensitivity normally entails a large piezoelectric assembly and, consequently, a relatively large, heavy unit with low resonance frequency.

The mass of the accelerometer becomes important when measuring on light test objects. To avoid mass-loading errors, the dynamic mass of the transducer should be much less than the dynamic mass of the structure at the point of attachment [$0,2 \varrho_S c_L h^2/f$ in the case of a flat plate, see equation (13)].

5.3 Amplifier and filter

The signals generated by the vibration pick-up shall be amplified, filtered and indicated as r.m.s. values. The structure-borne noise shall be measured with a sound level meter or an equivalent measurement system complying with the requirements for a type 0 or type 1 instrument as specified in IEC Publication 651 with the microphone replaced by the vibration pick-up. The filters shall be in accordance with IEC Publication 225.

5.4 Integrator

If an integrator to transform acceleration signals to velocity signals is used, it shall have characteristics which match the dynamic range of the measuring system. If this requirements is not satisfied and the signal to be measured is too low, the vibratory velocity levels shall be calculated directly from the vibratory acceleration levels (see annex F).

5.5 Calibration

The entire measuring system shall be calibrated at one or more frequencies before each series of measurements is begun. The peak value of an acceleration signal corresponding to an acceleration of $9,81 \text{ m/s}^2$ may serve as the calibration signal. In addition, the pick-up and the electrical measuring instrumentation should be checked as a unit electrically over the entire frequency range of interest at least every other year.

Example:

If the vibration pick-up is calibrated by a sinusoidal acceleration signal, the resulting vibratory velocity level (reference velocity¹⁾, v_0 : $5 \times 10^{-8} \text{ m/s}$, L_v , in decibels, is given by the following equation:

$$L_v = 20 \lg \frac{\hat{a}}{2\pi f v_0 \sqrt{2}} \quad \dots (6)$$

Hence, for a calibration with a peak acceleration value of $\hat{a} = 9,81 \text{ m/s}^2$ and a frequency, f , of 100 Hz, the vibratory velocity level¹⁾ is 106,9 dB.

6 Description, installation and operating conditions

6.1 General

In most cases, the emitted sound power will depend on both the installation and the operating conditions, and general recommendations on these are given in 6.2 to 6.4. If, however, airborne sound measurement test codes for the relevant family of machines exist, the installation and operating conditions specified in those codes shall be used.

6.2 Description of the machine

If the machine features auxiliary equipment or components which emit sound, these should be identified. The items of auxiliary equipment required to be running during the test shall be specified.

Sources of extraneous structure-borne sound should be identified.

NOTE — The procedures specified in this Technical Report do not allow the direct measurement of extraneous structure-borne sound. The use of correlation measurements or the comparison of vibration spectra of coupled assemblies may be necessary.

6.3 Installation

The installation and mounting of the machine shall, as far as possible, be that intended for its final application. If the structural surfaces of the machine are covered by non-structural materials (e.g. insulation), the vibration pick-up shall be mounted on a non-structural surface (see also annex B).

1) See footnote to 3.4.

ISO/TR 7849 : 1987 (E)

6.4 Operating conditions

The machine shall be operated in a manner representative of normal use. One or more of the following operating conditions may be appropriate (see also 6.1) :

- a) machine under nominal load/nominal operating conditions;
- b) machine under full load, if different from a);
- c) machine under no load (idling);
- d) machine under operating conditions corresponding to maximum sound radiation representative of normal use;
- e) machine under simulated load, operating under precisely defined conditions.

7 Determination of the vibratory velocity on the vibrating measurement surface

7.1 General

The specifications given in 7.2 to 7.8 are of a general nature, but if test codes for the relevant family of machine exist, the specific requirements in those codes shall be used.

NOTE — The accuracy of the measurement results depends to a large extent on the number and distribution of the measurement positions and the distribution of the vibratory velocity on the vibrating measurement surface.

Where an individual bandwidth contains a single strong tonal component, the uncertainty of the estimate determined by the method might be high.

7.2 Vibrating measurement surface

7.2.1 General

Suitable measurement surfaces shall be selected according to the criteria outlined in 7.2.2 to 7.2.4.

NOTE — The results of any preliminary investigations (see 7.2.4) and the structures of the radiating areas (e.g. the presence of stiffeners) should be taken into account when selecting the measurement surface.

7.2.2 Uniformly repeated structures

If the machine possesses uniformly repeated structures and if there are geometrical symmetries and symmetries in the excitation forces, then, provided that preliminary investigations have proved all elements to be equivalent with respect to the mean vibratory velocity level in any frequency band, measurements may be carried out on a single structure.

7.2.3 Uniformly distributed measurement positions

The vibrating measurement surface shall be divided into N parts of equal area S_S/N . One measurement position shall be situated in the centre of each partial surface.

7.2.4 Non-uniformly distributed measurement positions

If parts of the vibrating measurement surface are known from preliminary investigations to vibrate more intensely than others, the measurement positions may be distributed more densely over those parts vibrating more intensely.

In this case, each measurement position i represents one partial surface S_{S_i} (see 8.2).

7.3 Number of measurement positions

The initial number of measurement positions on the vibrating measurement surface may be chosen according to table 1.

Table 1 — Initial number of measurement positions

Area of the vibrating measurement surface, S_S m ²	Number of measurement positions
$S_S \leq 1$	10
$1 < S_S \leq 10$	20
$S_S > 10$	$2 \frac{S_S}{S_0}$
	where $S_0 = 1 \text{ m}^2$

The number of measurement positions shall be increased if the difference between the highest and lowest vibratory velocity level, in decibels, in any frequency band is larger than the number of positions given in table 1. Such an increase in the number of measurement positions may, for example, be necessary if a predominant pure tone exists within the relevant bandwidth.

The number of measurement positions shall be progressively doubled until the mean vibratory velocity level, \overline{L}_v (see 8.2), stays constant within a range of 1 dB.

7.4 Environmental conditions

The measuring equipment shall be selected according to the environmental condition (see 5.2), account being taken of the manufacturer's specifications. The influence of any cable (see clause A.2) may be reduced by using pick-ups with integrated impedance transducers.

7.5 Measurement procedure

For the specified operating conditions, the vibratory velocity level, L'_v , shall be determined at each measurement position for all frequency bands within the frequency range of interest. The vibratory velocity level, L'_v , may be determined from the vibratory acceleration level, L'_a , in accordance with annex F or from the acceleration signal by direct integration (see 5.4), thus avoiding calculations¹⁾. The measurement shall be carried out by using the time-weighting characteristic S ("slow") of the sound level meter or by an integrating sound level meter.

The measurement time should be chosen so that it is appropriate for the type of sound radiated by the structure and the signal processing techniques.

For steady sound, for example, the measurement time should be at least 10 s for centre frequencies of 200 Hz and higher. For time-varying sound, the measurement time shall be chosen in such a way that the noise of the machine is measured unambiguously for the specified operating mode.

SIST ISO/TR 7849:1997

If the preliminary investigations have shown that at particular measurement positions the vibratory velocity levels (or acceleration levels, see annex E) of the extraneous structure-borne sound are less than 10 dB below the levels of the machine when operating, they shall also be determined by a suitable method (see note in 6.2) and a correction made (see 8.1).

NOTE — If it is not possible to determine the levels of the extraneous structure-borne sound separately (e.g. owing to the inseparable coupling of the machine with other assemblies), the results calculated in accordance with clause 8 will be too high.

7.6 Mounting of the vibration pick-up

The vibration pick-up shall be mounted so that it senses as closely as possible the true velocity of the vibrating surface at the measurement position over the frequency range of interest. It shall be mounted in accordance with ISO 5348 with its vibration axis normal to the vibrating surface. For recommendations on mounting methods, see annex A.

7.7 Influence of the mass of the vibration pick-up

It is strongly recommended to use a light pick-up (see 5.2 for explanations). If such a pick-up is not available, the correction according to annex B for uniform structures (plates, cylinders) may be applied. For other structures, the accuracy of this correction is unknown.

7.8 Determination of the radiation factor

The radiation factor of the machine shall either be measured in accordance with the recommendations given in annex D or estimated in accordance with 8.3.2.

1) If only A-weighted vibratory velocity levels are to be determined, integration is necessary.