

INTERNATIONAL STANDARD

IEC
60269-2

Third edition
2006-11

Low-voltage fuses –

Part 2:

Supplementary requirements for fuses

for use by authorized persons

(fuses mainly for industrial application) –

Examples of standardized systems of fuses A to I

(<https://standards.iteh.ai/>)
Document Preview

IEC 60269-2:2006

<https://standards.iteh.ai/en/standards/iec/4643165c-beac-4185-a796-7ecc8142bcfd/iec-60269-2-2006>

This **English-language** version is derived from the original **bilingual** publication by leaving out all French-language pages. Missing page numbers correspond to the French-language pages.



Reference number
IEC 60269-2:2006(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

<https://standards.iteh.ai/catalog/standards-iec/4683165c-beac-4185-a796-7ecc8142bcfd/iec-60269-2-2006>

INTERNATIONAL STANDARD

IEC 60269-2

Third edition
2006-11

Low-voltage fuses –

Part 2:

Supplementary requirements for fuses

for use by authorized persons

(fuses mainly for industrial application) –

Examples of standardized systems of fuses A to I

(<https://standards.iteh.ai/>)
Document Preview

IEC 60269-2:2006

<https://standards.iteh.ai/standards/iec/4643165c-beac-4185-a796-7eec8142bcfd/iec-60269-2-2006>

© IEC 2006 Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembe, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE **XH**

For price, see current catalogue

CONTENTS

FOREWORD.....	25
INTRODUCTION.....	29
1 General scope.....	31
2 Normative references.....	33
Fuse system A – Fuses with fuse-links with blade contacts (NH fuse system)	
1 General.....	35
1.1 Scope.....	35
2 Terms and definitions.....	35
3 Conditions for operation in service.....	37
4 Classification.....	37
5 Characteristics of fuses.....	37
5.2 Rated voltage.....	37
5.3.1 Rated current of the fuse-link.....	37
5.3.2 Rated current of the fuse-holder.....	37
5.5 Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder.....	37
5.6 Limits of time-current characteristics.....	39
5.6.1 Time-current characteristics, time-current zones and overload curves.....	39
5.6.2 Conventional times and currents.....	39
5.6.3 Gates.....	39
5.7.2 Rated breaking capacity.....	39
6 Marking.....	41
6.1 Markings of fuse-holders.....	41
6.2 Markings of fuse-links.....	41
7 Standard conditions for construction.....	43
7.1 Mechanical design.....	43
7.1.2 Connections, including terminals.....	43
7.1.3 Fuse-contacts.....	43
7.1.5 Construction of fuse-bases.....	45
7.1.7 Construction of a fuse-link.....	45
7.2 Insulating properties.....	45
7.7 I^2t characteristics.....	45
7.8 Overcurrent discrimination of "gG" fuse-links.....	47
7.9 Protection against electric shock.....	47
8 Tests.....	49
8.1.4 Arrangement of the fuse and dimensions.....	49
8.1.6 Testing of fuse-holders.....	49
8.2.2.1 Points of application of the test voltage.....	49
8.2.3.2 Value of test voltage.....	49
8.2.3.3 Test method.....	51
8.2.4 Acceptability of test results.....	51
8.2.5 Resistance to tracking.....	51

8.3	Verification of temperature rise and power dissipation	51
8.3.1	Arrangement of the fuse	51
8.3.2	Measurement of the temperature rise	53
8.5.8	Acceptability of test results	55
8.7.4	Verification of overcurrent discrimination	55
8.9	Verification of resistance to heat	59
8.9.1	Fuse-base	59
8.9.2	Fuse-links with gripping lugs of moulded material or of metal fixed in moulded material	61
8.10	Verification of non-deterioration of contacts and direct terminal clamps	61
8.10.1	Arrangement of the fuse	61
8.10.2	Test method	65
8.10.3	Acceptability of test results	69
8.11	Mechanical and miscellaneous tests	71
Annex A (informative) Special test for cable overload protection		115

**Fuse system B – Fuses with striker fuse-links with blade contacts
(NH fuse system)**

1	General	117
1.1	Scope	117
2	Terms and definitions	117
3	Conditions for operation in service	117
4	Classification	117
5	Characteristics of fuses	117
5.2	Rated voltage	117
5.3.1	Rated current of the fuse-link	119
5.3.2	Rated current of the fuse-holder	119
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	119
5.6	Limits of time-current characteristics	119
5.7.2	Rated breaking capacity	119
6	Marking	119
7	Standard conditions for construction	119
7.1	Mechanical design	119
7.1.2	Connections, including terminals	119
7.1.3	Fuse-contacts	119
7.1.7	Construction of a fuse-link	121
7.7	I^2t characteristics	121
7.8	Overcurrent discrimination of "gG" fuse-links	121
7.9	Protection against electric shock	121
8	Tests	121
8.1.6	Testing of fuse-holders	121
8.3	Verification of temperature rise and power dissipation	121
8.7.4	Verification of overcurrent discrimination	123
8.9	Verification of resistance to heat	123
8.9.1	Fuse-base	123

Fuse system C – Fuse-rails (NH fuse system)

1	General	141
1.1	Scope	141
2	Terms and definitions	141
3	Conditions for operation in service	141
4	Classification	141
5	Characteristics of fuses	141
5.2	Rated voltage	141
5.3.2	Rated current	141
5.5.1	Rated power acceptance	141
6	Markings	143
7	Standard conditions for construction	143
7.1	Mechanical design	143
7.1.2	Connections, including terminals	143
7.2	Insulating properties	143
8	Tests	143
8.1.6	Testing of fuse-holders	143
8.3	Verification of temperature rise and power dissipation	145
8.3.1	Arrangement of the fuse	145
8.10	Verification of non-deterioration of contacts and direct terminal clamps	147
8.10.1	Arrangement of the fuse	147

**Fuse system D – Fuse-bases for busbar mounting (40 mm system)
(NH fuse system)**

1	General	157
1.1	Scope	157
2	Terms and definitions	157
3	Conditions for operation in service	157
4	Classification	157
5	Characteristics of fuses	157
5.2	Rated voltage	157
5.3.2	Rated current	159
5.5.2	Rated acceptable power dissipation of tandem fuse-bases	159
6	Markings	159
7	Standard conditions for construction	159
7.1	Mechanical design	159
7.1.2	Connections, including terminals	159
7.1.5	Construction of a fuse-base for busbar mounting	161
8	Tests	161
8.3	Verification of temperature rise and power dissipation	161
8.3.1	Arrangement of the fuse	161
8.9.1	Fuse-base	163
8.10	Verification of non-deterioration of contacts and direct terminal clamps	163
8.10.1	Arrangement of the fuse	163
8.10.2	Test method	165
8.11	Mechanical and miscellaneous tests	165

**Fuse system E – Fuses with fuse-links for bolted connections
(BS bolted fuse system)**

1	General	181
1.1	Scope.....	181
2	Terms and definitions	181
3	Conditions for operation in service.....	181
4	Classification.....	181
5	Characteristics of fuses	181
5.3.1	Rated current of the fuse-link.....	181
5.3.2	Rated current of the fuse-holder	181
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	183
5.6	Limits of time-current characteristics	183
5.6.1	Time-current characteristics, time-current zones and overload curves	183
5.6.2	Conventional times and currents.....	183
5.6.3	Gates	183
5.7.2	Rated breaking capacity	183
6	Markings	185
6.1	Markings of fuse-holders	185
6.2	Markings of fuse-links.....	185
7	Standard conditions for construction.....	185
7.1	Mechanical design.....	185
7.1.2	Connections including terminals	185
7.9	Protection against electric shock	185
8	Tests	185
8.3	Verification of temperature rise and power dissipation	185
8.3.1	Arrangement of the fuse	185
8.3.3	Measurement of the power dissipation of the fuse-link.....	185
8.4	Verification of operation	187
8.4.1	Arrangement of the fuse	187
8.5	Verification of breaking capacity.....	187
8.5.1	Arrangement of the fuse	187
8.5.8	Acceptability of test results.....	187
8.9	Verification of resistance to heat	187
8.10	Verification of non-deterioration of contacts.....	187
8.10.1	Arrangement of the fuse	187
8.10.2	Test method	187
8.10.3	Acceptability of the results.....	189
8.11	Mechanical and miscellaneous tests.....	189

**Fuse system F – Fuses with fuse-links having cylindrical contact caps
(NF cylindrical fuse system)**

1	General	209
1.1	Scope.....	209
2	Terms and definitions	209
3	Conditions for operation in service.....	209
4	Classification.....	209

5	Characteristics of fuses	209
5.2	Rated voltage	209
5.3.1	Rated current of the fuse-link.....	211
5.3.2	Rated current of the fuse-holder	211
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	211
5.6	Limits of time-current characteristics	213
5.6.1	Time-current characteristics, time-current zones and overload curves	213
5.6.2	Conventional times and currents.....	213
5.6.3	Gates	213
5.7.2	Rated breaking capacity	215
6	Marking	215
6.1	Markings of fuse-holders	215
6.2	Markings of fuse-links.....	215
7	Standard conditions for construction.....	217
7.1	Mechanical design.....	217
7.1.2	Connections including terminals	217
7.7	I^2t characteristics	217
7.8	Overcurrent discrimination of "gG" fuse-links.....	219
7.9	Protection against electric shock.....	219
8	Tests	219
8.1.6	Testing of fuse-holders.....	219
8.3.1	Arrangement of the fuse	221
8.7.4	Verification of overcurrent discrimination	225
8.9	Verification of resistance to heat	225
8.10	Verification of non-deterioration of contacts.....	227
8.10.1	Arrangement of the fuse.....	227
8.10.2	Test method	227
8.10.3	Acceptability of test results.....	227

**Fuse system G – Fuses with fuse-links with offset blade contacts
(BS clip-in fuse system)**

1	General	237
1.1	Scope.....	237
2	Terms and definitions	237
3	Conditions for operation in service.....	237
4	Classification.....	237
5	Characteristics of fuses	237
5.2	Rated voltage	239
5.3.1	Rated current of the fuse-link.....	239
5.3.2	Rated current of the fuse-holder	239
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	239
5.6.1	Time-current characteristics, time-current zones	239
5.6.2	Conventional times and currents.....	239
5.6.3	Gates	241
5.7.2	Rated breaking capacity	241

6	Markings	241
6.1	Markings of fuse-holders	241
6.2	Markings of fuse-links.....	241
7	Standard conditions for construction.....	241
7.1	Mechanical design.....	241
7.1.2	Connections including terminals	241
7.7	I^2t characteristics	243
7.9	Protection against electric shock	243
8	Tests	243
8.3.3	Measurement of the power dissipation of the fuse-link	243
8.4.1	Arrangement of the fuse	245
8.5.1	Arrangement of the fuse	245
8.7.4	Verification of overcurrent discrimination	245
8.9	Verification of resistance to heat	245
8.10	Verification of non-deterioration of contacts.....	245
8.10.1	Arrangement of the fuse	245
8.10.2	Test method	247
8.10.3	Acceptability of test results.....	247
8.11	Mechanical and miscellaneous tests.....	247

**Fuse system H – Fuses with fuse-links having "gD" and "gN" characteristics
(class J and class L time delay and non time delay fuse types)**

1	General	259
1.1	Scope.....	259
2	Terms and definitions	259
3	Conditions for operation in service.....	259
4	Classification.....	259
5	Characteristics of fuses	261
5.2	Rated voltage	261
5.3.1	Rated current of the fuse-link.....	261
5.3.2	Rated current of the fuse-holder	261
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	261
5.6	Limits of the time-current characteristics	261
5.6.1	Time-current characteristics, time-current zones	261
5.6.2	Conventional times and currents.....	261
5.6.3	Gates	263
5.7.2	Rated breaking capacity	263
6	Markings	263
6.1	Markings of fuse-holders	263
6.2	Markings of fuse-links.....	263
7	Standard conditions for construction.....	263
7.1	Mechanical design.....	263
7.6	Cut-off current characteristics.....	263
7.7	I^2t characteristics	265
7.9	Protection against electric shock	265

8	Tests	267
8.3	Verification of temperature rise and power dissipation	267
8.3.1	Arrangement of the fuse	267
8.4	Verification of operation	267
8.4.1	Arrangement of the fuse	267
8.6	Verification of cut-off current characteristics	269
8.7	Verification of I^2t characteristics and overcurrent discrimination	269
8.9	Verification of resistance to heat	271
8.10	Verification of non-deterioration of contacts	271
8.10.1	Arrangement of the fuse	271
8.10.2	Test method	273
8.10.3	Acceptability of test results	273
8.11	Mechanical and miscellaneous tests	273
8.11.2	Miscellaneous tests	273
Fuse system I – gU fuse-links with wedge tightening contacts		
1	General	299
1.1	Scope	299
2	Terms and definitions	299
3	Conditions for operation in service	301
3.9	Discrimination of fuse-links	301
4	Classification	301
5	Characteristics of fuses	301
5.2	Rated voltage	301
5.3.1	Rated current of the fuse-link	301
5.5	Rated power dissipation of a fuse-link	301
5.6.1	Time-current characteristics, time-current zones	303
5.6.2	Conventional times and currents	303
5.6.3	Gates	303
5.7.2	Rated breaking capacity	303
5.8	Cut-off current and I^2t characteristics	303
6	Markings	303
6.1	Markings of fuse-holders	303
6.2	Markings of fuse-links	303
7	Standard conditions for construction	305
7.1	Mechanical design	305
7.5	Breaking capacity	305
7.7	I^2t characteristics	305
7.8	Overcurrent discrimination of the fuse-links	305
8	Tests	305
8.1.1	Kind of tests	307
8.3.1	Arrangement of the fuse	307
8.3.3	Measurement of the power dissipation of the fuse-link	307
8.4.1	Arrangement of the fuse	307
8.5.1	Arrangement of the fuse	309
8.5.2	Characteristics of the test circuit	309
8.5.5	Test method	309

8.5.8	Acceptability of test results	309
8.7.3	Verification of compliance for fuse-links at 0,01 s	309
8.9	Verification of resistance to heat	309
8.11	Mechanical and miscellaneous tests	309
Figure 101	– Fuse-links with blade contacts	77
Figure 102	– Fuse-bases for fuse-links with blade contacts	83
Figure 103	– Replacement handle	89
Figure 104	– Time-current zones for "gG" fuse-links	91
Figure 105	– Dummy fuse-link according to 8.3.4.1, 8.9.1 and 8.10	101
Figure 106	– Measuring points according to 8.3.4 of IEC 60269-1, 8.3.4.1, 8.3.4.2 and 8.10.2 of fuse system A	103
Figure 107	– Test knife according to 8.5.5.1.2	103
Figure 108	– Example of a measuring device for determining the withdrawal forces according to 8.9.1 and 8.11.1.2	105
Figure 109	– Facility for verifying the mechanical strength of gripping lugs (see 8.11.1.8)	107
Figure 110	– Measuring points according to 8.10.2	109
Figure 111	– Reference fuse-base	111
Figure 112	– Design mark for isolated gripping-lugs	113
Figure 201	– Fuse-links with blade contacts with striker	127
Figure 202	– Fuse-bases for fuse-links with blade contacts with striker	135
Figure 301	– Fuse-rails for fuse-links with blade contacts	149
Figure 302	– Test arrangement for fuse-rails	153
Figure 401	– Busbar mounting bases, 1 pole	167
Figure 402	– Busbar mounting bases, 3 pole	169
Figure 403	– Busbar mounting base, size 00, 2 × 3 pole (tandem fuse-base)	171
Figure 404	– Test arrangement for single-pole and triple-pole fuse-bases for busbar-mounting according to 8.3.1	173
Figure 405	– Test arrangement for two single-pole and six single-pole fuse-bases in tandem arrangement for busbar-mounting according to 8.3.1	175
Figure 406	– Test arrangement for the verification of the peak withstand current	177
Figure 407	– Dummy fuse-link	179
Figure 501	– Fuse-links for bolted connection – Sizes A, B, C and D	191
Figure 502	– Fuse-links for bolted connection – Sizes A and B	193
Figure 503	– Typical fuse-holder	195
Figure 504	– Time-current zones for "gG" fuse-link	199
Figure 505	– Time-current zones for "gG" fuse-link	201
Figure 506	– Power dissipation test rig	203
Figure 507	– Breaking capacity test rig for fuse-links for bolted connection	205
Figure 601	– Fuse-links with cylindrical caps	229

Figure 602 – Fuse-links with cylindrical contact caps with striker – Additional dimensions for sizes 14 × 51 and 22 × 58 only.....	231
Figure 603 – Base for fuse-links with cylindrical caps	233
Figure 701 – Fuse-links having offset blade contacts, sizes E1, F1, F2 and F3	249
Figure 702 – Typical fuse-holder.....	251
Figure 703 – Time-current zones for "gG" fuse-links	253
Figure 704 – Time-current zones for "gG" fuse-links	255
Figure 705 – Power dissipation test rig	257
Figure 801 – Fuse-links (1-600 A).....	275
Figure 802 – Fuse-links (700 – 6 000 A)	277
Figure 803 – Fuse-base and contacts for fuse-links 1 – 600 A	279
Figure 804 – Fuse-base and contacts for fuse-links 700 – 6 000 A.....	281
Figure 805 – Dummy fuse-links.....	283
Figure 806 – Test arrangement.....	285
Figure 807 – Time-current zones for "gN" fuse-links	287
Figure 808 – Time-current zones for "gN" fuse-links	289
Figure 809 – Time-current zones for "gN" fuse-links	291
Figure 810 – Time-current zones for "gD" fuse-links	293
Figure 811 – Time-current zones for "gD" fuse-links	295
Figure 812 – Time-current zones for "gD" fuse-links	297
Figure 901 – Time-current zones for current ratings 100 A, 200 A, 355 A and 630 A.....	313
Figure 902 – Time-current zones for current ratings 160 A and 315 A	315
Figure 903 – Time-current zones for current ratings 250 A and 500 A.....	317
Figure 904 – Time-current zones for current ratings 200 A and 400 A.....	319
Figure 905 – Dimensions for fuse-links with L type and U type tags	321
Figure 906 – Power dissipation test rig	323
Figure 907 – Breaking capacity test rig	325
Table 101 – Conventional time and current for "gG" fuse-links with rated current lower than 16 A.....	39
Table 102 – Gates for specified pre-arcing and operating times of "gG" fuse-links	39
Table 103 – Minimum rated breaking capacities.....	39
Table 104 – Marking of fuse-links	41
Table 105 – Minimum cross-sectional ranges of unprepared conductors	43
Table 106 – Pre-arcing and operating I^2t values at 0,01 s for "gG" fuse-links	45
Table 107 – Maximum operating I^2t values for "aM" fuse-links	47
Table 108 – Pre-arcing I^2t values for discrimination	47
Table 109 – Survey of tests on fuse-holders and number of fuse-holders to be tested	49

Table 110 – Rated impulse withstand voltage	51
Table 111 – Torque to be applied to the terminal screws	53
Table 112 – Test currents	55
Table 113 – Test currents and I^2t limits for discrimination test	57
Table 114 – Torques to be applied when no values are given by the manufacturer	63
Table 115 – Cross-sectional area of aluminium conductors for tests corresponding to 8.10	63
Table 116 – Test sequence for direct terminal clamps.....	67
Table 117 – Permissible changes of the resistance.....	71
Table 118 – Force to withdraw the fuse-link from the fuse-base contacts.....	73
Table 201 – Position and force of the striker	121
Table 301 – Minimum cross-sectional ranges of unprepared conductors for fuse-rails.....	143
Table 302 – Survey of complete tests on fuse-rails and number of fuse-rails to be tested	145
Table 401 – Minimum cross-sectional ranges of unprepared conductors for fuse-bases for busbar mounting.....	159
Table 402 – Torques to be applied to contact making screws.....	161
Table 403 – Test currents	163
Table 404 – Force to withdraw the fuse-link from the fuse-base contacts.....	165
Table 501 – Conventional time and current for "gG" fuse-links.....	183
Table 502 – Gates for specified pre-arcing times of "gG" fuse-links	183
Table 601 – Maximum rated current of fuse-links with cylindrical caps.....	211
Table 602 – Maximum rated current of fuse-holders.....	211
Table 603 – Maximum values of the rated power dissipation of a fuse-link.....	213
Table 604 – Rated acceptable power dissipation of a fuse-holder	213
Table 605 – Conventional time and current for "gG" fuse-links with rated current lower than 16 A.....	213
Table 606 – Gates for specified pre-arcing and operating times of "gG" fuse-links with rated current lower than 16 A.....	215
Table 607 – Minimum rated breaking capacities.....	215
Table 608 – Colours of marking	217
Table 609 – Minimum range of cross-sections for rigid copper conductors.....	217
Table 610 – Pre-arcing and operating I^2t values at 0,01 s for "gG" fuse-links.....	219
Table 611 – Maximum operating I^2t values for "aM" fuse-links	219
Table 612 – Torque to be applied to the terminal screws	221
Table 613 – Test currents	223
Table 614 – Test currents and I^2t limits for discrimination test	225

Table 701 – Conventional time and current for "gG" fuse-links	239
Table 702 – Gates for specified pre-arcing times of "gG" fuse-links	241
Table 703 – Sizes of copper conductors	243
Table 704 – Pre-arcing I^2t values at 0,01 s for "gG" fuse-links	243
Table 801 – Conventional time and current for "gD" and "gN" fuse-links	261
Table 802 – Gates for specified pre-arcing times of "gD" and "gN" fuse-links	263
Table 803 – Pre-arcing I^2t values at 0,01 s for "gD" and "gN" fuse-links.....	265
Table 804 – Cross-sectional area of copper conductors for tests corresponding to 8.3 and 8.4	267
Table 805 – Maximum cut-off current (I_c) for "gD" and "gN" fuse-links at 200 kA prospective current	269
Table 806 – Maximum operating I^2t values for "gD" and "gN" fuse-links at 200 kA prospective current	271
Table 901 – Maximum power dissipation values.....	301
Table 902 – Minimum rated breaking capacities.....	303
Table 903 – Pre-arcing I^2t values for gU fuse-links at 0,01 s	305
Table 904 – Cross-sectional area of conductors for power dissipation and temperature- rise tests.....	307

iTech Standards
 (https://standards.itih.ai)
 Document Preview

IEC 60269-2:2006

https://standards.itih.ai/standards/iec/4643165c-beac-4185-a796-7eec8142bcfd/iec-60269-2-2006