
Power transformer and reactor fittings - Part 5: Liquid level, pressure devices and flow indicators - Amendment A1

Power transformer and reactor fittings -- Part 5: Liquid level, pressure and flow indicators, pressure relief devices and dehydrating breathers

Zubehr fr Transformatoren und Drosselspulen -- Teil 5: Flüssigkeitsstandanzeiger, Druckanzeigeeinrichtungen und Durchflussmesser, Druckentlastungsventile und Luftentfeuchter

iTeh STANDARD PREVIEW

(standards.iteh.ai)

Accessoires pour transformateurs de puissance et bobines d'inductance -- Partie 5: Indicateurs de niveau de liquide isolant, manomètres et indicateurs de circulation de liquide isolant, soupapes de sret et asscheurs d'air

<https://standards.iteh.ai/en/standards/SIST-EN-50216-5-2002-A1-2004>

Ta slovenski standard je istoveten z: EN 50216-5:2002/A1:2002

ICS:

29.180 Transformatorji. Dušilke Transformers. Reactors

SIST EN 50216-5:2002/A1:2004 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 50216-5:2002/A1:2004](https://standards.iteh.ai/catalog/standards/sist/d202a7ac-0030-4ad8-a361-bc41576c6b5e/sist-en-50216-5-2002-a1-2004)

<https://standards.iteh.ai/catalog/standards/sist/d202a7ac-0030-4ad8-a361-bc41576c6b5e/sist-en-50216-5-2002-a1-2004>

EUROPEAN STANDARD

EN 50216-5/A1

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2002

ICS 29.180

English version

**Power transformer and reactor fittings
Part 5: Liquid level, pressure devices and flow indicators**

Accessoires pour transformateurs
de puissance et bobines d'inductance
Partie 5: Indicateurs de niveau de liquide
isolant, manomètres et indicateurs
de circulation de liquide isolant

Zubehör für Transformatoren
und Drosselspulen
Teil 5: Flüssigkeitsstandanzeiger,
Druckanzeigeeinrichtungen
und Durchflussmesser

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This amendment A1 modifies the European Standard EN 50216-5:2002; it was approved by CENELEC on 2002-11-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this amendment the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This amendment exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

This amendment was prepared by the Technical Committee CENELEC TC 14, Power transformers.

The text of the draft was submitted to the Unique Acceptance Procedure and was approved by CENELEC as amendment A1 to EN 50216-5:2002 on 2002-11-01.

The following dates were fixed:

- latest date by which the amendment has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2003-11-01
- latest date by which the national standards conflicting with the amendment have to be withdrawn (dow) 2005-11-01

3 Direct reading dial type liquid level indicators

3.2.3 **Replace** in Table 1 "24 V d.c. to 127 V d.c." with "24 V d.c. to 220 V d.c.".

4 Liquid pressure gauges – Differential pressure gauges

4.2.3 **Replace** in Table 2 "48 V d.c. to 127 V d.c." with "24 V d.c. to 220 V d.c.".

<https://standards.iteh.ai/catalog/standards/sist/d202a7ac-0030-4ad8-a361-bc41576c6b5e/sist-en-50216-5-2002-a1-2004>

5 Liquid flow indicators

5.2.3 **Replace** in Table 3 "48 V d.c. to 127 V d.c." with "24 V d.c. to 220 V d.c.".
