



**SLOVENSKI STANDARD**  
**SIST ISO 7904-1:2002**  
**01-marec-2002**

---

8 fgb]`YÿUJ!`CnbU VY!`%`XY.`Cgbcj bY`cnbU VY

Plain bearings -- Symbols -- Part 1: Basic symbols

Paliers lisses -- Symboles -- Partie 1: Symboles de base

**Ta slovenski standard je istoveten z: ISO 7904-1:1995**

[SIST ISO 7904-1:2002](https://standards.iteh.ai/catalog/standards/sist/afe63e2a-90ea-4026-861e-48e01d4b9bec/sist-iso-7904-1-2002)

<https://standards.iteh.ai/catalog/standards/sist/afe63e2a-90ea-4026-861e-48e01d4b9bec/sist-iso-7904-1-2002>

**ICS:**

21.100.10      Drsni ležaji      Plain bearings

**SIST ISO 7904-1:2002**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 7904-1:2002

<https://standards.iteh.ai/catalog/standards/sist/afe63e2a-90ea-4026-861e-48e01d4b9bec/sist-iso-7904-1-2002>

INTERNATIONAL  
STANDARD

**ISO**  
**7904-1**

First edition  
1995-01-15

---

---

**Plain bearings — Symbols —**

**Part 1:**  
Basic symbols

iTeh STANDARD PREVIEW

(standards.iteh.ai)

*Paliers lisses — Symboles —*

*Partie 1: Symboles de base*

<https://standards.iteh.ai/catalog/standards/sist/afe63e2a-90ea-4026-861e-48e01d4b9bec/sist-iso-7904-1-2002>



Reference number  
ISO 7904-1:1995(E)

**ISO 7904-1:1995(E)****Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 7904-1 was prepared by Technical Committee ISO/TC 123, *Plain bearings*.

ISO 7904 consists of the following parts, under the general title *Plain bearings — Symbols*:

- *Part 1: Basic symbols*
- *Part 2: Applications*

© ISO 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

## Introduction

In the field of plain bearings there is a great number of multiple designations, thus considerable errors are possible in the interpretation of standards and technical literature. Because of this uncertainty, further designations are continuously added which increase the confusion. This part of ISO 7904 is an attempt to elaborate a uniform basic system of symbols for the future.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 7904-1:2002

<https://standards.iteh.ai/catalog/standards/sist/afe63e2a-90ea-4026-861e-48e01d4b9bec/sist-iso-7904-1-2002>

**iTeh STANDARD PREVIEW**  
This page intentionally left blank  
**(standards.iteh.ai)**

SIST ISO 7904-1:2002

<https://standards.iteh.ai/catalog/standards/sist/afe63e2a-90ea-4026-861e-48e01d4b9bec/sist-iso-7904-1-2002>

# Plain bearings — Symbols —

## Part 1: Basic symbols

### 1 Scope

This part of ISO 7904 defines basic symbols for use in the field of plain bearings. Additional signs are also defined for use as superscripts and subscripts.

The system is founded on characters of the Latin and Greek alphabets, Arabic figures and other signs, e.g. points, commas, horizontal lines or asterisks. In the simplest case, a symbol consists of the basic character alone; in the most complex, of the basic character with subscripts and superscripts (additional signs).

For the purpose of international applicability, all symbols have been derived from English words, and designations used in technical literature up to now have been adopted as far as possible. Wide conformity of the symbols for all types of bearings has been attempted.

The present classification may be used in calculations and technological and geometrical determinations as well as in the quality assurance of plain bearings. It may be enlarged according to circumstances.

Quantities which have a fixed value for a certain construction are designated by capital letters, where possible. Depending on the special field of application, the basic characters can be appropriately combined with secondary signs. These signs, however, should only be used if there is a risk of confusion; multiple designations can be avoided by suitable indexing with secondary signs.

### 2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this part of ISO 7904. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this part of ISO 7904 are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 7904-2:1994, *Plain bearings — Symbols — Part 2: Applications*.

### 3 Basic characters

Basic characters consist of one or, in exceptional cases, of two or three capital or lower-case letters.

Variables shall be in italic typeface; abbreviations shall be in Roman typeface.

#### EXAMPLES

$N$  = rotational frequency;  $S_o$  = Sommerfeld number; HRC = Rockwell hardness.

### 4 Additional signs

#### 4.1 Subscripts

Subscripts may consist of one, two or three letters, digits or letter/digit combinations. In general, the first letter of a subscript corresponds to the first letter of

the English concept which is referred to by the subscript. Subsequent letters shall also follow this concept. The expressions used should be as short as possible.

When the signs correspond to a variable, they shall be in italic typeface; when they refer to an abbreviation, they shall be in Roman typeface.

#### EXAMPLES

$c$  = circular;  $cr$  = critical;  $cal$  = calculated.

If subscripts are combined, they shall be separated by means of commas but without a space between. For example, the permissible minimum lubricant film thickness at the transition to boundary lubrication would then be designated as  $h_{lim,tr}$ . As such expressions are rather awkward, use of substitute expressions in these cases is also permitted, such as one single letter or (better still) one digit as subscript which has not yet been used; e.g.  $h_1$  instead of  $h_{lim,tr}$ .

## 4.2 Superscripts

Superscripts shall consist of points, lines, commas, asterisks or other characteristic signs. Only two superscripts are permitted per letter symbol.

#### EXAMPLE

$\bar{c}^*$

## 5 Application and distinction by means of basic characters, subscripts and superscripts

Angles and directions of rotation are defined positively as rotating left-hand (counter-clockwise); the same applies to rotational frequencies, peripheral and angular velocities.

A parameter is represented by the basic character with an asterisk (\*); e.g.  $F^*$  for the bearing capacity parameter. If the bearing capacity parameter of a journal bearing is to be distinguished from that of a thrust bearing, this can be done by the designation  $F_r^*$  or  $F_{ax}^*$ . However, if several different bearing capacity parameters are used, they can be distinguished in the relevant standard or publication by appropriate subscripts; e.g. 1, 2, 3.

#### EXAMPLE

The letter  $C$  may be used to designate the bearing clearance in general,  $C_{ax}$  the wedge depth of thrust bearings,  $C_r$  the radial clearance and  $C_D$  the diametral clearance.

## 6 Symbols and terms

### 6.1 Basic characters (Roman alphabet)

$A$	area; elongation at fracture; heat-emitting surface
$a$	distance; acceleration; thermal diffusivity
$B$	(breadth); nominal width (at right angles to the direction of motion); effective bearing width
$b$	width
$C$	nominal clearance; concentration; chamfer
$c$	specific heat capacity; stiffness coefficient
$D$	nominal bearing diameter
$d$	diameter; damping coefficient
$E$	modulus of elasticity
$e$	eccentricity
$F$	bearing force (nominal load); force
$f$	coefficient of friction; function
$G$	shear modulus
$g$	acceleration due to gravity
$H$	nominal height
HB	Brinell hardness
HRB	Rockwell hardness (ball)
HRC	Rockwell hardness (cone)
HV	Vickers hardness
$h$	height; film thickness; local lubricant film thickness; lining thickness
$I$	moment of inertia; definite integral
$i$	—
$J$	—
$j$	$\sqrt{-1}$
$K$	coefficient; constant; auxiliary variable
$k$	heat transmission coefficient
$L$	nominal length; length of sliding surface in direction of motion; length of pad in circumferential direction



$l$	length	$X$	—
$M$	moment; mixing factor	$x$	Cartesian coordinate; distance
$m$	mass	$Y$	—
$N$	rotational frequency (revolutions per time unit)	$y$	Cartesian coordinate; distance
$n$	number	$Z$	number of sliding surfaces (pads) or pockets per bearing; necking after fracture
$O$	—	$z$	Cartesian coordinate; distance
$o$	—		
$P$	power; heat flow		
$p$	pressure; specific load		
$Q$	flow rate; volume flow rate		
$q$	—		
$R$	nominal radius; roughness (surface finish); resistance; material strength	$\alpha$	heat transfer coefficient; angle; coefficient of thermal expansion; pressure viscosity exponent
$Re$	Reynolds number	$\beta$	angle; temperature viscosity exponent
$r$	radius; repeatability	$\Gamma$	—
$S$	security	$\gamma$	angle
$So$	Sommerfeld number (special form of bearing force parameter $F^*$ )	$\Delta$	difference; Laplace operator
$SP$	switching period	$\delta$	angle
$s$	wall thickness; displacement amplitude (mechanical oscillation)	$\varepsilon$	relative eccentricity; relative elongation
$T$	temperature	$\zeta$	hydraulic resistance coefficient
$t$	time	$\eta$	dynamic viscosity
$U$	surface velocity in $x$ -direction; rotational velocity; flow velocity	$\theta$	—
$u$	velocity component in $x$ -direction; deformation in $x$ -direction; uncertainty of measurement	$\vartheta$	—
$V$	volume; surface velocity in $y$ -direction; displacement velocity	$\kappa$	resistance ratio
$VG$	viscosity grade	$\Lambda$	—
$VI$	viscosity index	$\lambda$	thermal conductivity
$v$	velocity component in $y$ -direction; deformation in $y$ -direction	$\mu$	relative stiffness of the bearing
$W$	surface velocity in $z$ -direction; work (energy)	$\nu$	kinematic viscosity; Poisson's ratio
$w$	velocity component in $z$ -direction; deformation in $z$ -direction; air flow velocity (ambient)	$\Xi$	—
		$\xi$	restrictor ratio
		$\circ$	—
		$\Pi$	product; parameter

## 6.2 Basic characters (Greek alphabet)

NOTE 1 As there is a risk of confusion with the corresponding Roman letters, some Greek capital letters have not been specified.

$\alpha$  heat transfer coefficient; angle; coefficient of thermal expansion; pressure viscosity exponent

$\beta$  angle; temperature viscosity exponent

$\Gamma$  —

$\gamma$  angle

$\Delta$  difference; Laplace operator

$\delta$  angle

$\varepsilon$  relative eccentricity; relative elongation

$\zeta$  hydraulic resistance coefficient

$\eta$  dynamic viscosity

$\theta$  —

$\vartheta$  —

$\iota$  —

$\kappa$  resistance ratio

$\Lambda$  —

$\lambda$  thermal conductivity

$\mu$  relative stiffness of the bearing

$\nu$  kinematic viscosity; Poisson's ratio

$\Xi$  —

$\xi$  restrictor ratio

$\circ$  —

$\Pi$  product; parameter

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

SIST ISO 7904-1:2002

<https://standards.iteh.ai/catalog/standards/sist/afe63e2a-90ea-4026-861e-48e01d4b9bec/sist-iso-7904-1-2002>