



SLOVENSKI STANDARD

SIST EN 300 396-5 V1.2.1:2006

01-julij-2006

Df]nYa b]`gbc dc j b]`fUX]c`fH9 HF 5 ĹĚ`HY b] bY`nU H]j Y`nU`bYdcgfYXb]`bU]b
XY`c j Ub`UfB A ĹĚ`É) "XY. `FUX]`g_]j a Ygb]_`dfY cXU

Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 5: Gateway air interface

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 396-5 V1.2.1:2006](https://standards.iteh.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-a2d824b089ef/sist-en-300-396-5-v1-2-1-2006)

[https://standards.iteh.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-](https://standards.iteh.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-a2d824b089ef/sist-en-300-396-5-v1-2-1-2006)

[a2d824b089ef/sist-en-300-396-5-v1-2-1-2006](https://standards.iteh.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-a2d824b089ef/sist-en-300-396-5-v1-2-1-2006)

Ta slovenski standard je istoveten z: **EN 300 396-5 Version 1.2.1**

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

SIST EN 300 396-5 V1.2.1:2006 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 396-5 V1.2.1:2006

<https://standards.iteh.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-a2d824b089ef/sist-en-300-396-5-v1-2-1-2006>

ETSI EN 300 396-5 V1.2.1 (2006-05)

European Standard (Telecommunications series)

Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 5: Gateway air interface

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 396-5 V1.2.1:2006](https://standards.iteh.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-a2d824b089ef/sist-en-300-396-5-v1-2-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-a2d824b089ef/sist-en-300-396-5-v1-2-1-2006>



Reference

REN/TETRA-08079-5

Keywords

air interface, gateway, protocol, radio, TETRA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 396-5 V1.2.1:2006

<https://standards.iteh.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-a2d824b0892c/sist-en-300-396-5-v1-2-1-2006>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2006.
All rights reserved.

DECT™, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	16
Foreword.....	16
1 Scope	17
2 References	17
3 Definitions and abbreviations.....	18
3.1 Definitions	18
3.2 Abbreviations	21
4 Overview of protocol.....	23
4.1 General	23
4.2 The DM channel.....	24
4.3 DM call procedures for operation with a gateway.....	25
4.3.1 Constraints on the frame structure	27
4.3.2 Setting up a call through a DM-GATE	27
4.3.2.1 Group call from TMO to DM-MS via a DM-GATE.....	28
4.3.2.2 Group call from DM-MS via a DM-GATE.....	30
4.3.2.3 Individual call from TM-MS to DM-MS via a DM-GATE	32
4.3.2.4 Individual call from DM-MS to TM-MS via a DM-GATE	35
4.3.3 Changeover in a call via a DM-GATE.....	37
4.3.4 Pre-emption of a direct mode call through a DM-GATE.....	39
4.3.5 Short Data Service through a gateway.....	40
4.3.6 Group call from DM-MS via DM-REP/GATE.....	41
5 DM-MS layer 3 service description (for operation with a gateway).....	42
5.1 Introduction	42
5.2 Services offered at the DMCC-SAP.....	42
5.3 Description of primitives at the DMCC-SAP.....	43
5.4 Description of parameters at the DMCC-SAP.....	43
5.5 States for DMCC-SAP	44
5.6 Services offered at the DMMM-SAP	44
5.7 Description of primitives at the DMMM-SAP	45
5.7.1 DMMM-REGISTRATION primitive	45
5.7.2 DMMM-REPORT primitive.....	46
5.8 Description of parameters at the DMMM-SAP.....	46
6 DM-MS layer 3 protocol (for operation with a gateway).....	47
6.1 Introduction	47
6.1.1 DMCC protocol states	47
6.1.2 DMMM protocol states.....	47
6.1.2.1 NOT-REGISTERED.....	47
6.1.2.2 WAIT-REGISTRATION.....	47
6.1.2.3 REGISTRATION-ACCEPTED	47
6.1.2.4 REGISTRATION-REJECTED	47
6.2 Circuit mode calls.....	48
6.2.1 Procedures for outgoing call set-up through a gateway	48
6.2.1.1 Outgoing call set-up	48
6.2.1.2 Temporary group address.....	51
6.2.1.3 Layer 3 addressing in DM-GSETUP PDU.....	51
6.2.1.3.1 Called party address	51
6.2.1.3.2 Area selection	51
6.2.1.3.3 Calls to external subscribers	51
6.2.1.3.4 Calling party address	51
6.2.2 Procedures for incoming call set-up.....	51
6.2.2.1 Incoming call set-up without presence check.....	51
6.2.2.2 Incoming call set-up with presence check.....	51
6.2.2.3 Transmitting Party Number Identification (TPNI) during incoming call set-up	52

6.2.3	Usage of DM-OCCUPIED PDU	52
6.2.3.1	Sending of DM-OCCUPIED PDU by master DM-MS	52
6.2.3.2	Late entry by slave DM-MS	52
6.2.4	Procedures during occupation	52
6.2.4.1	Master DM-MS	52
6.2.4.2	Slave DM-MS	53
6.2.4.3	Transmitting Party Number Identification (TPNI) during occupation	54
6.2.4.3.1	Master DM-MS	54
6.2.4.3.2	Slave DM-MS	55
6.2.5	Procedures during reservation	55
6.2.5.1	Master DM-MS	55
6.2.5.2	Slave DM-MS	55
6.2.5.3	Pre-emption of short data sent as a transaction within a circuit mode call	56
6.2.6	Procedures to set up a new call by pre-emption	56
6.3	Short Data Service (SDS) procedures	56
6.3.1	Sending short data	57
6.3.1.1	Sending short data on a free channel	57
6.3.1.1.1	Sending unacknowledged short data on a free channel	57
6.3.1.1.2	Sending acknowledged short data on a free channel	57
6.3.1.2	Sending short data by pre-emption	58
6.3.1.3	Sending short data during circuit mode transmission	58
6.3.1.4	Sending short data as a transaction within a circuit mode call	58
6.3.1.4.1	Pre-emption to send short data as a transaction within a circuit mode call	58
6.3.1.4.2	Changeover to send short data as a transaction within a circuit mode call	58
6.3.1.4.3	Sending the short data as master of the circuit mode call	58
6.3.2	Receiving short data	59
6.3.2.1	Receiving unacknowledged short data	59
6.3.2.2	Receiving acknowledged short data	59
6.3.3	Additional addressing	59
6.3.3.1	DM-MS sending short data	59
6.3.3.2	DM-MS receiving short data	59
6.3.4	Extended error protection	59
6.3.5	SDS-TL service in DM-MS	59
6.3.5.1	Service primitives at the DMTL-SAP	60
6.3.5.2	DMTL-SDS primitives' parameters	60
6.3.5.3	DMTL-SDS PDUs	60
6.3.5.4	DMTL-SDS procedures	60
6.4	Procedures for mobility management	60
6.4.1	Solicited registration	60
6.4.2	Unsolicited registration	61
6.4.3	Cancellation of registration by gateway	61
6.4.4	Other criteria for DMMM state change	62
6.4.5	Action on entering state REGISTRATION-REJECTED	62
6.4.6	Layer 3 addressing in DM-GREGISTER REQUEST PDU	62
6.5	Usage of DMA-UNITDATA primitive	62
6.5.1	Sending a DMCC PDU	62
6.5.2	Sending a DMMM PDU	63
6.5.3	Protocol control function for delivery of received message	63
6.6	General procedures	63
6.6.1	Usage restriction type and validity time	63
7	DM-MS layer 2 service description (for operation with a gateway)	64
7.1	Introduction	64
7.2	Layer 2 architecture	64
7.3	Service descriptions	64
7.3.1	Services at the DMA-SAP	64
7.3.1.1	Services provided to layer 3	64
7.3.1.2	Service primitives at the DMA-SAP	64
7.3.1.2.1	DMA-REPORT primitive	64
7.3.1.2.2	DMA-UNITDATA primitive	65
7.3.2	Services at the DMC-SAP	65
7.3.2.1	Services provided to layer 3	65

7.3.2.2	Service primitives at the DMC-SAP	65
7.3.2.2.1	DMC-CONFIGURE primitive	65
7.3.2.2.2	DMC-REPORT primitive	65
7.3.3	Services at the DMD-SAP	66
7.3.3.1	Services provided to the U-plane application	66
7.3.3.2	Service primitives at the DMD-SAP	66
7.4	Parameter listing	66
8	DM-MS layer 2 protocol (for operation with a gateway)	67
8.1	Introduction	67
8.1.1	Functions of lower MAC	67
8.1.2	Functions of upper MAC	67
8.2	Interface between lower and upper MAC	68
8.2.1	Logical channels defined at the DMV-SAP	68
8.2.2	Service primitives at the DMV-SAP	68
8.2.3	PDU mapping of the logical channels at the DMV-SAP	68
8.2.4	Scrambling mechanism	68
8.2.5	PDU error detection	69
8.2.6	Modes of operation	69
8.3	Basic capabilities of the physical layer	69
8.3.1	DM-MS capabilities	69
8.3.1.1	DM only and dual mode capable MS operation	69
8.3.1.2	Dual watch capable MS operation	69
8.4	Usage of DM channel with gateway	69
8.4.1	Definition of DM channel	70
8.4.1.1	DM channel arrangement	70
8.4.1.1.1	DM channel arrangement for operation with a DM-GATE	70
8.4.1.1.2	DM channel arrangement for operation with a type 1A DM-REP/GATE	70
8.4.1.1.3	DM channel arrangement for operation with a type 1B DM-REP/GATE	71
8.4.1.2	DM channel operation	71
8.4.2	DM-MAC states	72
8.4.2.1	DM-MAC state definitions	72
8.4.2.2	DM-MS channel surveillance procedures	73
8.4.2.2.1	Initial determination of DM channel state	73
8.4.2.2.1.1	Initial determination of state of carrier	73
8.4.2.2.1.2	Determination of state of one DM channel when other DM channel is busy	74
8.4.2.2.2	Fast call set-up surveillance in idle mode	74
8.4.2.2.2.1	Fast call set-up surveillance when idle on a free carrier	74
8.4.2.2.2.2	Fast call set-up surveillance when idle on a carrier that is not free	75
8.4.2.2.3	DM-MS channel surveillance at call set-up (circuit mode call or short data message)	75
8.4.2.2.4	DM-MS channel surveillance for registration outside the registration phase	75
8.4.2.3	Master DM-MS channel maintenance procedures during a call transaction	76
8.4.2.4	Slave DM-MS channel maintenance procedures during a call	77
8.4.2.4.1	Slave MS channel maintenance during call transaction	77
8.4.2.4.2	Slave MS signal quality measurement during call transaction	77
8.4.2.4.3	Slave MS channel maintenance during reservation	77
8.4.3	Criteria for changing DM-MAC states	77
8.4.3.1	Criteria for changing DM-MAC state for master DM-MS	77
8.4.3.2	Criteria for changing DM-MAC state for slave DM-MS	77
8.4.3.3	Criteria for changing DM-MAC state for idle DM-MS	78
8.4.4	DM-MS channel monitoring procedures	79
8.4.4.1	DM channel when setting up a circuit mode call through a gateway	79
8.4.4.2	DM channel when receiving a circuit mode call set-up from a gateway	80
8.4.4.3	DM channel in occupation during a circuit mode call	80
8.4.4.4	DM channel in reservation during a circuit mode call	80
8.4.4.5	DM channel in occupation during an SDS call	80
8.4.4.6	DM channel during pre-emption signalling	81
8.4.4.7	DM channel during registration phase	81
8.4.4.8	DM channel in occupation for an unsolicited registration	81
8.4.5	Transmission of layer 3 messages by DM-MAC	82
8.4.5.1	Transmission of C-plane messages by DM-MAC	82
8.4.5.1.1	Transmitting DM-SETUP	82

8.4.5.1.2	Transmitting DM-SETUP PRES	82
8.4.5.1.3	Transmitting DM-CONNECT	82
8.4.5.1.4	Transmitting DM-DISCONNECT	82
8.4.5.1.5	Transmitting DM-CONNECT ACK	82
8.4.5.1.6	Transmitting DM-RELEASE	82
8.4.5.1.7	Transmitting DM-OCCUPIED	83
8.4.5.1.8	Transmitting DM-TX CEASED	83
8.4.5.1.9	Transmitting DM-TX REQUEST	83
8.4.5.1.10	Transmitting response to DM-TX REQUEST	83
8.4.5.1.11	Transmitting DM-PREEMPT	83
8.4.5.1.12	Transmitting response to DM-PREEMPT	84
8.4.5.1.13	Transmitting DM-SDS UDATA and DM-SDS DATA	84
8.4.5.1.14	Transmitting response to DM-SDS DATA	84
8.4.5.1.15	Transmitting DM-INFO	84
8.4.5.1.16	Transmitting DM-GSETUP	84
8.4.5.1.17	Transmitting DM-GTX REQUEST	85
8.4.5.1.18	Transmitting DM-GPREEMPT	86
8.4.5.1.19	Transmitting DM-GREGISTER REQUEST	86
8.4.5.1.20	Transmitting DM-GCANCEL ACK	87
8.4.5.2	Transmission of U-plane messages by DM-MAC	87
8.4.6	Transmission of layer 2 messages generated by DM-MAC	87
8.4.6.1	Transmitting DM-RESERVED	87
8.4.6.2	Transmitting DM-SDS OCCUPIED	87
8.4.6.3	Transmitting DM-TIMING REQUEST	87
8.4.6.4	Transmitting DM-TIMING ACK	87
8.4.7	General DM-MAC procedures	88
8.4.7.1	DM-MAC repeat transmissions	88
8.4.7.2	DM-MAC frame countdown procedure	88
8.4.7.3	Use of timers	88
8.4.7.4	Linearization	88
8.4.7.5	Fragmentation	89
8.4.7.6	Fill bit indication	89
8.4.7.7	Selection of pseudo address	89
8.4.7.8	Slot flag indication	89
8.4.7.9	Requests bitmap	89
8.4.7.10	Dual watch operation	89
8.4.7.11	Air interface encryption	89
8.4.7.12	Channel A or B operation	89
8.4.7.13	Sending short data as a transaction within a circuit mode call	90
8.4.7.14	SDS and registration transaction time remaining	90
8.4.7.14.1	SDS time remaining	90
8.4.7.14.2	Registration transaction time remaining	90
8.4.7.15	Timing change procedure	90
8.4.7.16	Timing change at changeover or pre-emption	90
8.4.7.17	Modification of slot/frame numbering by gateway	91
8.4.7.18	Modification of channel timing by gateway	91
8.5	MAC procedures for transfer of signalling messages	91
8.5.1	Formation of MAC PDU	91
8.5.2	Addressing	92
8.5.2.1	Transmission of message	92
8.5.2.1.1	Addressing in synchronization burst carrying gateway-specific message	92
8.5.2.1.2	Addressing in synchronization burst carrying non-gateway-specific message	92
8.5.2.1.3	Lifetime of pseudo SSI	93
8.5.2.1.4	Additional elements in synchronization burst	94
8.5.2.1.5	Addressing in normal burst	94
8.5.2.2	Reception of message	94
8.5.2.3	Usage of MNI	95
8.5.3	Use of air interface encryption	95
8.5.4	Fragmentation and reconstruction	95
8.5.4.1	Fragmentation by a DM-MS	95
8.5.4.2	Reconstruction by a DM-MS	96
8.5.5	Fill bit addition and deletion	97

8.5.6	Transmission and reception of messages by layer 2 unacknowledged service	98
8.5.6.1	Transmission of message	99
8.5.6.2	Reception of message.....	99
8.5.7	Random access protocol during occupation and reservation periods.....	101
8.5.7.1	Introduction.....	101
8.5.7.2	Procedures for master DM-MS	102
8.5.7.2.1	Indicating frames available for requests	102
8.5.7.2.2	Monitoring frames available for requests	102
8.5.7.2.3	Response to pre-emption request.....	103
8.5.7.2.4	Response to timing change request.....	103
8.5.7.2.5	Response to DM-GRELEASE message	103
8.5.7.3	Procedures for requesting DM-MS	103
8.5.8	Procedures for sending messages during registration phase	105
8.5.8.1	Procedures for registering DM-MS during registration phase	105
8.5.8.1.1	Preparing for registration access.....	105
8.5.8.1.2	First transmission of solicited registration request	105
8.5.8.1.3	Valid access slots.....	105
8.5.8.1.4	Waiting for response.....	105
8.5.8.1.5	Subsequent transmission of request.....	106
8.5.8.1.6	Abandoning registration access attempt	106
8.5.8.2	Procedures for pre-empting DM-MS during registration phase	106
8.5.8.2.1	Preparing for random access.....	106
8.5.8.2.2	First transmission of pre-emption request	106
8.5.8.2.3	Valid slots for pre-emption.....	106
8.5.8.2.4	Waiting for response.....	106
8.5.8.2.5	Subsequent transmission of request.....	107
8.5.8.2.6	Abandoning random access attempt	107
8.6	MAC procedures in traffic mode.....	108
8.6.1	Introduction.....	108
8.6.2	Criteria for transmission and reception of traffic	108
8.6.3	Change of U-plane mode	108
8.6.3.1	Call set-up by DM-MS	108
8.6.3.2	Incoming call set-up	108
8.6.3.2.1	Incoming call set-up without presence check	108
8.6.3.2.2	Incoming call set-up with presence check	109
8.6.3.3	Late entry	109
8.6.3.4	End of traffic transmission	109
8.6.3.4.1	Master DM-MS	109
8.6.3.4.2	Slave DM-MS.....	109
8.6.4	Exchange of information at the DMD-SAP.....	109
8.6.5	Stealing from circuit mode capacity	109
9	Gateway layer 3 call control procedures	109
9.1	Introduction	109
9.2	Gateway call control states.....	110
9.2.1	Gateway TMO call control states	110
9.2.1.1	IDLE	110
9.2.1.2	MO-CALL-SETUP	110
9.2.1.3	MT-CALL-SETUP	110
9.2.1.4	CALL ACTIVE.....	110
9.2.1.5	CALL DISCONNECT	110
9.2.1.6	WAIT	110
9.2.2	Gateway DM call control states.....	111
9.2.2.1	IDLE	111
9.2.2.2	CALL SETUP NORMAL ORIGINATING.....	111
9.2.2.3	CALL SETUP PRES_CHECK ORIGINATING.....	111
9.2.2.4	CALL SETUP TERMINATING	111
9.2.2.5	PRE-EMPTION	111
9.2.2.6	CALL ACTIVE TX OCCUPATION.....	111
9.2.2.7	CALL ACTIVE TX RESERVATION.....	111
9.2.2.8	CALL ACTIVE RX OCCUPATION.....	111
9.2.2.9	WAIT RSP OCCUPATION	111

9.2.2.10	ACK'D SHORT DATA INITIATED.....	111
9.2.2.11	UNACK'D SHORT DATA INITIATED.....	111
9.3	Layer 3 circuit mode call control procedures	112
9.3.1	Incoming call set-up from TMO	112
9.3.1.1	Incoming individual call set-up from TMO	112
9.3.1.2	Incoming group call set-up from TMO	115
9.3.1.3	Sending of DM-OCCUPIED PDU by master gateway	116
9.3.2	Outgoing call set-up to TMO.....	116
9.3.2.1	Outgoing call to TMO set-up procedures.....	116
9.3.2.2	Colliding call set-up signalling over the TMO air interface (Um)	119
9.3.2.3	Unsuccessful call set-up to TMO	119
9.3.3	Call maintenance procedures	119
9.3.3.1	End of transmission.....	119
9.3.3.1.1	Reception of DM-TX CEASED PDU from current master DM-MS	119
9.3.3.1.2	Reception of D-TX CEASED PDU from TMO	120
9.3.3.1.3	Gateway initiated DM-TX CEASED	120
9.3.3.2	Reception of D-TX INTERRUPT from TMO	120
9.3.3.3	Incoming TMO transmission during DM channel reservation.....	121
9.3.3.4	Reception of a DM request to transmit during DM channel reservation.....	121
9.3.3.4.1	Response to valid DM-GTX REQUEST (or DM-GPREEMPT) PDU.....	121
9.3.3.4.2	Response to valid DM-TX REQUEST (or DM-PREEMPT) PDU	123
9.3.3.5	TMO permission to transmit withdrawn during a call	124
9.3.3.6	TMO permission to continue with withdrawn call.....	124
9.3.3.7	SwMI initiated call continuation	125
9.3.3.8	Call modification.....	125
9.3.3.8.1	DM-MS initiated call modification	125
9.3.3.8.2	SwMI initiated call modification	125
9.3.3.9	Call disconnection.....	126
9.3.3.9.1	Reception of DM-RELEASE from current master DM-MS (or call lost).....	126
9.3.3.9.2	Call disconnection by SwMI	126
9.3.3.9.3	Expiry of call length timer.....	127
9.3.3.10	TMO call restoration.....	127
9.3.3.11	Unsolicited D-TX GRANTED PDU.....	127
9.3.3.12	Extension and end of reservation period.....	128
9.3.4	Gateway pre-emption procedures	128
9.3.4.1	DM-MS pre-emption of a gateway operating as master.....	128
9.3.4.1.1	New call pre-emption during call set-up	129
9.3.4.1.2	New call pre-emption during DM channel occupation.....	129
9.3.4.1.3	New call pre-emption during DM channel reservation.....	130
9.3.4.1.4	DM-MS pre-emption during DM channel occupation to continue existing call.....	130
9.3.4.1.5	DM-MS pre-emption during DM channel occupation to send short data within ongoing call	131
9.3.4.2	Pre-emption procedures during gateway slave operation.....	132
9.3.4.2.1	Transmission interrupt from TMO	132
9.3.4.2.2	Pre-emption initiated by gateway during an ongoing call	133
9.3.4.2.3	New call pre-emption by gateway	134
9.3.4.2.4	Pre-emption by another DM-MS	135
9.3.4.3	Pre-emption procedure when gateway idle	135
9.4	Layer 3 short data service procedures	135
9.4.1	Incoming SDS message from TMO.....	135
9.4.1.1	Transmission of short data message from TMO using DM unacknowledged service	135
9.4.1.2	Transmission of short data message from TMO using DM acknowledged service	136
9.4.1.3	Pre-emption of DM unacknowledged or acknowledged SDS transaction	137
9.4.1.4	Transmission of short data message from TMO during DM channel occupation.....	137
9.4.1.5	Transmission of short data message from TMO during DM channel reservation.....	138
9.4.2	Outgoing DM SDS message to TMO	138
9.4.2.1	Reception of outgoing SDS message on DM channel.....	138
9.4.2.1.1	Reception of outgoing unacknowledged SDS message on DM channel	138
9.4.2.1.2	Reception of outgoing acknowledged SDS message on DM channel	138
9.4.2.2	Reception of DM short data sent within ongoing call	139
9.4.3	SDS-TL Service.....	140
9.5	Addressing methods on TMO air interface	140
9.5.1	Receiving group call from TMO.....	140

9.5.2	Receiving individual call from TMO.....	140
9.5.3	Call set-up to TMO.....	141
9.6	Information element mapping between TM and DM PDUs.....	141
9.6.1	TMO communication type - DMO call type flag mapping.....	141
9.6.2	TMO call priority - DMO priority mapping.....	141
9.6.3	TMO short data type identifier - DMO short data type identifier mapping.....	142
9.6.4	TMO TX demand priority - DMO priority level mapping.....	142
10	Gateway layer 3 mobility management procedures.....	142
10.1	Introduction.....	142
10.2	Gateway MM states.....	142
10.2.1	MM protocol states - TMO.....	142
10.2.2	MM protocol states - DM.....	142
10.2.2.1	REGISTRATIONS SOLICITED.....	142
10.2.2.2	REGISTRATIONS NOT PERMITTED.....	142
10.2.2.3	REGISTRATIONS PERMITTED.....	142
10.3	Gateway MM procedures.....	143
10.3.1	Gateway registration to SwMI.....	143
10.3.2	Gateway MM procedures on DM.....	143
10.3.3	Receiving DM registration requests.....	144
10.3.3.1	Solicited registration requests.....	144
10.3.3.2	Unsolicited registration requests.....	145
10.3.4	Registration cancellation.....	145
10.3.5	Procedures for U-MM STATUS and D-MM STATUS.....	145
10.3.5.1	Procedures for sending U-MM STATUS.....	145
10.3.5.2	Procedures for receiving D-MM STATUS.....	146
11	Gateway U-plane converter.....	146
11.1	Introduction.....	146
11.2	Start of call transaction.....	147
11.2.1	Call transaction from DMO to TMO.....	147
11.2.2	Call transaction from TMO to DMO.....	147
11.3	U-plane conversion during call transaction.....	147
11.3.1	U-plane conversion from DMO to TMO.....	147
11.3.2	U-plane conversion from TMO to DM.....	148
11.4	Stopping transmission/reception.....	149
11.4.1	Call transaction from DMO to TMO.....	149
11.4.2	Call transaction from TMO to DMO.....	149
12	Gateway DM layer 2 service description.....	149
12.1	Introduction.....	149
12.2	Gateway DM layer 2 architecture.....	150
12.2.1	Lower layer management in layer 2.....	150
12.3	Service descriptions.....	150
12.3.1	Services at the GMA-SAP.....	150
12.3.1.1	Services provided to layer 3.....	150
12.3.1.1.1	Protocol control function for delivery of received message.....	150
12.3.1.2	Service primitives at the GMA-SAP.....	151
12.3.1.2.1	GMA-REPORT primitive.....	151
12.3.1.2.2	GMA-UNITDATA primitive.....	151
12.3.2	Services at the GMC-SAP.....	151
12.3.2.1	Services provided to layer 3.....	151
12.3.2.2	Service primitives at the GMC-SAP.....	151
12.3.2.2.1	GMC-CONFIGURE primitive.....	151
12.3.2.2.2	GMC-REPORT primitive.....	152
12.3.3	Services at the GMD-SAP.....	152
12.3.3.1	Services provided to the U-plane converter.....	152
12.3.3.2	Service primitives at the GMD-SAP.....	152
12.3.3.2.1	GMD-REPORT primitive.....	152
12.3.3.2.2	GMD-UNITDATA primitive.....	152
12.4	Parameter listing.....	152
13	Gateway DM layer 2 protocol.....	153

ITh STANDARD PREVIEW

(standards.itech.ai)

SIST EN 300 396-5 V1.2.1:2006

[https://standards.itech.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-](https://standards.itech.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-a24824b0890c/sist-en-300-396-5-v1-2-1-2006)

[a24824b0890c/sist-en-300-396-5-v1-2-1-2006](https://standards.itech.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-a24824b0890c/sist-en-300-396-5-v1-2-1-2006)

13.1	Introduction	153
13.1.1	Functions of lower MAC	154
13.1.2	Functions of upper MAC	154
13.2	Interface between lower and upper MAC.....	155
13.3	Basic capabilities of the gateway physical layer	155
13.3.1	DM-GATE capabilities.....	155
13.3.2	Type 1A DM-REP/GATE capabilities	156
13.3.2.1	Type 1A DM-REP/GATE: DM RF carrier in same sub-band as TM downlink carrier.....	156
13.3.2.2	Type 1A DM-REP/GATE: DM RF carrier in same sub-band as TM uplink carrier.....	156
13.3.2.3	Type 1A DM-REP/GATE: DM RF carrier not in either TMO sub-band.....	157
13.3.3	Type 1B DM-REP/GATE capabilities.....	157
13.3.3.1	Type 1B DM-REP/GATE: frequency usage method 1	158
13.3.3.2	Type 1B DM-REP/GATE: frequency usage method 2	158
13.4	Usage of DM channel.....	159
13.4.1	Gateway operation.....	159
13.4.1.1	DM-GATE operation	159
13.4.1.2	DM-REP/GATE operation.....	160
13.4.1.2.1	Type 1A DM-REP/GATE: DM RF carrier in same sub-band as TM downlink carrier	160
13.4.1.2.2	Type 1A DM-REP/GATE: DM RF carrier in same sub-band as TM uplink carrier	161
13.4.1.2.3	Type 1A DM-REP/GATE (if DM RF carrier not in TMO sub-band) or type 1B DM-REP/GATE with frequency usage method 1	161
13.4.1.2.4	Type 1B DM-REP/GATE with frequency usage method 2.....	162
13.4.2	Gateway DM-MAC states	163
13.4.2.1	Gateway DM-MAC state definitions	163
13.4.2.2	Gateway channel surveillance procedures	164
13.4.2.2.1	Channel surveillance when idle on a channel in unknown or free state (i.e. in state 0 or 1)	164
13.4.2.2.2	Channel surveillance when idle on a busy channel (i.e. in state 2, 3 or 4)	165
13.4.2.2.3	Channel surveillance when idle at DM-MS call set-up	165
13.4.2.2.4	Channel surveillance before call set-up by gateway (circuit mode call or short data).....	166
13.4.2.2.5	Channel surveillance before registration phase	167
13.4.2.2.6	Channel surveillance before registration cancellation	168
13.4.2.3	Master gateway channel maintenance during a call	168
13.4.2.4	Slave gateway channel maintenance during a call	168
13.4.3	Criteria for changing gateway state	169
13.4.3.1	Criteria for changing DM-MAC state for master gateway	169
13.4.3.2	Criteria for changing DM-MAC state for slave gateway	169
13.4.3.3	Criteria for changing DM-MAC state for idle gateway	170
13.4.4	Gateway channel monitoring procedures.....	172
13.4.4.1	DM channel during reception of fragmented DM-GSETUP message	172
13.4.4.2	DM channel during call set-up with presence check.....	172
13.4.4.3	DM channel in reservation during circuit mode call set-up	172
13.4.4.4	DM channel following circuit mode connection by gateway.....	173
13.4.4.5	Gateway as master in circuit mode occupation	173
13.4.4.6	Gateway as slave in circuit mode occupation	173
13.4.4.7	DM channel in reservation during a circuit mode call	173
13.4.4.8	Gateway as master in SDS occupation.....	173
13.4.4.9	Gateway as slave in SDS occupation	174
13.4.4.10	DM channel following pre-emption or changeover acceptance by gateway	174
13.4.4.11	DM channel following pre-emption acceptance by a master DM-MS	175
13.4.4.12	DM channel following pre-emption request generated by gateway	175
13.4.4.13	Gateway as master in registration phase	175
13.4.4.14	Gateway as master during registration cancellation.....	175
13.4.5	Transmission of layer 3 messages by layer 2.....	176
13.4.5.1	Transmission of C-plane messages by layer 2	176
13.4.5.1.1	Transmitting DM-SETUP and DM-SETUP PRES	176
13.4.5.1.2	Transmitting DM-CONNECT ACK.....	177
13.4.5.1.3	Transmitting DM-RELEASE	177
13.4.5.1.4	Transmitting DM-OCCUPIED.....	177
13.4.5.1.5	Transmitting DM-TX CEASED.....	178
13.4.5.1.6	Transmitting response to DM-TX REQUEST.....	179
13.4.5.1.7	Transmitting DM-PREEMPT	179
13.4.5.1.8	Transmitting response to DM-PREEMPT	180

13.4.5.1.9	Transmitting DM-SDS UDATA and DM-SDS DATA.....	180
13.4.5.1.10	Transmitting response to DM-SDS DATA	181
13.4.5.1.11	Transmitting DM-INFO	182
13.4.5.1.12	Transmitting response to DM-GSETUP.....	182
13.4.5.1.13	Transmitting response to DM-GTX REQUEST.....	183
13.4.5.1.14	Transmitting response to DM-GPREEMPT	183
13.4.5.1.15	Transmitting DM-GRELEASE	184
13.4.5.1.16	Transmitting response to registration request.....	184
13.4.5.1.17	Transmitting registration cancellation	184
13.4.5.2	Transmission of U-plane messages by layer 2	185
13.4.6	Transmission of layer 2 messages.....	185
13.4.6.1	Layer 2 messages sent in DMAC-SYNC PDU	185
13.4.6.1.1	Transmitting DM-RESERVED	185
13.4.6.1.2	Transmitting DM-SDS OCCUPIED.....	186
13.4.6.1.3	Transmitting DM-TIMING ACK	186
13.4.6.2	Gateway presence signal	186
13.4.6.2.1	Channel free	186
13.4.6.2.2	Channel in occupation	187
13.4.6.2.3	Channel in reservation	188
13.4.6.2.4	Channel in registration phase	188
13.4.7	General layer 2 procedures	188
13.4.7.1	Repeat transmissions.....	188
13.4.7.2	Frame countdown procedure.....	188
13.4.7.3	Use of timers	189
13.4.7.4	Linearization	189
13.4.7.5	Fragmentation	190
13.4.7.6	Fill bit indication	190
13.4.7.7	Use of pseudo address.....	190
13.4.7.8	Slot flag indication	190
13.4.7.9	Requests bitmap	190
13.4.7.10	Receiving the TM channel	190
13.4.7.11	Air interface encryption	190
13.4.7.12	Channel A or B operation	190
13.4.7.13	Sending short data as a transaction within a circuit mode call.....	191
13.4.7.14	SDS and registration transaction time remaining.....	191
13.4.7.14.1	SDS time remaining	191
13.4.7.14.2	Registration transaction time remaining.....	191
13.4.7.15	Modification of slot/frame numbering by gateway.....	191
13.4.7.16	Modification of channel timing by gateway.....	191
13.4.8	DM-REP/GATE procedures for DM re-transmission of DM signalling messages	192
13.4.8.1	DM re-transmission of master DM-MS signalling messages received in a DSB.....	193
13.4.8.1.1	General procedures.....	193
13.4.8.1.2	Re-transmission of DM-SETUP message	193
13.4.8.1.3	Re-transmission of DM-SDS DATA or DM-SDS UDATA message	194
13.4.8.1.4	Re-transmission of unsolicited DM-GREGISTER REQUEST	195
13.4.8.1.5	Re-transmission of other messages in a DSB when not using multi-slot regeneration.....	195
13.4.8.1.6	Re-transmission of other messages in a DSB during traffic transmission with multi-slot regeneration	195
13.4.8.2	DM re-transmission of master DM-MS signalling messages received in a DNB	195
13.4.8.2.1	Call transaction without multi-slot regeneration	195
13.4.8.2.2	Call transaction with multi-slot regeneration.....	196
13.4.8.3	Regeneration of missing repetitions on the slave link.....	196
13.4.8.4	DM re-transmission of messages received from a slave DM-MS.....	197
13.5	Layer 2 procedures for transfer of signalling messages	197
13.5.1	Formation of MAC PDU	197
13.5.2	Addressing.....	198
13.5.2.1	Transmission of message	198
13.5.2.1.1	Addressing in synchronization burst carrying gateway-specific message.....	198
13.5.2.1.2	Addressing in synchronization burst carrying non-gateway-specific message.....	198
13.5.2.1.3	Gateway pseudo SSI.....	199
13.5.2.1.4	Additional elements in synchronization burst	199
13.5.2.1.5	Addressing in normal burst.....	199

13.5.2.2	Reception of message.....	200
13.5.2.3	Usage of MNI.....	200
13.5.3	Use of air interface encryption.....	200
13.5.4	Fragmentation and reconstruction.....	201
13.5.4.1	Fragmentation by a gateway	201
13.5.4.2	Reconstruction by a gateway.....	201
13.5.4.2.1	Reconstruction by a DM-GATE.....	201
13.5.4.2.2	Reconstruction of master link message by DM-REP/GATE.....	201
13.5.4.2.3	Reconstruction of slave link message by DM-REP/GATE	202
13.5.5	Fill bit addition and deletion	202
13.5.6	Transmission and reception of messages by layer 2 unacknowledged service	202
13.5.6.1	Transmission of message	203
13.5.6.2	Reception of message.....	203
13.5.7	Random access protocol during occupation and reservation periods.....	205
13.5.7.1	Introduction.....	205
13.5.7.2	Procedures for master gateway	205
13.5.7.2.1	Indicating frames available for requests	205
13.5.7.2.2	Monitoring frames available for requests	206
13.5.7.2.3	Response to pre-emption or changeover request	206
13.5.7.3	Procedures for requesting slave gateway	208
13.5.7.3.1	Transmission of message by requesting slave gateway	208
13.5.7.3.2	Looking for response	208
13.5.7.3.3	Abandoning transmission attempt	209
13.5.8	Procedures in registration phase	209
13.5.8.1	Start of registration phase.....	209
13.5.8.2	Receiving registration requests	209
13.5.8.3	Sending response.....	209
13.5.8.4	Maintenance of registration phase.....	210
13.5.8.5	Termination of registration phase	210
13.6	Gateway procedures in traffic mode.....	210
13.6.1	Introduction.....	210
13.6.2	Criteria for transmission and reception of traffic.....	211
13.6.3	Change of U-plane mode.....	211
13.6.3.1	Call transaction from DMO to TMO.....	211
13.6.3.2	Call transaction from TMO to DMO.....	212
13.6.3.2.1	Call set-up without presence check	212
13.6.3.2.2	Call set-up with presence check	212
13.6.3.3	End of traffic transmission.....	212
13.6.3.3.1	Call transaction from DMO to TMO.....	212
13.6.3.3.2	Call transaction from TMO to DMO.....	212
13.6.4	Exchange of information at the GMD-SAP.....	213
13.6.4.1	Interface at gateway transmitting traffic on DMO side.....	214
13.6.4.2	Interface at gateway receiving traffic on DMO side	214
13.6.5	Stealing from circuit mode capacity	215
13.6.5.1	Transmission on STCH	215
13.6.5.2	Criteria for C-plane stealing.....	215
13.6.5.3	Reception on STCH	216
13.6.6	DM-REP/GATE procedures for DM re-transmission of DM U-plane traffic	216
13.6.6.1	Call transaction without multi-slot regeneration	216
13.6.6.2	Call transaction with multi-slot regeneration	216
14	DM PDU descriptions	217
14.1	Layer 2 PDUs sent in DSB.....	217
14.1.1	DMAC-SYNC PDU	217
14.1.2	DPRES-SYNC PDU	218
14.2	Layer 2 PDUs sent in DNB	220
14.3	Layer 2 information element coding	220
14.3.1	Addressing for URT = 0010 ₂	220
14.3.2	Addressing for URT = 0011 ₂	220
14.3.3	Addressing for URT = 0100 ₂ or 0101 ₂	220
14.3.4	Addressing for URT = 0110 ₂	221
14.3.5	Channel state.....	221

14.3.6	Channel usage	221
14.3.7	DM-REP function flag.....	221
14.3.8	Not used	222
14.3.9	Maximum DM-MS power class.....	222
14.3.10	M-DMO flag	222
14.3.11	MNI of SwMI	223
14.3.12	Number of validity time units	223
14.3.13	Registration access parameter.....	223
14.3.14	Registration label	223
14.3.14A	Registration phase terminated flag.....	223
14.3.15	Registration phase time remaining.....	224
14.3.16	Registrations forwarded flag.....	224
14.3.17	Registrations permitted	224
14.3.18	Repeater operating modes.....	225
14.3.19	Spacing of uplink	225
14.3.19A	System wide services not available.....	226
14.3.20	SwMI availability flag	226
14.3.21	Timing for DM-REP function.....	226
14.3.22	Two-frequency repeater flag	227
14.3.23	Usage restriction type (URT).....	227
14.3.24	Validity time unit	227
14.3.25	Value of DT264	227
14.3.26	Values of DN232 and DN233.....	228
14.4	Messages generated by layer 2	228
14.5	Layer 3 PDUs	228
14.5.1	DM-GSETUP	229
14.5.2	DM-GCONNECT	230
14.5.3	DM-GACK	230
14.5.4	DM-GRELEASE	231
14.5.5	DM-GTX REQUEST	231
14.5.6	DM-GTX ACCEPT	232
14.5.7	DM-GPREEMPT	232
14.5.8	DM-GPRE ACCEPT	233
14.5.9	DM-GREJECT	233
14.5.10	DM-GREGISTER REQUEST	234
14.5.11	DM-GREGISTER ACCEPT	234
14.5.12	DM-GREGISTER REJECT	235
14.5.13	DM-GREGISTER CANCEL.....	235
14.5.14	DM-GCANCEL ACK	236
14.6	Message dependent elements coding	236
14.6.1	Gateway message subtype	237
14.6.2	Registration transaction time remaining	238
14.6.3	Reservation announced	238
14.6.4	Type of DM-GTX REQUEST	238
14.6.5	Type of registration request	238
14.7	DM-SDU elements coding	238
14.7.1	Area selection	240
14.7.2	Called party address type flag.....	240
14.7.3	Called party MNI.....	241
14.7.4	Called party SSI	241
14.7.5	Calling party TSI flag	241
14.7.6	External subscriber number	241
14.7.7	Gateway reject cause	241
14.7.8	Gateway release cause	242
14.7.9	Registration label	242
14.7.10	Registration reject cause	242
14.7.11	Request label.....	242
14.7.12	Serviced GSSI.....	242
14.7.13	Serviced GSSI flag.....	243
14.7.14	Type of DM-GACK.....	243
14.7.15	Value of DM-MS waiting timer.....	243

ITeH STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 396-5 V1.2.1:2006
standards.iteh.ai/catalog/standards/sist/0c6a21d6-b9cd-4a5e-bc53-
a2d824b089ef/sist-en-300-396-5-v1-2-1-2006