

INTERNATIONAL STANDARD



**Multicore and symmetrical pair/quad cables for digital communications –
Part 8: Symmetrical pair/quad cables with transmission characteristics up to
1 200 MHz – Work area wiring – Sectional specification**

IEC 61156-8:2009

<https://standards.iteh.ai/en/standards/iec/4514f07e-2504-46f9-89f1-9781406693aa/iec-61156-8-2009>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2013 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

IEC 61156-8:2009

<https://standards.iteh.ai/catalog/standards/iec/4514f07e-2504-46f9-89f1-9781406693aa/iec-61156-8-2009>

INTERNATIONAL STANDARD



**Multicore and symmetrical pair/quad cables for digital communications –
Part 8: Symmetrical pair/quad cables with transmission characteristics up to
1 200 MHz – Work area wiring – Sectional specification**

IEC 61156-8:2009

<https://standards.iteh.ai/en/standards/iec/4514f07e-2504-46f9-89f1-9781406693aa/iec-61156-8-2009>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.20

ISBN 978-2-8322-0853-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions	6
4 Installation considerations.....	7
4.1 Installation conditions	7
4.2 Climatic conditions.....	7
5 Materials and cable construction	7
5.1 General remarks.....	7
5.2 Cable construction.....	7
5.2.1 Conductor.....	7
5.2.2 Insulation.....	7
5.2.3 Cable element	7
5.2.4 Cable make-up	8
5.2.5 Screening of cable core	8
5.2.6 Sheath.....	8
5.2.7 Identification	8
5.2.8 Finished cable	8
6 Characteristics and requirements.....	8
6.1 General remarks.....	8
6.2 Electrical characteristics.....	9
6.2.1 Conductor resistance.....	9
6.2.2 Resistance unbalance.....	9
6.2.3 Dielectric strength.....	9
6.2.4 Insulation resistance.....	9
6.2.5 Mutual capacitance	9
6.2.6 Capacitance unbalance.....	9
6.2.7 Transfer impedance.....	9
6.2.8 Coupling attenuation	10
6.2.9 Current-carrying capacity	10
6.2.10 Shield resistance	10
6.3 Transmission characteristics.....	10
6.3.1 Velocity of propagation (phase velocity)	10
6.3.2 Phase delay and differential delay (delay skew).....	10
6.3.3 Attenuation	11
6.3.4 Unbalance attenuation	11
6.3.5 Near-end crosstalk (<i>NEXT</i>).....	12
6.3.6 Far-end crosstalk (<i>FEXT</i>)	12
6.3.7 Alien (exogenous) near-end crosstalk	12
6.3.8 Alien (exogenous) far-end crosstalk	12
6.3.9 Alien (exogenous) crosstalk of bundled cables	12
6.3.10 Impedance.....	12
6.3.11 Return loss (<i>RL</i>).....	12
6.4 Mechanical and dimensional characteristics and requirements	13
6.4.1 Dimensional requirements.....	13
6.4.2 Elongation at break of the conductors	13

6.4.3	Tensile strength of the insulation.....	13
6.4.4	Elongation at break of the insulation.....	13
6.4.5	Adhesion of the insulation to the conductor	13
6.4.6	Elongation at break of the sheath.....	13
6.4.7	Tensile strength of the sheath	13
6.4.8	Crush test of the cable.....	13
6.4.9	Impact test of the cable.....	13
6.4.10	Bending under tension	13
6.4.11	Repeated bending of the cable.....	14
6.4.12	Tensile performance of the cable	14
6.4.13	Shock test of the cable.....	14
6.4.14	Bump test of the cable	14
6.4.15	Vibration test of a cable	14
6.5	Environmental characteristics	14
6.5.1	Shrinkage of insulation.....	14
6.5.2	Wrapping test of insulation after thermal ageing	14
6.5.3	Bending test of insulation at low temperature	14
6.5.4	Elongation at break of the sheath after ageing.....	14
6.5.5	Tensile strength of the sheath after ageing.....	14
6.5.6	Sheath pressure test at high temperature	14
6.5.7	Cold bend test of the cable	14
6.5.8	Heat shock test.....	15
6.5.9	Damp heat steady state	15
6.5.10	Solar radiation	15
6.5.11	Solvents and contaminating fluids.....	15
6.5.12	Salt mist and sulphur dioxide	15
6.5.13	Water immersion	15
6.5.14	Hygroscopicity	15
6.5.15	Wicking	15
6.5.16	Flame propagation characteristics of a single cable.....	15
6.5.17	Flame propagation characteristics of bunched cables.....	15
6.5.18	Halogen gas evolution.....	15
6.5.19	Smoke generation.....	15
6.5.20	Toxic gas emission	15
6.5.21	Integrated fire test	15
7	Introduction to the blank detail specification	16
	Bibliography.....	17
	Table 1 – Transfer impedance.....	10
	Table 2 – Coupling attenuation.....	10
	Table 3 – Attenuation, constant values	11
	Table 4 – Return loss (<i>RL</i>).....	12

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES
FOR DIGITAL COMMUNICATIONS –****Part 8: Symmetrical pair/quad cables
with transmission characteristics up to 1 200 MHz –
Work area wiring – Sectional specification**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 61156-8 edition 1.1 contains the first edition (2009) [documents 46C/887/FDIS and 46C/894/RVD], its corrigendum (July 2009) and its amendment 1 (2013) [documents 46C/957/CDV and 46C/966/RVC].

A vertical line in the margin shows where the base publication has been modified by amendment 1. Additions and deletions are displayed in red, with deletions being struck through.

International Standard IEC 61156-8 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61156 series, under the general title: *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

(<https://standards.iteh.ai>)
Document Preview

IEC 61156-8:2009

<https://standards.iteh.ai/standards/iec/4514f07e-2504-46f9-89f1-9781406693aa/iec-61156-8-2009>

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 8: Symmetrical pair/quad cables with transmission characteristics up to 1 200 MHz – Work area wiring – Sectional specification

1 Scope

This sectional specification relates to IEC 61156-1 and IEC 61156-7. The cables described herein are specified up to 1 200 MHz and are specifically designed to build patch, equipment, and work area cables as defined in ISO/IEC 11801 and ISO/IEC 15018.

It covers a cable having four individually screened (STP) pairs. The cable may be provided with a common screen over the cable core. The transmission characteristics are specified for a frequency range 4 MHz to 1 200 MHz and at 20 °C.

These cables can be used for various communication channels which use as many as four pairs simultaneously. In this sense, this sectional specification provides the cable characteristics required by system developers to evaluate new systems.

The cables covered by this sectional specification are intended to operate with voltages and currents normally encountered in communication systems. These cables are not intended to be used in conjunction with low impedance sources, for example the electric power supplies of public utility mains.

2 Normative references

IEC 61156-8:2009

<https://standards.iteh.ai/en/standards/iec/511f07e-2504-46f9-89f1-9781406693aa/iec-61156-8-2009>

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 61156-1:2007, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC 61156-7, *Multicore and symmetrical pair/quad cables for digital communications – Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz – Sectional specification for digital and analog communication cables*

3 Terms and definitions

For the purposes of this document, the terms and definitions defined in IEC 61156-1 apply.

4 Installation considerations

4.1 Installation conditions

Installation considerations are defined in Clause 4 of IEC 61156-1.

4.2 Climatic conditions

Under static conditions, the cables shall operate in the temperature range from $-20\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$. The temperature dependence of the cables is specified, and should be taken into account for the design of an actual cabling system.

5 Materials and cable construction

5.1 General remarks

The choice of materials and cable construction shall be suitable for the intended application and installation of the cable. Particular care shall be taken to meet any special requirements for the fire performance (such as burning properties, smoke generation, evolution of halogen gas, etc.).

5.2 Cable construction

The cable construction shall be in accordance with the details and dimensions given in the relevant detail specification.

5.2.1 Conductor

The conductor shall be solid or stranded annealed copper conductor, in accordance with IEC 61156-1 and shall have a nominal diameter between 0,4 mm to 0,65 mm. The stranded conductor should have preferably seven strands. Higher conductor diameters may be used if compatible with the connecting hardware.

5.2.2 Insulation

The conductor shall be insulated with a suitable thermoplastic material. Examples of suitable materials are

- polyolefin;
- fluoropolymer;
- low-smoke zero-halogen thermoplastic material.

The insulation may be solid or cellular with or without a solid dielectric skin. The insulation shall be continuous and shall have a thickness such that the completed cable meets the specified requirements.

The insulation colour code is not specified but shall be indicated in the relevant detail specification. The colours shall be readily identifiable and shall correspond reasonably with the standard colours shown in IEC 60304.

NOTE It is acceptable to mark or stripe the "a" wire with the colour of the "b" wire to facilitate pair identification.

5.2.3 Cable element

The cable element shall be screened pair or quad adequately twisted.

The screen of the cable element shall be in accordance with 5.2.3.1 of IEC 61156-1.

5.2.4 Cable make-up

A spacer may be used to separate the cable elements. The cable elements, including spacers, shall be assembled to form the cable core.

The core of the cable may be wrapped with a protective layer of non-hygroscopic and not-wicking material.

5.2.5 Screening of cable core

When required by the relevant detail specification, a screen for the cable core shall be provided.

The screen shall be in accordance with 5.2.5 of IEC 61156-1.

5.2.6 Sheath

The sheath material shall consist of a suitable thermoplastic material.

Examples of suitable materials are

- polyolefin;
- PVC;
- fluoropolymer;
- low-smoke zero-halogen thermoplastic material.

The sheath shall be continuous, having a thickness as uniform as possible. A non-metallic ripcord may be provided. When provided, the ripcord shall be non-hygroscopic and not-wicking.

The colour of the sheath is not specified, but it shall be stated in the relevant detail specification.

5.2.7 Identification

Each length of cable shall be identified as to the manufacturer, and when required, the year of manufacture, using one of the following methods:

- a) appropriately coloured threads or tapes;
- b) with a printed tape;
- c) printing on the cable core wrapping;
- d) marking on the sheath.

Additional markings, such as length marking, etc., are permitted. If used, such markings shall refer to this specification.

5.2.8 Finished cable

The finished cable shall be adequately protected for storage and shipment.

6 Characteristics and requirements

6.1 General remarks

This clause lists the characteristics and minimum requirements of a cable complying with this sectional specification. Test methods shall be in accordance with Clause 6 of IEC 61156-1.

All the tests shall be carried out on a cable length of 100 m, unless otherwise specified.