# SLOVENSKI STANDARD

## SIST EN 60966-2-6:2004

april 2004

Radio frequency and coaxial cable assemblies - Part 2-6: Detail specification for cable assemblies for radio and TV receivers; Frequency range 0 to 3.000 MHz, IEC 60169-24 connectors (IEC 60966-2-6:2003)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 60966-2-6:2004</u> https://standards.iteh.ai/catalog/standards/sist/0d9a9f79-3ff7-42c4-b6e3-b2ad13aee696/sist-en-60966-2-6-2004

ICS 33.120.10

Referenčna številka SIST EN 60966-2-6:2004(en)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 60966-2-6:2004</u> https://standards.iteh.ai/catalog/standards/sist/0d9a9f79-3ff7-42c4-b6e3-b2ad13aee696/sist-en-60966-2-6-2004

### **EUROPEAN STANDARD**

## EN 60966-2-6

# NORME EUROPÉENNE

## **EUROPÄISCHE NORM**

May 2003

ICS 33.120.10

Supersedes EN 60966-2-6:1999

#### **English version**

## Radio frequency and coaxial cable assemblies Part 2-6: Detail specification for cable assemblies for radio and TV receivers -Frequency range 0 to 3 000 MHz, IEC 61169-24 connectors (IEC 60966-2-6:2003)

Ensemble de cordons coaxiaux et de cordons pour fréquences radioélectriques Partie 2-6: Spécification particulière pour cordons de connexion de récepteurs TV ou radio -Bande de fréquences de 0 à 3 000 MHz, connecteurs CEI 61169-24 (standards.iteHEG)60169-24 Steckverbinder (CEI 60966-2-6:2003)

Konfektionierte Koaxial- und Hochfrequenzkabel Teil 2-6: Bauartspezifikation für konfektionierte Kabel für Ton- und Fernsehrundfunkempfänger -Frequenzbereich 0 bis 3 000 MHz, (IEC 60966-2-6:2003)

SIST EN 60966-2-6:2004 https://standards.iteh.ai/catalog/standards/sist/0d9a9f79-3ff7-42c4-b6e3b2ad13aee696/sist-en-60966-2-6-2004

This European Standard was approved by CENELEC on 2003-05-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and United Kingdom.

# **CENELEC**

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

#### Foreword

The text of document 46A/510/FDIS, future edition 2 of IEC 60966-2-6, prepared by SC 46A, Coaxial cables, of IEC TC 46, Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60966-2-6 on 2003-05-01.

This European Standard supersedes EN 60966-2-6:1999.

The following dates were fixed:

 latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement

(dop) 2004-02-01

 latest date by which the national standards conflicting with the EN have to be withdrawn

(dow) 2006-05-01

#### **Endorsement notice**

The text of the International Standard IEC 60966-2-6:2003 was approved by CENELEC as a European Standard without any modification.

In the official version, for the Introduction, the following notes have to be added for the standards indicated:

\_\_\_\_\_

# INTERNATIONAL **STANDARD**

# **IEC** 60966-2-6

Second edition 2003-03

### Radio frequency and coaxial cable assemblies -

#### Part 2-6:

Detail specification for cable assemblies for radio and TV receivers - Frequency range 10 to 3 000 MHz, IEC 61169-24 connectors

## (standards.iteh.ai)

Ensemble de cordons coaxiaux et de cordons pour fréquences radioélectriques — https://standards.iteh.ai/catalog/standards/sist/0d9a9f79-3ff7-42c4-b6e3-

Partie 2:613aee696/sist-en-60966-2-6-2004

Spécification particulière pour cordons de connexion de récepteurs TV ou radio - Bande de fréquences de 0 à 3 000 MHz. connecteurs CEI 60169-24

© IEC 2003 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland 



PRICE CODE

F

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

#### RADIO FREQUENCY AND COAXIAL CABLE ASSEMBLIES -

# Part 2- 6: Detail specification for cable assemblies for radio and TV receivers - Frequency range 0 to 3 000 MHz, IEC 61169-24 connectors

#### **FOREWORD**

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards 04
- 6) Attention is drawn to the possibility that some of the elements of this international Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying anylor all such patent rights.

International Standard IEC 60966-2-6 has been prepared by subcommittee 46A: Coaxial cables, of IEC technical committee 46: Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories.

This second edition cancels and replaces the first edition published in 1998, of which it constitutes a technical revision.

The text of this standard is based on the following documents:

FDIS Report on voting	
46A/510/FDIS	46A/543/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until 2006. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

#### INTRODUCTION

This detail specification applies to flexible coaxial cables described in IEC 60096-2. It relates to cable assemblies for radio and TV receivers, and in particular to the cable subfamily F.

This detail specification should be used together with the following IEC publications:

IEC 60966-1:1999, Radio frequency and coaxial cable assemblies – Part 1: Generic specification – General requirements and test methods

IEC 60966-2-1:1991, Radio frequency and coaxial cable assemblies – Part 2-1: Sectional specification for flexible coaxial cable assemblies

IEC 60966-2-2:1992, Radio frequency and coaxial cable assemblies – Part 2-2: Blank detail specification for flexible coaxial cable assemblies

IEC 61169-24:2001, Radio frequency connectors – Part 24: Sectional specification – Radio frequency coaxial connectors with screw coupling, typically for use in 75 ohm cable distribution systems (type F)

IEC 60410:1973, Sampling plans and procedures for inspection by attributes

IEC 61022:1989, Interconnection of radio and TV receivers to feeder system outlets

IEC 61196-1:1995, Radio-frequency cables – Part 1: Generic specification – General, definitions, requirements and test methods ARD PREVIEW

(standards.iteh.ai)

<u>SIST EN 60966-2-6:2004</u> https://standards.iteh.ai/catalog/standards/sist/0d9a9f79-3ff7-42c4-b6e3-b2ad13aee696/sist-en-60966-2-6-2004

[1]	Prepared by	150	[2] Document No. 60966-2-6				
	IEC SC 46A	ILEC	Issue: Second issue				
		<b></b>	Date: 21/03/03				
[3]	Available from:	on: IEC 60966-1					
	IEC	Sectional specificat	tion: IEC 60966-2-1				
	3 rue de Varembé Genève Suisse	Blank detail specification: IEC 60966-2-2					
[5]	[5] Additional references:						
Detail specification for coaxial cable assemblies for radio and TV receivers							
	L IEC 727/03						
[6]	APPR						
[7]	Characteristic impedance: 75	Ω I A [8] A Frequ	uency range: 0/to 3 000 MHz				
(standards.iteh.ai)							
[9]	[9] Weight: 40 g/m + 50 g (typically) [10] Minimum inside radius:						
SIST EN 6096for2statio(bending 25 mm							
https://standards.iteh.ai/catalog/standards/sig/namre/bending-4754mme3-							
[11]	Climatic category: 40/70/21	1	icable test group: Ba, Eb, Eh, Ee, Mn				
[13]		a 150 04400	04 (5)				
Conn	ector type:	IEC 61169-	· ·				
		Straight					
Cable	Cable type: IEC 61196-6 (under development)						
		75 yy					
		or equiva	alent				
	Marking: Optional						
Taper sleeves: On both ends (colour optional)							
[14]	Variants		[15]				
				1 of 3 pages			

[16]	[17]	[18]	[19]				
Inspection values, ratings or characteristics	Clause	Value	Remarks				
Electrical							
Reflection properties	8.1	> 20 dB > 15 dB > 12 dB > 10 dB	5 MHz to 400 MHz 400 MHz to 862 MHz 862 MHz to 1 GHz 1 GHz to 3 GHz				
Operational attenuation (Insertion loss)	8.3	< 0,08 + 0,4 dB/m	up to 3 GHz				
Screening effectiveness:							
Transfer impedance							
Class A	12.1, 12.2 of IEC 61196-1	(5 mΩ/m)	5 MHz				
Class B	further tests UC (under consideration)	UC					
Screening attenuation							
Class A	8.9 (further tests UC)	> 85 dB > 65 dB	30 MHz to 1 GHz 1 GHz to 3 GHz				
Class B		> 75 dB > 55 dB	30 MHz to 1 GHz 1 GHz to 3 GHz				
Voltage proof	8.10	1,0 kV	50 Hz peak value				
Insulation resistance iTeh	STANDA	RD10PMQEV	Test voltage 500 V				
Inner and outer conductor continuity	(standar	ds.iteh.ai)	Low voltage DC				
Mechanical CICTURY (2004)							
Tensile https://standa		lards/sist/00/9a9f79-3ff, en-60966-2-6-2004	7-42c4-b6e3 Interface OK Duration 1 min Test 8.12				
Flexure	9.2	500 cycles	Force 5 N 20/min Test 8.9				
Flexing endurance	9.3	20 cycles	Test 8.12 and 8.9				
Cable assembly crushing	9.4	700 N	Test 8.3				

Under qualification approval, the qualification shall be conducted in accordance with 13.3 of IEC 60966-2-1 taking into account the specified variants. Only the tests whose results might depend on the variants shall be repeated.

Under capability approval, the qualification shall be conducted on the relating CQCs as defined in 13.4 of IEC 60966-2-1 and described in the capability manual (CM). Unless otherwise specified in the CM, only lot by lot tests from groups Ba and Eb shall be conducted on delivered products, all other tests shall be performed on CQCs as defined in 13.4 of IEC 60966-2-1 and described in the CM.