

INTERNATIONAL STANDARD



Wind turbines –

Part 11: Acoustic noise measurement techniques

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 61400-11:2012](https://standards.iteh.ai/catalog/standards/iec/ac2bd353-8397-445d-84b1-5689fe298261/iec-61400-11-2012)

<https://standards.iteh.ai/catalog/standards/iec/ac2bd353-8397-445d-84b1-5689fe298261/iec-61400-11-2012>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2012 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.
If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

[IEC 61400-11:2012](https://standards.iteh.ai/catalog/standards/iec/ac2bd353-8397-445d-84b1-5689fe298261/iec-61400-11-2012)

<https://standards.iteh.ai/catalog/standards/iec/ac2bd353-8397-445d-84b1-5689fe298261/iec-61400-11-2012>



IEC 61400-11

Edition 3.0 2012-11

INTERNATIONAL STANDARD



Wind turbines –
Part 11: Acoustic noise measurement techniques

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 61400-11:2012](https://standards.iteh.ai/catalog/standards/iec/ac2bd353-8397-445d-84b1-5689fe298261/iec-61400-11-2012)

<https://standards.iteh.ai/catalog/standards/iec/ac2bd353-8397-445d-84b1-5689fe298261/iec-61400-11-2012>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XA**

ICS 27.180

ISBN 978-2-83220-463-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms and definitions	9
4 Symbols and units	12
5 Outline of method	13
6 Instrumentation	14
6.1 Acoustic instruments	14
6.1.1 General	14
6.1.2 Equipment for the determination of the equivalent continuous A-weighted sound pressure level.....	14
6.1.3 Equipment for the determination of A-weighted 1/3-octave band spectra	14
6.1.4 Equipment for the determination of narrow band spectra	14
6.1.5 Microphone with measurement board and windscreen	14
6.1.6 Acoustical calibrator	16
6.1.7 Data recording/playback systems	16
6.2 Non-acoustic Instruments	16
6.2.1 General	16
6.2.2 Anemometers	16
6.2.3 Electric power transducer	17
6.2.4 Other instrumentation	17
6.3 Traceable calibration	17
7 Acoustic measurements and measurement procedures	17
7.1 Acoustic measurement positions	17
7.2 Acoustic measurements	20
7.2.1 General	20
7.2.2 Acoustic measurement requirements	20
7.2.3 A-weighted sound pressure level	21
7.2.4 A-weighted 1/3-octave band measurements.....	21
7.2.5 A-weighted narrow band measurements	21
7.2.6 Optional acoustic measurements at positions 2, 3 and 4.....	21
7.2.7 Other optional measurements	21
8 Non-acoustic measurements	21
8.1 General	21
8.2 Wind speed measurements	22
8.2.1 Determination of the wind speed during wind turbine operation.....	22
8.2.2 Wind speed measurements during background noise measurements.....	23
8.3 Downwind direction	24
8.4 Other atmospheric conditions	24
8.5 Rotor speed and pitch angle measurement.....	24
9 Data reduction procedures.....	24
9.1 General methodology for sound power levels and 1/3-octave band levels.....	24
9.2 Calculation of sound pressure levels	27

9.2.1	General	27
9.2.2	Calculation of average sound spectra and uncertainty per bin	27
9.2.3	Calculation of average wind speed and uncertainty per bin	29
9.2.4	Calculation of noise levels at bin centres including uncertainty	30
9.3	Apparent sound power levels.....	31
9.4	Apparent sound power levels with reference to wind speed in 10 m height	32
9.5	Tonal audibility	33
9.5.1	General methodology for tonality	33
9.5.2	Identifying possible tones	34
9.5.3	Classification of spectral lines within the critical band.....	34
9.5.4	Identified tone	37
9.5.5	Determination of the tone level	37
9.5.6	Determination of the masking noise level.....	37
9.5.7	Determination of tonality.....	37
9.5.8	Determination of audibility	38
9.5.9	Background noise	38
10	Information to be reported	39
10.1	General	39
10.2	Characterisation of the wind turbine	39
10.3	Physical environment	39
10.4	Instrumentation	40
10.5	Acoustic data	40
10.6	Non-acoustic data	41
10.7	Uncertainty.....	41
Annex A (informative)	Other possible characteristics of wind turbine noise emission and their quantification	42
Annex B (informative)	Assessment of turbulence intensity	44
Annex C (informative)	Assessment of measurement uncertainty	45
Annex D (informative)	Apparent roughness length	47
Annex E (informative)	Characterization of a secondary wind screen.....	49
Annex F (normative)	Small wind turbines	53
Annex G (informative)	Air absorption	57
Bibliography.....		58
Figure 1	– Mounting of the microphone	15
Figure 2	– Picture of microphone and measurement board.....	16
Figure 3	– Standard pattern for microphone measurement positions (plan view)	18
Figure 4	– Illustration of the definitions of R_0 and slant distance R_1	19
Figure 5	– Acceptable meteorological mast position (hatched area)	22
Figure 6	– Flowchart showing the data reduction procedure.....	26
Figure 7	– Flowchart for determining tonal audibility for each wind speed bin	33
Figure 8	– Illustration of $L_{70} \%$ level in the critical band.....	35
Figure 9	– Illustration of lines below the $L_{70} \% + 6$ dB criterion	36
Figure 10	– Illustration of $L_{pn,avg}$ level and lines classified as masking.....	36
Figure 11	– Illustration of classifying all spectral lines.....	37
Figure E.1	– Example 1 of a secondary wind screen	50

Figure E.2 – Example 2 of secondary wind screen 51

Figure E.3 – Example on insertion loss from Table E.1 52

Figure F.1 – Allowable region for meteorological mast position as a function of β –
Plan view 54

Figure F.2 – Example immission noise map 56

Figure G.1 – Example of 1/3-octave spectrum 57

Table C.1 – Examples of possible values of type B uncertainty components relevant
for apparent sound power spectra 46

Table C.2 – Examples of possible values of type B uncertainty components for wind
speed determination relevant for apparent sound power spectra 46

Table D.1 – Roughness length 47

Table E.1 – Example on reporting of insertion loss 51

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 61400-11:2012](#)

<https://standards.iteh.ai/catalog/standards/iec/ac2bd353-8397-445d-84b1-5689fe298261/iec-61400-11-2012>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

WIND TURBINES –

Part 11: Acoustic noise measurement techniques

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61400-11 has been prepared by IEC technical committee 88: Wind turbines.

This third edition of IEC 61400-11 cancels and replaces the second edition published in 2002 and its Amendment 1 (2006). It constitutes a technical revision, introducing new principles for data reduction procedures.

The text of this standard is based on the following documents:

FDIS	Report on voting
88/436/FDIS	88/440/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61400 series, under the general title *Wind turbines*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual edition of this document may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 61400-11:2012](#)

<https://standards.iteh.ai/catalog/standards/iec/ac2bd353-8397-445d-84b1-5689fe298261/iec-61400-11-2012>

INTRODUCTION

The purpose of this part of IEC 61400 is to provide a uniform methodology that will ensure consistency and accuracy in the measurement and analysis of acoustical emissions by wind turbine generator systems. This International Standard has been prepared with the anticipation that it would be applied by:

- wind turbine manufacturers striving to meet well defined acoustic emission performance requirements and/or a possible declaration system (e.g. IEC/TS 61400-14);
- wind turbine purchasers for specifying performance requirements;
- wind turbine operators who may be required to verify that stated, or required, acoustic performance specifications are met for new or refurbished units;
- wind turbine planners or regulators who must be able to accurately and fairly define acoustical emission characteristics of a wind turbine in response to environmental regulations or permit requirements for new or modified installations.

This standard provides guidance in the measurement, analysis and reporting of complex acoustic emissions from wind turbine generator systems. The standard will benefit those parties involved in the manufacture, installation, planning and permitting, operation, utilization, and regulation of wind turbines. The measurement and analysis techniques recommended in this document should be applied by all parties to ensure that continuing development and operation of wind turbines is carried out in an atmosphere of consistent and accurate communication relative to environmental concerns. This standard presents measurement and reporting procedures expected to provide accurate results that can be replicated by others.

<https://standards.iteh.ai>
Document Preview

[IEC 61400-11:2012](https://standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/iec/ac2bd353-8397-445d-84b1-5689fe298261/iec-61400-11-2012>

WIND TURBINES –

Part 11: Acoustic noise measurement techniques

1 Scope

This part of IEC 61400 presents measurement procedures that enable noise emissions of a wind turbine to be characterised. This involves using measurement methods appropriate to noise emission assessment at locations close to the machine, in order to avoid errors due to sound propagation, but far away enough to allow for the finite source size. The procedures described are different in some respects from those that would be adopted for noise assessment in community noise studies. They are intended to facilitate characterisation of wind turbine noise with respect to a range of wind speeds and directions. Standardisation of measurement procedures will also facilitate comparisons between different wind turbines.

The procedures present methodologies that will enable the noise emissions of a single wind turbine to be characterised in a consistent and accurate manner. These procedures include the following:

- location of acoustic measurement positions;
- requirements for the acquisition of acoustic, meteorological, and associated wind turbine operational data;
- analysis of the data obtained and the content for the data report; and
- definition of specific acoustic emission parameters, and associated descriptors which are used for making environmental assessments.

This International Standard is not restricted to wind turbines of a particular size or type. The procedures described in this standard allow for the thorough description of the noise emission from a wind turbine. A method for small wind turbines is described in Annex F.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60688, *Electrical measuring transducers for converting a.c. electrical quantities to analogue or digital signals*

IEC 60942:2003, *Electroacoustics – Sound calibrators*

IEC 61260:1995, *Electroacoustics – Octave-band and fractional-octave-band filters*

IEC 61400-12-1:2005, *Wind turbines – Part 12-1: Power performance measurements of electricity producing wind turbines*

IEC 61400-12-2, *Wind turbines – Part 12-2: Power performance verification of electricity producing wind turbines*¹

¹ To be published.

IEC 61672 (all parts), *Electroacoustics – Sound level meters*

ISO/IEC Guide 98-3, *Uncertainty of measurement – Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

3 Terms and definitions

For the purposes of this standard, the following terms and definitions apply.

3.1

apparent sound power level

L_{WA}

A-weighted sound power level re. 1 pW of a point source at the rotor centre with the same emission in the downwind direction as the wind turbine being measured, L_{WA} is determined at bin centre wind speeds at hub height

Note 1 to entry: Apparent sound power level is expressed in dB re. 1 pW.

3.2

apparent sound power level with reference to wind speed at 10 m height

$L_{WA,10m}$

A-weighted sound power level re. 1 pW of a point source at the rotor centre with the same emission in the downwind direction as the wind turbine being measured, $L_{WA,10m}$ are determined at bin centre wind speeds at 10 m height within the measured wind speed range

Note 1 to entry: Apparent sound power level with reference to wind speed at 10 m height is expressed in dB re. 1 pW.

3.3

audibility criterion

L_a

frequency dependent criterion curve determined from listening tests, and reflecting the subjective response of a “typical” listener to tones of different frequencies

Note 1 to entry: Audibility criterion is expressed in dB re. 20 μ Pa.

3.4 sound pressure levels

3.4.1 A-weighted sound pressure levels

L_A

sound pressure levels measured with the A frequency weighting networks specified in IEC 61672

Note 1 to entry: A-weighted sound pressure levels are expressed in dB re. 20 μ Pa.

3.4.2 C-weighted sound pressure levels

L_C

sound pressure levels measured with the C frequency weighting networks specified in IEC 61672

Note 1 to entry: C-weighted sound pressure levels are expressed in dB re. 20 μ Pa.

3.5

bin centre

centre value of a wind speed bin

3.6 inclination angle

 ϕ

angle between the plane of the measurement board and a line from the microphone to the rotor centre

Note 1 to entry: Inclination angle is expressed in °.

3.7 maximum power

maximum value of the binned power curve for the power optimised mode of operation

Note 1 to entry: Maximum power is expressed in kW.

3.8 measured wind speed at height Z

 $V_{Z,m}$

wind speed measured at height Z with a mast mounted anemometer

Note 1 to entry: Measured wind speed at height Z is expressed in m/s.

3.9 measured nacelle wind speed at hub height

 $V_{nac,m}$

wind speed measured at hub height with a nacelle anemometer

Note 1 to entry: Measured nacelle wind speed at hub height is expressed in m/s.

3.10 normalised nacelle wind speed at hub height

 $V_{nac,n}$

normalised wind speed measured at hub height with a nacelle anemometer corrected to standard meteorological conditions

Note 1 to entry: Normalised nacelle wind speed at hub height is expressed in m/s.

3.11 normalised wind speed derived from power curve

 $V_{P,n}$

normalised wind speed derived from power curve under standard meteorological conditions

Note 1 to entry: Normalised wind speed derived from power curve is expressed in m/s.

3.12 normalised wind speed at hub height during background noise measurements

 $V_{B,n}$

normalised wind speed at hub height from anemometer

Note 1 to entry: Normalised wind speed at hub height during background noise measurements is expressed in m/s.

3.13 normalised wind speed at hub height

 $V_{H,n}$

normalised wind speed at hub height

Note 1 to entry: Normalised wind speed at hub height is expressed in m/s.

3.14 normalised wind speed at height Z

 $V_{Z,n}$

normalised wind speed at height Z from mast mounted anemometer

Note 1 to entry: Normalised wind speed at height Z is expressed in m/s.

3.15

reference distance

R_0

nominal horizontal distance from the centre of the base of the wind turbine to each of the prescribed microphone positions

Note 1 to entry: Reference distance is expressed in m.

3.16

reference roughness length

$z_{0\text{ref}}$

roughness length of 0,05 m used for converting wind speed to meteorological reference conditions

Note 1 to entry: Reference roughness length is expressed in m.

3.17

sound pressure level

L_p

10 times the \log_{10} of the ratio of the square mean sound pressure to the square of the reference sound pressure of 20 μPa

Note 1 to entry: Sound pressure level is expressed in dB re. 20 μPa .

3.18

tonal audibility

$\Delta L_{a,k}$

difference between the tonality and the audibility criterion in each wind speed bin, where k is the centre value of the wind speed bin

Note 1 to entry: Tonal audibility is expressed in dB.

3.19

tonality

ΔL_k

difference between the tone level and the level of the masking noise in the critical band around the tone in each wind speed bin where k is the centre value of the wind speed bin

Note 1 to entry: Tonality is expressed in dB.

3.20

wind speed bin

wind speed interval, 0,5 m/s wide, centred around integer and half-integer wind speeds open at the low end, and closed at the high end

3.21

wind speed at 10 m height

V_{10}

wind speed at 10 m height for reporting apparent sound power levels and spectra with reference to 10 m height

Note 1 to entry: Wind speed at 10 m height is expressed in m/s.

4 Symbols and units

D	rotor diameter (horizontal axis turbine) or equatorial diameter (vertical axis turbine)	(m)
H	height of rotor centre (horizontal axis turbine) or height of rotor equatorial plane (vertical axis turbine) above local ground near the wind turbine	(m)
L_A or L_C	A or C-weighted sound pressure level	(dB)
L_{Aeq}	equivalent continuous A-weighted sound pressure level	(dB)
$L_{pn,j,k}$	sound pressure level of masking noise within a critical band in the “ j^{th} ” spectra at the “ k^{th} ” wind speed bin	(dB)
$L_{pn,avg,j,k}$	average of analysis bandwidth sound pressure levels of masking noise in the “ j^{th} ” spectra at the “ k^{th} ” wind speed bin	(dB)
$L_{pt,j,k}$	sound pressure level of the tone or tones in the “ j^{th} ” spectra at the “ k^{th} ” wind speed bin	(dB)
$L_{WA,k}$	apparent sound power level, where k is a wind speed bin centre value	(dB)
log	logarithm to base 10	
P_m	measured electric power	(kW)
P_n	normalised electric power	(kW)
R_1	slant distance, from rotor centre to actual measurement position	(m)
R_0	reference distance	(m)
S_0	reference area, $S_0 = 1 \text{ m}^2$	(m ²)
T_C	air temperature	(°C)
T_K	absolute air temperature	(K)
U_A	type A uncertainty	(-)
U_B	type B uncertainty	(-)
V_H	wind speed at hub height, H	(m/s)
V_P	derived wind speed from power curve	(m/s)
V_z	wind speed at height, z	(m/s)
V_{nac}	wind speed from nacelle anemometer	(m/s)
f	frequency of the tone	(Hz)
f_c	centre frequency of critical band	(Hz)
p	atmospheric pressure	(kPa)
z_0	roughness length	(m)
z_{0ref}	reference roughness length, 0,05 m	(m)