

# INTERNATIONAL STANDARD



Optical fibre cables –  
Part 5-20: Family specification – Outdoor microduct fibre units, microducts and  
protected microducts for installation by blowing

Document Preview

IEC 60794-5-20:2014

<https://standards.iteh.ai/catalog/standards/iec/a2f60305-78d6-478b-823d-c2190be410b3/iec-60794-5-20-2014>



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

<https://standards.iteh.ai/catalog/standards/iec/a2f60305-78d6-478b-823d-c2190be410b3/iec-60794-5-20-2014>

<https://standards.iteh.ai/catalog/standards/iec/a2f60305-78d6-478b-823d-c2190be410b3/iec-60794-5-20-2014>

# INTERNATIONAL STANDARD



Optical fibre cables –  
Part 5-20: Family specification – Outdoor microduct fibre units, microducts and  
protected microducts for installation by blowing

Document Preview

[IEC 60794-5-20:2014](#)

<https://standards.iteh.ai/catalog/standards/iec/a2f60305-78d6-478b-823d-c2190be410b3/iec-60794-5-20-2014>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE



ICS 33.180.01, 33.180.10

ISBN 978-2-8322-1420-6

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references .....	6
3 Symbols .....	7
4 General requirements .....	8
4.1 Construction .....	8
4.1.1 General .....	8
4.1.2 Microduct fibre units .....	9
4.1.3 Microducts .....	9
4.1.4 Protected microducts .....	9
4.1.5 Microduct fittings .....	9
4.1.6 Microduct hardware .....	10
4.2 Optical fibres .....	10
4.3 Installation performance tests .....	10
4.3.1 Installation conditions .....	10
4.3.2 Tests applicable .....	11
4.3.3 Mechanical and environmental tests .....	11
5 Microduct fibre unit.....	11
5.1 Tests applicable.....	11
5.2 Family requirements and test conditions for microduct fibre unit tests .....	12
5.3 Tensile performance .....	12
5.4 Crush.....	12
5.5 Repeated bending.....	13
5.6 Torsion .....	13
5.7 Kink .....	13
5.8 Bend .....	13
5.9 Temperature cycling .....	13
5.10 Ageing .....	14
5.11 Water immersion.....	14
5.12 Buffer removal .....	14
6 Microduct .....	14
6.1 Tests applicable.....	14
6.2 Tensile performance .....	15
6.3 Crush.....	15
6.4 Impact .....	16
6.5 Repeated bending.....	16
6.6 Torsion .....	16
6.7 Kink .....	16
6.8 Bend .....	16
6.9 Microduct route verification test .....	17
6.10 Microduct pressure withstand.....	17
6.11 Ageing .....	17
7 Protected microducts .....	17
7.1 Tests applicable.....	17
7.2 Tensile performance .....	18
7.3 Crush.....	18

7.4	Impact .....	19
7.5	Repeated bending.....	19
7.6	Kink .....	19
7.7	Bend.....	19
7.8	Microduct route verification test .....	19
7.9	Microduct pressure withstand.....	20
7.10	Ageing .....	20
Annex A	(informative) Examples of microduct fibre units, microducts, and protected microducts.....	21
Annex B	(informative) Product descriptions (blank detail specification and minimum requirements) .....	22
Annex C	(normative) Product constructions .....	25
Annex D	(normative) Transmission requirements .....	28
D.1	Attenuation of cabled fibre .....	28
D.2	Fibre bandwidth requirements .....	29
Annex E	(normative) IEC 60794-1-21 Method Exx – Microduct inner clearance test .....	30
E.1	Object.....	30
E.2	General.....	30
E.3	Sample .....	30
E.4	Test equipment.....	30
E.5	Procedure .....	30
E.6	Requirements .....	30
E.7	Details to be recorded.....	31
Figure A.1	– Protected microducts, tight package .....	21
Figure A.2	– Microduct fibre units .....	21
<a href="https://standards.iteh.ai/catalog/standards/iec/a2f60305-78d6-478b-823d-c2190be410b3/iec-60794-5-20-2014">https://standards.iteh.ai/catalog/standards/iec/a2f60305-78d6-478b-823d-c2190be410b3/iec-60794-5-20-2014</a>		
Table 1	– Tests applicable for installation performance .....	11
Table 2	– Tests applicable for mechanical and environmental performance of microduct fibre unit .....	11
Table 3	– Tests applicable for mechanical and environmental performance of microduct .....	15
Table 4	– Tests applicable for mechanical and environmental performance of protected microduct .....	18
Table B.1	– Microduct fibre unit description .....	22
Table B.2	– Microduct description .....	23
Table B.3	– Protected microduct description .....	24
Table C.1	– Typical microduct fibre unit construction .....	25
Table C.2	– Microduct construction .....	26
Table C.3	– Protected microduct construction .....	27
Table D.1	– Multimode maximum cable attenuation coefficient (dB/km) .....	28
Table D.2	– Single-mode maximum cable attenuation coefficient (dB/km) – Premises cabling applications .....	28
Table D.3	– Single-mode maximum cable attenuation coefficient (dB/km) – All other applications .....	29
Table D.4	– Minimum multimode fibre bandwidth (MHz×km) .....	29

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## OPTICAL FIBRE CABLES –

**Part 5-20: Family specification –  
Outdoor microduct fibre units, microducts and  
protected microducts for installation by blowing**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60794-5-20 has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

The text of this standard is based on the following documents:

CDV	Report on voting
86A/1497/CDV	86A/1543/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 60794 series, published under the general title *Optical fibre cables*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[IEC 60794-5-20:2014](#)

<https://standards.iteh.ai/catalog/standards/iec/a2f60305-78d6-478b-823d-c2190be410b3/iec-60794-5-20-2014>

## OPTICAL FIBRE CABLES –

### Part 5-20: Family specification – Outdoor microduct fibre units, microducts and protected microducts for installation by blowing

#### 1 Scope

This part of IEC 60794 is a family specification that covers outdoor microduct fibre units and corresponding microducts and protected microducts for installation by blowing. The protected microducts are intended for duct, directly buried or lashed applications.

Microduct fibre units differ from microduct optical fibre cables (see IEC 60794-5-10) in that they provide less protection to the fibres that they contain. Specifically, microduct fibre units rely on the structure of the microduct, protected microduct or appropriate housing to support installation and to provide additional mechanical protection for the optical fibre over the lifetime of the product.

Systems built with components covered by this standard are subject to the requirements of sectional specification IEC 60794-5 where applicable.

Annex A gives examples of microduct optical fibre units and microducts.

Annex B describes a blank detail specification for outdoor microduct fibre units and the associated microducts and incorporates some minimum requirements. Detail product specifications may be prepared on the basis of this family specification using Annex B as a guide. Annex C provides normative product constructions for microduct optical fibre units, microducts and protected microducts.

<https://standards.iteh.ai/catalog/standards/iec/a2160305-78d6-478b-823d-c2190be410b3/iec-60794-5-20-2014>

The parameters specified in this standard may be affected by measurement uncertainty arising either from measurement errors or calibration errors due to lack of suitable standards. Acceptance criteria should be interpreted with respect to this consideration.

The number of fibres tested is intended to be representative of the microduct fibre unit design and should be agreed between the customer and supplier.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 60793-1-40, *Optical fibres – Part 1-40: Measurement methods and test procedures – Attenuation*

IEC 60793-1-53, *Optical fibres – Part 1-53: Measurement methods and test procedures – Water immersion*

IEC 60793-2-10, *Optical fibres – Part 2-10: Product specifications – Sectional specification for category A1 multimode fibres*



IEC 60793-2-50, *Optical fibres – Part 2-50: Products specification – Sectional specification for class B single-mode fibres*

IEC 60794-1-1, *Optical fibre cables – Part 1-1: Generic specification – General*

IEC 60794-1-2, *Optical fibre cables – Part 1-2: Generic specification – Basic optical cable test procedures*

IEC 60794-1-21, *Optical fibre cables – Part 1-21: Generic specification – Basic optical cable test procedures – Mechanical test methods*

IEC 60794-1-22, *Optical fibre cables – Part 1-22: Generic specification – Basic optical cable test procedures – Environmental test methods*

IEC 60794-3:2001, *Optical fibre cables – Part 3: Sectional specification – Outdoor cables*

IEC 60794-5, *Optical fibre cables – Part 5: Sectional specification – Microduct cabling for installation by blowing*

IEC 60794-5-10, *Optical fibre cables – Part 5-10: Family specification – Outdoor microduct optical fibre cables, microducts and protected microducts for installation by blowing*

IEC 60811-202, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 202: General tests – Measurement of thickness of non-metallic sheath*

IEC 60811-203, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 203: General tests – Measurement of overall dimensions*

IEC 60811-501, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 501: Mechanical tests – Tests for determining the mechanical properties of insulating and sheathing compounds*

<https://standards.iteh.ai/catalog/standards/iec/a2f60305-78d6-478b-823d-c2190be410b3/iec-60794-5-20-2014>

IEC 60811-601, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 601: Physical tests – Measurement of the drop-point of filling compounds*

IEC 60811-602, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 602: Physical tests – Separation of oil in filling compounds*

IEC 60811-604, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 604: Physical tests – Measurement of absence of corrosive components in filling compounds*

ISO/IEC 11801, *Information technology – Generic cabling for customers premises*

### 3 Symbols

For the purposes of this part of IEC 60794 the following symbols apply.

$\lambda_{CC}$	Cabled fibre cut-off wavelength
$\Delta D$	minimum wall thickness
$\Delta D'$	Minimum thickness of the outer sheath of the protected microduct
$d$	Nominal outer diameter of the fibre unit
DS	Detail specification
ID	Nominal inner diameter of the microduct

OD	Nominal outer diameter of the microduct
OD'	Nominal outer diameter of the protected microduct
$T_M$	The acceptable amount of short-term tensile load that can be applied to the fibre unit without permanent degradation of the characteristics of the fibres in the tensile performance test
$T_{A1}$	Temperature cycling test low-temperature limit (usage and storage) according to IEC 60794-1-2, Method F1
$T_{A2}$	Temperature cycling test secondary low-temperature limit for extended storage temperature range according to IEC 60794-1-2, Method F1
$T_{B1}$	Temperature cycling test high-temperature limit (usage and storage) according to IEC 60794-1-2, Method F1
$T_{B2}$	Temperature cycling test secondary high-temperature limit for extended storage temperature range according to IEC 60794-1-2, Method F1
$t_1$	Temperature cycling dwell time
$n \times d$	The product of a variable and the fibre unit outer diameter used for determining appropriate sizes for bends, mandrels, etc.
$n \times OD$	The product of a variable and the outer diameter of the microduct used for determining appropriate sizes for bends, mandrels, etc.
$n \times OD'$	The product of a variable and the outer diameter of the protected microduct used for determining appropriate sizes for bends, mandrels, etc.
W	Weight of 1 km of microduct, protected microduct or fibre unit

## 4 General requirements

### 4.1 Construction

#### 4.1.1 General

In addition to the constructional requirements in IEC 60794-5, where applicable, the following considerations apply to outdoor microduct fibre units and their corresponding microducts and protected microducts.

The products covered in this specification should be designed and manufactured for expected operating lifetimes of at least 20 years.

The microduct fibre units are designed to be installed in microducts or protected microducts and in appropriate housings. The microducts and protected microducts that are compatible for use with microduct fibre units are defined in this document. Microduct fibre units are optimised for installation and operating lifetime in these microducts.

It shall be possible to install or remove the microduct fibre unit from microduct or protected microduct by blowing during the operational lifetime except under the following conditions:

- microduct fibre units or microducts are compromised by multiple installation or removal operations;
- microducts are fouled with sediment, debris, or other foreign matter due to inadequate maintenance;
- microducts are damaged by extrinsic factors such as dig-ups, earth heaves, etc.

In such cases, the affected section of microduct shall be cleared, repaired or replaced prior to any microduct fibre unit installations.

The microduct fitness should be verified with dimensional clearance and static pressure testing of the microduct route.

The materials in the microduct fibre unit, microduct or protected microduct shall take into consideration local regulations.

#### 4.1.2 Microduct fibre units

In general, microduct fibre units are the smallest and most flexible of all optical cable products for outdoor use and are intended for installation within microducts. The fibre unit structure is designed to improve blowing performance compared to a bare fibre and to provide mechanical and environmental protection for the fibres during installation and over the life of the product. Fibre unit designs are not described in detail but some examples are given in Annex A. The microduct fibre units are not as mechanically robust as traditional outdoor optical fibre cables and, therefore, require the use of suitable installation and handling practices to prevent damage. Ad hoc installation practices could degrade optical performance or reduce the product's operating lifetime.

#### 4.1.3 Microducts

A microduct suitable for installation of microduct fibre units is a small, flexible, lightweight tube with an outer diameter typically 8 mm or less. Compared to microduct optical fibre cables (see IEC 60794-5-10), microduct fibre units place greater reliance on microducts and protected microducts or appropriate closures to provide mechanical protection for the optical fibres. Therefore, a microduct must meet the realistic impact, compression and bending requirements for an application. A protected microduct may be required (see 4.1.4).

Microducts shall be able to resist pressure differences needed for installation by blowing. The microducts shall be circular and uniform in cross-section throughout their length, and their inner surface may have a low coefficient of friction. Inner- and outer-diameters shall be specified. As an option, a supplier may provide a special lining or lubricating coating on the interior of the microduct to aid installation. These layers should not reduce the specified inside diameter of the microduct.

Microducts generally are intended for benign installation within ducts or as components within a protected microduct as described in 4.1.4. In all cases, it shall be possible to identify each individual microduct throughout the length. When using colours they shall be a reasonable match to IEC 60304.

Microducts installed outdoors and not occupied shall be sealed at each end to prevent the introduction of moisture, debris, insects, or other such foreign contaminants that could subsequently hinder the successful installation of fibre unit. Microducts installed outdoors and not immediately occupied shall be tested for obstructions prior to use.

#### 4.1.4 Protected microducts

A protected microduct is one or more microducts surrounded by a protective sheath, a larger protective duct and/or an integral thick sheath (such that it complies with the requirements of Clause 7). A protected microduct can provide additional crush and impact protection compared to a stand-alone microduct. This additional protection may be needed for a specific operating environment or installation method. The protective sheath may include an integrated layer of armouring or thicker outer sheath. In all cases it shall be possible to identify each individual microduct throughout the length. When using colours, they shall be a match to IEC 60304 using visual inspection.

#### 4.1.5 Microduct fittings

Microduct fittings are components needed to physically align, connect and seal the junction between two or more sections of microduct, or to connect microduct to hardware, or to seal the space between a microduct fibre unit and microduct. Multiple microducts may be connected in series in order to support extended microduct fibre unit installation distances, or connected in a branch-type configuration with multiple output terminae for a given input, within the same system. The latter may be employed in campus type local area networks