INTERNATIONAL STANDARD



First edition 1989-09-15

Polypropylene (PP) valves for pipes under pressure — Basic dimensions — Metric series

iTeh S Robinets en polypropylène (PP) pour tubes avec pression – Dimensions de base – (standards.iteh.ai)

ISO 8242:1989 https://standards.iteh.ai/catalog/standards/sist/68460453-26c8-4cd2-ae7cf337c232c5fc/iso-8242-1989



Reference number ISO 8242 : 1989 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at VIEW least 75 % approval by the member bodies voting.

(standards.iteh.ai)

International Standard ISO 8242 was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids.* ISO 8242:1989

https://standards.iteh.ai/catalog/standards/sist/68460453-26c8-4cd2-ae7c-

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

© ISO 1989

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Polypropylene (PP) valves for pipes under pressure – **Basic dimensions** – Metric series

iTeh STANDARD PREVIEW (standards.iteh.ai)

0 Introduction

valves with plain spigot ends for PP pipe diameters from 16 to 125 mm, given in table 2; This International Standard deals with current types of 242:1989

polypropylene (PP) valves; it should be used for iguidance by ards/sist/68460453-26c8-4cd2-ae7c-valves with plain socket ends for PP pipe diameters the manufacturer and user and as a basis for specific standards:/iso-8242 from 16 to 125 mm, given in table 3; It may later be extended to include other types of valves, when

the development of plastics materials in the field of pipe systems makes this necessary.

The possible connections to the various pipe systems are given in ISO 7349.

Extension to include other types should be made by observing the principles laid down in this International Standard.

1 Scope

This International Standard specifies the series of diameters to be used and the basic dimensions which are common to all types of polypropylene (PP) valves for pipes under pressure for the transport of fluids, regardless of their method of manufacture and composition.

2 Field of application

This International Standard applies to

- valves for nominal outside diameters, d_{e} , from 16 to 160 mm with flanges from DN 10 to DN 150, given in table 1;

 valves with threaded ends for PP pipe diameters from 20 to 63 mm, given in table 4.

3 References

ISO 7-1, Pipe threads where pressure-tight joints are made on the threads - Part 1: Designation, dimensions and tolerances.

ISO 161-1, Thermoplastics pipes for the transport of fluids -Nominal outside diameters and nominal pressures - Part 1: Metric series.

ISO 2536, Unplasticized polyvinyl chloride (PVC-U) pressure pipes and fittings, metric series - Dimensions of flanges.

ISO 7279, Polypropylene (PP) fittings for pipes under pressure - Sockets for fusion using heated tools - Metric series -Dimensions of sockets.

ISO 7349, Thermoplastics valves - Connection references.

4 Basic dimensions

4.1 Valves with flanges







			Dim	nensions in millimetres
Nominal outside diameter of pipe	Dimension face-to-face		Pitch circle diameter of bolt holes	Nominal flange size
$d_{e}^{(1)}$	L ²⁾		d ³⁾	DN ⁴⁾
Ŭ		tol.		T 7
16		NDARD		10
20	130	ndards.it	eh ai ⁶⁵	15
25	150		75	20
32	160	ISO * 2 180 8242:1989	85	25
40 http	s://standards.iteh.ai/ca	<u>150 6242.1969</u> htslog/standards/sist/	8460453-7668-4cd	32
50	²⁰⁰ f3	37c232c5fc/iso-8242	-1989 110	40
63	230	/ 62 52 6 51 6 / BO 02 12	125	50
75	290		145	65
90	310		160	80
110	350		180	100
125	350	± 3	190	110
125	400	<u> </u>	210	125
140	400		210	125
160	480		240	150

1) Nominal outside diameter of thermoplastics pipes in accordance with ISO 161-1.

2) Face-to-face dimensions for valves with flanges.

3) Pitch circle diameter of bolt holes in accordance with ISO 2536.

4) Nominal size for flanges in accordance with ISO 2536.

NOTE — The centre-to-face dimension for three-way values is L/2.

4.2 Valves with plain spigot ends

These valves may be fusion jointed to accessories.



Figure 2



4.3 Valves with plain socket ends



Table 3

Idu	ne z	Table	: 3
	Dimensions in millimetres		Dimensions in millimetres
Spigot diameter (equal to the nominal outside diameter of pipe)	Spigot length (minimum)	Inside diameter of socket ¹⁾ (equal to the nominal outside diameter of pipe)	Socket reference length (minimum)
$d_{e^{1}}$	[2)		
16	13,3	d_e^{2)}	(1 ³⁾
20	14,5	16	13,3
25		20	14,5
32	iTeh S ⁶ TANDAR	PRE 25IEW	16
40	^{20,5} tondordo	$(1)^{32}$	18,1
50	^{20,5} tandards	.[[e][.a]] ₄₀	20,5
63	27,4	50	23,5
75	31 <u>ISO 8242:1</u>		27,5
90 ht	ps://standards.jgh_ai/catalog/standards/	/s/st/68460453-2658-4cd2-ae7c-	31
110	41,5 f337c232c5fc/iso-	8242-1989 90	35,5
125	46	110	41,5
) Spigot diameter of valve equal	to the nominal outside diameter of	125	46

1) Spigot diameter of valve equal to the nominal outside diameter of thermoplastics pipes in accordance with ISO 161-1.

2) Spigot length equal to the minimum socket length in accordance with ISO 7279.

1) Tolerances of inside diameter of socket in accordance with ISO 7279.

2) Inside diameter of the plain socket equal to the nominal diameter of thermoplastics pipes in accordance with ISO 161-1.

3) Minimum socket length in accodance with ISO 7279.

4.4 Valves with threaded ends

These valves are supplied with male threaded ends that comply with ISO 7-1.



Figure 4

Table 4

	140		Dimensions in millimetres
Nominal outside diameter of pipe $d_{e}^{1)}$	Thread designation ²⁾	Overall length $\begin{array}{c} L_2\\ \pm 2 \end{array}$	Thread length $\frac{l_2}{\pm 2}$
20	1/2	134	16
25	3/4	151	17,5
32	eh STAND	ARD PREV	19,5
40	1 1/4	200	22
50	(standa)	rds.itæh.ai)	22
63	2	254	26

1) Nominal outside diameter of thermoplastics pipes in accordance with ISO 161-1.

2) The complete thread/designationitis/giventialog/otprilards/sist/68460453-26c8-4cd2-ac7cf337c232c5fc/iso-8242-1989

iTeh STANDARD PREVIEW (standards iteh ai) This page intentionally left blank

<u>ISO 8242:1989</u> https://standards.iteh.ai/catalog/standards/sist/68460453-26c8-4cd2-ae7cf337c232c5fc/iso-8242-1989

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 8242:1989</u> https://standards.iteh.ai/catalog/standards/sist/68460453-26c8-4cd2-ae7cf337c232c5fc/iso-8242-1989

UDC 621.646.2 : 678.742.3

Descriptors : polypropylene, plastics products, pressure equipment, pressure pipes, valves, dimensions.

Price based on 4 pages