
Večparni kabli do končnega uporabnika, uporabljeni v telekomunikacijskih omrežjih z visokimi bitnimi hitrostmi - 2. del: Cevni in vkopani kabli

End user multi-pair cables used in high bit rate telecommunication networks – Part 2: Duct and buried cables

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 50406-2:2004](https://standards.iteh.ai/catalog/standards/sist/44664d3e-dc10-4e11-8de0-d474f9b8c7de/sist-en-50406-2-2004)

<https://standards.iteh.ai/catalog/standards/sist/44664d3e-dc10-4e11-8de0-d474f9b8c7de/sist-en-50406-2-2004>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 50406-2:2004

<https://standards.iteh.ai/catalog/standards/sist/44664d3e-dc10-4e11-8de0-d474f9b8c7de/sist-en-50406-2-2004>

EUROPEAN STANDARD

EN 50406-2

NORME EUROPÉENNE

EUROPÄISCHE NORM

June 2004

ICS 33.120.10

English version

**End user multi-pair cables used
in high bit rate telecommunication networks
Part 2: Duct and buried cables**

Câbles multi-paires de l'utilisateur final
utilisés dans les réseaux
de télécommunication à hauts-débits
Partie 2: Câbles pour conduites
et enterrés

Vielpaarige Kabel für Endanwender
für Telekommunikationsnetzwerke
mit hoher Bitrate
Teil 2: Kabel für das Verlegen
in Kabelschächten und in Erdreich

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This European Standard was approved by CENELEC on 2004-02-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

This European Standard was prepared by the Technical Committee CENELEC TC 46X, Communication cables.

The text of the draft was submitted to the Unique Acceptance Procedure and was approved by CENELEC as EN 50406-2 on 2004-02-01.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2005-02-01
 - latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2007-02-01
-

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 50406-2:2004

<https://standards.iteh.ai/catalog/standards/sist/44664d3e-dc10-4e11-8de0-d474f9b8c7de/sist-en-50406-2-2004>

Contents

| | | |
|-------|--|----|
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terminology and abbreviations | 5 |
| 3.1 | Terminology | 5 |
| 3.2 | Abbreviations | 5 |
| 4 | General information | 6 |
| 4.1 | General cable description | 6 |
| 4.2 | Environment and product safety requirement | 6 |
| 4.3 | Testing | 6 |
| 5 | Requirements for conductor | 6 |
| 5.1 | Construction and dimensions | 6 |
| 5.2 | Mechanical requirements | 6 |
| 5.3 | Electrical requirements | 7 |
| 5.3.1 | Conductor resistance | 7 |
| 5.3.2 | Conductor resistance unbalance | 7 |
| 6 | Requirements for insulation | 7 |
| 6.1 | Construction material and dimensions | 7 |
| 6.1.1 | Construction | 7 |
| 6.1.2 | Colour code | 7 |
| 6.2 | Mechanical requirements | 7 |
| 6.3 | Electrical requirements | 7 |
| 6.3.1 | Insulation resistance | 7 |
| 6.3.2 | Dielectric strength | 7 |
| 7 | Requirements for cable element | 8 |
| 7.1 | Construction and dimensions | 8 |
| 7.1.1 | Screening of the cable element | 8 |
| 7.1.2 | Spare cable elements | 8 |
| 8 | Requirements for cable core | 8 |
| 8.1 | Design | 8 |
| 8.1.1 | General | 8 |
| 8.1.2 | Screen | 8 |
| 8.1.3 | Interstitial fillers | 8 |
| 9 | Requirements for filling compounds | 9 |
| 10 | Requirements for the screening of the cable core | 9 |
| 11 | Requirement for the armour | 9 |
| 12 | Requirements for the sheath | 9 |
| 12.1 | Colour of sheath | 9 |
| 12.2 | Mechanical requirements | 9 |
| 13 | Cable identification | 10 |

ITEH STANDARD PREVIEW

(standards.iteh.ai)

SIST EN 50406-2:2004

[https://standards.iteh.ai/catalog/standards/sist/44664d3e-dc10-4e11-8de0-](https://standards.iteh.ai/catalog/standards/sist/44664d3e-dc10-4e11-8de0-d4749b8c7dc/sist-en-50406-2-2004)

[d4749b8c7dc/sist-en-50406-2-2004](https://standards.iteh.ai/catalog/standards/sist/44664d3e-dc10-4e11-8de0-d4749b8c7dc/sist-en-50406-2-2004)

| | | |
|--------|---|----|
| 14 | Requirements for finished cable..... | 10 |
| 14.1 | Mechanical requirements..... | 10 |
| 14.1.1 | Bending | 10 |
| 14.1.2 | Impact | 10 |
| 14.1.3 | Tensile (under consideration) | 10 |
| 14.1.4 | Crush resistance..... | 10 |
| 14.2 | Environmental requirements | 10 |
| 14.2.1 | Temperature range | 10 |
| 14.2.2 | Cold bend | 11 |
| 14.2.3 | Fauna and mould proofing..... | 11 |
| 14.2.4 | Moisture barriers..... | 11 |
| 15 | Electrical requirements..... | 11 |
| 15.1 | Dielectric strength | 11 |
| 15.2 | Mutual capacitance | 11 |
| 15.3 | Capacitance unbalance | 11 |
| 15.4 | Velocity of propagation | 11 |
| 15.5 | Attenuation | 12 |
| 15.6 | Longitudinal Conversion Loss (LCL)..... | 12 |
| 15.7 | Near End Crosstalk (NEXT)..... | 12 |
| 15.8 | Equal Level Far-End Crosstalk (ELFEXT)..... | 12 |
| 15.9 | Power Sum (PS) of crosstalk losses | 12 |
| 15.10 | Mean impedance..... | 12 |
| 15.11 | Return loss | 12 |
| 15.12 | Coupling attenuation | 13 |
| 15.13 | Transfer impedance..... | 13 |
| 15.14 | Transmission properties..... | 13 |
| 16 | Product qualification requirements..... | 13 |

1 Scope

This European Standard defines outdoor multi-pair/quad cables for use in high bit rate telecommunication networks with their relative definitions and requirements.

It covers radially water blocked cables, with an overall screen, with performances up to 60 MHz, to be used in outdoor networks intended to connect the broadband outside plant to the individual customer premises with a maximum recommended length of connection of 1 km.

The electrical, environmental, mechanical and transmission performance characteristics of the cables, related to their reference test methods, are detailed.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

| | | |
|--------------|--------|--|
| EN 50289 | series | Communication cables - Specifications for test methods (<i>Basic reference standards</i>) |
| EN 50290 | series | Communication cables (<i>Basic reference standards</i>) |
| EN 60811-1-1 | 1993 | Insulating and sheathing materials of electric and optical cables – Common test methods – Part 1-1: General application - Measurement of thickness and overall dimensions - Tests for determining the mechanical properties (IEC 60811-1-1) |
| EN 60811-1-2 | 1995 | Insulating and sheathing materials of electric cables - Common test methods – Part 1-2: General application - Thermal ageing methods (IEC 60811-1-2:1985 + corrigendum May 1986 + A1:1989) |
| HD 402 S2 | 1984 | Standard colours for insulation for low-frequency cables and wires (IEC 60304:1982) |
| IEC 60028 | 1925 | International standard of resistance for copper |

3 Terminology and abbreviations

3.1 Terminology

For the purpose of this European Standard, the definitions of EN 50290-1-2 apply.

3.2 Abbreviations

| | |
|------|--|
| ADSL | Asymmetric Digital Subscriber Lines |
| ATM | Asynchronous Transfer Mode |
| DSL | Digital Subscriber Line |
| EMC | Electromagnetic Compatibility |
| EMI | Electromagnetic Interference |
| FSAN | Full Service Access Network |
| HDSL | High-bit-rate Digital Subscriber Lines |

| | |
|----------|--|
| ISDN | Integrated Digital Services Network |
| ISDN-BRA | ISDN-Basic Rate Access |
| ISDN-PRA | ISDN-Primary Rate Access |
| Mbps | Mega-bits per second |
| TBD | To be determined |
| VDSL | Very-high-bit-rate Digital Subscriber Lines |
| XDSL | Generic term referring to all DSLs, ISDN, HDSL, ADSL, VDSL, etc. |

4 General information

4.1 General cable description

These cables are designed for outdoor high bit rate telecommunication networks. They are water-blocked cables with an overall screen.

High bit rate applications targeted in this specification involve frequencies up to 60 MHz. To restrict emission and to ensure satisfactory electromagnetic immunity, these cables include an overall screen.

These cables contain from one pair up to 200 pairs (ffs) that can be either in pairs or quads.

4.2 Environment and product safety requirement

Safety local and regional regulation (e.g. relevant European directives) is assumed to be met by these cables.

4.3 Testing

SIST EN 50406-2:2004

<https://standards.iteh.ai/catalog/standards/sist/44664d3e-dc10-4e11-8de0-4474f0878022/en-50406-2-2004>

For all test procedures described in this subclause, the test conditions shall be the standard atmospheric conditions (23 ± 5) °C and 20 %-70 % Relative Humidity, unless otherwise stated. All measured and computed values are to be rounded to the number of decimal places given in the corresponding requirement or objective.

The parameters specified in this standard may be affected by measurement uncertainty arising either from measurement errors or calibration errors due to a lack of suitable standards. Acceptance criteria shall be interpreted with respect to this consideration.

5 Requirements for conductor

5.1 Construction and dimensions

The conductor shall consist of annealed copper, uniform in quality and free from defects. The properties of the copper shall be in accordance with IEC 60028.

The conductor shall be solid, circular in section. Normally the conductor should be drawn in one piece. Joints in the conductor are permitted, provided that the tensile strength of a joint is not less than 85 % of the un-jointed solid conductor.

The diameter of the conductor shall be between 0,4 mm to 0,8 mm.

5.2 Mechanical requirements

The conductor elongation at break shall be tested according to EN 50289-3-2 and shall be minimum 10 % for 0,4 mm wires and better than 15 % for wires with diameters superior to 0,4 mm.

5.3 Electrical requirements

5.3.1 Conductor resistance

While measured in accordance with EN 50289-1-2, the conductor resistance shall meet the computed values when using EN 50290-2-1, Subclause 12.1.

5.3.2 Conductor resistance unbalance

While measured in accordance with EN 50289-1-2, the conductor resistance unbalance shall be maximum 2 %.

6 Requirements for insulation

6.1 Construction material and dimensions

6.1.1 Construction

Conductor insulation shall be composed of solid, cellular or composite (e.g. foam skin) polyolefin.

The insulation shall be continuous, having a thickness as uniform as possible. The minimum thickness of the insulation shall be measured in accordance with the method specified in EN 60811-1-1, Subclause 8.2.

The insulation shall be applied to fit closely to the conductor. The stripping properties of the insulation shall be checked in accordance with the method specified in EN 60811-1-1, Subclause 8.1. It shall be possible to strip the insulation from the conductor easily and without damage to the insulation or the conductor.

SIST EN 50406-2:2004

When required the insulated conductors shall be coloured for identification. Colours shall correspond reasonably with the standard colours shown in HD 402:50406-2-2004

6.1.2 Colour code

The colour code shall be agreed between the customer and the manufacturer.

6.2 Mechanical requirements

Shrinkage of insulation shall be checked against EN 50290-2-23. The shrinkage shall be less than 5 %.

6.3 Electrical requirements

6.3.1 Insulation resistance

When tested according to EN 50289-1-4, the insulation resistance shall be at least 5 000 Mohm.km under 500 V d.c.

6.3.2 Dielectric strength

Dielectric strength shall be tested according to EN 50289-1-3. The test shall be conducted with 1 kV d.c. or 700 V a.c. for 2 s.